

# Tabulars with reledmac

## Sommario

This file provides example of using tabular environments with *reledmac*.

We use `edtabularl`, `edtabularc` and `edtabularr`, with marginal, critical and familiar notes. We also use optional arguments of `\pstart`.

## 1 Left align

1	linea prima	linea prima	sidenote l
2	linea secunda	linea secunda <sup>1</sup>	sidenote l
3	linea tertia	linea tertia	sidenote l
4	linea quarta	linea quarta	
5	linea quinta	linea quinta <sup>1</sup>	
6	linea sexta	linea sexta	
7			

## 2 Center align

8	linea prima	linea prima	
9	linea secunda	linea secunda <sup>2</sup>	sidenote c
10	linea tertia	linea tertia	sidenote c
11	linea quarta	linea quarta	sidenote c
12	linea quinta	linea quinta <sup>2</sup>	
13	linea sexta	linea sexta	
14			

---

<sup>1</sup>familiar footnote A.

<sup>2</sup>familiar footnote A.

---

<sup>1</sup>familiar footnote B.

<sup>2</sup>familiar footnote B.

---

3 tertia ] critical note A

10 tertia ] critical note A

---

4 quarta ] critical note B

11 quarta ] critical note B

### 3 Right align

15	linea prima	linea prima
sidenote <sup>16</sup>	linea secunda	linea secunda <sup>3</sup>
sidenote <sup>17</sup>	linea tertia	linea tertia
sidenote <sup>18</sup>	linea quarta	linea quarta
19	linea quinta	linea quinta <sup>3</sup>
20	linea sexta	linea sexta
21		

---

<sup>3</sup>familiar footnote A.

---

<sup>3</sup>familiar footnote B.

---

17 tertia ] critical note A

---

18 quarta ] critical note B