

Typesetting Poetry Collections with `poemscol`*

John Burt
burt@brandeis.edu

8 August 2020

Abstract

`poemscol` provides commands for \LaTeX for setting collections of poetry. It is especially suited for setting collections of poetry in which several volumes are combined, such as in a critical edition of a poet's Collected Poems. It provides the structures required to produce a critical edition of the kind specified by the Modern Language Association's Committee on Scholarly Editions, and it automatically marks every occasion where a stanza break falls on a page break.

Contents

1	Introduction	4
2	Dependencies and compatibility with other packages	7
2.1	General	7
2.2	Prose sections	7
2.3	Multi-layer footnotes	7
2.4	Special running header for long poems	8
2.5	Verse drama and dramatist	8
2.6	Parallel text editions	8
2.7	Crop marks	8
2.8	Incompatibility with memoir and verse	9
2.9	Conflict with BibLaTeX	9
2.10	Compatibility with earlier versions of <code>poemscol</code>	9
3	Marking up individual poems	10
3.1	The title of the poem	10
3.1.1	Title placement schemes	11
3.1.2	Using title placement schemes: verse width and title width	12
3.1.3	Customization of titles	13
3.1.4	Subtitles and special titles	15

*This document corresponds to `poemscol` 3.1415926, dated 8 August 2020.

3.2	The body of the poem	15
3.2.1	The poem environment	15
3.2.2	Customizing the poem environment	15
3.2.3	Hyphenation is off in the poem environment	16
3.2.4	The stanza environment	17
3.2.5	Verse lines and line numbering	18
3.3	Special line markup	19
3.3.1	Indentation, line breaks, runover, and broken lines	19
3.3.2	Customizing broken lines	21
3.3.3	Right-flushed runover lines	22
3.4	Cross references by line number	22
4	Making a table of contents	22
4.1	Setup	22
4.2	Printing the table of contents	23
4.3	Contents entries for notes sections and the index	23
4.4	Customizing contents entries	24
5	Making an index of titles and first lines	26
5.1	Setup	26
5.2	Printing the index	26
5.3	Making multiple indices	26
6	Collections with multiple volumes	27
7	Recording textual notes, emendations, and explanatory notes	28
7.1	Setup for endnote sections	28
7.2	Customizing endnotes	29
7.3	Textual notes of various kinds	30
8	Creating new kinds of endnote	34
9	Multi-level footnotes	36
10	Notes at the end of poems	37
11	Printing endnotes and index	38
12	Forewords, Appendices, Contents Entries	39
13	Special cases	40
13.1	Epigraphs, attributions etc.	40
13.2	Appending publication date	41
13.3	Pausing line numbering	42
13.4	Quoted verse	42
13.5	Multiline poem titles	42
13.6	Poems in sections	43

13.7	Poetic sequences	43
13.8	Titles with marginal markers	45
13.9	Titles with footnotes	47
13.10	Empty poem titles and italicized poem titles	48
13.11	Problem titles	49
13.12	Customizing titles	50
13.13	Customizing indentations in titles in the text body	51
13.14	Customizing indentations in titles in the Contents	52
13.15	Visual formatting	52
14	Customizing page geometry and page styles	53
14.1	Font sizes, skips, sinks, indents, and penalties	53
14.2	Customizing page styles	54
14.3	Special page style for long poems	55
14.4	Page geometry and type leading	55
15	Prose Sections with line numbers	56
15.1	Setup	56
15.2	Endnotes for prose sections	57
16	Paragraph and sentence annotation	58
16.1	Setup	58
16.2	Cross references by sentence and paragraph	61
16.3	End notes by sentence and paragraph	61
16.4	Footnotes by sentence and paragraph	61
16.5	Bible chapter and verse	61
17	Parallel text editions	62
17.1	Setup for parallel texts in verse	62
17.2	Parallel texts and on the fly note types	63
17.3	Parallel texts and generic note types	64
17.4	Parallel text labels	65
17.5	Parallel prose passages	65
18	Using poemscol in a multilingual world	66
19	A sample driver file	67
20	A sample poem markup	68
21	A sample divider page	69
22	Implementation	71
22.1	Page geometry and crop marks	71
22.1.1	Internal font size commands	72
22.2	Miscellaneous dimensions and constants	73
22.3	Title Schemes	79

22.4	Verse	80
22.5	Miscellaneous internal counters	83
22.6	Miscellaneous token lists	84
22.7	Miscellaneous booleans	84
22.8	Defining page styles	85
22.9	Environments: poem, and stanza	88
22.10	Environments: main title page, divider pages	91
22.11	Marginal line numbers, verse lines, line cross references, etc.	91
22.12	Setup for contents, textual notes, emendations, and explanatory notes	98
22.13	Appendices, Forewords, Contents Entries	103
22.14	Book, volume, and volume section titles	105
22.15	Commands for setting titles of poems and sequences	109
22.15.1	Poem Titles	109
22.15.2	Poetic Sequences: Setting the Main Title	115
22.15.3	Sections of poetic sequences	117
22.15.4	Subsections of sequences	120
22.16	Titles with footnotes	133
22.17	Epigraphs, headnotes, attributions, dedications	135
22.18	Tools used for making note sections	137
22.19	Commands to make notes and send info to contents	138
22.20	Emendations and explanatory notes	141
22.21	Making new notes sections	143
22.22	Prose sections	146
22.23	Annotation by Sentence and Paragraph Number	151
22.24	Using Footnotes	158
22.25	Notes at the foot of individual poems	160
22.26	Embarrassing kludges	163
22.27	Marking stanza breaks on page turns	163
22.28	Parallel Texts	164
22.29	Parallel Texts in Prose	188
22.30	Finishing up	190
22.31	Visual formatting	195
22.32	Special environments: cjquotation and theindex	195

1 Introduction

`poemscol` provides the structures necessary for editing a critical edition of a volume of poems (or of a collection of a poet's works) such as those required by the Modern Language Association's Committee on Scholarly Editions. `poemscol` numbers the lines, and produces separate, formatted endnote sections (or, optionally, multiple layers of footnotes) for emendations, textual collations, and explanatory notes, tying each note to the range of lines upon which it is a comment.

Producing line numbers for verse is something for which \LaTeX would seem to be especially suited. A line of verse, after all, is not a carriage return but a

logical unit, an element of versification more than of typesetting, perhaps running over several physical lines, or perhaps split into half-lines as speakers or subjects change. With `poemscol` you mark lines, stanzas, and entire poems up as logical units, and `LATEX` does the formatting and counting. Once you have marked out the logical units of the poem, `poemscol` will automatically mark every textual note, emendation, or explanatory note with the range of line numbers to which it applies.

Editions of Collected Poetry might also require special structures to reflect the fact that they are made up of the contents of several volumes of poetry. In particular, such editions require facilities for setting up specially formatted divider pages between volumes. They also require tables of contents and other front matter, as well as an index of titles and first lines (or, optionally, several separate indices) and other sorts of back matter. `poemscol` automatically generates a table of contents, an index of titles and first lines, and divider pages for the sections of the volumes. It produces running headers of the form “Emendations to pp. xx-yy” for the note sections.

In poetry which does not have a regular stanzaic form, it is useful to be able to mark automatically occasions where there is a stanza break at the bottom of a page which the reader might not notice. Doing this by hand is not only tedious and easy to get wrong, but also a process you will have to start over again if anything about your volume changes — if you add a poem, say, or even decide to break a title across two lines. `poemscol` takes care of this process, so that the editor need never worry about it, automatically marking cases where the page break coincides with a stanza break with a symbol.

`poemscol` includes facilities for typesetting parallel text editions of poems, for instance to compare different versions or translations of the same poem on the recto and verso pages. `poemscol` will keep the line numbering of the two texts separate, will provide separate endnote sections for textual notes, emendations, and explanatory notes for the different texts, and will also make marginal markers to tie lines in the verso text to the equivalent line in the recto text.

`poemscol` is also suited for verse drama, and the package `dramatist` has been modified to work with `poemscol`.

`poemscol` can provide line numbers and notes for prose sections such as the author’s introduction or prose poetry. (It can also handle inset prose passages in the midst of verse, pausing and restarting verse line numbering as the editor desires.) It also has some limited facilities for typesetting and annotating line-numbered parallel passages in prose. `poemscol` is not, however, designed for typesetting critical editions of large scale prose works, although very possibly it could be tweaked to work. For critical editions of prose works, several other packages are available, including the `EDMAC` format, a `TEX` format analogous to but distinct from `LATEX`, by John Lavagnino and Dominik Wujastyk, or `ledmac`, a port of `EDMAC` into `LATEX` originally by Peter Wilson and now maintained as `reledmac` by Maïeul Rouquette, or `ednotes`, a completely independent set of commands for critical editions which builds on `manypar` and `lineno`, by Uwe Lück.

`poemscol` can number and annotate prose marked in “paragraph number: sentence number” format (or bible chapter and verse). The advantage of this method

of numbering lines of prose is that what is numbered is something the author chose to create (sentences and paragraphs) rather than an accidental feature of typesetting (line numbers). Paragraph and sentence numbering will also be stable across multiple editions, and, like line numbers in verse, provides a common system of reference.

`poemscol` provides the ability to make cross references to verse line numbers, to line numbers in prose sections, or to paragraph and sentence numbers in sections with “paragraph and sentence” annotation.

`poemscol` also provides a few bells and whistles, such as the ability to create new endnote or footnote sections on the fly, the ability to center a poem on the longest line (or to move the margin of the verse block wherever you wish), and the ability to place a mark in the margin indicating where in the apparatus commentary on that line can be found. For long poems, `poemscol` can provide a special running header which indicates the range of lines to be found on the page. It has a special command to place the publication date under the poem just at the left margin of the verse block even when the verse block is centered. `poemscol` also provides notes to be placed just after a poem (rather than at the bottom of the page or in the endnote sections). It gives the user fine control over the placement of line numbers and the placement and format of titles including multi-line titles. The user can choose whether to concatenate the notes for a poem into a single paragraph, or to give each note a separate paragraph. The user can print the notes in single or multicolumn format. The names of things like the Contents can be changed to facilitate editions in languages other than English. Just about every feature of `poemscol` can be easily customized.

The best features of `poemscol` are of course simply that it is `TeX`: it uses `TeX`'s automatic kerning and setting of ligatures, its algorithm for justifying lines (in prose sections), and `LATeX`'s way of setting verse.

Using `LATeX` to typeset critical editions offers more advantages than simply the ability to automate tedious and easy to fumble tasks. `TeX` compilers have the ability to produce output in Adobe pdf format. Adobe pdf output can be used as camera ready copy, saving your publisher time and expense, and perhaps making a marginally economic critical edition a bit easier to bring to press. Furthermore, since typesetting the edition yourself in `LATeX` obviates the publisher's own typesetting of your text, it removes another possible source of new errors. (You should expect to work with your publisher on the final design of the book, but `LATeX` is a flexible language which will enable you to reproduce most book designs.)

Editions made in the formats of proprietary software such as QuarkXPress[©] or InDesign[©] will become not only obsolete but unreadable if those programs pass from use. Since your `LATeX` sources for your edition are in ASCII, or perhaps Unicode, they provide a permanent record of your local intentions at every point in your edition, whether or not those who wish to consult your files have access to a `LATeX` compiler, or indeed (since most of the commands have self-explanatory names) whether or not they can read `LATeX` code.

Although `LATeX` is a typesetting language, not a content markup language, the ability to create new commands which the language offers comes very close to enabling one to realize the ideal of completely separating content markup from

formatting. One advantage of this kind of markup is that even if the appearance of the poem on the page may be ambiguous, the editor's intentions about the logical structure of the poem will be preserved in the \LaTeX source. Should you wish later to produce an electronic edition of your work, perhaps using the XML markup approved by the Text Encoding Initiative, transforming your texts from \LaTeX to XML would largely (although not entirely) be a matter of performing a series of global search-and-replaces, and could conceivably be done with XSLT or with perl.

This is a long manual, but there is no need to study it all before beginning. In the first place, it includes all the commented-on source code for the package, which will only matter to you if you are planning to customize it in some way I didn't anticipate, or if you need to know how the commands work internally. (The code section begins on page 71.) The most important commands are explained in the first 30 pages, and even there many sections discuss things you may not need to know immediately. Also, many sections conclude with a subsection which suggests ways of customizing the output, usually giving suggestions in increasing order of difficulty. You'll have to be the judge of what to skip the first time through.

2 Dependencies and compatibility with other packages

2.1 General

`poemscol` depends upon several other packages, which you should be sure you have in your preamble and search path: `fancyhdr` for managing the running headers, `makeidx` and `multicol` for managing the index, `geometry`, and `iftthen` and `keyval` to simplify page geometry.

If you are planning to generate multiple indices, substitute `splitindex` for `makeidx` in your list of packages.

2.2 Prose sections

If you plan to number lines in prose contexts, and to make textual notes, emendations, or explanatory notes in prose contexts, you will need to add the `lineno` package to your preamble. I use the "right" and "modulo" options with this package, but you can set the options however you wish to make how you number the lines of prose sections consistent with how you number the lines of verse sections.

2.3 Multi-layer footnotes

If you plan to use paragraph-formatted footnotes rather than endnotes, you should load `manyfoot`. You should load it with the "ruled," and "para" options. (`poemscol`'s footnote commands are just a wrapper around `manyfoot`.) `manyfoot` inherited some of the limitations of \LaTeX in dealing with long inserts at the end of the page, so you may have to do some fiddling. As fixes to these problems

emerge, I will incorporate them into `poemscol`. `manyfoot` does not allow multiple paragraph footnotes when typesetting in “para” mode. This is probably a feature, not a bug, since one would want such notes to be set in several paragraphs, rather than running them together into one, as `manyfoot` would naturally want to do in para mode. For that reason, I have defined the two traditional classes of note in which multiple paragraph notes are likely to appear, “sources,” and “explanatory notes,” to be typeset in “plain” mode, which opens a new paragraph with each note. If your textual notes or emendations sections also have multiple paragraph notes, you should re-define them in order to produce footnotes in plain rather than in para mode, if you wish to produce footnotes rather than endnotes.

`manyfoot` sometimes gets into conflicts with other packages over the number of `\counts` it uses, causing L^AT_EX to complain that there is no room for a `\newcount`. If this happens, issue `\usepackage{etex}` and `\reserveinserts` in your preamble.

2.4 Special running header for long poems

For long poems, it is a convenience to have a running header that includes information about what lines of the poem appear on that page in the form firstline–lastline. The `fancypagestyle` `longpoem` will set that information in the running header. That page style uses the `\marks` mechanism, and requires more `\marks` than are available by default. To use it, you will need to add the `etex` and `emarks` packages to your preamble.

2.5 Verse drama and dramatist

Massimiliano Dominici has made his `dramatist` package compatible with `poemscol`, for which I am very grateful. Versions 1.2a or later of `dramatist` are compatible with versions 2.3 or later of `poemscol`.

2.6 Parallel text editions

If you are using the six pre-defined endnote sections for parallel text editions (`\rectotextnote`, `\versotextnote`, `\rectoemendation`, `\versoemendation`, `\rectoexplanatory`, `\versoexplanatory` and their prose equivalents `\rectoprosetextnote` and so on) you won’t need to add any new packages. If you are defining your own endnote sections using `\definewnotetype` you may need the `\keeptitlestraight` hack described below at section 17, page 62. If you use `\keeptitlesstraight` you should add `etoolbox` to your package list.

2.7 Crop marks

`poemscol` no longer provides cropmarks, but is compatible with the style packages that do. I use `crop`, with the `letter`, `pdftex`, `cam`, and `center` options.

2.8 Incompatibility with memoir and verse

Unfortunately, `poemscol` is not compatible with the `memoir` class and the `verse` package, because they share some command names. I will eventually prepare a workaround for this problem.

2.9 Conflict with BibLaTeX

`BIBTEX` works with `poemscol` with no problem. But a bug I haven't yet tracked down (probably involving `\makeatletter`) complicates the use of `BibLaTeX`. To use `BibLaTeX` you will need to open up the `.bbl` file. You will find near the top the following lines:

```
\makeatletter
\@ifundefined{ver@biblatex.sty}
  {\@latex@error
  {Missing 'biblatex' package}
  {The bibliography requires the 'biblatex' package.}
  \aftergroup\endinput}
{}
```

Just comment out these lines and you will be able to use the `.bbl` file as usual.

2.10 Compatibility with earlier versions of poemscol

Making `poemscol` compatible with `lineno` required me also to change the commands for turning verse line numbering on and off, which means that version 2.3 of `poemscol` is incompatible with prior versions. The old command `\makelinenumbers` has been replaced with `\makeverselinenumbers` to distinguish it from a command from the `lineno` world. (`\makelinenumbers` will still work, but I have deprecated it.) To turn on verse line numbering, issue `\makeverselinenumbers`. Because the counter “`linenumber`” has been changed to “`verselinenumber`,” you must use `\global\verselinenumbersfalse` to turn off line numbering, rather than `\global\linenumbersfalse` as before.

Up to version 2.44 `poemscol` borrowed the code for `\sidepar` non-floating marginal paragraphs from the `memoir` class, and also made `\leftsidepar` and `\rightsidepar` commands on their model. Version 2.46 modified Peter Wilson's original code for `\sidepar`, so therefore I have changed the names of `\sidepar`, `\leftsidepar`, and `\rightsidepar` to `\pmclsidepar`, `\pmclleftsidepar` and `\pmclrightsidepar` respectively. If you used any of these commands in your files, you will need to change their names.

Up to version 2.5 the `\definewnotetype` command took four arguments, using the third argument for both the running header for the notes section and for the entry in the table of contents. In order to make it easier to handle titles in languages other than English I have found it necessary to separate these two uses, so `\definewnotetype` now takes five arguments. You will need to retrofit files that use the old version of this command. You can see the details at section 8, page 34.

Version 3 introduced the boolean `\ifleftaligntitles`, for aligning the title with the left edge of a verse block centered on the longest line. Version 3.1 introduces new title placement schemes, including one which centers the title on the longest line of a verse block at the left margin. This made the meaning of `\ifleftaligntitles` ambiguous. So I have changed that boolean to `\iftitlesatleftmarginofcenteredblock`.

Up to version 3.141 the marginal marks associated with poem titles set by `\JHpoemtitle` and `\margrefstextnote` moved in towards the verse block when the verse block is centered on the longest line. These marks could be returned to their normal position in the margin by setting the boolean `\margrefstomargin` to true. As of version 3.141 these marks are set in the margin by default even when verse block centering is in effect. The boolean `\margrefstomargin` controls nothing, but has been left in case I decide to restore the possibility of moving the marginal marks in when the lines are centered. You can control the horizontal placement of these marginal marks by changing the value of the length `\JHmarginparsep`.

3 Marking up individual poems

First, a word about the command names. The command names may seem ugly and long. And there are separate commands for many tasks that seem closely related, such as a command to mark the title of a section of a poetic sequence, and a separate command to mark a subsection. But the names do describe pretty much what each command does, and they do specify exactly what the object they mark is supposed to be. The markup is designed to look like content markup, marking objects as a poem title, as a stanza, as a line, and so on. `poemscol` gives all of these content terms typographical meaning.

There are also many commands for special purposes whose necessity may not seem clear until the editor finds him or herself in the jam the command was designed for. For instance, `poemscol` normally encourages a page break before the title of a poem, or before the title of a section of a poetic sequence, to discourage page breaks between the title and the poem. But for the first section of a poetic sequence, or the first section of a poem in sections, one does not want to encourage L^AT_EX to break the page before the section title, since that would leave the title of the sequence or the title of the larger poem as an orphan on the previous page. `\sequencefirstsectiontitle` and its siblings are designed for this situation. Although all commands like `\sequencefirstsectiontitle` discourage page breaks before the title (and all of the commands discourage page breaks after the title), widowed or orphaned titles, and orphaned first lines will still sometimes happen, particularly if you have a multi-line sequence title followed by a multi-line section title. For these cases, a page break at some other suitable point will have to be explicitly issued to move widowed or orphaned lines to better places.

3.1 The title of the poem

`\poemtitle` `\poemtitle`, as its name implies, sets its argument as the title of the poem. The

command takes one argument — the title, of course. The command typesets the title in the body of the volume (testing first to see whether there is enough space at the bottom of the page to get the title and a couple of lines of the poem in), typesets the title in the table of contents (with the page number), typesets the title in the textual notes (adding the page number, and checking to see whether there is room enough on the page), and prepares similar entries in the lists of emendations and in the explanatory notes (if you need them) as well as in the endnote sections for any species of endnote you have defined for yourself. `poemscol` gives default values for such things as the font size, the separation between the top of the title and the bottom of the previous poem, the separation between the bottom of the title and the first line, and so on. It also sets penalties in order to encourage page breaks just before a title, and to discourage page breaks between a title and a poem.

You can change all these values in your preamble by changing the value of the parameters for the relevant commands, listed below in the implementation section, using either `\setlength` or `\renewcommand` (depending upon what you are changing). Some common values you might change are described in section 3.1.3.

3.1.1 Title placement schemes

There are a number of places where a title might be set. I have defined for this purpose five “title placement schemes.” For each one there is a boolean which turns on the choice, and a “scheme” command which switches that boolean on and switches off the booleans for the other schemes. They are

- Aligned with the left print margin, or indented from it according to the scheme of title indentations (whether it is the title to a poem, to a section, to a subsection, or so on). The hierarchy of indentations for various kinds of title is described below at section 13.13, page 51. I will call the boolean that describes this situation `\ifnormaltitleindentation` because it was the default for `poemscol`. You invoke this title scheme with the command `\normaltitleindentationscheme`
- Aligned with the left margin of a left-aligned verse block. The verse block is normally inset from the left print margin by the length `\leftmargini` (the default distance between the left margin of a list environment — I defined titles as lists — and the surrounding text). I will call the boolean that describes title placement at the left verse margin `\iftitlesatleftversemargin`. You invoke this title scheme with the command `\titlesatleftversemarginscheme`.
- Centered over the longest line of a left-aligned verse block. I will call the boolean that describes this title placement `\iftitlescenteredonleftverseblock`. The corresponding command is `\titlescenteredonleftverseblockscheme`.

- Aligned with the left margin of a verse block centered on the page on the longest line. This will be associated with the boolean `\iftitlesatleftmarginofcenteredblock`. (In version 3.0 this boolean was called `\ifleftaligntitles`. I have removed that boolean because its meaning is ambiguous now.) The command to invoke this title scheme is `\titlesatleftmarginofcenteredblockscheme`.
- Titles centered over a centered verse block. I call this `\ifcentertitleson`. The corresponding command is `\centertitlesscheme`. I have retained the command `\centertitles` from earlier versions of `poemscol` for compatibility. This scheme can also be used to center the titles (and epigraphs, headnotes and other top matter) over a non-centered verseblock too, if you don't use the optional argument to `\begin{poem}` describe in the next section, or if you turn off centering of the verse block by issuing the boolean `\textcenteringturnedonfalse`.

3.1.2 Using title placement schemes: verse width and title width

`\centertitlesscheme`, `\titlescenteredonleftverseblockscheme`, and `\titlesatleftmarginofcenteredblockscheme` require additional information about each poem. Here are some details about the uses of these schemes.

`\centertitlesscheme` For each poem you wish to center you will have to set the length of the length variable `\versewidth` to the width of the longest line. To do this, use `\settowidth` as follows:

```
\settowidth{\versewidth}{text of longest line}.
```

`\centertitlesscheme` will center the titles even if you do not center the verse block on the longest line. To center the verseblock use the optional argument to `\begin{poem}` as follows:

```
\begin{poem}[\versewidth].
```

(For further instructions about how to center the verse block on the longest line, see section 3.2.2 on page 15.)

`\centertitlesscheme` also moves in epigraphs, headnotes, attributions, and dedications towards the center. Since an epigraph or a headnote may be a prose paragraph, or a passage of verse, it would be unwise to set them in a centering environment, so `\centertitles` just moves the margins of epigraphs and headnotes in towards the center. To adjust the placement of epigraphs and similar things, see section 13.1, page 40. Single line epigraphs, attributions, and dedications, however, will be centered if `\centertitlesscheme` is in effect. There are special commands for single line epigraphs, attributions, or dedications. To set these, issue `\shortpoemepigraph`, `\shortpoemdedication`, or `\shortpoemattriution`.

`\titlescenteredonleftverseblockscheme`

Using `\titlescenteredonleftverseblockscheme` scheme will require you to make known the width of the longest line of the poem being set *and* the width of the title. You will need to use the `\settowidth` command to set the length of `\versewidth` and `\poemtitlewidth`. For example:

```

\settowidth{\poemtitlewidth}{poem title}
\settowidth{\versewidth}{text of longest line}.

```

Normally you should not use the optional argument to `\begin{poem}` with this title scheme. But you may have already marked up all your poems such a way as to leave open the choice of centering them. You can turn off centering of the verse block, without erasing all of the optional arguments, by issuing `\textcenteringturnedonfalse`. You can turn on centering the text block again by issuing `\textcenteringturnedontrue`.

In this scheme, `\shortpoemepigraph`, `\shortdedication`, and `\shortattribution` will not center their arguments on the line, but set them flush with the beginning of the title.

If you don't set the length of `\poemtitlewidth` this scheme will simply set the left margin of the title over the center of the poem. (This may be an effect you want.)

Note: this scheme will only yield proper results if the title is shorter than the longest line is.

`\titlesatleftmarginofcenteredblockscheme`

Rather than centering the title over a centered block of verse, one might prefer to align the title with the left margin of the centered verse block. The length `\versewidth` is used both to center the verse block and to place the title at the verse block's left margin. You will need to use `\settowidth` to set the length of `\versewidth` before issuing `\poemtitle` or the other title-making commands (such as `\sequencesectiontitle`). Issue `\settowidth{\versewidth}{Text to be used for centering}` just before you issue the `\poemtitle` or `\epigraph` command. In addition, you must center to verse block by using the optional argument `\versewidth` to `\begin{poem}`, for example: `\begin{poem}[\versewidth]`

For more about how to use `\settowidth` to center the verse block or to align titles, epigraphs, and so forth with the left margin of the verse block, see section 3.2.2, page 15.

Consult the table to see when you should issue `\settowidth` and when you should use the optional argument to `\begin{poem}`.

Table 1: Placement in Title Schemes

Scheme	Lengths to Set	Argument to <code>\begin{poem}</code>
<code>\normalindentationtitlescheme</code>	None	None
<code>\titlesatversemarginscheme</code>	None	None
<code>\titlescenteredonleftverseblockscheme</code>	<code>\poemtitlewidth</code> <code>\versewidth</code>	None
<code>\titlesatleftmarginofcenteredblockscheme</code>	<code>\versewidth</code>	<code>\begin{poem}[\versewidth]</code>
<code>\centertitlescheme</code>	<code>\versewidth</code>	<code>\begin{poem}[\versewidth]</code>

3.1.3 Customization of titles

`\leftalignepigraphs` You may also wish to align epigraphs, dedications, attributions, or head-

notes with the left margin of the verse block (even if you center the titles). To do this, issue `\leftalignepigraphstrue` to set the boolean `\ifleftalignepigraphs`. `\leftalignepigraphstrue` will also align attributions, dedications, and other pre-texts of poems. (It will not affect the dedications and attributions on volume title pages, which are set using the `\volumededication`, `\volumeepigraph`, and `\volumeattribution` commands.) A new group of commands, `\shortpoemepigraph`, `\shortpoemededication`, `\shortpoemattriution`, `\JHshortepigraph` and `\JHshortdedication` will appear at the places controlled by the new “title schemes” listed above. These commands will not obey `\leftalignepigraphs`.

`\poemtitlefont` `\poemtitlefont` globally sets the font size (and leading) for all poem titles in the main text. For instance, you can change the font parameters for the font for setting poem titles from 14 points type on 18 points leading to 12 on 14 by issuing `\renewcommand{\poemtitlefont}{\fontsize{12}{14}\selectfont}` in your preamble. There are similar commands to set the font size and leading for the titles of poetic sequences, sequence sections, titles of volumes, and so on. You can find a complete list of those font parameters at section 22.1.1, page 72.

`\poemtitlefont` and its siblings do not change the default typeface. To change the default typeface to, say, Times Roman, or Tex Gyre Pagella, use the commands `\LaTeX` or `\XeLaTeX` provide for that purpose (e.g. `\usepackage{tgpagella}`). Changing the default typeface is probably something you would want to do globally, not at the level of classes of title, anyway.

`\contentspoemtitlefont` `\contentspoemtitlefont` globally sets the font size (and leading) for poem titles in the table of contents. There are similar commands for each of the other kinds of titles in the table of contents. They can be changed just as the font parameters for titles in the main text are changed, using `\renewcommand`. You can find a complete list of those font parameters at section 22.1.1, page 72.

`\afterpoemtitleskip` `\afterpoemtitleskip` sets the vertical separation between a poem and its title. To change its value, for instance, to `\medskip` (the default is `\smallskip`), issue `\renewcommand{\afterpoemtitleskip}{\medskip}` in your preamble. `\afterpoemskip` sets the vertical separation between the end of a poem and the title of the next poem. “Skips” for other kinds of title can be changed the same way. You can find a complete list of these skips at section 22.2, page 78.

`\poemtitlepenalty` `\poemtitlepenalty` encourages but does not require a page break just before a poem title. To change the penalty, for instance, from -1000 to -3000, issue `\renewcommand{\poemtitlepenalty}{\penalty-3000}` in your preamble. Penalties for other kinds of title can be changed the same way. A complete list of all of the special commands for setting font sizes, skips, and penalties, is in section 14.1, page 53, below.

`\putpagenumberinnotesfalse` If you don’t want the entry in the notes section for this poem to include the page number of the poem, issue `\putpagenumberinnotesfalse`.

`\titleindent` `\titleindent` is an internal command for indented parts of titles. You should change it with caution. In the commands for setting the sections and subsections of poetic sequences, `poemscol` uses `\titleindent` internally to set up a hierarchy of indentations. (A section of a sequence is indented one `\titleindent`. A subsection is indented two. And so on.) `\titleindent` is also used internally in

the commands for multiple line titles. Instructions about changing the value of `\titleindent` can be found in section 14.1. Each kind of title, for poems, sections of poems, sequences, and so forth, has its own default indentation both in the text and in the table of contents. You can see a list of these default values, and instructions about how to change them, at 13.13, page 51.

3.1.4 Subtitles and special titles

`\poemsubtitle` Subtitles of poems should be issued as the arguments to the `\poemsubtitle` command.

Multiple line titles (if it matters how they are broken up on page), titles of subsections of poems, titles of sequences of poems, titles of the elements of a sequence of poems, and “empty” titles (for untitled poems) are all special cases, with special commands, which will be dealt with below at sections 13.5 and 13.7. You can also create new varieties of title. For instructions on how to do this, see section 13.12 below, page 50.

3.2 The body of the poem

3.2.1 The poem environment

`poem` The body of every poem should be placed in a `poem` environment. Putting the body of the poem between `\begin{poem}` and `\end{poem}` resets the line counter to 1, puts the poem in a modified `verse` environment (to handle run over lines automatically), and turns off automatic hyphenation with the `poem` environment.

`pmclverse` `poemscol` slightly modifies the `verse` environment from the standard `LATEX` definition, increasing the indentation used for run over lines, in order to make the difference between the indented run over portion of a long line, on one hand, and an explicitly indented second line, on the other, more obvious in the output. `poemscol` also adds a little bit more white space between stanzas than the standard `LATEX` `verse` environment does. (I found that the standard stanza breaks did not leap out on the page as stanza breaks.) The verse environment for `poemscol` is `pmclverse`, defined below on page 80. You don’t have to place poems explicitly in the `pmclverse` environment. The `poem` environment automatically opens (and closes) `pmclverse`.

3.2.2 Customizing the poem environment

`\versewidth` The `poem` environment uses an optional argument to center the verse block on a line of a given width. If your poem has short lines, and you wish to center it on the page, rather than set it against the left margin of the normal `poem` environment, you can give the width of the line you want to use to center the poem as the optional argument. To center a verse block 30 ems wide, for instance, issue `\begin{poem}[30em]`.

Rather than specifying the length explicitly, you can use the length `\versewidth` as the optional argument to `\begin{poem}`. You can set the length of `\versewidth` to the proper amount using `\settowidth` as follows:

`\settowidth{\versewidth}{Text of line to use for centering}.`

Once you have set `\versewidth` to center the poem on a sample line, you use it to center the `poem` environment this way:

`\begin{poem}[\versewidth].`

Notice that the optional argument is in square braces, not in curly braces.

If you are planning to align the poem title with the left margin of the centered verse block you should use the `\versewidth` method to center the verse block, since `\versewidth` is used to place the title in that case. (You can just enter a length into the optional argument of `\begin{poem}`, but in that case, if you are left-aligning the poem title, you should set `\versewidth` to that value by issuing e.g. `\setlength{\versewidth}{30em}`.)

`\linenumberscenteredwithverse` If you want to center the verse on the page using the optional argument to `\begin{poem}`, you probably also want to move the line numbers in, so as to be closer to the line. `poemscol` will do this by default. If you wish to leave the line numbers at the margin, set the boolean `\linenumberscenteredwithverse` to false. For centered verse, the distance between the line numbers and the verse can be set by setting the length of `\marginparsepmin` (not `\marginparsep`). The default value of `\marginparsepmin` is 2 em.

`\centertitles`
`\ifcenterepigraphson` If you center the poem on a sample line, you probably also want to center the title of the poem too, which you can do by issuing `\centertitles`. (`\centertitles` invokes the title centeringscheme.) If you decide against centering the title, you can either just remove or comment out the `\centertitles` command, or switch a boolean by issuing `\centertitlesonfalse`. By default, `\centertitles` also moves epigraphs, dedications, headnotes, and attributions toward the center. To prevent this, issue `\centerepigraphsonfalse`. This boolean applies to the regular `\epigraph`, `\headnote` and `\dedication` commands, not to the single-line `\shortpoemepigraph`, `\shortpoemededication` and `\shortpoemattriution` commands, whose places are defined by the title scheme that is in force when they are issued.

`\iftextcenteringturnedon` Suppose you have marked up many poems with the optional second argument to `\begin{poem}`, which would cause the text block to be centered on the longest line, but change your mind about centering all the poems. You can turn off centering, without erasing all of the second arguments, by issuing `\textcenteringturnedonfalse`. You can turn on centering the text block again by issuing `\textcenteringturnedontrue`.

`\versemarginadjust` If you don't want to center the verse block on the longest line, but do want to adjust its horizontal placement, you can adjust the placement of the verse block by changing the value of the length `\versemarginadjust`. For most commonly used type sizes, setting `\versemarginadjust` to 28pts will put the verse block at the left margin, aligned with the page number.

3.2.3 Hyphenation is off in the poem environment

`poemscol` turns off automatic hyphenation in poetry environments. The idea here is that every hyphen in the printed poem is authorial, obviating the need for you

to compile a hyphenated-lines list to distinguish between authorial hyphens and hyphens you added for lineation purposes. Line-ending hyphens should not be a feature of verse anyway, I think.

You may wish to restore automatic hyphenation in poetry environments for your own edition. If you do so you must keep track of added hyphens yourself. This list will be easy to compile, however, because only authorial hyphens will appear in your source code. Automatically added hyphens will appear only in the output. (You might even modify the output routine so that automatically added hyphens have a different look. That would be non-trivial, but Donald Knuth has an exercise about doing just that in *The T_EXbook*.) To restore automatic hyphenation, copy the definition of the `poem` environment (below at page 90) and redefine the environment using `\renewenvironment`, commenting out the line that reads `\language=255`. Place the renewed definition of the environment in your preamble, with `\makeatletter` before the renewed definition and `\makeatother` after it. If you are restoring automatic hyphenation for a parallel-text edition, be aware that `\startparalletexts` also (defined below at page 167) redefines the `poem` environment, so you will have to change `\startparalletexts` using `\renewcommand` as well.

`poemscol` turns automatic hyphenation back on in prose contexts, so if you wish to keep a hyphenation list for such things as authorial prefaces and so on, you must do so yourself manually. (Alternatively, you can turn automatic hyphenation off in those contexts as well, by setting the `\language` to 255. For an example of how to do this, look at the definition of the `poem` environment in the implementation section below. If you do turn automatic hyphenation off, it would be wise to restrict the change to some particular environment, rather than changing the `\language` globally. You might wish, for instance, to turn automatic hyphenation off in the `prosesection` environment.)

3.2.4 The stanza environment

`stanza` Every stanza should be placed in its own stanza environment. Every poem should have at least one stanza. Marking the beginning and end of every stanza (with `\begin{stanza}` and `\end{stanza}`) provides `poemscol` with a way of detecting cases in which a page boundary falls on a stanza break, since in those cases a page turn happens when one is *inside* a poem environment but *not* inside a stanza environment. Further, marking the beginning and end of every stanza makes the logical structure of the poem (and the editor's intentions about it) clear to readers of your source code. If you want to change the `stanza` environment consult its definition below at page 88.

`indentedverse` To indent stanzas (or stretches of verse) relative to the margin you can use the `indentedverse` environment. You can also set different stanzas or passages at a hierarchy of levels of indentation. (For how to do this, see section 3.3.1 below, page 19.)

`\stanzaatbottom`
`\nostanzaatbottom` If you wish to change the symbol used to mark cases in which a break falls on a page turn, issue the command `\stanzaatbottom`, using as the argument whatever you wish to use to mark such cases. The default is `\stanzaatbottom{*}`, which is

suitable for a published volume. If you are preparing a typescript for submission, you may wish to set `\stanzaatbottom` to “stanza break.”

If you wish also to mark all cases where there is *not* a stanza break at the bottom of the page, issue the command `\nostanzaatbottom`, using as the argument whatever you wish to mark such cases. The default is `\relax` (which is to say, “don’t do anything”).

3.2.5 Verse lines and line numbering

<code>\verseline</code>	<code>\verseline</code> should mark the end of every line, except the last line of every stanza (which should be marked with <code>\end{stanza}</code>). <code>\verseline</code> marks the end of every line as a prosodic unit (since a line of verse is not simply a carriage return), and advances the line counter. There are commands below for changing the line counter’s horizontal placement (how close it is to the left or right margin of the line) and appearance. (See section 22.11 for these.)
<code>\setverselinemodulo</code>	<code>\setverselinemodulo</code> sets how often a marginal line number appears. To print a line number every five lines, issue <code>\setverselinemodulo{5}</code> . The default value is 10.
<code>\makeverselinenumbers</code>	Marginal verse line numbering is on by default. To turn line numbering off, issue <code>\global\verselinenumbersfalse</code> . To turn it back on, issue <code>\makeverselinenumbers</code> .
<code>\verselinenumberstoright</code> <code>\verselinenumberstoleft</code>	To put all of the line numbers to the left, issue <code>\verselinenumberstoleft</code> in your preamble. <code>\verselinenumberstoright</code> puts the line numbers in the right margin. (These two commands use non-floating marginal note commands derived from the memoir class, <code>\pmclleftsidepar</code> and <code>\pmclrightsidepar</code> , respectively.)
<code>\verselinenumbersouter</code> <code>\verselinenumbersgutter</code>	If you wish the line numbers to appear in the outer margins of each two-page spread, issue <code>\verselinenumbersouter</code> in your preamble. If you want the line numbers to appear in the inner margins, issue <code>\verselinenumbersgutter</code> in your preamble. (These two commands use <code>\pmclsidepar</code> , derived from <code>\sidepar</code> from the memoir class, but modified by Dan Leucking.)
<code>\marginparsep</code>	You can adjust the distance between the marginal line number and the text with <code>\setlength{\marginparsep}{your length}</code> . The default value for <code>\marginparsep</code> is 18pt, and the default value for the width of the box in which the line numbers are set, <code>\marginparwidth</code> , is 18 pt. If you are setting with the line numbers to the right, <code>\marginparwidth</code> can be as small as you wish, although your log file will be full of complaints if you make it too small. But if you are setting with the line numbers to the left, if <code>\marginparwidth</code> is narrower than the width of the line number, the line number will be moved down a line. Setting <code>\marginparsep</code> to zero lines the verse line numbers up with the page numbers, and puts both at the margin. If you move the verse line numbers by changing <code>\marginparsep</code> , you can move the page numbers to keep them aligned by changing <code>\headoffsetlength</code> to the same value.
<code>\marginparsepmin</code>	If the verse block is centered on the longest line, the distance between the line numbers and the verse can be set by setting the length of <code>\marginparsepmin</code> (not <code>\marginparsep</code>). The default value of <code>\marginparsepmin</code> is 2em.
<code>\pmclsideparvshift</code>	The line numbers should print on the baseline. You can adjust them to move

them up or down by changing the value of a length called `\pmclsideparvshift`. The default value is `\setlength{\pmclsideparvshift}{0ex}`.

3.3 Special line markup

3.3.1 Indentation, line breaks, runover, and broken lines

`\verseindent` The `\verseindent` command is to be used for formally indented lines. It should not be used to indent the run over portion of long lines (which `poemscol` handles automatically anyway). `\verseindent` indents the line a bit less than the run over portion of long “bent” lines are indented, so that the two cases can be visually distinguished. By default, the length of `\verseindent` is 2 em. To change it, say to 3 em, you should change the length `\verseindentamount` by issuing `\setlength{\verseindentamount}{3em}`.

You can create a hierarchy of indentations by issuing `\verseindent` multiple times. But you can also use an optional argument to `\verseindent`, with the number indicating how many levels of indentation to add to this line, like so `\verseindent[3]` for the third level of indentation, (with each level being one `\verseindent` deep). If you use this option, don’t put any white space between the end of the `\verseindent` command and the beginning of the poetic text, otherwise `poemscol` will add about 10pt of unwanted extra white space. (The only real consequence of forgetting about this will be that `\verseindent[1]` will be about 10pts deeper than plain `\verseindent`, which may not really be an issue for you.)

`indentedverse` You might want to indent whole stanzas, or perhaps extended passages of verse, relative to the rest of the poem (you might, for instance, want to indent refrains systematically). This would be tedious to do using `\verseindent`. Put stretches of verse you wish to indent in the `indentedverse` environment. Whatever is in this environment will be indented. The indentation will be of the length `\indentedstanzaamount`, which is by default set to `\verseindentamount`, which by default is 2 em. You can change `\indentedstanzaamount` to 3em, by issuing `\setlength{\indentedstanzaamount}{3em}`.

You can also set a hierarchy of intended stanzas or passages by issuing an optional argument to `\begin{indentedverse}`. So, for instance, `\begin{indentedverse}[2]` will indent that environment by two `\indentedstanzaamounts` (4 em), and `\begin{indentedverse}[3]` will indent that environment by three `\indentedstanzaamounts`, or 6 em. Note that if you use the optional argument, you must enclose it in square brackets, not curly ones. Note also that (for reasons I have not been able to track down) `\indentedverse[1]` indents the stanza slightly more deeply than plain `\indentedverse`. To preserve a consistent look for a hierarchy of indented stanzas, use `\indentedverse[1]` for the lowest level of indentation, not plain `\indentedverse`.

`\linebend` `poemscol` automatically runs over long lines, indenting the run over portion on the next physical line. If you are unhappy with where `poemscol` has run over a particular line, you can “bend” that line by issuing `\linebend` at the point where

you wish it to run over. The run over portion of the line will be indented just as if `poemscol` had “bent” the line at your selected point. This command only works if you have chosen to bend the line at some point earlier than `poemscol` would have chosen on its own.

You may also wish to use `\linebend` to reproduce how your author broke up long lines on the page (if you know that your author cared about such things and did not leave them up to the typesetter).

`\linebend` should only be used for managing run over lines, not for cases in which a line is to be broken into separate half-lines. For cases in which a line is to be broken into half-lines, use the `\brokenline` command. The two commands do similar (but not identical) things. But a “linebend” is a feature of typesetting, and a “broken line” is a feature of versification, and it seems best to distinguish them logically. (`\linebend`, like `\brokenline`, issues a carriage return without incrementing the line number, but `\linebend` adds indentation to the next line.)

If you want to extend a line further into the right margin, beyond the normal break point, you can probably do so by using a combination of `\nobreak` and `\hbox`, or by turning all of the spaces in that line into unbreakable spaces, marked with `~` in your source. But `poemscol` will complain if you do this, and rightly so, since the result is likely to be ugly. It would probably be wiser to adjust the lengths `\leftmargin` and `\rightmargin` in the definition of the `pmclverse` environment, allowing all of the lines to be a little bit longer. The `pmclverse` environment is defined below, at section 22.4, page 80.

`\runoverindent`

To change the indentation for the run over portion of verse lines globally, issue the amount of indentation you desire as the argument to `\runoverindent`. `\runoverindent` is currently set to 6 em, rather more than the standard amount in the definition of the \LaTeX `verse` environment. By default, the runover portion of long lines is indented. You may wish to flush the runover portion to the right margin instead. For instructions about how to do this, see section 3.3.3, page 22.

`\brokenline`
`\versephantom`

`\brokenline` should be used where you wish to break the line without incrementing the line counter. Authors often break a line into two half-lines, setting the beginning of the second half-line flush with the end of the first half-line. (Sometimes these broken lines indicate a change of speaker. Sometimes they just indicate a change of subject, usually an abrupt one, a change which calls attention to itself by interrupting a line rather than waiting for a line break or stanza break). `\brokenline` is normally used with `\versephantom`, which adds white space exactly as long as its argument would have been had it been set in type. `\versephantom` thus provides an easy way of setting the beginning of the second half-line flush with the end of the first, whatever the font size or special formatting of the first line.

The sestet of Yeats’s sonnet “Leda and the Swan,” has such a broken line:

A shudder in the loins engenders there
The broken wall, the burning roof and tower
And Agamemnon dead.
Being so caught up,
So mastered by the brute blood of the air,

Did she put on his knowledge with his power
Before the indifferent beak could let her drop?

To set the broken line properly, issue:

```
And Agamemnon dead.\brokenline  
\versephantom{And Agamemnon dead.} Being so caught up,\verseline
```

`\stanzalinestraddle` Some poets (such as Robert Penn Warren) occasionally introduce a stanza break in the middle of a broken line, considering the line to be a single metrical unit despite the fact that it straddles a stanza break. To record these cases, mark the end of the first half-line with `\end{stanza}` as usual. But instead of opening the next stanza with `\begin{stanza}` issue `\stanzalinestraddle` instead. This will make sure that the line counter counts the straddling line as only one line, despite the stanza break. `\stanzalinestraddle` is usually used with `\versephantom`.

3.3.2 Customizing broken lines

`\tweakbrokenline` By default, `poemscol` sets the line numbers level with the ends of broken lines. If the line numbers are set to the right of the text, this seems the obvious choice. Conceivably you might want to set the line number level with the beginning of a broken line when the line numbers are set to the left. To ensure that the line numbers of broken lines are set level with the beginning of a broken line when the line number is on the left, issue `\tweakbrokenline` in your preamble.

You should issue `\tweakbrokenline` with caution, because although it changes how `\brokenline` is handled, it does not change the handling of long lines with `runover`. `Runover` lines will still set the line number level with the end of the line. You can have `runover` lines set their line number level with the beginning of the line by issuing `\startverseline` at the beginning of the line.

`\brokenlineatbeginning` Conceivably you might want `\brokenline` to set the line number level with the beginning of the line in every case. To do this, issue `\brokenlineatbeginning` in your preamble. If you do this, you should be prepared to mark the beginning of `runover` lines with `\startverseline`.

`\startverseline` If you begin a verse line with `\startverseline` the line number will be set level with the beginning of the line rather than with the end. This is useful, for instance, if you want to ensure that the line number of a line with `runover` is set level with the beginning of the line. You can, if you don't want to keep track of where `runover` lines are, start every line with `\startverseline`.

`\tweakstartverseline` Rather than setting the line number of every `runover` line level with the beginning of the line, it may make more sense for you to set the line number level with the beginning in cases where the line number is to the left, and level with the end in cases where the line number is to the right. You might want to do this, for instance, if you have decided to set all the verse lines at the outer margin (by issuing `\verselinenumbersouter` in your preamble), or have decided to set all the verse lines at the inner margin (by issuing `\verselinenumbersgutter` in your preamble). To ensure that `\startverseline` does this, issue `\tweakstartverseline` in your preamble.

3.3.3 Right-flushed runover lines

`rightflushverse` By default, `poemscol` indents the runover portion of long lines by the amount `\runoverindent` (by default 6 em). It is possible to set verse so that the runover portion is flushed to the right margin. To do this, you should put the `\rightflushverse` environment inside the `\poem` environment. And you must mark the beginning of each verse line with `\rightversebegin`. Christian Ebert has reminded me that the `\rightflushverse` environment must be issued *inside* the poem environment. Otherwise it simply flushes every line to the right.

It is rather clumsy to need a special environment for verse with right flushed runover. I plan to provide a command for switching between a verse environment that indents runover lines and a verse environment that flushes runover lines to the right. I have seen examples of this kind of environment from Markus Kohm and Christian Ebert, but so far I haven't been able to persuade them to play well with `poemscol`

3.4 Cross references by line number

`\poemlinelabel` `\poemlinelabel` enables crossreferences by line number. To make a line label, issue `\poemlinelabel{text of label}` right after the line to which you wish to refer, where “text of label” is some distinctive label you can use for a reference elsewhere. (You should issue the command *after* the `\verseline` or `\end{stanza}` command, to make sure that the line number will be correct.) To produce the reference, just issue `\ref{text of label}` as usual. (`\poemlinelabel` is just a crudely hacked version of `\label` from L^AT_EX.) `\pageref{text of label}` will set the page number of the page on which the label appears.

4 Making a table of contents

4.1 Setup

`\makepoemcontents` I found the normal L^AT_EX commands for making tables of contents for scholarly works unsuited for making tables of contents of poetry, so I have provided my own. To make a table of contents for your poems, issue `\makepoemcontents`.

`\makepoemcontents` takes an optional argument, which sets the page number for the table of contents. If your publisher wishes to add some front matter so that the contents will appear on page vii, you should issue `\makepoemcontents[7]`.

It might seem as though you would want to issue this command in your preamble. In fact it is better to issue it in the body of the document, immediately *after* issuing the `\putpoemcontents`, the command which inputs and typesets a table of contents from a prior run. If you issue `\makepoemcontents` before issuing `\putpoemcontents`, you will simply erase the table of contents from the prior run (the one which will have all the contents information you are intending to use) and enter an empty table of contents into your document.

4.2 Printing the table of contents

`\putpoemcontents` Information for your table of contents will be written to an external file with the extension `.ctn`. `\makepoemcontents` creates this file, and opens an output channel to send information to it. `\putpoemcontents` closes the file and reads it into your document.

You will need to run your book through \LaTeX twice in order to generate a table of contents, the first time to generate the titles and the references for the page numbers, and the second time to use the labels to which the references point to enter the page numbers. (Under some circumstances — if you have an index, for instance — you may need three passes rather than two.)

`\resetpagestyle` Because the table of contents uses a special page style and special fonts `\putpoemcontents` issues `\resetpagestyle`, which restores the default fancy page style to “main” once it has input the contents, and restores the font size to `\normalsize` as well.

`\pagenumbering` Be sure to reset the style of page numbering (from `\pagenumbering{roman}` to `\pagenumbering{arabic}`) after issuing `\putpoemcontents`, since when you read in the external file created by `\makepoemcontents` the page numbering will be set to roman numerals. The command `\resetpagestyle` (which is called by `\putpoemcontents`) will reset the fancy page style to that used in the main body of the volume, but it won’t change the page numbering to arabic, in case there is some frontmatter between the contents and the main text, so you should be sure to do so yourself. (Front matter is normally given page numbers in roman numerals.) If you neglect to issue `\pagenumbering{arabic}` at the end of your front matter, the page numbering will remain in roman numerals. The notes sections use the page numbers from the poem to construct running headers of the form “Notes to pp. xx–yy.” If those numbers are roman numerals rather than arabic ones, `poemscol` will not recognize them as numbers, and you will get the infamous “Missing Number” error that puzzles so many users of \LaTeX .

4.3 Contents entries for notes sections and the index

`\puttextnotes` `\puttextnotes`, and its siblings `\putemendations` and `\putexplanatory`, input the formatted endnotes sections into your document, and put entries for them into your table of contents. You will have to run \LaTeX again to set the page numbers of those sections in the table of contents properly. The first run sets the title of the endnotes section and a label to find the page number to add to the table of contents, and the second run actually sets page number. (These commands are described below, in section 11.) All of these commands also restore normal hyphenation for the endnotes sections.

`\putpoemindex` `\putpoemindex` inputs the formatted index (after your raw entries have been processed by `MakeIndex`), and adds an entry for it into the table of contents. Remember that if you are making an index of titles and first lines you may need to run your file through \LaTeX twice more after running `MakeIndex`, to put the entry for the index and its correct page number into your table of contents.

`\putmultiplepoemindex` Use `\putmultiplepoemindex` instead if you are making several indices. For

instructions about `\putmultiplepoemindex` see section 5.3, p. 26.

4.4 Customizing contents entries

Lines in the table of contents usually include an indent (how much of one depends upon what the entry is — whether it is a volume title, a poem title, or something else), then the title itself. If the entry is for a poem, for a section of a poem, for a poetic sequence, or for a section or subsection of a poetic sequence, a slash follows the title, followed by the page number. All of the commands that generate lines in the table of contents are somewhat messy and somewhat rigid, but you can modify them if you wish. Here are some ways of customizing contents entries, in increasing order of difficulty.

`\setcontentsleaders` By default the title and the page are separated by a slash (actually by `~/~`). If you wish to change this, say to put dot leaders in instead, issue what you wish to use as the argument to `\setcontentsleaders`. For instance `\setcontentsleaders{\poemdotfill}` will flush the number to the right margin, and insert leading dots up to the number. The argument to `\setcontentsleaders` can be whatever you wish to use to separate the title from the page number, such as a colon, a hard space (`~`), or even `\hfil` to flush the page number to the right margin.

`\contentspoemtitlefont` You can change the font sizes that are used to set particular classes of title in the contents by redefining the commands that are used to set the font size for that kind of title. For instance, if you wanted to set the titles of all poems in 12 point type on 14.5 point leading, issue

```
\renewcommand{\contentspoemtitlefont}{\fontsize{12}{14.5}\selectfont}
```

in your preamble. You can find a list of the various relevant font size commands below at section 22.1.1, page 72.

`\contentsindentoneamount` You can also change the amount of the indentations used in the hierarchy of indentations in the table of contents by changing the value of the elements of that hierarchy. You can change “`contentsindentoneamount`” (the amount a poem title is normally indented, by default 24pt) to, say, 36pt, by issuing `\contentsindentoneamount=36pt` in your preamble. You can find all of the values in the contents indentation hierarchy at section 22.2, page 76.

`\pmclcontentsentry` There is a simple way of adding a new contents entry using the command `\pmclcontentsentry`. The command creates an entry on the model of the entry for the textual notes section. It takes three arguments. The first is the title of the section. The second is the indentation of the entry (typically `\contentsindentone`, `\contentsindenttwo`, or `\contentsindentthree`, but any indentation command will do). The third is the page number. Remember that `\contentsindentone` is a command, not a length. The length of the indentation is `\contentsindentoneamount`. The command is defined as `\hspace{contentsindentoneamount}`. You can suppress the page number by setting the boolean `\putpagenumbersincontentsfalse`.

A more general way to add a entry in the table of contents is to use the command `\pmclecontentsentrydefaults`. This command takes four arguments: (1) The title (2) the indentation command (3) the font size (e.g. `\contentendnotesfont` for the same font size used in contents entries for the endnotes sections) and (4) the page number. Here also you can suppress the page number by setting the boolean `\putpagenumbersincontentsfalse`.

`\setlength`

To change the amount various kinds of title are indented in the Table of Contents, see below at section 13.14, page 52.

`\renewcommand`

You can also make global changes to the appearance of a particular kind of contents entry. To change the appearance of a kind of entry (for all sections of sequences of poems, for instance), go to the definition of the title of that kind of entry (e.g. `\sequencesectiontitle`) below, and copy the definition into a `\renewcommand` for that kind of title; find where that command calls the `\c@ntentsinfo` command, and change the arguments to that command to suit you. (You should consult section 13.12, page 50, to see what all of the arguments to `\c@ntentsinfo` do.) Put the whole renewed version of the title command into your preamble, being sure to issue `\makeatletter` before the `\renewcommand` and to issue `\makeatother` after it. (You have to put this whole `\renewcommand` between `\makeatletter` and `\makeatother` because `\c@ntentsinfo` and several other commands called to set titles include the `@` character, which you can't use in command names except in the `.sty` file. Internal commands like `\c@ntentsinfo`, which are used by other commands but are under most circumstances not meant to be invoked by users directly, have an `@` in their names so that the user won't accidentally redefine them.) You can find the commands for making titles below at section 22.15.1, page 109.

Here, for instance, is the code that defines titles for sections of poetic sequences:

```
\newcommand{\sequencesectiontitle}[1]{%
\set@p@emtitle{#1}{\poemtitlepenalty}{\poemtitlefont}
{\titleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}
{\titleindentamount}
\c@ntentsinfo{#1}{\contentsindenttwo}{\contentspoemtitlefont}
{\contentsindentthreamount}
\t@xtnotesinfo{#1}}
```

Notice in the above that entries for sequence sections in the table of contents are given the indentation `\contentsindenttwo`. To give them the indentation `\contentsindentthree` and to set the runover portion of long titles with the indentation `\contentsindentfour` put this in your preamble:

```
\makeatletter
\renewcommand{\sequencesectiontitle}[1]{%
\set@p@emtitle{#1}{\poemtitlepenalty}{\poemtitlefont}
{\titleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}
{\titleindentamount}
\c@ntentsinfo{#1}{\poemsectiontitleindent}{\contentspoemtitlefont}
{\contentsindentfouramount}}
```

```
\t@xtnotesinfo{#1}}
\makeatother
```

`\c@contentsinfo` You can make even more sweeping and fundamental changes in the look of your table of contents by redefining the `\c@contentsinfo` command itself, which can be found below at section 22.15.1. Think very hard about this before doing it.

5 Making an index of titles and first lines

5.1 Setup

`\indexingontrue` First you must add the `makeidx` package to the list of packages you call in your preamble. (If you are planning to set several indices, call `splitindex` instead.) Then, to set up the Index section of your volume, issue `\indexingontrue` in your preamble. This will create the external file for your index information and send that file the typesetting information for its title. You must process this external file (the `.idx` file) with `MakeIndex` to create a properly organized and formatted index. `MakeIndex` sorts the various multi-level “index cards” generated by all of the `\index` commands in your source files.

5.2 Printing the index

`\putpoemindex` Once you have processed your `.idx` file with `MakeIndex`, and generated the sorted and formatted `.ind` file for your book, the `\putpoemindex` command will insert the typeset index where you issue it, and put an entry for your index in your table of contents. You will have to run your file through \LaTeX twice again to make the page number for that entry correct.

`poemscol` sets up a two-column index with a simple running header. (Setting up a two-column index, however, requires that you include the `multicol` package in your `\usepackage` list.) To turn indexing off, issue `\global\indexingonfalse`.

Enter the individual index entries in the poems as you normally would for use by `MakeIndex` (say, after each title and first line). One of the nice features of `MakeIndex` is that every entry has two parts, one for specifying the sort key of the entry (or subentry), the other for specifying the font and typesetting information of the entry (or subentry). This enables you to drop all of the initial uses of “the” in titles for sorting purposes, while still including the “the” in the title. It also enables you to distinguish titles from first lines (by italicizing them), and to include typesetting information (such as italicization) in titles or first lines without messing up their sort order.

5.3 Making multiple indices

`poemscol` can work with `splitindex` to generate more than one index. You might, for instance, wish a separate index of titles and index of first lines, or an index of

proper names. To do this, call `splitindex` in your list of packages. Then, in your preamble, declare the indices you are planning to use, e.g.:

```
\newindex[Index of Titles]{idx}
\newindex[Index of First Lines]{fir}
\newindex[Onomastic Index]{ono}
```

The second argument is the “shortcut” defined by `splitindex`, and will be used to mark index entries in your text (see below), and used also as the extension for the external index files used by `MakeIndex`.

Then mark up individual entries. Some entries (in the example above, the “Index of Titles” examples) can be marked up with `\index` just as if you were using only one index. Entries for other indices should be marked using the `\sindex` command from `splitindex`, as follows

```
\sindex[fir]{Of Man’s first disobedience and the fruit}
```

where the first argument is the “shortcut” and the second is the index entry. If you are loading `splitindex` with the `split` option, the different types of index entry will be sent to separate output streams, which each must be processed separately with `MakeIndex`. `TEX` has only a limited number of such output streams, however, so it is probably wiser not to choose that option, but to use `splitindex.tex`, `splitindex.pl`, or one of the other means provided with the `splitindex` package to break up the index into the separate parts, each of which must be processed with `MakeIndex` separately.

To include the indices, and to add entries for them to the table of contents, issue `\putmultiplepoemindex` for each one. `\putmultiplepoemindex` takes four arguments, which are: 1. The three letter “shortcut” used by `\splitindex`, 2. The title of the Index on its first page, 3. The running header for that index section, and 4. The name of the section as you wish it to appear in the Table of Contents. So, for instance

```
\putmultiplepoemindex{fir}{INDEX OF FIRST LINES}{Index of First
Lines}{First Line Index}
```

includes an index with shortcut “fir,” title “INDEX OF FIRST LINES,” running header “Index of First Lines,” and contents entry “First Line Index.”

6 Collections with multiple volumes

`volumetitlepage` The `volumetitlepage` environment is an environment for divider pages in collections made up of several volumes. Volume title pages will always appear on recto pages with blank verso pages. `poemscol` will also automatically create a blank verso page preceding the volume title page if it is necessary. The `maintitlepage` environment is for the title page of the whole book. The main title page will also

automatically always be on a recto page. These divider pages have special page styles, with no page numbers and no running headers.

<code>\wholebooktitle</code>	<code>\wholebooktitle</code> is for the title of the entire collection. <code>\volumetitle</code> is for the title of an individual volume within a Collected Poems. <code>\wholebooktitle</code> merely sets its argument in a very large font. <code>\volumetitle</code> also sets an entry in the table of contents (with no page number, but followed by extra vertical space) and in the endnotes (with no page number).
<code>\volumetitlefirstline</code> <code>\volumetitlemiddleline</code> <code>\volumetitlelastline</code> <code>\volumesubtitle</code>	The <code>\volumetitlefirstline</code> , <code>\volumetitlemiddleline</code> , and <code>\volumetitlelastline</code> commands are for multi-line titles of volumes gathered into the collection. (Use these last commands if you want to specify how a long title is broken up both in the text and in the table of contents. <code>poemscol</code> will break up long titles on its own anyway if you don't specify how to break them up, but you might not be happy with how it breaks up the lines.) <code>\volumesubtitle</code> is for setting the subtitle to a volume. In addition to setting the text in the body of your edition, these commands send the title (and the formatting information about it) to the table of contents file and to the various endnotes files.
<code>\volumesectiontitle</code>	<code>\volumesectiontitle</code> is for setting the title of a section of a volume. <code>\volumesectiontitle</code> merely prints the title in a large font in boldface in the text. It always prints at the top of a page, but it does not ensure that that page is a recto page, does not reserve the whole page for the title, or put a blank verso page following the title. It prints the title in the contents without a page number, and prints the title in the textual notes (but not in the other endnote sections) in boldface on a separate line. Because it is so different from other titles, it does not use the three internal commands (<code>\set@p@emtitle</code> , <code>\c@ntentsinfo</code> , and <code>\t@xtnotesinfo</code>) that all of the other title commands use, so modifying those internal commands will not change <code>\volumesectiontitle</code> .
<code>\volumeepigraph</code> <code>\volumeattribution</code>	<code>\volumeepigraph</code> and <code>\volumeattribution</code> are for epigraphs and attributions on the divider pages.
<code>\volumeheader</code> <code>\lefthead</code> <code>\righthead</code>	<code>\volumeheader</code> or <code>\righthead</code> is for setting the right running header for that volume (except for divider pages, the table of contents, the notes sections, and other special cases). Normally that is just the name of the particular volume. <code>\lefthead</code> is for setting the left running header for the entire book (except for divider pages, the table of contents, the notes sections, and other special cases). Normally that is the name of the entire book.

7 Recording textual notes, emendations, and explanatory notes

7.1 Setup for endnote sections

<code>\maketextnotes</code> <code>\makeemendations</code> <code>\makeexplanatorynotes</code>	To collect textual collations, issue <code>\maketextnotes</code> in your preamble. To collect emendation notes, issue <code>\makeemendations</code> in your preamble. To collect explanatory notes, issue <code>\makeexplanatorynotes</code> in your preamble. These commands open external files for emendations, textual collations, and explanatory notes (with extensions <code>.emd</code> , <code>.ent</code> , and <code>.enx</code> respectively). <code>poemscol</code> reads these
--	--

files back into the main document at the place you specify with `\puttextnotes`, `\putexplanatory`, or `\putemendations`, or at the end (if you use the `\finish` command). These commands also send to the external files the commands for typesetting the title of each section (e.g. Explanatory Notes), for making an entry in the table of contents for each endnote section, and for modifying the running headers of the notes sections to xx–yy format (e.g. “Explanatory Notes to pp. 55–7”).

`poemscol` opens an entry (headed with the title, and the page the poem appears on in the body of the text, in boldface) in the textual notes section for every poem (since, minimally, you want to include information about the variants and copy text of the poem). In the emendations or explanatory notes sections `poemscol` sets this information only if you actually have emendations or explanatory notes on that poem. If you have defined a new endnote section using `\definewnotetype` `poemscol` will also only set the poem heading in the notes if there actually is a note for that poem.

The notes for each poem are set in a block paragraph, with a new paragraph for every `\poemtitle` command, and the line counter for the notes is reset to 1 with every `\begin{poem}`. (For long poems in books or cantos, it you might use `\poemtitle` for the canto names or numbers, or perhaps you might want to design a new species of title using the commands described below at section 13.12, page 50.)

By default, there is one paragraph per poem, with a hanging indent to give prominence to the page number.

If you wish to use multi-layer footnotes rather than endnotes, you do not need to issue `\maketextnotes` or its relatives (but you should of course issue `\textnotesatfoot` or its relatives). You can mix footnotes or endnotes as you wish. You may, for instance, wish to set explanatory notes as footnotes, and textual notes and emendations as endnotes. Instructions for setting up `poemscol` to make such footnotes are in section 9 below.

7.2 Customizing endnotes

`\iftextnotessinglepar`
`\ifemendationssinglepar`
`\ifexplanationssinglepar`

You may, particularly if you are annotating long poems, wish each note to appear in its own paragraph rather than in a block paragraph with the other notes to that poem. To do this, you need to set the relevant boolean. Issue `\textnotessinglepartrue` `\emendationssinglepartrue` or `\explanationssinglepartrue` to give each such note a separate paragraph. (Similar booleans will be automatically defined for any species of endnote you create.) By default, these notes will have a hanging indent, to give prominence to the line number.

`\noteindentation`

You may have notes with multiple paragraphs. The default settings for all of the forms of endnotes set them with hanging indentation, which probably is not a good idea for multiple paragraph notes. There are two ways of approaching this problem. The first way is to change all of the paragraphs of the notes to normal indentation, which you can do by issuing `\literaltextnote{\setlength{\parindent}{\noteindentation}}` just after

issuing `\maketextnotes`. You can change the amount of indentation by changing the value of the length `\noteindentation` (the default value is 1 em). You should remember to issue similar commands for emendations, explanatory notes, and whatever kinds of notes you create using `\definewnotetype`.

`\noteparbreak`

Alternatively, if you want to keep the hanging indent for the page number, but still have paragraph breaks in the note, issue `\noteparbreak` whenever you want a paragraph break in the midst of a note. The first paragraph will have a hanging indent for the page number, but every paragraph that follows a `\noteparbreak` will have normal paragraph indentation. By default, `\noteparbreak` indents the new paragraph 1em. You can change this by changing the value of the length `\noteindentation`.

`\iftextnotestwocol`

`\ifemendationstwocol`

`\ifexplanationstwocol`

By default, notes are set in single columns. To set them in two column mode, set the relevant booleans to true, e.g. `\textnotestwocoltrue`. Again, any note type you create with `\definewnotetype` will automatically define the “twocol” boolean that goes with it.

`\putpagenumberinnotesfalse`

`\puttitleinnotesfalse`

You may not wish to have the poem’s page number and title appear in the notes. To turn off the appearance of the page number in the notes, issue `\putpagenumberinnotesfalse`. You may also not wish to put the poem’s title in the notes. To turn off the appearance of the poem’s title in the notes, issue `\puttitleinnotesfalse`. `poemscol` assumes that the notes to a poem will begin with either the poem’s title, or its page number, or both, so although you can set either boolean to “false,” don’t set both of them to “false.” `poemscol` will let you do this, but the results will be strange. Also, `\puttitleinnotesfalse` applies only to the textnotes. Emendations, explanatory notes, and any note types you create with `\definewnotetype` will include the title of the poem.

`\contentsendnotesindent`

`\contentsendnotesfont`

You can control the appearance of the entry for endnote sections in the table of contents by changing the definition of `\contentsendnotesindent` (set by default to `\contentsindentone`) or `\contentsendnotesfont` (set by default to `\contentspoemtitlefont`.)

7.3 Textual notes of various kinds

`\sources`

To record information about the copy text, editions and publication history of individual poems, or any information not tied to specific lines in the poem, you should place that information in the argument to the `\sources` command. `\sources` sends information to the external file for textual notes, but does not tag what it sends with line numbers, hence its use for sending “sources.” Typically, you should issue this command after you have issued `\poemtitle` and before you issue `\begin{poem}`. That way the “sources” will appear in the textual notes section just after the title of the poem, but before the notes on particular lines. You could conceivably use `\sources` send typesetting information to the textual notes file (such as to force a page break), but I prefer to do that by using `\literaltextnote`, which also sends information to the external file for textnotes without sending line numbers. Although they do the same thing, I use `\sources` to send editorial information to the textual note section, but use `\literaltextnote` to send formatting instructions to the textual note section, so that the different purposes of the note

are clear at first glance. You can send typesetting information to other sections by using `\literalemend`, `\literalexplain`, or `\literalcontents`. `poemscol` also creates a similar “literal” command for any type of endnote you create on the fly using `\definewnotetype`.

There is one subtle difference between `\sources` and `\literaltextnote`. If you issue the commands to set your textual notes as footnotes rather than endnotes, notes issued with `\sources` will be set as footnotes, but anything issued using `\literaltextnote` will be discarded. To set textual notes as footnotes, see section 9, page 36, below.

<code>\textnote</code>	<code>\textnote</code> is used to capture variants and tie them to the correct line number.
<code>\emendation</code>	You don’t have to count line numbers; <code>poemscol</code> keeps track of them for you. Issue
<code>\explanatory</code>	<code>\textnote</code> immediately after the <code>\verseline</code> command which marks the ending of the line you wish to comment upon. Put the text of your note (which may be simply the recording of a variant in standard notation) into the argument of the command. You should put both the lemma and the variants or comment in the argument to the <code>\textnote</code> command. For emendations, use <code>\emendation</code> , and for explanatory notes, use <code>\explanatory</code> . These notes go to their own endnote sections. The only difference is that each poem opens a new paragraph (headed with the poem’s title and page number) for its own textual notes, but such paragraphs for explanatory notes or emendations are only opened if there actually are explanatory notes or emendations for that poem.

<code>\sameword</code>	To put the <code>~</code> glyph in your note (used for recording places where the variant and the copy text have the same word, as for instance when recording a variation of punctuation) use <code>\sameword</code> . To put the <code>^</code> glyph into your text (used for recording places where a punctuation mark is missing in a variant), use <code>\missingpunct</code> .
------------------------	---

For notes that refer to ranges of lines, `\textnote`, `\emendation`, and `\explanatory` have an optional argument, which records how many lines the note refers to. There are two ways of using this argument. The grubby but simple way is simply to put into the argument the number of lines it refers to. If, for instance, you issue `\textnote[4]{lemma rest of note}`, `poemscol`, rather than printing merely the number of the line which closed just before you issued `\textnote`, will print a line range, beginning at that line, and ending at the fourth line after it. If that `\textnote` were issued after line 214, this is to say, the output in the textual notes would be: 214–218: lemma] rest of note.

It seems clumsy to count the lines referred to by a note, especially since you don’t have to count lines to set where the note begins. A more sophisticated way, and one which involves no counting, is to make a unique poem line label for the last line of the range by issuing `\poemlinelabel{some unique label}` just after the `\verseline` or `\end{stanza}` that ends the range. (To use `\poemlinelabel` see section 3.4.) Then, back after the `\verseline` or `\end{stanza}` command that closes the first line of the range, put the text of the label into the optional argument of `\textnote` as follows: `\textnote[some unique label]{lemma]rest of note}`. This is the preferred method. The line-counting method is deprecated, but retained for backwards compatibility with earlier versions. If you use the label method, you will have to run your file through \LaTeX twice, once to define the labels, and once to set the

text.

Here is a complete example:

```
Yes, then I met the beast. Well, better, indeed,\verseline
\textnote[had it been the]{better, indeed, / Had it been the] better if
it / Had been the 1953TS (revised in black pencil
on 1953TS to 1953)}
Had it been the manifest beast and the circumstantial\verseline
\poemlinelabel{had it been the}
Avatar of destruction. But no beast then: the towering\verseline
Definition, angelic, arrogant, abstract,\verseline
Greaved in glory, thewed with light, the bright\verseline
Brow tall as dawn. I could not see the eyes.\end{stanza}
```

Overlapping lemmas, or lemmas that include stanza breaks, do not pose any difficulties for `poemscol`.

`\emendation` and `\explanatory` are used exactly as `\textnote` is. Issue the emendation or the explanatory note as the argument to the command. Place the command immediately after the `\verseline` that concludes the line to which it is a comment. These commands also can take optional arguments to specify line ranges.

`\accidental`

`\accidental` behaves exactly like `\textnote`. Accidentals are included by default, but if you issue `\global\includeaccidentalstrue` in your preamble, you will remind yourself of that fact. If you wish to distinguish between accidentals and substantives, using `\accidental` provides a way of doing so.

If you wish to exclude accidentals from your printed output, but to mark them in your source files, so that your published collation in the textual notes endnotes section consists only of substantives, issue `\global\includeaccidentalsfalse` in your preamble. Many publishers are reluctant to publish accidentals, believing that they are, well, less substantive than substantives. Using the `\accidental` command allows you to exclude accidentals from the published version should your publisher insist, while preserving the information about them in your source files should the publisher's mind change. In the very worst case, if you have marked all the accidentals in this way you can still produce a list of accidentals for later use, and other scholars can search for accidentals in your source files simply by searching for the string `\accidental`.

`poemscol` does not provide for a separate backmatter section for accidentals, but it would be trivial to construct one, using `\definewnotetype`, described in section 8 below. You may, for instance, use `\definewnotetype` to create a command called `\newaccidental`, then issue `\let\accidental=\newaccidental`.

`\tsvariant`

`\tsentry`

Some publishers may turn up their noses at typescript or manuscript variants (changes on a manuscript or typescript as opposed to differences between published versions) in just the way they turn up their noses at accidentals. If you wish to distinguish between published variants and typescript, manuscript, or galley variants, `\tsvariant` (for a whole note) and `\tsentry` (for a typescript entry in a list of variants in a textual note that includes other kinds of variant) provide ways

of doing so. By default, typescript variants are included. To exclude typescript variants, issue `\global\includetypescriptsfalse` in your preamble. You can issue `\global\includetypescriptstrue` in your preamble, to remind yourself that you are including typescript variants. In that (default) case `\tsvariant` will behave exactly like `\textnote`, and entries in other notes marked with `\tsentry` will be included in your output.

Here is how to use `\tsentry`: if you wish to include typescript entries in a single note including those entries in a list with variants from other published versions (as for instance when a word appears in a typescript but only in the second edition of the published poem), simply issue `\textnote` as usual, marking the relevant variant in the list of variants with the `\tsentry` command. If typescript variants are excluded, the typescript entry will also be excluded.

Here is a typical use of the `\tsentry` command:

```
Of moonlit desert. A stallion, white and flashing, slips,\verseline
\textnote{Of moonlit} Of the moonlit {\em NY\}\tsentry{, SP85TS
(revised in black pen to SP85)}
```

Notice that since the `\tsentry` comes in the middle of the list, it begins with a comma. You might expect an `\unskip` command before the comma, to prevent L^AT_EX from adding white space before the comma. `poemscol` automatically provides the `\unskip` if the entry starts with a comma or a semicolon.

You can mark individual variants with `\tsentry` in the arguments to the `\explanatory` and `\emendation` commands as well, and `\tsentry` will also behave normally in any endnote or footnote section you define using `\definewnotetype`.

`poemscol` does not provide for a separate backmatter section for typescript variants, but it would be trivial to construct one, again using `\definewnotetype`. To do this, you would also have to copy all of the emendations, explanatory notes, and textual notes which have a `\tsentry` in their arguments, and add `\tsvariant` commands in those places. For information about `\definewnotetype` see section 8.

`\margreftextnote`
`\margrefexplanatory`
`\margrefemendation`

Some editions include a marginal mark in the text showing where in the apparatus a textual note on that line can be found. (The edition of William Blake's poetry and prose edited by Harold Bloom and David V. Erdman, for instance, includes such marks.) `\margreftextnote` sets a label in the textual notes section, and sets a marginal note with a page reference to that label in the main text. Issue `\margreftextnote` *before* issuing the `\verseline` or `\end{stanza}` that closes the line to which it refers. (The textual note itself can be an ordinary `\textnote`, and should be placed, as usual, *after* the `\verseline` or `\end{stanza}`.) `\margrefexplanatory` does the same thing for explanatory notes, and `\margrefemendation` does the same thing for emendations. If you define a new kind of endnote with `\definewnotetype`, you will automatically also define a new `\margref` command for that kind of note. For details about how these markers work, see section 13.8, page 46.

`\quotedversecorrectiontextnote` If you quote verse *within* a textual note, an explanatory note, or an emenda-

tion, you may want to use the normal L^AT_EX `verse` environment for that quotation, rather than the special markup for `poemscol`. You can also use the special `pmclverse` environment, which enlarges the indentation of runover lines and the white space between stanzas. But you should not use the `poem` environment within the textual notes.

If a textual note *ends* with a quotation in verse, you should follow the `\textnote` entry with `\quotedversecorrectiontextnote`. I found that if I quoted verse in the note sections a dirty trick I used to send the notes to the external files would cause the following notes on that poem in the notes sections to be set in a new paragraph. (This is of course not a problem if the quoted verse is the last thing in the notes to that poem, since the next poem will open a new paragraph in the notes anyway. It is also not a problem if more of the individual `textnote` follows the verse. It's only a problem if the last thing in the note is quoted verse, and the note is not the last one on that poem.) The command should set it flush as it is, but I have found odd cases I can't understand in which that doesn't work, so the command has an optional argument, which should be the additional length you need to adjust the next line by to make it flush. The default is `0pt`. `\quotedversecorrectionexplanatory` and `\quotedversecorrectionemendation` should follow explanatory notes or emendations that end with snippets of verse. These three commands are an embarrassing kludge on my part. They simply send commands to the relevant note sections that prohibit opening a new paragraph. You should issue this command in the main text right after the close of the `textnote` (not in the text of the `textnote` itself).

8 Creating new kinds of endnote

`\definewnotetype` The `\definewnotetype` command can be used to create new kinds of endnote, in case the kinds `poemscol` has predefined do not suffice. `\definewnotetype` takes five arguments. They are (assuming you are creating a new kind of note to be called a “mynote”):

1. A base name used to construct
 - some `\if` variables (e.g. `\ifmynoteson` to see whether you are collecting “mynotes”, `\ifnomynoteyet` to see whether you have written a “mynote” for a particular poem yet, `\ifmynotestwocol` to set the notes in two column mode, and `\ifmynotesinglepar` to set the notes in one paragraph per note form, rather than in block paragraphs). `poemscol` will only open an entry for a poem in the “mynotes” section if there actually is a “mynote” on that poem. Note that every `\if` that refers to a section is plural (`\ifmynoteson`, `\ifmynotestwocol`, `\ifmynotesinglepar`) and that every `\if` that refers to a singular note is singular (`\ifnomynoteyet`).
 - The name for the output channel for writing the notes to the appropriate external file. This name will always be plural (e.g. “mynotes”).

- The name for the “literal” command for writing literal, unexpanded text on the file (as `\literaltextnote` does on the `textnotes` file), and for the note command that sends the actual textual note (line number and all) to the section (e.g. `\literalmynote` and `\mynote`), also the command to write notes in line-numbered prose (e.g. `\prosemynote`) or prose numbered by paragraph and sentence (e.g. `\pmmynote`). These commands will always be singular.
 - The name of the `\put` command (e.g. `\putmynotes`) which closes the external file for the notes section, reads it back in to your document, and adds an entry in the table of contents for that notes section. This command will always be plural. (There won’t be a `\makemynotes` command, because `\definewnotetype` takes its place.)
 - The name of the `\margref` command for putting a marginal mark next to a line giving the page number in the apparatus where a note is to be found (e.g. `\margrefmynote`)
2. The extension for the external file which will hold the notes as you generate them. “Emendations” for instance, are written to an external file called `\jobname.emd` The file name will always be `\jobname`, and the different species of endnotes will all have distinctive extensions. (`\jobname` is a command that always expands to the name of your top level source file. If, for instance, I am setting running a file called “myfile.tex” through L^AT_EX `\jobname.emd` translates to “myfile.emd.”)
 3. The title of the notes section as you wish it to appear in the running header (e.g. “Mynotes to”).
 4. The title of the notes section as you wish it to appear on the first page of the notes section (e.g. “MYNOTES”).
 5. The title of the notes section as you wish it to appear in the table of contents (e.g. “Mynotes”).

So, for instance,

```
\definewnotetype{xyznote}{xyz}{Xyznotes to}{XYZNOTES}{Xyznotes}
```

creates the booleans `\ifxyznoteson`, `\ifnoxyznoteyet`, and `\ifxyznotessinglepar`, the commands `\xyznote`, `\literalxyznote`, `\prosexyznote`, `\pmxyznote`, and `\putxyznotes` (and, although you don’t ever have to use it explicitly, `\firstxyznote`) the output channel `xyznotes`, the external file `\jobname.xyz`, an entry in the contents for “Xyznotes”, and an endnotes section with a running header of the form “Xyznotes to pp. xx–yy” and a title XYZNOTES.

`\xyznote` takes the same arguments that `\textnote` does (which is to say, an optional argument for a label for entering line ranges, and an argument for the

lemma and the comment). There won't be an entry for a poem in the "Xyznotes" endnotes section unless there actually is an xyznote for the poem.

`\prosexyznote` (for "xyznotes" on line-numbered prose passages) takes the same arguments `\prosetextnote` does (which is to say, an optional argument for a label for entering line ranges, an argument for a label to capture the line number of the first line, and an argument for the lemma and the comment). For notes on passages of line-numbered prose, see section 15, page 56.

`\pmxyznote` (for prose passages numbered by paragraph and sentence) takes the same arguments as `\pmtextnote`. For notes on passages of prose numbered by paragraph and sentence, see section 16, page 58.

9 Multi-level footnotes

`\textnotesatfoot` `poemscol` will set multiple levels of footnotes in block paragraphs, separating each level with a rule. To enable this feature, call the `manyfoot` package as follows in your preamble: `\usepackage[ruled,para*]{manyfoot}`.

To set your textual notes as footnotes, issue `\textnotesatfoot` in your preamble. If you do this, `poemscol` will actually create two sets of footnotes for textnotes, one for those that are called with `\textnote`, which will produce an unindented block of notes, and one for those that are called with `\sources`, which will produce individual indented paragraphs, opening a new paragraph with every note. `\sources` notes often have several paragraphs, so they are inappropriate for block-paragraph or "para" mode, and because those paragraphs are often in fact prose paragraphs, rather than blocks of notations, they are indented, so that they will be read as prose. To set your emendations as footnotes, issue `\emendationsatfoot` in your preamble. These notes will be set by default as block paragraphs. If you have multiple-paragraph notes in your emendations, you should redefine these notes to set plain rather than para style notes. (See the next paragraph for how to do this.) To set your explanatory notes as footnotes, issue `\explanationsatfoot`. These notes will also, by default, be plain style notes, with one indented paragraph per note. You do not need to issue `\maketextnotes`, `\makeemendations` or `\makeexplanatorynotes` if you set those notes as footnotes. If you use `\literaltextnote` anywhere in your file, however, you will lose the text it would have put in your textnotes, since `\literaltextnote` just writes its argument onto the external file for textual notes. The arguments to `\literalexplain` and `\literalemendation` will be discarded as well if explanatory notes or emendation notes are set as footnotes.

`\iftextfootnotespara`
`\ifsourcesfootnotespara`
`\ifemendationfootnotespara`
`\ifexplanfootnotespara`

To change the style of your footnotes between plain and para modes, globally change the values some of the following booleans. `\ifsourcesfootnotespara`, obviously, is true if footnotes from the `\sources` command are set in "para" mode (default is false). `\iftextfootnotespara` is true if footnotes from `\textnote` are set in "para" mode (default is true). `\ifemendationfootnotespara`, or `\ifexplanfootnotespara` are the booleans which set the style of footnotes from `\emendation` and `\explanatory` respectively. By default, footnotes from `\emendation` are set in "para" mode (`\emendationfootnotesparatrue`), and

footnotes from `\explanatory` are set in “plain” mode (`\explanfootnotesparafalse`). To change explanatory footnotes from plain to para mode, for instance, issue `\global\explanfootnotesparatrue`. Counterintuitive as it sounds, you must issue this *before* issuing `\textnotesatfoot`, `\emendationsatfoot`, or `\explanationsatfoot`.

When `\sources` is defined to send endnotes to the textual notes section, they usually appear immediately underneath the title of the volume or poem they comment upon in the endnotes section. If you are having `\sources` output footnotes, it would be a good idea to open the note with the title of the volume or poem it is a comment upon, in case there is more than one poem on the page.

When note classes are set as footnotes, the symbol which marks cases in which a page turn falls on a stanza break will be set *beneath* the footnotes. This is a consequence of the way `poemscol` uses the `\mark` mechanism to keep track of these cases, so I have not figured out how to change it. But it may well be more of an idiosyncrasy than a bug, particularly if the symbol is changed from `*` to something like “stanza break at page turn.”

`\DeclareNewFootnote`

To create a new level of footnote, you must first declare it to make it known to `manyfoot`, which requires each level of footnote to be given a unique suffix (usually a capital letter of the alphabet). You can declare a new footnote level called `\footnoteE` for instance, by issuing `\DeclareNewFootnote[para]{E}`. You will want notes which don’t put a mark in the body of the text, and begin with the line number or range of line numbers of the lemma. To define a footnote called `\mynote`, first declare new footnote `\footnoteE` (A, B, C and D are reserved for sources, textual notes, emendations, and explanatory notes, respectively, and H is reserved for use for titles with authorial footnotes). Then issue:

```
\newcommand{\mynote}[2][0]{\setlemmarange{#1}\
\FootnotetextE{\citerange}{#2}
\resetlemmacounters}
```

`\setlemmarange`, `\citerange`, and `\resetlemmacounters` are internal commands to enable your footnote to handle line ranges in the lemma. They are defined in the implementation section below, at section 22.18. If a `\mynote` refers to a range of lines, you can issue the same kinds of optional argument that are used with `\textnote`.

10 Notes at the end of poems

`\poemendnote`
`\makepoemendnotes`
`\putpoemendnotes`

You may wish, rather than using endnotes or footnotes, simply to print your notes at the end of each poem. To do this for simple notes, issue `\makepoemendnotes` just after `\begin{poem}`. Issue `\poemendnote` where you wish to make a note, using the same conventions for line ranges you use for `\textnote`. Where you want to output the notes, issue `\putpoemendnotes`. These notes can have multi-line lemmas, just like textual notes.

`\ifpoemendnotessinglepar`

By default, each poem end note is given its own paragraph. To concatenate them into one big paragraph, issue `\poemendnotessingleparfalse`.

<code>\poemendemendationnote</code> <code>\makepoemendemendationnotes</code> <code>\putpoemendemendationnotes</code>	<p>You can also print emendation notes at the end of each poem. To do this, issue <code>\makepoemendemendationnotes</code> just after <code>\begin{poem}</code>. Issue <code>\poemendemendationnote</code> where you wish to make a note, using the same conventions you use for <code>\textnote</code>. Where you want to output the notes, issue <code>\putpoemendemendationnotes</code>. These notes can have multi-line lemmas, just like textual notes.</p> <p>By default, each poem end note is given its own paragraph. To concatenate them into one big paragraph, issue <code>\poemendemendationnotessingleparfalse</code>.</p>
<code>\poemendexplanatorynote</code> <code>\makepoemendexplanatorynotes</code> <code>\putpoemendexplanatorynotes</code>	<p>You can print explanatory notes at the end of each poem. To do this, issue <code>\makepoemendexplanatorynotes</code> just after <code>\begin{poem}</code>. Issue <code>\poemendexplanatorynote</code> where you wish to make a note, using the same conventions you use for <code>\textnote</code>. Where you want to output the notes, issue <code>\putpoemendexplanatorynotes</code>. These notes can have multi-line lemmas, just like textual notes.</p> <p>By default, each poem end note is given its own paragraph. To concatenate them into one big paragraph, issue <code>\poemendexplanatorynotessingleparfalse</code>.</p>
<code>\poemendtextnote</code> <code>\makepoemendtextnotes</code> <code>\putpoemendtextnotes</code>	<p>You can print textual notes at the end of each poem. To do this, issue <code>\makepoemendtextnotes</code> just after <code>\begin{poem}</code>. Issue <code>\poemendtextnote</code> where you wish to make a note, using the same conventions you use for <code>\textnote</code>. Where you want to output the notes, issue <code>\putpoemendtextnotes</code>. These notes can have multi-line lemmas, just like textual notes.</p> <p>By default, each poem end note is given its own paragraph. To concatenate them into one big paragraph, issue <code>\poemendtextnotessingleparfalse</code>.</p>
<code>\ifpoemendtextnotessinglepar</code>	<p>By default, each poem end note is given its own paragraph. To concatenate them into one big paragraph, issue <code>\poemendtextnotessingleparfalse</code>.</p>

11 Printing endnotes and index

<code>\testforauxonfirstrun</code>	<p>If you don't want to listen to L^AT_EX complain about missing references during your first run, issue <code>\testforauxonfirstrun</code>, which won't let <code>\finish</code>, <code>\putexplanatory</code>, <code>\puttextnotes</code>, or <code>\putemendations</code> run unless there is an <code>.aux</code> file for a previous run. <i>Be sure to issue this command before issuing <code>\begin{document}</code>, since that reads in the existing <code>.aux</code> file, and overwrites it with a new one.</i></p>
<code>\putemendations</code>	<p>This command closes the external file for emendations and reads it in. It also puts an entry for the emendations section into your table of contents. After <code>\putemendations</code> has read in the external file for emendations, you will need to run your file through L^AT_EX again, to put the correct page number in the table of contents file.</p>
<code>\puttextnotes</code> <code>\putexplanatory</code>	<p><code>\puttextnotes</code> and <code>\putexplanatory</code> do the same thing for the textual notes and for the explanatory notes.</p> <p>Each of these last three commands restores normal hyphenation. Since all three are printed with the <code>\small</code> font size, the hyphen character is defined only for that size. This should not create other issues, however, because the commands that prohibit hyphenation in the <code>poem</code> environment (and in the <code>contentsentry</code> environment) are local to those environments, so the restoration of the hyphen character may be redundant.</p>

`\putpoemindex` `\putpoemindex` reads in the index at this point, and adds an entry for the index to external file for the table of contents.

`\putmultiplepoemindex` If you are generating several indices using `splitindex` `\putmultiplepoemindex` reads in one of them at this point. For instructions about this command, see section 5.3, p. 26.

`\finish` The `\finish` command is deprecated but still available. It is designed to be placed just before `\end{document}` (which, in fact, it replaces — but you should still put an `\end{document}` at the end of your document for form’s sake). `\finish` closes the external files for the three notes sections and reads them back into the document (turning the automatic hyphenation back on for these sections). It adds entries to the table of contents file for the notes sections. It reads in the formatted index file (which you have made from your raw `.idx` file using `MakeIndex` between `LATEX` runs) and adds an entry for the index to the table of contents. Then it closes the external file for the table of contents and reads that in (putting it at the end of the document, as I explained before). Then it adds a page explaining that the symbol (by default `*`) at the bottom of certain pages marks places where a stanza break and a page break coincide. If you have an editor’s introduction preceding your notes section, or a list of abbreviations, you may wish to consult the `\finish` command for suggestions about how to add the lines to read those files in and add entries for them in the table of contents.

12 Forewords, Appendices, Contents Entries

`\makeappendix` To make a an Appendix, or any other inserted prose section, use `\makeappendix`. `\makeappendix` takes one argument, the title. The new section will open on a recto page, and its first page will be in the empty page style. The title of the section will appear on the page in the style of the textual notes section. The title of the section will appear in the running header of subsequent pages. An entry for the new section, with the page number, will be added to the table of contents. The entry will be formatted the way the entries for textual notes and explanatory notes are formatted.

`\appendixtitle` If you wish to add an Appendix which you don’t want to start on a new page but do want to have a contents entry for, use `\appendixtitle` instead of `\makeappendix`.

`\makesubappendix` `\makesubappendix` behaves exactly as `makeappendix` does, except the contents entry will be indented by the length `\subappendixtitleindentamount`.

`\subappendixtitle` If you wish to add an Subappendix which you don’t want to start on a new page but do want to have a contents entry for, use `\subappendixtitle` instead of `\makesubappendix`.

`\appendixincontents` If you wish to suppress contents entries for appendices, issue the boolean `\appendixincontentsfalse`. Contents entries for appendices or subappendices will be suppressed so long as that boolean is set to false.

`\makeforeword` `\makeforeword` and `\forewordtitle` behave basically the way `\makeappendix` and `\appendixtitle`. I provided separate commands because it occurred to me that one might want to treat front matter and back matter sections differently in

the table of contents, so I have allowed for different indentations for their contents entries.

`\pmclcontentsentry` If you want to add a line to the table of contents that will follow the formatting of other entries in the contents, issue `\pmclcontentsentry`. `\pmclcontentsentry` takes three arguments. The first is the title you wish to put in the contents. The second is the length of the indentation to appear in the contents (usually `\contentsindentone`, `\contentsindenttwo`, or `\contentsindentthree`, but you can use any arbitrary length). The third argument is the page number. The argument could be a `\pageref` rather than a number. if you define the `\label` for that `\pageref` somewhere else in your file.

13 Special cases

13.1 Epigraphs, attributions etc.

`\epigraph` `\epigraph`, `\headnote`, `\attribution`, and `\poemdedication` set their arguments as epigraphs, headnotes, attributions, or dedications for poems or poetic sequences. There are in addition the special commands `\JHepigraph` and `\JHdedication`, which place a mark in the margin showing where in the notes comments on that epigraph or dedication may be found.

`\volumeepigraph` If you have dedications, epigraphs, or attributions on the divider pages of editions that combine several volumes of poetry, use `\volumededication`, `\volumeepigraph`, and `\volumeattribution`.

`\centertitles` If `\centertitles` or `\centeritlescheme` is in effect, epigraphs, headnotes, dedications, and attributions will all be centered on the page. (`\volumeepigraph`, `\volumededication`, and `\volumeattribution`, however, are unaffected by `\centertitles`.) If your epigraph or headnote is a prose passage of more than one line, or of more than one paragraph, or a verse passage of more than line, or even more than one stanza, the `\epigraph` command will work properly if `\centertitles` is in effect, which is to say it will draw the margins in towards the center, rather than centering the epigraph line by line.

Issuing `\centertitles` moves the margins in on both sides by the length `\centerepigraphindentation` (the default is 6em). The margins for uncentered epigraphs and the like are controlled by the length `\normalepigraphindentation` (the default is 1.5em). Both values can be adjusted by using `\setlength`.

After issuing `\centertitles` you can move epigraphs and similar things back to the margin by issuing `\centerepigraphsonfalse`. After issuing `\centertitles` you can put titles at the margin while leaving epigraphs alone by issuing `\centertitlesonfalse`.

If you use the standard \LaTeX `verse` environment within an epigraph, you may wish to add a `\smallskip` between stanzas. (To my eye that environment does not leave enough white space between stanzas.) Alternatively, you can use the special `pmclverse` environment. You can even use the `poem` environment, but if you do this, you should so mark line breaks with `\\` and stanza breaks with a blank line, as in the standard `verse` environment. If you mark up the epigraph

with things like `\verseline` and `\end{stanza}` you may wind up with marginal line numbers in your epigraph.

You may also wish to align epigraphs, dedications, attributions, or headnotes with the left margin of the verse block (even if you center the titles). To do this, issue `\leftalignepigraphstrue` to set the boolean `\ifleftalignepigraphs`. Remember that for `\leftalignepigraphstrue` to work, you will need to use the `\settowidth` command. Issue `\settowidth{\versewidth}{Text to be used for centering.}` just before you issue the `\poemtitle` command. `\leftalignepigraphstrue` will also align attributions, dedications, and other pre-texts of poems.

`\shortpoemepigraph`
`\shortpoemdedication`
`\shortpoemattrIBUTION`

Because `\centerepigraphs` merely draws in the margins on both sides rather than centering each line line by line, short epigraphs may not appear well centered. `\shortpoemepigraph`, `\shortpoemdedication` and `\shortpoemattrIBUTION`, are better for single line epigraphs, since they will center their arguments line by line.

The commands `\shortpoemepigraph`, `\shortpoemdedication` and `\shortpoemattrIBUTION` will all place their texts in accordance with the title placement scheme you select in your preamble. `\normaltitleindentationscheme` will place them near the left text margin. `\titlesatleftversemarginscheme` will place them at the left verse margin. `\titlescenteredonleftverseblockscheme` will center them over the longest line of a left-flushed verse block. `\titlesatleftmarginofcenteredblockscheme` will place them at the left margin of a centered verse block. `\centertitlesscheme` will center them over a centered verse block. You can center epigraphs and similar things on the page over an uncentered verse block by issuing the boolean `\centerepigraphson`.

`\JHshortepigraph`

I have also defined `\JHshortepigraph` and `\JHshortdedication`, which set marginal marks pointing to where notes on the epigraph or dedication in the textual notes section may be found, in the manner of `\JHpoemtitle`. These commands too obey the title placement scheme that may be in effect.

13.2 Appending publication date

`\poemdate`

You can append the date of the poem with `\poemdate`. Issue `\poemdate` just after `\end{poem}`. You can include both the composition and publication date if you wish simply by including both dates in the argument. (In fact, you can put anything in the argument, not just dates.) By default `\poemdate` places the date one `\bigskip` under the left margin of the verse block of the poem, whether the poem is set at the left margin or whether the verse block is centered on the longest line. You can move the placement of the date left or right by changing the value of the length `\dateindent`. If you wish to change `\dateindent` you will have to issue `\setlength{\dateindent}{your value}` before each instance of `\poemdate`, since `poemscol` recalculates `\dateindent` freshly for every poem.

There is a slight bug in `\poemdate`. If there is a page turn between the last line of the poem and the date, and the last line has a runover portion, the date will be set flush with the indented runover portion of the line rather than with the beginning of the line. This should not in practice be a problem, because you

should use `\longpage` or several `\shortpage` commands to move the widowed date line anyway. (For `\longpage` and `\shortpage` see section 13.15, page 52.)

13.3 Pausing line numbering

`\saveverselinenumber`
`\restoreverselinenumber`

There are cases in which you might want to pause and resume line numbering later at the same number. For instance, you may have inset prose passages which do not take line numbers, but you wish to resume line numbering the verse after the passage. The way to set this is to issue `\end{stanza}` at the end of the stanza before the prose insert. Then issue `\saveverselinenumber`. Then issue `\end{poem}`. Insert the prose quotation (perhaps followed by `\attribution`). Then issue `\begin{poem}` followed by `\restoreverselinenumber` and `\begin{stanza}`. Then begin entering the rest of the poem as usual. Longer, independent prose sections (such as the author's preface or prose poems) require different handling. To provide line numbers and notes for such prose sections, see section 15.

13.4 Quoted verse

`quotedverse`

Sometimes you wish to quote verse within verse (as when a speaker in a verse play quotes a poem). The `quotedverse` environment is designed for this contingency. If you issue `\verseline` commands or the `stanza` environment, line counting and annotation will proceed as usual in quoted verse.

13.5 Multiline poem titles

`\poemtitlefirstline`
`\poemtitlemiddleline`
`\poemtitlelastline`

Very long titles present special problems. In the first place, they require special provisions to make sure that page breaks don't happen in the middle of a title, or immediately after a title. In the second place, they raise questions about how the author wished to break them up over several lines. If you think it might matter, these commands make it possible for you to ensure that long titles are broken in exactly the same way in your text and in your table of contents. (I didn't pursue this question for titles in notes sections, and in notes sections these commands simply concatenate a long title.)

There are similar commands for most but not all of the whole series of titles for sequences, sequence sections, sequence subsections, and so on. If you need commands for a kind of multi-line title that is not already defined, see below at section 13.12, page 50.

Alternatively, you can just let `poemscol` handle the long titles by itself. If you are pretty sure that the author did not care how long titles were broken up, this would probably be the best thing to do. Remember also that if `poemscol` breaks a title across two lines, you can always force it not break the line by using enclosing the argument to `\poemtitle` in an `\hbox`. You may get a complaint on your log file about an overfull `\hbox` if you do this, however.

13.6 Poems in sections

`\poemsectiontitle` `\poemsectiontitle` and `\poemsubsectiontitle`, as their names imply, set their arguments as the titles of sections or subsections of poems. `\poemfirstsectiontitle` is for the first section of a poem with many sections. (It differs from `\poemsectiontitle` in that it tries to make it harder for a page break to separate the title of a poem from the title of its first section.) `\poemsectiontitlefirstline`, `\poemsectiontitlemiddleline`, `\poemsectiontitlelastline`, `\poemsectiontitlenocontents`, and `\poemsectiontitlebaretitle`), as their titles imply, are used for special cases such as long section titles, if you wish to specify explicitly how the title is to be broken up in the text and in the table of contents. You can construct variants of these commands for dealing with special cases I didn't anticipate by using the commands described in section 13.12.

13.7 Poetic sequences

`\sequencetitle` `\sequencetitle` Sequences of related poems, perhaps with an over-title, demand special handling in the text, in the notes sections, and in the table of contents. (A moment's thought will show that they are different in some ways from poems in sections. For one thing, a sequence manifests a different relationship between part and whole than a poem in sections does, and often provides stronger experiences of momentary closure between sections.) `\sequencetitle` sets its argument as the title of the sequence, `\sequencesectiontitle` sets the titles of the sections of the sequence, and `\sequencesubsectiontitle` sets the titles of subsections of the sequence (there is even a command for the title of sub-subsections, `\sequencesubsubsectiontitle`). `\sequencefirstsectiontitle` gives a little more vertical space between the main title and the first section title than `\sequencesectiontitle` gives between adjacent sections later on in the sequence (since the over-title for the sequence is in larger type) and adjusts the page breaking penalties to reflect the fact that such titles should not occur near the bottom of a page, since there should be no page break between the sequence title and the title of the first section of the sequence (although page breaks are permissible, indeed even slightly favored, between later sections). There should also never be a page break between a section title and the first or second line of the section. The penalties `poemscol` sets should take care of these automatically, but you may still have cases which require you to specify a page break with `\pagebreak` or `\newpage`. There are a host of other commands, all with self-explanatory titles, that deal with some special situations that arise in setting the elements of poetic sequences, such as cases where you wish to specify how long titles will be broken up into lines, or where you wish no entry to be made for the section in the table of contents or in the notes sections. These commands don't of course exhaust the dizzying possibilities, but from them you can construct whatever other commands you may need.

Here is a list of all of the defined title commands.

- Commands for Poem titles

- `\poemtitle`
- `\poemtitlefirstline`
- `\poemtitlemiddleline`
- `\poemtitlelastline`
- `\poemsubtitle`
- `\poemtitlenotitle`
- `\poemtitlenocontents`
- `\poemtitlebaretitle`
- `\poemtitleonlycontents`
- `\poemtitleonlynotes`
- Poems in Sections
 - `\poemsectiontitle`
 - `\poemsectiontitlefirstline`
 - `\poemsectiontitlemiddleline`
 - `\poemsectiontitlelastline`
 - `\poemsectiontitlenocontents`
 - `\poemsectiontitlebaretitle`
 - `\poemfirstsectiontitle`
 - `\poemfirstsectiontitlebaretitle`
 - `\poemsubsectiontitle`
- Sequence Titles
 - `\sequencetitle`
 - `\sequencetitlefirstline`
 - `\sequencetitlemiddleline`
 - `\sequencetitlelastline`
 - `\sequencetitlenonotes`
- Sequence Sections
 - `\sequencesectiontitle`
 - `\sequencesectiontitlenocontents`
 - `\sequencesectiontitlenonotes`
 - `\sequencesectiontitlebaretitle`
 - `\sequencesectiontitlefirstline`
 - `\sequencesectiontitlemiddleline`

- `\sequencesectiontitlelastline`
- `\sequencefirstsectiontitle`
- `\sequencefirstsectiontitlenocontents`
- `\sequencefirstsectiontitlenonotes`
- `\sequencefirstsectiontitlefirstline`
- `\sequencefirstsectiontitlemiddleline`
- `\sequencefirstsectiontitlelastline`
- `\sequencesectionsubtitle`

- Sequence Subsections

- `\sequencesubsectiontitle`
- `\sequencesubsectiontitlenocontents`
- `\sequencefirstsubsectiontitle`
- `\sequencefirstsubsectiontitlenocontents`
- `\sequencesubsectiontitlefirstline`
- `\sequencesubsectiontitlemiddleline`
- `\sequencesubsectiontitlelastline`
- `\sequencefirstsubsectiontitlefirstline`
- `\sequencefirstsubsectiontitlemiddleline`
- `\sequencefirstsubsectiontitlelastline`
- `\sequencesubsubsectiontitle`
- `\sequencesubsubsectiontitlenocontents`
- `\sequencefirstsubsubsectiontitlenocontents`

13.8 Titles with marginal markers

`\JHpoemtitle` In his edition of the poetry of José Maria Heredia, Tilmann Altenberg placed a marker in the margin next to poem titles with a reference to where in the apparatus notes on that poem could be found. To do this, use the `\JHpoemtitle` command. This command takes two arguments: first, the title of the poem, second, the label used by the `\label` command on the page of the notes section to which the title refers. So, you would issue the poem title command this way: `\JHpoemtitle{Los desvelados}{EP_LosDesvelados_AC}`.

(Up to version 2.49 of `poemscol` you had to be sure to define the label in the notes sections by issuing `\literaltextnote{\label{EP_LosDesvelados_AC}}`. This is no longer necessary, and `\JHpoemtitle` defines both the `\label` and the `\pageref`.)

Instructions are given in section 22.15.4, p. 122 for how to construct similar commands for sequences, sequence sections, and so on. The following related commands are defined already:

- `\JHsequencetitle`
- `\JHsequencefirstsectiontitle`
- `\JHsequencesectiontitle`
- `\JHsequencesubsectiontitle`
- `\JHpoemsectiontitle`
- `\JHpoemfirstsectiontitle`
- `\JHpoemsubtitle`
- `\JHepigraph`
- `\JHprosesectiontitle`
- `\JHdedication`

`\setmargpoemtitle` `\setmargpoemtitle` is a more general version of `\JHpoemtitle`, with the second argument being any commands you want to be issued just after the title is processed.

`\margreftextnote` Another feature of Altenberg’s Heredia edition is a marginal mark attached to lines to which text notes refer showing where in the apparatus a comment upon that line is to be found. `\margreftextnote` sets a label in the textual notes section, and sets a marginal note with a page reference to that label in the main text. Issue `\margreftextnote` *before* issuing the `\verseline` or `\end{stanza}` that closes the line to which it refers. (The textual note itself can be an ordinary `\textnote`, and should be placed, as usual, *after* the `\verseline` or `\end{stanza}`.)

`\margreftextnote` generates its own label, so there is no need to make up one yourself.

`\margreftextnote` and its siblings use a new kind of insert, `\JHmarginpar`, to set the marginal marks. This is so that you can control the placement of these marks independently of how you place the line numbers (which use `\pmclsidepar`) or other marginal marks you may define using `\marginpar`.

Horizontal placement of the mark is controlled by the length `\JHmarginparsep`, which is set by default to 0 pt. Vertical placement of the marginal mark for a textual note, relative to the baseline, is set by the length `\JHmarginparvshift`, which is set by default to 0 pt. The horizontal placement of the marginal mark set by `\JHpoemtitle`, and its siblings, however, is controlled by the length `\JHtitlemarginparsep`. `\JHtitlemarginparsep` is set by default to value of `\JHmarginparsep`, so that the two kinds of mark should align with each other by default.

By default these marginal references are placed in the right margin. If you wish to set them in the left margin, issue the command `\JHmarksleft`. If you wish to place them back into the right margin, issue the command `\JHmarksright`. If you wish the marks to always be in the outer margin, issue the command

`\JHmarksouter`. If you wish the marks to always be in the inner margin, issue `\JHmarksgutter`. (The marks for titles and the marks for notes always appear on the same side of the page, and the different `\JHmarks` commands always move both kinds of mark.)

If you are centering the verse block on the longest line, the verse line numbers normally move in towards the verse block. (To center the verse block on the longest line, see section 3.2.2.) The marginal marks for `\margreftextnote` do not do this, since they are designed to line up with the marginal mark produced by `\JHpoemtitle`. You can change the alignment if you wish by changing the value of either the length `\JHmarginparsep`, which controls the placement of marginal marks for notes, or changing the value of the length `\JHtitlemarginparsep`, which controls the placement of the marginal marks for titles.

If you define a new endnote type using `\definewnotetype`, `\definewnotetype` will also define a new `\margref` command to go with it. So, for example, if you define a new note type called `\mynote`, you will automatically also define a “margref” command called `\margrefmynote` which will place a mark in the margin with a label showing where in the end notes sections the text of that `\mynote` can be found.

`\setmargrefmarker`

Altenberg’s edition used a ding from the pifonts collection in the marginal marks made by `\margreftextnote` and its siblings. I have set the default to `\dag`, so as not to depend upon yet another style package. You can choose another mark using `\setmargrefmarker` (e.g. `\setmargrefmarker{\ding{228}}`).

`\settitlemargrefmarker`

Altenberg’s edition also used a different marker for marginal marks for the titles of poems from that used for marginal marks made by `\margreftextnote`. By default that marker is `\dag`, but you can change it by using `\settitlemargrefmarker`,

`\margrefemendation`

`\margrefemendation` is a version of `\margreftextnote` for emendations.

`\margrefexplanatory`

`\margrefexplanatory` is a version of `\margreftextnote` for explanatory notes.

13.9 Titles with footnotes

In James Benstead’s edition of the collected poems of Hugh MacDiarmid, many of the titles of the poems have footnotes by the author. Under most circumstances, one can put a note about the title in the textual notes section simply by, after the `\begin{poem}` command, issuing something like this: `\literaltextnote{title} text of note`. (One can make similar notes for the explanatory notes section or for the emendations section.) But MacDiarmid’s notes are authorial, not editorial, and should be considered part of the title. At the same time, the notes should not be printed in the Table of Contents, nor for that matter in the endnotes sections.

`\footnotepoemtitle`

`\footnotepoemtitle` is for the default case. It takes two arguments. The first argument is the title of the poem. The second is the text of the footnote.

`\footnotepoemtitlefirstline`

`\footnotepoemtitlefirstline` `\footnotepoemtitlemiddleline` and `\footnotepoemtitlelastline` are for long titles in which how the author broke up the title on the page matters, and one or more of the lines has a footnote. These commands also take two arguments, of which the first is the title line

and the second is the text of the footnote. You can intersperse these commands with `\poemtitlefirstline`, `\poemtitlemiddleline` or `\poemtitlelastline` (depending on which line has the footnote). The lines will be broken in the same way in the text and in the table of contents.

`\footnotesplitpoemtitle` `\footnotesplitpoemtitle` is for the most general case. Use it if there is a footnote in the middle of the title, or if you have a long title and don't need to ensure that it is broken in the text and in the table of contents in the same way. `\footnotesplitpoemtitle` takes three arguments. The first argument is the first part of the title, up to the footnote mark, the second is the text of the footnote, and the third is the rest of the title.

I have not created footnoted titles for sequences, sequence sections, and so on. But if you compare how those titles are defined in the implementation section below and how footnoted titles are defined at 22.16 (page 133), how to write those commands should be clear.

You can control where the footnotes for footnoted titles are placed. By default, those footnotes are conventional footnotes (and all their parameters are set in the way normal L^AT_EX footnotes are set). You can force the default setting by issuing the command `\maketitlefootnotesplain` in your preamble. If you are setting your textual notes or other notes at the foot of the page using “layers” of footnotes, you can treat these footnotes as just another layer by issuing the command `\maketitlefootnoteslayered` in your preamble. (“Layered” footnotes are described at section 9, page 36.) If you wish to place these footnotes at the end of the poem, you must issue `\maketitlefootnotesatpoemend` in the preamble. Just before you declare a title with a footnote, issue `\makepoemendnotes`, and just after issuing `\end{poem}` for that poem, issue `\putpoemendnotes`.

13.10 Empty poem titles and italicized poem titles

`\poemtitlenotitle` `\poemtitlenotitle`, with its paradoxical name, is for poems without formal titles. Usually such poems are referred to by their first lines. This command does not produce a title in the text, but sets its argument in the table of contents and in the notes. Usually you use the first line as the moral equivalent of a title.

`\poemtitleitalic` Titles with italics or other special formatting posed special problems in earlier versions (before version 1.7) since the typesetting commands gummed up how I passed parameters around that I was unable to solve using `\protect`. All of these commands are obsolete now, but are retained for backward compatibility. `\poemtitleitalic` takes two arguments. The first is the title of the poem with the italics (or small capitals or international characters or what have you), for typesetting, and the second is the title without the commands, for cross reference purposes. (Actually, now that `poemscol` no longer needs to treat italics in titles in a different way, it can be anything you want, since the second argument is discarded.)

`\poemtitlenotitleitalic` `\poemtitlenotitleitalic`, with its doubly paradoxical name, is for poems without formal titles but with italicized words in their first lines. `\poemtitlenotitleitalic` takes two arguments. The first is the first line with the italics (for typesetting purposes), and the second is the first line without the

italics (for crossreference purposes). This command is obsolete now that italics in titles no longer require special handing, but is retained for backwards compatibility.

13.11 Problem titles

`\poemtitlebaretitle`
`\poemtitleonlycontents`
`\poemtitleonlynotes`

If you have a problem title, one for instance in which the title in the text might cause problems in the contents or in the notes, you can send information separately to the places it will be used. For example, a user planned to attach a footnote to a poem title, but didn't want the mark or the text of the note to show up in the contents or in the endnotes. I would usually have advised him to use `\sources` to send the text of the note to the endnotes, but he really wanted the title to include the footnote mark and to put the footnote on the same page. The solution to this problem was to set the title in the text separately from setting it in the notes and in the contents. `\poemtitlebaretitle`, for instance simply sets the title in the text. Then you can use `\poemtitleonlycontents` to send the title to the contents and `\poemtitleonlynotes` to send the title to the notes. These commands are defined for poem titles, and for some but not all of the whole range of titles including sequence titles, sequence section titles, sequence section subtitles, and so on. But it would be easy to roll your own versions of these commands by looking below at section 13.12, page 50, or at the models in the code below at section 22.15.1, page 109.

`\poemtitlenocontents`
`\poemtitlenonotes`
`\poemtitlenotitle`

There are also commands to send information to any two of the relevant locations but not the third. `\poemtitlenocontents` sends the title to the text and to the notes, but not to the contents. `\poemtitlenonotes` sends the title to the text and to the contents, but not to the notes. `\poemtitlenotitle` sends the title to the contents and the notes, but not to the main text.

Remember that in the last resort, you can send information to the contents section with `\literalcontents`. To actually set a contents entry using `\literalcontents` is a tall order, however, since you would have to include all the information from the `\c@ntentsinfo` command for the relevant type of title. (For what `\c@ntentsinfo` does, see section 13.12, below.) For instance, for a poem called Test Poem, that would be:

```
\literalcontents{\setlength\contentsentryoverrun{\contentsindenttwoamount }
\begin{contentsentryenvironment}
\contentsindentone
{\contentspoemtitlefont
Test
Poem}
\contentsleaders
\pageref{testpoemlabel} % pick a unique label
\end{contentsentryenvironment}
\par}
```

Another tricky thing about this method is the `\pageref` line in the above, which is a `pageref` to find and set in the contents the number of the page the poem

appears on. You should put `\label{testpoemlabel}`, with any unique text for the label (so long as it is the same one used in the `\pageref` line), on the page of the text where the poem occurs, in order to capture the correct page number. (Alternatively, you could just put the actual page number in what you send to the contents with `\literalcontents` instead of the `pageref` line, but you will have to remember to change this number if anything changes in your edition.)

Remember also that you can send information to the relevant notes sections using `\literaltextnote`, `\literalexplain`, and `\literalemend`.

13.12 Customizing titles

`poemscol` provides a large number of ways of setting titles, but conceivably you may wish to define your own. Here is a template for designing a new kind of title. Suppose you wish to create a kind of title called `\mytitle`. It would take one argument, which would be the title itself. The command defining the `\mytitle` command should call three commands, `\set@p@emtitle`, to set the title in the main text and make the label for use by the contents and notes sections, `\c@ntentsinfo` to set the title in the table of contents, and `\t@xtnotesinfo`, which sets the title in the notes sections. (You should enclose the whole thing between `\makeatletter` and `\makeatother`.)

`\set@p@emtitle` `\set@p@emtitle` takes six arguments, which are, in order, (1) the title (which, if you are calling this command inside of the definition of `\mytitle` should just be `#1`), (2) commands to be issued before setting the title (minimally, a penalty, such as `\poemtitlepenalty`), (3) the font size in which the title is to be set in the text (such as `\poemtitlefont` or `\large`), (4) any indentation of the title (`\relax` for `\poemtitle`, or `\titleindent` for `\sequencesectiontitle`), (5) commands to be issued after the title is set (such as `\afterpoemtitleskip`) and (6) the amount overrun lines in the title should be indented.

`\c@ntentsinfo` `\c@ntentsinfo` takes four arguments, which are, in order, (1) the title, (2) the indentation of the title in the table of contents (such as `\contentsindentone`), (3), the font size in which the title should be set (such as `\contentspoemtitlefont`) and (4) the amount overrun lines in the table of contents should be indented (such as `\contentsindenttwoamount`).

`\t@xtnotesinfo` `\t@xtnotesinfo` takes one argument, the title.
So, for example, to create a new kind of title called `\mytitle` which looks just like `\poemtitle`, issue

```

\makeatletter
\newcommand{\mytitle}[1]{%
\set@p@emtitle{#1}{\poemtitlepenalty}{\poemtitlefont}%
{\relax}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}{\z@}%
\c@ntentsinfo{#1}{\contentsindentone}{\contentspoemtitlefont}%
{\contentsindenttwoamount}%
\t@xtnotesinfo{#1}%
}
\makeatother

```

(The `\z@` which is the sixth argument to `\set@p@emtitle` above is a constant set to zero. You will also notice that I became completely hysterical on the subject of preventing a page break after a poem title.)

By default, `poemscol` does not indent the overrun portion of titles relative to the first line of the title, but if that first line is indented will set the overrun portions to be indented the same amount. Overrun portions of titles in the table of contents will be indented by one `\contentsindentamount` more than the first line is indented. Both of these behaviors can be changed by changing the arguments to `\set@p@emtitle` or `\c@ntentsinfo`.

If you wish to design a title which might have multiple lines, and you wish to specify how those lines are broken up, you will need to write three commands: one for the first line, one for middle lines, and one for the last lines. (This only matters if you care how the title is broken up. You can choose to let L^AT_EX do the breaking if you wish.) Before issuing `\set@p@emtitle` issue `\firstlinesettings`, `\middlelinesettings`, or `\lastlinesettings` (as the case may require). And issue `\restoresinglelinesettings` last of all in each of your three commands. The lines will be broken in the table of contents and in the body of the text in the same way, but will be run in in the notes sections.

```
\firstlinesettings
\middlelinesettings
\lastlinesettings
\restoresinglelinesettings
```

13.13 Customizing indentations in titles in the text body

Titles of poems, subtitles, titles of sequences, sections of sequences (and subsections and so on), appear in the text with a hierarchy of indentations. If you want to change anything about these indentations, you don't need to modify the various title-setting commands, but only to change the length of the relevant indentation command. I have given the indentations for each class of title a defined length, which you can change by changing the definition of the indentation command. (e.g. `\renewcommand{\poemtitleindent}{\hspace{3em}}`.) For many of these indentations you can also simply change the applicable length (e.g. `\setlength{\sequencesubtitleindentmount}{\titleindenttwoamount}`.)

The "amount" part in the command is important. `\poemtitleindentamount` is a length. On the other hand, `\sequencesectiontitleindentindent` is a command, defined defined as

```
\hspace{\sequencesectiontitleindenttitleindentamount}.
```

The table lists all the commands for these indentations. In the table "Extra Lines" refers to the indentation for the second and third lines (and so on) of multi-line titles. If you wish to change the indentation of any of the titles whose default length is listed as 0 in the table, you must use the `\renewcommand` method. (I found that setting the length of one of the indentations to 0pt added a few points of white space I could not figure out how to get rid of, so by default those commands are defined not by using a length but by, for example, `\newcommand{\poemtitleindent}{\relax}`.)

Table 2: Indentations in Titles

Entity Title	Indentation	Default Length
Volume	<code>\volumetitleindentamount</code>	0pt
Extra Lines	<code>\volumetitlesecondlineindentamount</code>	0pt
Volume Subtitle	<code>\volumesubtitleindentamount</code>	<code>\titleindentamount</code> (1pc)
Extra Lines	<code>\volumesubtitlesecondlineindentamount</code>	<code>\titleindentamount</code>
Volume Section	<code>\volumesectiontitleindentamount</code>	0pt
Extra Lines	<code>\volumesectiontitlesecondlineindentamount</code>	0pt
Poem	<code>\poemtitleindentamount</code>	0pt
Extra Lines	<code>\poemtitlesecondlineindentamount</code>	0pt
Poem Subtitle	<code>\poemsubtitleindentamount</code>	<code>\titleindentamount</code>
Poem Section	<code>\poemsectiontitleindentamount</code>	<code>\titleindentamount</code>
Extra Lines	<code>\poemsectiontitlesecondlineindentamount</code>	<code>\titleindentamount</code>
Poem Subsection	<code>\poemsubsectiontitleindentamount</code>	<code>\titleindenttwoamount</code>
Sequence	<code>\sequencetitleindentamount</code>	0pt
Extra Lines	<code>\sequencetitlesecondlineindentamount</code>	0pt
Sequence Subtitle	<code>\sequencesubtitleindent</code>	<code>\titleindentamount</code>
Extra Lines	<code>\sequencesubtitlesecondlineindentamount</code>	<code>\titleindentamount</code>
Sequence Section	<code>\sequencesectiontitleindentamount</code>	<code>\titleindentamount</code>
Extra Lines	<code>\sequencesectiontitlesecondlineindentamount</code>	<code>\titleindentamount</code>
Sequence Section Subtitle	<code>\sequencesectionsubsubtitleindentamount</code>	<code>\titleindenttwoamount</code>
Extra Lines	<code>\sequencesectionsubsubtitlesecondlineindentamount</code>	<code>\titleindenttwoamount</code>
Sequence Subsection	<code>\sequencesubsectiontitleindentamount</code>	<code>\titleindenttwoamount</code>
Sequence Subsubsection	<code>\sequencesubsubsectiontitleindentamount</code>	<code>\titleindentthreeamount</code>
Appendix	<code>\appendixtitleindentamount</code>	0pt
SubAppendix	<code>\subappendixtitleindentamount</code>	<code>\titleindentamount</code>
Foreword	<code>\forewordtitleindentamount</code>	0pt
Notes Sections	<code>\notestitleindentamount</code>	0pt

13.14 Customizing indentations in titles in the Contents

There is also a hierarchy of indentations for titles in the Table of Contents. Again, to change the indentations in the Contents, you don't need to redefine the title-setting commands, only to change the value of the relevant length. The table shows the hierarchy of indentations in the Table of Contents:

13.15 Visual formatting

`\longpage` The ideal in L^AT_EX is to separate content markup and formatting as completely
`\shortpage` as possible. In the text itself you simply mark the logical units (a poem, a title, a stanza, a textual note), and a header program (like `poemscol`) interprets the meaning of those terms typographically. However, one still winds up having to do some visual formatting. Especially in prose sections, such as in the textual notes, you will sometimes have to enlarge or shrink a page by one line in order to avoid an intractable widow or club line, and when one does so one must be careful to do the same to the other member of the two-page spread of which that page is a part so that the spread will be properly balanced. These commands enable one to wiggle pagelength enough to handle these problems. Since verse sections should be set with `\raggedbottom` in effect, the commands are not necessary in verse sections.

`\longpage` and `\shortpage` are cumulative: issuing `\longpage` twice lengthens the page by two lines, and issuing `\shortpage` twice shortens the page by two lines.

Table 3: Indentations in Contents

Entity Title	Indentation	Default Length
Volume	<code>\contentsvolumetitleindentamount</code>	Opt
Extra Lines	<code>\contentsvolumetitlesecondlineindentamount</code>	Opt
Volume Subtitle	<code>\contentsvolumesubtitleindentamount</code>	<code>\contentsindentoneamount</code> (24pt)
Extra Lines	<code>\contentsvolumesubtitlesecondlineindentamount</code>	<code>\contentsindentoneamount</code>
Volume Section	<code>\contentsvolumesectiontitleindentamount</code>	Opt
Extra Lines	<code>\contentsvolumesectiontitlesecondlineindentamount</code>	Opt
Poem	<code>\contentspoemtitleindentamount</code>	<code>\contentsindentoneamount</code>
Extra Lines	<code>\contentspoemtitlesecondlineindentamount</code>	<code>\contentsindentoneamount</code>
Poem Section	<code>\contentspoemsectiontitleindentamount</code>	<code>\contentsindenttwoamount</code>
Extra Lines	<code>\poemsectiontitlesecondlineindentamount</code>	<code>\contentsindenttwoamount</code>
Sequence	<code>\contentssequencetitleindentamount</code>	<code>\contentsindentoneamount</code>
Extra Lines	<code>\contentssequencetitlesecondlineindentamount</code>	<code>\contentsindentoneamount</code>
Sequence Section	<code>\contentssequencesectiontitleindentamount</code>	<code>\contentsindenttwoamount</code>
Extra Lines	<code>\contentssequencesectiontitlesecondlineindentamount</code>	<code>\contentsindenttwoamount</code>
Sequence Subsection	<code>\contentssequencesubsectiontitleindentamount</code>	<code>\contentsindentthreeamount</code>
Sequence Subsubsection	Does not appear in Contents	
Appendix or Foreword	<code>\contentsappendixtitleindentamount</code>	Opt
Notes Sections	<code>\contentsnotestitleindentamount</code>	Opt

14 Customizing page geometry and page styles

14.1 Font sizes, skips, sinks, indents, and penalties

`poemscol` sets the font sizes, but not the typeface, of fonts for many common tasks, in order to create a hierarchy of sizes. They can be changed with a `\renewcommand` of the following form, where the first number is the font size in points and the second is the leading:

```
\renewcommand{\volumetitlefont}{\fontsize{18}{23}\selectfont}
```

The following table gives the default values for the fonts. The titles of the fonts give their uses. `backmatterheaderfont` is for setting the titles of back matter sections. Sequence section titles use `poemtitlefont`. `backmattertextfont` is `\small`, `backmatterintrofont` is `\normalsize`.

Font	Size	Leading
<code>volumetitlefont</code>	18	23
<code>volumesubtitlefont</code>	14	18
<code>poemtitlefont</code>	14	18
<code>sequencetitlefont</code>	16	20
<code>subsectiontitlefont</code>	12	14.5
<code>backmatterheaderfont</code>	16	20
<code>backmattervolumefont</code>	12	14.5
<code>backmattervolumesubtitlefont</code>	11	13
<code>contentsvolumefont</code>	13	20
<code>contentsvolumesubtitlefont</code>	12	14.5
<code>contentssequencetitlefont</code>	10	14
<code>contentspoemtitlefont</code>	10	14

The following table gives various skips, sinks, penalties, and indentations. The titles of these should be self-explanatory. These should be changed with

`\renewcommand` as follows:

```
\renewcommand{\volumetitlesink}{\leavevmode\vspace{23.5pt}}
```

Name	Argument	Comment
backmattersink	21.5pt	
backmatterafterheadersink	11pt	
afterpoemtitleskip	<code>\smallskip</code>	
afterpoemskip	<code>\bigskip</code>	
aftersequencetitleskip	<code>\medskip</code>	
stanzaskip	<code>\medskip</code>	Extra skip between stanzas
titleindent	<code>\titleindentamount (1pc)</code>	use <code>\setlength</code> to change
parindent	<code>\titleindentamount</code>	
volumetitleshift	<code>\volumetitleshiftamount (1pc)</code>	use <code>\setlength</code> to change
contentsindentone	24pt	
contentsindenttwo	42pt	
contentsindentthree	60pt	
contentsindentfour	72pt	
runoverindentvalue	6em	for runover lines in verse
verseindent	2em	for formally indented lines
notesclubpoempenalty	-300	
notessequenceclubpenalty	-1500	
notesvolumetitlepenalty	-1500	
epigraphquoteleftmargin	1.5em	for epigraphs, attributions, etc.
epigraphquoterightmargin	1.5em	

14.2 Customizing page styles

`poemscol` sets several default page styles, defined below. The main page style is “fancy,” which is used for the main body of the poetry, prose frontmatter (such as introductions), and the endnotes sections. “`Volumefirststyle`” is for the first page of a volume of poems. “`Volumetitlestyle`” is for the title page of a volume of poems. The external file for the table of contents redefines “fancy,” so you should issue `\resetpagestyle` after issuing `\putpoemcontents`. `\resetpagestyle` resets the page style to “main” (which is the same as the original “fancy”).

Because `\putpoemcontents` resets the page style to “main,” any page style you defined in the preamble becomes forgotten if you include a table of contents. There are two possible solutions to this. The first is to define your page style after you have issued `\putpoemcontents`. The second is to redefine the fancy page style “main,” so that it does what you want. In either case, do not forget to issue `\pagenumbering{arabic}` after `\putpoemcontents`, else all of your page numbers will be in roman numerals. You can find the default definitions of those “fancy” and “main” below at 22.8, page 85.

You can change the text in the left (verso) running head by issuing `\lefthead{your header}` or `\volumeheader{your header}`. (The commands are synonyms.) You can change the text in the right (recto) running head by issuing `\righthead{your header}`.

14.3 Special page style for long poems

The fancy page style “longpoem” will add information of the form “firstline–lastline” to the running header. This page style otherwise resembles “main,” and “fancy.” Issue `\pagestyle{longpoem}` to use this page style. If you use “longpoem,” be sure to call `etex` and `emarks` in your preamble. Also, when a poem ends, be sure to issue `\newpage`, otherwise the running header will list the first line on the page from the first poem and the last line on the page from the second poem.

If you use “longpoem” and you have a table of contents, you must issue `\pagestyle{longpoem}` at some point *after* issuing `\putpoemcontents`. Do not forget to issue `\pagenumbering{arabic}` after `\putpoemcontents`, else all of your page numbers will be in roman numerals. Also, if you have back matter, you must issue `\pagestyle{main}` at the end of your poetry section, before the back matter starts, since otherwise your header will include the last line number `poemscol` saw. Issuing `\pagestyle{main}` will restore the normal page headers for the backmatter sections.

The header will include the abbreviation l. (for a single line) or ll. (for a range of lines). You can change either abbreviation with `\changesinglelineabbrev` or `\changemultiplelineabbrev`. So, for instance, to get rid of the abbreviations entirely, issue `\changemultiplelineabbrev{\relax}` and `\changesinglelineabbrev{\relax}`.

You may need to play with `\lefthead` and `\righthead` to get the information you want into the header. You might, for instance, want to use something like `\lefthead{‘‘Your main title’’ \hfil ‘‘Your poem title’’}` and `\righthead{‘‘Your volume title’’ \hfil ‘‘Your poem title’’}`. Whatever else you put into the header, the last thing should be your poem title, since it will be followed by the line numbers.

14.4 Page geometry and type leading

You have to give geometry the values that suit you. I include the values I used in my own book, just to give you a starting place. The default values for `marginparsep` and `marginparwidth` are different now (18pt and 18pt respectively). With that warning, here is a list of the values I used:

<code>textheight</code>	6.75in
<code>marginparsep</code>	18pt
<code>marginparwidth</code>	18pt
<code>headheight</code>	14pt
<code>paperwidth</code>	6in
<code>paperheight</code>	9in
<code>inner</code>	4.5pc
<code>outer</code>	4.5pc
<code>footskip</code>	15pt

In my own book I also, strictly to save money, and at the price of some ugliness,

changed the definition of `\normalsize` and `\small`, so that the former was 10 pt type on 11 pt leading (rather than 12 pt), and that the latter was 9 pt type on 10 pt leading. You can reproduce this setting by issuing `\tightleading`, although I would advise not doing so unless you are under financial constraints.

15 Prose Sections with line numbers

15.1 Setup

`poemscol` uses the `lineno` package to make marginal line numbers for prose sections such as the Author's Introduction, Afterword, Author's Notes, or such prose interludes or prose poems the volume may include. To control the appearance, placement, and frequency of marginal line numbers in prose sections, you may wish to consult the manual to `lineno`. I have added a minimal user interface to make `lineno` cohere with `poemscol`. You may have to fiddle with the parameters of both `poemscol` and `lineno` to persuade them to set marginal line numbers that look the same way in prose and verse contexts. The default values should work as is.

Line numbers in prose sections are placed using a different `\length` from that used in verse sections. Essentially, verse sections, and prose sections which use paragraph and sentence numbering — see below, in section 16 — place the marginal line numbers using `\marginparsep`. Prose sections which are numbered by line use `\linenumbersep` instead, which is a length defined in the `lineno` package. I have given values for both lengths which seem to place line numbers on the left and on the right side in prose sections roughly where they are placed in verse sections. You can change these values with `\setcounter{countername}{length}`.

`\verselinenumberstoleft` and `\verselinenumberstoright` also place the line numbers to the left or to the right, respectively, in prose sections. If you wish the numbering to appear on a different side in prose contexts you can set the side by issuing `\leftlinenumber` or `\rightlinenumber`. These last are commands from the `lineno` package. The two forms in which line numbers switch sides in prose contexts can't at the moment be used, because of a clash between how `lineno` handles line numbers that switch sides and the way I pass the line numbers to notes sections. If you have set the verse line numbers to switch sides, prose line numbers will appear on the right side. I hope soon to find a workaround for this problem.

By default, the line modulo for prose sections is the same as that for verse sections; if you have a line number every 5 lines in verse, you will have the same in prose. You can set the prose line modulo independently with `\setprosemodulo`.

`poemscol` may deal with rather long stretches of prose, but it is not designed to be used for critical editions of extended prose texts, as `EDMAC`, `reledmac`, or `ednotes` are. The method of entering line ranges into notes in prose contexts is something of a hack, and rather a worse one than the one employed in verse contexts, since it involves using two labels for each note, one to capture the line number of the

beginning, the other to capture the line number of the end. Other limitations of this method may show up with longer prose extracts.

`\prosesectiontitle` Prose sections may be titled with `\prosesectiontitle` which is essentially just `\poemtitle`, or `\prosesectiontitlenotitle`, which is essentially just `\poemtitlenotitle`. (Remember that if you use the latter command, you must specify a “dummy” title to use in the note and contents sections.) They will be formatted in the notes and contents sections as poems are. Alternatively, you can use the commands for defining new kinds of titles, in section 13.12, page 50, to make new kinds of titles for prose sections.

`prosesection` Prose sections should be enclosed in a `prosesection` environment (between `\begin{prosesection}` and `\end{prosesection}`). Entering this environment sets the modulo repeat for line numbering to the same value that prevails in verse contexts, and resets the prose line number to zero. If for some reason you do not wish to reset the line number but continue on from where it left off at the end of the last prose section, use the `prosesectionnoreset` environment instead.

`\setprosemodulo` If you wish to set the modulo repeat for line numbering in prose to some value different for that from verse contexts, issue the new modulo as the argument to `\setprosemodulo`.

It is possible, if a prose section is interpolated in the midst of verse, to number the prose and verse continuously. To move from a verse passage to a prose passage, just before the `\end{poem}` at the end of the first verse passage issue `\saveverselinenumber` to save the number of the verse passage. After you issue `\begin{prosesection}` issue `\resetlinenumber[\theverselineumberscratch]` to apply that number to the prose section. To number continuously while moving from prose to verse is more tricky. One way might be to mark a label at the end of the prose passage with `\proselinelabel{prose end label}` (or some other suitably unique label). This label will record the line number of the last prose line. Pass that value to `\restoreverselinenumber` by issuing `\setcounterfromref{verselinenumberscratch}{prose end label}`. Then issue `\restoreverselinenumber` just after issuing the `\begin{poem}` that restarts the verse again. I would recommend against numbering verse and prose continuously, however, since a verse line and a prose line are different categories of thing, the one being an element of prosody, the other being only an element of typography.

`\proselinelabel` `\proselinelabel` is simply `\linelabel` from `lineno`. I have provided the new name to make it easy to distinguish from `\poemlinelabel`.

15.2 Endnotes for prose sections

`\prosetextnote` Special versions of `\textnote`, `\emendation` and `\explanatory` are available for use in prose sections. `\prosetextnote`, `\proseemendation`, and `\proseexplanatory` differ from the verse versions in that they each require an extra argument, a unique label to be used in locating the line number for use by the notes commands. If `\maketextnotes`, `\makeemendations`, or `\makeexplanatorynotes` have been issued, the endnotes will be sent to the usual sections, where all the notes from that prose section will be grouped into a para-

graph, with the entry headed by the title given by `\prosesectiontitle`, just as if that were the title of a poem. `\textnotesatfoot`, `\emendationsatfoot`, and `\explanationsatfoot` will send the notes from prose contexts to the usual footnote levels. Notes commands in prose contexts take three arguments. As in verse sections, in prose sections `textnotes`, explanatory notes, and emendations have an optional first argument for recording line ranges. As in verse sections, you can record these line ranges either by simply putting in the argument how many lines the lemma will refer to (a deprecated method retained for backward compatibility reasons), or the argument of a `\proselinelabel` command on the last line of the lemma. (The only difference from the verse version here is that you should make the label using the `\proselinelabel` command, rather than with the `\poemlinelabel` command.) The second argument is a label to identify each note uniquely, which is used to find the line number at which the note begins. You will need a different label for every note. The third argument is the text of the note, which should include both the lemma and the rest of the note, as in the notes for verse sections. `\proseemendation` and `\proseexplanatory` are coded the same way. So, if you wished to make a textual note on a passage that begins with “Call me Ishmael.” and ends “a way of driving away the spleen,” you would issue at the point where the note is to occur (at the beginning of the passage):

```
\prosetextnote[a way of driving away the spleen] {Call me Ishmael}
{Call me Ishmael \ldots\ a way of driving away the spleen} text of
textual note}
```

On the last line of the passage to which the note refers you would issue:
`\proselinelabel{a way of driving away the spleen}.`

`\prosetsvariant`
`\proseaccidental`
`\prosetsaccidental`

You can issue `\sources` and `\tsentry` in prose contexts as usual. For typescript variants and accidental variants you need to issue `\prosetsvariant`, `\proseaccidental`, and `\prosetsaccidental`. `\prosetsvariant` is entered just as `\prosetextnote` is, with an optional argument (for use with line ranges, as usual), and two mandatory arguments (the first a label to capture the line number, the second the lemma and comment).

`\proseaccidental` and `\prosetsaccidental` take only the two mandatory arguments, since by definition an accidental variant is confined to one line.

One caveat: because the line numbers for notes in prose contexts are generated by a label/ref mechanism, each note will result in a complaint about an undefined reference the first time the file is run through L^AT_EX. Either run the first pass in quiet mode, or be prepared to ignore a lot of griping until L^AT_EX has generated the .aux file at the end of the first run.

16 Paragraph and sentence annotation

16.1 Setup

Annotating a prose section by sentence number, or by paragraph number and sentence number, has some advantages over annotating it by line number. The

principal advantage is that the annotation and reference system can remain stable over multiple editions, even if they are set in different formats. The most familiar of such systems is the chapter and verse system in the Bible, introduced by Archbishop Stephen Langton in the thirteenth century (who divided the Vulgate edition into numbered chapters) and by Robert Estienne in the sixteenth century (who added the verse numbers). Such a form of annotation might be especially useful for medieval prosimetra, a form combining verse and prose. (Hence the commands that follow often begin with `pm`.)

`pmsection` You should put prose marked up for sentence and paragraph annotation in a `pmsection` environment. You do not need to put prose marked up for sentence and paragraph annotation in a `prosesection` environment. That environment is only needed if you are line-numbering prose. You also do not need to load the `lineno` package if you are using the sentence and paragraph system for annotating prose. You might, however, still wish to set the title with `\prosesectiontitle`.

`\setprosebysentence` `\setprosebysentence` sets `poemscol` to number prose by sentence rather than by line number. This command is mostly a placeholder now, used only for setting the value of `\marginparsep` to something better for prose. (`\marginparsep` sets how far the line numbers are from the text block.) `\verselinenumberstoleft`, `\verselinenumberstoright`, and `\verselinenumbersswitch` each pick convenient values for `\marginparsep`. By default these values all line up on the page, but if you change any of them, you may have to use `reset \marginparsep` to some value you will have to find by trial and error, since they each use `\marginparsep` in slightly different ways. You can change `\marginparsep` either by using `\setlength{\marginparsep}{length}` or, better, by using `\renewcommand` to change the setting of `\marginparsep` in `\verselinenumberstoleft` or whatever else you intend to use. Adjust `\headoffsetlength` to make the page numbers line up with the line numbers.

`\pmsentence` Each sentence must begin with `\pmsentence`. `\pmsentence` increments the sentence counter, optionally puts the sentence number in the running text, and optionally puts the sentence number in the margin.

`\runningsentencenumberstrue` sets sentence numbers in the running text. To set sentence numbers in the margin, issue `\marginsentencenumberstrue`. You can issue both, either, or neither of these commands.

`\setpmmodulo` If you are putting sentence numbers in the margin, you need not number every sentence. Indeed, if there is more than one sentence on a line, the numbers will overwrite each other (unless you use the `marn.sty` package, and substitute `\marn` for `\pmclrightsidepar`, `\pmclleftsidepar` or `\pmclsidepar` in the code for `\pmsentence`). You can also avoid overlapping sentence numbers by using `\pmsentencetwo` and its siblings, defined below. You can set the modulo for sentence marginal numbers by issuing `\setpmmodulo`.

`\pmsentencetwo`
`\pmsentencethree`
`\pmsentencefour` If you know, from a prior run, that there will be a second or third sentence on some particular line, marking them with these commands will ensure that the marginal sentence numbers do not overwrite each other. These commands are something of a kludge, but they will do until I figure out how to do this better.

<code>\pmnumberstoright</code> <code>\pmnumberstoleft</code> <code>\pmnumbersgutter</code> <code>\pmnumbersouter</code>	<p>If you wish to control the margin in which sentence and paragraph numbers appear, issue <code>\pmnumbersright</code>, <code>\pmnumbersleft</code>, <code>\pmnumbersgutter</code>, or <code>\pmnumbersouter</code>. By default, these numbers will line up with the line numbers in verse sections. If you change the value of <code>\marginparsep</code> for prose sections from those used by their verse equivalents, it is a good idea to issue the verse equivalent command (<code>\versenumberstoright</code> or whatever) again when you move from a prose to a verse environment.</p> <p><code>\runningsentencenumberformat</code> sets the format of running sentence numbers. Currently it is <code>\textsuperscript</code> (the numbers are set as superscripts) and <code>\tiny</code>. The format of marginal sentence numbers is set by <code>\marginsentencenumberformat</code>. Currently it is <code>\tiny</code>. Definitions of both commands are found at section 22.23, page 151. You can change either with <code>\renewcommand</code>.</p>
<code>\pmpara</code> <code>\pmsentencebypara</code> <code>\pmsparainmartrue</code> <code>\pmpararunningtrue</code>	<p>You can also number paragraphs. Each paragraph must begin with <code>\pmpara</code>. <code>\pmpara</code> increments the paragraph counter, optionally puts the paragraph number in the running text, and optionally puts the paragraph number in the margin. To reset the sentence counter at the beginning of each paragraph, issue <code>\pmsentencebyparatrue</code> in your preamble. To set paragraph numbers in the margin, issue <code>\pmsparainmartrue</code>. To set paragraph numbers in the running text, issue <code>\pmpararunningtrue</code>. You can issue both, either, or neither of these last two commands. Which margin these numbers are set in is controlled by the same commands that control placement of marginal sentence numbers.</p> <p>If you begin a paragraph with <code>\pmpara poemscol</code> will assume that you intend to include the paragraph number in your notes (in the form <code><paragraph number>:<sentence number></code> for simple references, or <code><first paragraph number>:<first sentence number> - <lastparagraph number>:<last sentence number></code> for ranges of sentences) even if you do not reset the sentence number at the beginning of each paragraph. Normally you would not issue <code>\pmpara</code> if you are not resetting the sentence number at the beginning of each paragraph, since under those circumstances you don't really need to keep track of the paragraph numbers, in which case each note would simply include the sentence number (just as in verse it would include the line number). In the unusual event in which you wish to put the paragraph number in the margin but refer only to sentence numbers in the notes, simply follow every use of <code>\pmpara</code> with <code>\pmparasfalse</code>.</p>
<code>\pmpararunningformat</code> <code>\pmparmarformat</code>	<p>The format of running paragraph numbers is set by <code>\pmpararunningformat</code>. Currently it is <code>\textbf</code> and <code>\small</code>. The format of marginal paragraph numbers is set by <code>\pmparmarformat</code>. Currently it is <code>\textbf</code> and <code>\small</code>. The definitions of these commands are found at section 22.23, page 155, Either can be changed with <code>\renewcommand</code>.</p>
<code>\ifsupressfirstpara</code> <code>\ifsupressfirstsentence</code>	<p>Some readers find it annoying to have the first sentence or the first paragraph marked. To suppress the appearance of the first sentence number, whether in the margin or in the running text, issue <code>\suppressfirstsentencetrue</code>. To suppress the appearance of the first paragraph number, whether in the margin or in the running text, issue <code>\suppressfirstparatrue</code>. These commands will not affect the appearance of entries in the endnote sections or in the footnotes.</p>

16.2 Cross references by sentence and paragraph

`\sentencelabel` To make labels that refer to sentences or paragraphs, issue `\sentencelabel`. The label will be either both the paragraph number and the sentence number (if you are resetting sentence numbers by paragraph), or only the sentence number (if you are not resetting sentence numbers by paragraph).

16.3 End notes by sentence and paragraph

`\pmtextnote` `\pmtextnote`, `\pmexplanatory`, `\pmemendation`, `\pmaccidental`, `\pmtsvariant`
`\pmexplanatory` and `\pmtsaccidental` are special versions of the usual endnote commands for
`\pmemendation` use with annotations by sentence and paragraph. If you have not issued
`\pmaccidental` `\pmsentencebypara` these commands will write the sentence number at the head
`\pmtsvariant` of each note, where the line number would usually go. If you have issued
`\pmtsaccidental` `\pmsentencebypara`, these commands will issue both the paragraph and sen-
tence number, in the format `<paragraph number>:<sentence number>`. You
can refer to ranges of sentences (or paragraphs and sentences) in a way very
similar to how you do so in verse sections. At the end of the range, issue a
`\sentencelabel` command, with a unique label. At the beginning of the range,
issue your `\pmtextnote` command with the optional argument in square brackets
before the main argument, giving your unique label as the value of that argument,
e.g. `\pmtextnote[some label]{text of lemma} comment`. At the end of your
range, issue `\sentencelabel{some label}`, using the same label you put in the
square brackets for the `\pmtextnote`. If you have not issued `\pmsentencebypara`,
the range will simply be the range of sentence numbers. If you have issued
`\pmsentencebypara`, the range will include paragraph and sentence numbers, like
this: `<first paragraph number>:<first sentence number> – <lastparagraph num-
ber>:<last sentence number>`, for example: 4:12–6:13.

`\sources` needs no special handling if you are annotating by sentence and paragraph.

16.4 Footnotes by sentence and paragraph

`\textnoteatfoot` shifts `\pmtextnotes` to the foot, as with `\prosetextnote`.
`\emendationsatfoot` and `\explanationsatfoot` work the same way.

16.5 Bible chapter and verse

Since `\pmsentence` and `\pmpara` are the moral equivalents of bible verse and chapter, `\biblechapter` and `\bibleverse` are provided for convenience.

17 Parallel text editions

17.1 Setup for parallel texts in verse

`poemscol` can make parallel text editions in which the contrasting versions are set on facing verso and recto pages. `poemscol` does not automatically provide the page breaks for parallel editions, and even if it did, one would still probably have to specify page breaks every two or three pages to keep the texts in register anyway, so you will have to use `\newpage` to mark every page break. If you are willing to set the page breaks yourself, however, `poemscol` does provide commands for keeping the line count correct on successive recto or verso pages, and for keeping track of whether or not one was in the middle of a stanza when one closed the previous verso or recto page (as the case may be). And it provides, in the `\synchrolabel` and `\synchronoref` commands, a way of marking which lines on the recto side correspond to particular lines on the verso side. `\synchronoref` will even tag the marginal line number it makes with a marker to specify the text to which it refers.

```
\startparalleltxts
\finishparalleltxts
  parallelverse
```

You must begin a region of parallel text on a *verso* page. A parallel text region must begin with `\startparalleltxts` and end with `\finishparalleltxts`. Setting parallel texts requires one to redefine the poem and stanza environments, and `\startparalleltxts` redefines those environments. You can make those changes local to the parallel text region by using `\begin{parallelverse}` and `\end{parallelverse}` rather than `\startparalleltxts` and `\finishparalleltxts`. `\startparalleltxts` and `\finishparalleltxts` can be issued on their own but I have combined them to make the `parallelverse` environment.

Although usually with `poemscol` it is up to you where to put the marginal line numbers, when you issue `\startparalleltxts` the positions are fixed as follows: marginal line numbers are in the left margin, line cross references (marking which lines in the recto text correspond to which lines in the verso text, which are made with `\synchronoref`) are in the right margin.

```
\startrectopage
\finishrectopage
\startversopage
\finishversopage
```

Verso pages should begin with `\startversopage` and end with `\finishversopage`. Recto pages should begin with `\startrectopage` and end with `\finishrectopage`. You have to declare the page breaks manually, so be sure you are putting the `\finishversopage` or `\finishrectopage` commands in places which will work. `\finishparalleltxts` just makes certain that stanzas, and poems, that you opened in a region of parallel texts are closed when you leave it.

```
\versopoemtitle
\rectopoemtitle
\versopoemtitlenocontents
\rectopoemtitlenocontents
```

Use `\versopoemtitle` and `\rectopoemtitle` rather than `\poemtitle` for the title of the poem (or prose passage) on the verso or recto pages. If you are making a parallel text of Wordsworth's 1805 and 1850 versions of *The Prelude*, you might want to use something like `\versopoemtitle{The Prelude (1805 Version)}` and `\rectopoemtitle{The Prelude (1850 Version)}`. I have also made versions of these commands that do not make entries in the table of contents, should the need arise for them. If you wish to make titles for other things, such as poetic sequences or sequence sections, you can use the techniques described in section 13.12 above, page 50, except substitute the command `\versoset@p@emtitle` or

`\rectoset@p@emtitle` for `\set@p@emtitle`, using all the same arguments you would have used with `\set@p@emtitle`.

17.2 Parallel texts and on the fly note types

If you are making a parallel text edition, you may need to use `\definewnotetype` to make the different kinds of endnote for the parallel texts. For instance, if you are making a parallel text of Wordsworth's 1805 and 1850 versions of *The Prelude*, you may use something like `\fiveexplanatory` and `\fiftyexplanatory` for explanatory notes for the poems on the verso and recto pages.

`\keeptitlestraight`

Without special care, `poemscol` may become confused about whether it has seen, for example, a `\fiveexplanatory` for a particular book of *The Prelude* or not, and, if `\settitleinnotes` is set, may neglect to put the title of that book of *The Prelude* in the notes for the first note for that book. To remedy this, `\versopoemtitle` and `\rectopoemtitle` set up a way of keeping track whether each species of note has appeared already or not. While setting parallel texts `poemscol` checks at the beginning of every verso or recto page whether the the different species of endnote for the poem on that page has appeared before. On rare occasions this turns out not to be frequently enough in cases where you are defining your own kinds of endnote. In this case, the following hack, `\keeptitlesstraight`, will check whether the verso or recto poem has set that species of note each time it is issued. Suppose, for instance, going back to our Wordsworth example, that you have defined, using `\definewnotetype`, the following six kinds of endnotes: `\fivetextnote` `\fiveemendation`, `\fiveexplanatory`, `\fiftytextnote`, `\fiftyemendation`, and `\fiftyexplanatory`. You should define a new command called `\keeptitlesstraight` to keep track of these six kinds of note. Here is how it might look:

```
\newcommand{\keeptitlesstraight}{
\pretocmd{\fivetextnote}{\versotitleinnotescheck}{\relax}{\relax}
\pretocmd{\fiveemendation}{\versotitleinnotescheck}{\relax}{\relax}
\pretocmd{\fiveexplanatory}{\versotitleinnotescheck}{\relax}{\relax}
\pretocmd{\fiftytextnote}{\rectotitleinnotescheck}{\relax}{\relax}
\pretocmd{\fiftyemendation}{\rectotitleinnotescheck}{\relax}{\relax}
\pretocmd{\fiftyexplanatory}{\rectotitleinnotescheck}{\relax}{\relax}
}
```

All those fields filled with `\relax` are for reporting the success or failure `\pretocmd` has had in appending `\versotitleinnotescheck` (or `\rectotitleinnotescheck`) to the different endnotes commands. You may wish to replace the `\relax` with something like `\typeout{fiftytextnote modified}` or `\typeout{fiftytextnote not modified}`.

If you are using the `\keeptitlestraight` hack described here, you should add `etoolbox` to your package list.

`\resetttitleinnotes`

If you are defining new kinds of note, and a section of non-parallel texts follow a section of parallel texts, you will need to issue the following hack after the parallel

texts close (again I am using the Wordsworth example):

```
\newcommand{\resettitleinnotes}{
\nofiveemendationyettrue%
\nofiveexplanatoryyettrue%
\nofivetextnoteyettrue%
\nofiftyemendationyettrue%
\nofiftyexplanatoryyettrue%
\nofiftytextnoteyettrue%
}
```

17.3 Parallel texts and generic note types

`\rectotextnote` In case you find using these hacks a bit burdensome, I have defined for your convenience six generic kinds of endnote for use in parallel text editions: `\rectoemendation`, `\rectoexplanatory`, `\versotextnote`, `\versoemendation`, `\versoexplanatory`, as well as `\rectoprosetextnote`, `\versoprosetextnote`, `\rectoproseemendation`, `\versoproseemendation`, `\rectoprosexplanatory`, and `\versoprosexplanatory`.

I have also defined `\literalrectotextnote`, `\literalversotextnote`, `\literalrectoemendation`, `\literalversoemendation`, `\literalrectoexplain`, and `\literalversoexplain` for sending material other than formal endnotes to these endnote sections.

You can use all of these without creating versions of `\keeptitlesstraight` and `\resettitleinnotes`.

`\makerectotextnotes` To use these kinds of note, issue `\makeversotextnotes`, `\makerectoemendations`, `\makeversoemendations`, `\makeversoexplanatorynotes` or their recto equivalents in your preamble. You can mark up your texts with these notes just as you would do with `\textnote`, `\emendation` or `\explanatory` (or `\literalversotextnote`, `\literalversoemendation` and `\literalversoexplain`), without any of the special hacks I have just described.

`\changerectotextnotesname` I have given the endnotes sections generated by these notes rather generic names (`\rectotextnote` and `\versotextnote` for instance, both open endnote sections with the title TEXTUAL NOTES, with a running header of the form “Textual Notes to pp. xx–yy” and a contents entry of Textual Notes). You will probably need to change those to something more descriptive. You can change any of these with `\changeversotextnotesname{Your Title}`, `\changeversotextnotesheader{Your running header}`, and `\changeversotextnotescontentsname{Your contents entry}`. You can change the appearance of these notes by changing the values of the booleans `\versotextnotessinglepar` and `\versotextnotestwoacol`. Similar sets of commands are available for `\versoemendation` and `\versoexplanatory` and their recto equivalents.

`\putrectotextnotes` To include these note sections in your document, issue `\putversotextnotes`, `\putrectotextnotes`, `\putversoemendations`, `\putrectoemendations`, `\putversoexplanatorynotes`, or `\putrectoexplanatorynotes` at the point

where you wish them to appear. These commands behave exactly like `\puttextnotes`.

17.4 Parallel text labels

`\synchrolabel` You may want to mark cross references to make it clear to the reader which
`\synchroref` line of the poem on the recto side of the spread corresponds to a particular line
`\setsynchroflag` on the verso side. To mark these cross references, you need to make a label
on the verso side (using `\synchrolabel`), and a corresponding reference on the
recto side (using `\synchroref`). You may also wish to add a mark to that refer-
ence (using `\setsynchroflag`) to specify to the reader what edition it refers
to. So, for instance, if your verso text is the 1805 version of Wordsworth’s
The Prelude, and your recto text is the 1850 version, you may wish to spec-
ify `\setsynchroflag{1805: }`, which will preface the references put out by the
`\synchroref` command with ‘1805:’. Suppose you wished to tie these correspond-
ing passages from the “Boy of Winander” episode in Book 3. To make the label,
issue the `\synchrolabel` command on the verso side (the 1805 side) just after the
`\verseline` or `\end{stanza}` which closes the line you wish to label:

```
This boy was taken from his mates, and died \verseline
In childhood ere he was full ten years old \verseline
\synchrolabel{full ten years old}
```

You don’t have to quote the whole line in the label, but it should be long enough
to uniquely pick out that line in the poem. (If the line is repeated in the poem,
you will have to exercise your ingenuity in making up a unique label.)

Over on the recto side (the 1850 side), you will want to use `\synchroref` in
order to print the marginal cross reference. The `\synchroref` command should
come *before* the `\verseline` that closes the line it is tied to, as follows:

```
This Boy was taken from his mates, and died\verseline
In childhood, ere he was full twelve years old.
\synchroref{full ten years old}\verseline
```

17.5 Parallel prose passages

`parallelprose` `poemscol` is not designed to manage long parallel texts in prose, but for shorter
`\startparalleltextprose` texts up to a couple of dozen pages, such as two versions of an Author’s Pref-
`\finishparalleltextprose` ace, say, `poemscol` has the `parallelprose` environment. (You can also use
`\startparalleltextprose` and `\finishparalleltextprose`.) Like passages of
parallel text in verse, parallel prose passages must start on a verso page.

`\startversoprosepage` Each verso page must start with `\startversoprosepage` and fin-
`\finishversoprosepage` ish with `\finishversoprosepage`, and each recto page must start with
`\startrectoprosepage` `\startrectoprosepage` and finish with `\finishrectoprosepage`. If a page con-
`\finishrectoprosepage` tinues a paragraph from the previous page, say, from a previous recto page, put

the beginning of the text on the second page right after the `\startrectopage` command with no blank line. (Alternatively, you could just begin that page with `\noindent`.)

`\parastart` You must mark the beginning and end of every paragraph in parallel prose passages with `\parastart` and `\paraend`.

`\paraend` You will have to pick the page breaks manually, using `\newpage`, once you find where L^AT_EX would naturally break the page. Because how L^AT_EX justifies text is a little unpredictable, however, you may find that the line before the page break, which filled the line before you added the page break, is actually a little shorter, and thus is no longer justified, once you add the page break. You may well not be able to exactly fill out the line by trial and error, adding a word or even just a syllable, to the line at a time. You can kludge around the problem, however, by adding an `\hfil` between each word of the last line.

18 Using poemscol in a multilingual world

`\changecontentsname` By default, `poemscol` uses English language titles for such things as the Table of Contents, the Explanatory Notes, and so on, and uses English language running headers. As of version 2.5 these are easily changed. To change the name of the Table of Contents (the default is CONTENTS) to `Inhaltsverzeichnis`, issue `\changecontentsname{Inhaltsverzeichnis}`. To change the running header on contents pages, issue `\changecontentsheader{your header}`.

`\changenotesname` To change the name for the endnote section for textual notes (the default is TEXTUAL NOTES), issue `\changenotesname{your version}`. To change the running header (by default “Textual Notes to”) issue `\changenotesheader{your version}`. To change the name for the textual notes in the table of contents issue `\changetextnotescontentsname{your version}`.

`\changesinglepageabbrev` Running headers refer to single pages with the English abbreviation “p.” and to multiple pages with the English abbreviation “pp.” To change these issue `\changesinglepageabbrev{new abbrev}` or `\changemultiplepageabbrev{new abbrev}` respectively. The ultimate outcome is to translate a header of the form “Textual Notes to pp. xx-yy” to the form appropriate for your language.

`\changeemendationsname` To change the name for the endnote section for emendations (the default is EMENDATIONS), issue `\changeemendationsname{your version}`. To change the running header (by default “Emendations to”) issue `\changeemendationsheader{your version}`. To change the name for the emendations in the table of contents issue `\changeemendationscontentsname{your version}`.

`\changeexplanationsname` To change the name for the endnote section for explanatory notes (the default is EXPLANATORY NOTES), issue `\changeexplanationsname{your version}`. To change the running header (by default “Explanatory Notes to”) issue `\changeexplanationsheader{your version}`. To change the name for the explanatory notes in the table of contents issue `\changeexplanationscontentsname{your version}`.

`\changeindexname` To change the name for the index (the default is “Index of Titles and First Lines”, issue `\changeindexname{your version}`). To change the running header (the default is “Index of Titles and First Lines”) issue `\changeindexheader{your version}`. To change the contents entry for the index (the default is “Index of Titles and First Lines”) issue `\changeindexcontentsname{your version}`.

19 A sample driver file

If you are compiling a collected poems, you are probably preparing your volume from many files. You may (or may not) wish to subdivide your edition by the original volumes. Or you may subdivide by year, or by the significant phases of the poet’s career. One way to keep in control of the process is to create a driver file, which calls all the appropriate `.sty` files and sets the variables globally, and then read in the sections of the edition using `\input`. Here is a version of the driver file I used for *The Collected Poems of Robert Penn Warren*:

```
\documentclass[10pt,twoside]{article}
\usepackage{fancyhdr,kdgreek,makeidx,times,multicol,geometry,}
\usepackage{keyval,ifthen,mparhack,manyfoot,poemscol}
\begin{document}
\leftheader{The Collected Poems of Robert Penn Warren}
\makeexplanatorynotes
\makeemendations
\maketextnotes
\makepoemcontents
\makeverselinenumbers
\global\indexingontrue
\global\includeaccidentalstrue
\global\includetypescriptstrue
\input maintitle.tex
\input poems1922_1943.tex
\input thirtysix.tex
\input eleven.tex
\input sp43.tex
\input promises1.tex
\input promises2.tex
\input promises3.tex
\input yec1.tex
\input yec2.tex
\input yec3.tex
\input tale1.tex
\input tale2.tex
\input incarnations.tex
\input audubon.tex
\input orelse1.tex
\input orelse2.tex
\input arcturus.tex
```

```

\input nowthen.tex
\input beinghere.tex
\input rumor1.tex
\input rumor2.tex
\input cj1.tex
\input cj2.tex
\input altitudes.tex
\input poems1943_1989.tex
\input introduction.tex
\finish

```

20 A sample poem markup

Here is a poem Robert Penn Warren wrote in his first volume, *Thirty-Six Poems* (1935). The poem is the first poem of his sequence “Kentucky Mountain Farm.” I include the over-title, to demonstrate how to mark up such cases.

```

\sequencecitetitle{Kentucky Mountain Farm}
\index{Kentucky Mountain Farm@{\em Kentucky Mountain Farm\}}
\sources{Text: TSP. Variants: SP43, SP66 (Deletes ‘‘The Cardinal,’’ ‘‘The
Jay,’’ and ‘‘Watershed’’), SP75 (Same sections as SP66), SP85 (Restores
‘‘Watershed’’), {\em Helsinki\}} (includes only ‘‘Rebuke of
the Rocks’’ and
‘‘At the Hour of the Breaking of the Rocks’’).
‘‘The Owl’’ (above) was marked as a section of ‘‘Kentucky
Mountain Farm’’ when it first appeared in {\em Poetry,\}} but it was never
included in any book version of the entire sequence. The sequence in {\em
Poetry\}} included, in this order, ‘‘The Owl,’’ ‘‘The Cardinal,’’ and
‘‘Watershed.’’ TSP uses lower case Roman numerals in the section
titles. The typescript drafts in the Beinecke Library do not seem to
be setting copies.}
\sequencefirstsectiontitle{I. Rebuke of the Rocks}
\index{Rebuke of the Rocks@{\em Rebuke of the Rocks\}}
\sources{Text: TSP. Variants: {\em Nation\}, 11 Jan.\ 1928,
p.~47, {\em Literary
Digest,\}} 28 Jan.\ 1928, p.~32, {\em Vanderbilt Masquerader,\}} 10
(Dec.\ 1933), p.~16, SP43, SP66, SP75, SP85, {\em Helsinki\},
Broadside: The Press at Colorado College, printed on paper handmade by
Thomas Leech for the American Poetry Society, April~26, 1985. This
poem was not included in SP85 until the second set of galleys, in
which a photocopy of the SP75 text is a stapled insert.}
\begin{poem}
\begin{stanza}
Now on you is the hungry equinox,\verseline
\index{Now on you is the hungry equinox}
O little stubborn people of the hill,\verseline
\accidental{hill,] \sameword--- {\em Nation,\}} {\em Literary Digest\}}
\sameword, {\em Vanderbilt\}} (I include the reading

```

```

from {\em Vanderbilt\}
even though it is the same as in TSP, because
{\em Vanderbilt\} was published
after the other magazine versions but before TSP.))
The season of the obscene moon whose pull\verseline
Disturbs the sod, the rabbit, the lank fox,\verseline
Moving the waters, the boar's dull blood,\verseline
And the acrid sap of the ironwood.\end{stanza}

\begin{stanza}
But breed no tender thing among the rocks.\verseline
Rocks are too old under the mad moon,\verseline
\accidental{old\missingpunct} \sameword, {\em Vanderbilt\}}
Renouncing passion by the strength that locks\verseline
The eternal agony of fire in stone.\end{stanza}

\begin{stanza}
Then quit yourselves as stone and cease\verseline
\accidental{stone\missingpunct} \sameword, {\em Vanderbilt\}}
To break the weary stubble-field for seed;\verseline
Let not the naked cattle bear increase,\verseline
Let barley wither and the bright milkweed.\verseline
\accidental{milkweed.} milk-weed. {\em Vanderbilt\}}
Instruct the heart, lean men, of a rocky place\verseline
That even the little flesh and fevered bone\verseline
May keep the sweet sterility of stone.\end{stanza}
\end{poem}

```

21 A sample divider page

```

\begin{volumetitlepage}

\volumeheader{Being Here}
\volumeheader{Being Here}
\volumesubtitle{Poetry 1977--1980}
\volumededication{To Gabriel Thomas Penn\
(1836--1920)}
\bigskip

\volumeepigraph{OLD MAN: You get old and you can't do anybody
any good any more.\
BOY: You do me some good, Grandpa. You
tell me things.}

\bigskip

```

\volumeepigraph{There is in short no absolute time standard.}
\volumeattribution{{\em Van Nostrand's Scientific Encyclopedia,\/}\}
Fifth Edition, p. 2203}

\bigskip

\volumeepigraph{I thirst to know the power and nature of Time\ldots.}
\volumeattribution{St.\ Augustine: {\em Confessions,\/}\}
Book {\em XI,\/} Chapter {\em XXIII\/}\}
Translated by Albert C. Outler}

\bigskip

\volumeepigraph{Time is the dimension in which God
strives to define His own Being.}

\sources{The typescript material in the Beinecke Library indicates that this book went through many drafts, and some rethinking about what to include and how to order the poems. Until a late stage of production---very late, since the typescript includes a designed mock-up of the proposed title page---the title of this volume was {\em Life is a Fable.\/} Indeed, as late as the time the book was set in galleys it was called {\em Life is a Fable\/}, although the title was corrected on the galleys. Like {\em Now and Then\/}, the typescript was assembled from photocopies of re-typed copies of poems made after their magazine appearance, with annotations giving the name of the magazine in which they occurred. Unlike {\em Now and Then\/}, the typescript seems to have been typed in one piece, and the annotations added for the convenience of the permissions department at Random House. The page numbers have been added---presumably later---in blue pen. The copy is marked up in Warren's hand in black pencil, and in another hand in red pencil. (Unless marked otherwise, all of the mark-up described here is in black pencil.) \tentry{Like most Warren typescripts BHTS is single-spaced. The dedication to Gabriel Thomas Penn and the dialogue between the old man and the boy appeared on a separate page, and the three epigraphs appeared on another separate page. BHTS gives 1838 as the year of Gabriel Thomas Penn's birth (the error is corrected on the galleys). In the quotation from Augustine, the second word is corrected to "thirst" from "yearn," and the translator's name is added in pencil, not in Warren's handwriting.} In one of Warren's own copies at Western Kentucky University, he has corrected the date of Gabriel Thomas Penn's birth to 1837 (copy 310). Some revisions in this book may have come very late indeed. A letter to Erskine of January 28, 1980, refers to changes made in a bound manuscript that Warren kept after returning the

copy-edited typescripts. There are revisions not only on the galleys, but also on the page proofs. There are even some corrections on the ‘‘blues’’ for this volume, including some new copy on a card referred to in a note on the cover of the ‘‘blues’’ but now lost. The Secker and Warburg London edition is, except for the title page, printed from the American plates. There is a copy of this book, marked up by Warren with proposed revisions for Stuart Wright’s use on May 25, 1987, in the Special Collections Department of the Emory University Library. I quote Warren’s notes by permission. Warren has also marked up, slightly, a copy of this book now in the Robert Penn Warren Room of the Library of the Kentucky Museum at Western Kentucky University. I quote that volume too by permission. The setting typescript for the section of SP85 drawn from this volume consisted of taped-in photocopies of passages from BH. Because the revisions for SP85 are sometimes a vexed question, I have indicated where the SP85 revisions are made on SP85TS.}

`\sources{Title Page}` SP85 omits the dialogue between the old man and the young boy. SP85 capitalizes ‘‘time standard’’ in the quotation from Van Nostrand’s Scientific Encyclopedia, and does not capitalize ‘‘Time’’ in the quotation from Augustine.}

`\end{volumetitlepage}`

22 Implementation

22.1 Page geometry and crop marks

`\tightgeometry` There’s no reason why you should use the page geometry I used in *The Collected Poems of Robert Penn Warren*, and there are many reasons not to. But I include it just to show what is possible. If you issue `\tightgeometry` in your preamble, you will have the geometry I have used. If you issue `\tightleading` you will redefine `\normalsize` and `\small` to use tighter leading. Normal 10 point L^AT_EX uses 12 point leading. Strictly to save money, I redefined `\normalsize` to use 11 point leading. I use the `geometry` package, since it’s simpler to figure out. I give my page geometry here chiefly to remind the reader of some important variables that should be kept track of, such as `marginparsep`, which controls the separation of the marginal line numbers from the verse line, `marginparwidth`, which controls how wide the block for the marginal line numbers will be, `headsep`, which controls how far the text will be from the running headers, and `footskip`, which controls how far the last verse line will be from the marker which tells the reader that there is a stanza break at the end of the page (if there is one). I’ve also set the odd

side margin and the even side margin for two-sided printing. Finally, I have set the default handling of page endings to `\raggedbottom`. Verse should always be set with a ragged bottom margin, otherwise L^AT_EX will stretch the spaces between stanzas to make the bottom perfectly flush. When you enter prose sections, such as the editor's introduction, you should enter the command `\flushbottom` to make sure that the prose sections have flush page bottoms.

```

1 \newcommand{\tightgeometry}{\geometry{verbose, tmargin= 33pt,
2 textwidth=318.21pt, textheight=550pt,
3 marginparsep=7pt, marginparwidth=10pt,
4 headheight= 15pt,
5 headsep=19pt,
6 footskip=15pt,
7 lmargin=132pt}
8 \setlength{\oddsidemargin}{60pt}
9 \setlength{\evensidemargin}{65.41pt}}
10 \newcommand{\tightleading}{%
11 \makeatletter
12 \renewcommand\normalsize{%
13   \@setfontsize\normalsize\@xpt\@xipt
14   \abovedisplayskip 10\p@ \@plus2\p@ \@minus5\p@
15   \abovedisplayshortskip \z@ \@plus3\p@
16   \belowdisplayshortskip 6\p@ \@plus3\p@ \@minus3\p@
17   \belowdisplayskip \abovedisplayskip
18   \let\@listi\@listI}
19 \makeatother
20 \normalsize
21 \makeatletter
22 \renewcommand\small{%
23   \@setfontsize\small\@ixpt{10}%
24   \abovedisplayskip 8.5\p@ \@plus3\p@ \@minus4\p@
25   \abovedisplayshortskip \z@ \@plus2\p@
26   \belowdisplayshortskip 4\p@ \@plus2\p@ \@minus2\p@
27   \def\@listi{\leftmargin\leftmarginI
28             \topsep 4\p@ \@plus2\p@ \@minus2\p@
29             \parsep 2\p@ \@plus\p@ \@minus\p@
30             \itemsep \parsep}%
31   \belowdisplayskip \abovedisplayskip
32 }
33 \makeatother}
34
35

```

22.1.1 Internal font size commands

You will probably never need to use these font commands explicitly. I defined these for internal use within `poemscol`, so that a command will always call the same fonts.

As a way of making global changes to repeated features I have defined various special fonts for special purposes. For instance, in a Collected Poems in

which the poems are arranged by volume, with divider pages for the beginning of each volume, the first command sets the font for the volume title on the divider page, using the default font family, setting it in 18 point type on 23 point leading. The second command, as the name of the command indicates, sets the font for the subtitle of the volume to be 14 point type on 18 point leading. You can change these either by changing the values in your (renamed) style file, or by using `\renewcommand`. For instance, you can change the font parameters for the font for setting poem titles from 14 on 18 to 12 on 14 by issuing `\renewcommand{\poemtitlefont}{\fontsize{12}{14}\selectfont}` in your preamble. Notice that there are special fonts for titles in the back matter and in the table of contents as well.

```

36 \newcommand{\volumetitlefont}{\fontsize{18}{23}\selectfont}
37 \newcommand{\volumesubtitlefont}{\fontsize{14}{18}\selectfont}
38 \newcommand{\poemtitlefont}{\fontsize{14}{18}\selectfont}
39 \newcommand{\sequencetitlefont}{\fontsize{16}{20}\selectfont}
40 \newcommand{\subsectionfont}{\fontsize{12}{14.5}\selectfont}
41 \newcommand{\backmatterheaderfont}{\fontsize{16}{20}\selectfont}
42 \newcommand{\volumetitlesink}{\leavevmode\vspace{23.5pt}}
43 \newcommand{\backmattersink}{\leavevmode\vspace{21.5pt}}
44 \newcommand{\backmatterafterheadersink}{\leavevmode\vspace{11pt}}
45 \newcommand{\backmattertextfont}{\small}
46 \newcommand{\backmatterintrofont}{\normalsize}
47 \newcommand{\backmattervolumefont}{\fontsize{12}{14.5}\selectfont}
48 \newcommand{\backmattervolumesubtitlefont}{\fontsize{11}{13}\selectfont}
49 \newcommand{\contentsvolumefont}{\fontsize{14}{20}\selectfont}
50 \newcommand{\contentsvolumesubtitlefont}{\fontsize{12}{14.5}\selectfont}
51 \newcommand{\contentssequencetitlefont}{\fontsize{10}{14}\selectfont}
52 \newcommand{\contentspoemtitlefont}{\fontsize{10}{14}\selectfont}

```

22.2 Miscellaneous dimensions and constants

`poemscol` sets relatively large penalties for widows and clubs, both in the main text, and in the notes sections. There are also special penalties after volume titles in the notes sections, since one does not want to leave a volume title in the notes sections stranded at the bottom of a page. (Setting penalties may not automatically solve all the problems, however. You can fix an intractable widow problem in the contents or in the notes sections by issuing `\literalcontents{\pagebreak}` or `\literatemend{\pagebreak}` just before you issue the `\poemtitle` or `\volumetitle` that resulted in the problematic title line.) `poemscol` also manipulates penalties for places like the space between a poem's title and its first line. It defines special values for the white space before and after poems and for the amount of a stanza break. `\contentsindentone`, `\contentsindenttwo`, and so on are amounts to indent different hierarchical levels, say of poetic sequences and subsequences, in the table of contents.

```

53 \widowpenalty=300
54 \clubpenalty=300
55 \newcommand{\notespoemclubpenalty}{\penalty-300}

```

```

56 \newcommand{\notessequenceclubpenalty}{\penalty-1500}
57 \newcommand{\notesvolumetitlepenalty}{\penalty-1500}
Since the right margin of verse is ragged anyway, I allowed some flexibility for
slightly longer lines.
58 \hfuzz=2pt
For explicitly declared indented lines or ranges of lines:
59 \newlength{\verseindentamount}
60 \setlength{\verseindentamount}{2em}
61 \newcount\l@pcounter
62 \newcommand{\repeatedindent}[1]{\l@pcounter=#1%
63 \loop%
64 \ifnum\l@pcounter>0%
65 \hspace{\verseindentamount}%
66 \advance \l@pcounter -1
67 \repeat}
68 \newcommand{\verseindent}[1] [] {%
69 \ifthenelse{equal{#1}{}}{\hspace{\verseindentamount}}{\repeatedindent{#1}}}
70 %\newcommand{\verseindent}{\hspace{\verseindentamount}} %old version
71 \newlength{\indentedstanzaamount}
72 \setlength{\indentedstanzaamount}{\verseindentamount}
73 \newlength{\variablestanzaamount}
74 \setlength{\variablestanzaamount}{\indentedstanzaamount}
75 \newcommand{\adjustst@nzaindent}[1]{\l@pcounter=#1%
76 \loop%
77 \addtolength{\variablestanzaamount}{\indentedstanzaamount}%
78 \advance \l@pcounter -1%
79 \ifnum \l@pcounter>0
80 \repeat}
81 \newif\ifinindentedverse
82 \newenvironment{indentedverse}[1] [] {%
83 \inindentedversetrue%
84 \ifthenelse{equal{#1}{}}{\relax}{\adjustst@nzaindent{#1}}%
85 \let\=\@centercr%
86 \list{}{\itemsep\z@ \itemindent -\runoverindentvalue\listparindent \itemindent
87 \rightmargin 0sp\leftmargin 0sp\advance\leftmargin
88 \variablestanzaamount}\item[]}
89 {\endlist\inindentedversefalse\setlength{\variablestanzaamount}{\indentedstanzaamount}}
For multicolumn notes:
90 \setlength{\columnsep}{15pt}
A hierarchy of indentations for sequence section titles and subsection titles.
91 \newlength{\titleindentamount}
92 \setlength{\titleindentamount}{1pc}
93 %\newdimen\titleindentamount \titleindentamount=1pc
94 %\newdimen\titleindenttwoamount \titleindenttwoamount=2pc
95 \newlength{\titleindenttwoamount}
96 \setlength{\titleindenttwoamount}{2pc}
97 \newlength{\titleindentthreeamount}

```

```

98 \setlength{\titleindentthreeamount}{3pc}
99 %\newdimen\titleindentthreeamount \titleindentthreeamount=3pc
100 \newcommand{\titleindent}{\hspace{\titleindentamount}}
101 \setlength{\parindent}{1pc}
102 \newlength{\volumetitleindentamount}
103 \setlength{\volumetitleindentamount}{0pt}
104 %\newcommand{\volumetitleindent}{\hspace{\volumetitleindentamount}}
105 \newcommand{\volumetitleindent}{\relax}
106 \newlength{\volumetitlesecondlineindentamount}
107 \setlength{\volumetitlesecondlineindentamount}{0pt}
108 %\newcommand{\volumetitlesecondlineindent}{\hspace{\volumetitlesecondlineindentamount}}
109 \newcommand{\volumetitlesecondlineindent}{\relax}
110 % \titleindentamount=1pc
111 \newlength{\volumesubtitleindentamount}
112 \setlength{\volumesubtitleindentamount}{\titleindentamount}
113 \newcommand{\volumesubtitleindent}{\hspace{\volumesubtitleindentamount}}
114 \newlength{\volumesubtitlesecondlineindentamount}
115 \setlength{\volumesubtitlesecondlineindentamount}{\titleindentamount}
116 \newcommand{\volumesubtitlesecondlineindent}{\hspace{\volumesubtitlesecondlineindentamount}}
117 \newlength{\volumesectiontitleindentamount}
118 \setlength{\volumesectiontitleindentamount}{0pt}
119 % \newcommand{\volumesectiontitleindent}{\hspace{\volumesectiontitleindentamount}}
120 \newcommand{\volumesectiontitleindent}{\relax}
121 \newlength{\volumesectiontitlesecondlineindentamount}
122 \setlength{\volumesectiontitlesecondlineindentamount}{0pt}
123 % \newcommand{\volumesectiontitlesecondlineindent}{\hspace{\volumesectiontitlesecondlineindentamount}}
124 \newcommand{\volumesectiontitlesecondlineindent}{\relax}
125 \newlength{\poemtitleindentamount}
126 \setlength{\poemtitleindentamount}{0pt}
127 % \newcommand{\poemtitleindent}{\hspace{\poemtitleindentamount}}
128 \newcommand{\poemtitleindent}{\relax}
129 \newlength{\poemtitlesecondlineindentamount}
130 \setlength{\poemtitlesecondlineindentamount}{0pt}
131 % \newcommand{\poemtitlesecondlineindent}{\hspace{\poemtitlesecondlineindentamount}}
132 \newcommand{\poemtitlesecondlineindent}{\relax}
133 \newlength{\poemsubsubtitleindentamount}
134 \setlength{\poemsubsubtitleindentamount}{\titleindentamount}
135 \newcommand{\poemsubsubtitleindent}{\hspace{\poemsubsubtitleindentamount}}
136 \newlength{\poemsectiontitleindentamount}
137 \setlength{\poemsectiontitleindentamount}{\titleindentamount}
138 \newcommand{\poemsectiontitleindent}{\hspace{\poemsectiontitleindentamount}}
139 \newlength{\poemsectiontitlesecondlineindentamount}
140 \setlength{\poemsectiontitlesecondlineindentamount}{\titleindentamount}
141 \newcommand{\poemsectiontitlesecondlineindent}{\hspace{\poemsectiontitlesecondlineindentamount}}
142 \newlength{\poemsubsubsectiontitleindentamount}
143 \setlength{\poemsubsubsectiontitleindentamount}{\titleindenttwoamount}
144 \newcommand{\poemsubsubsectiontitleindent}{\hspace{\poemsectiontitleindentamount}}
145 \newlength{\sequencetitleindentamount}
146 \setlength{\sequencetitleindentamount}{0pt}
147 % \newcommand{\sequencetitleindent}{\hspace{\sequencetitleindentamount}}

```

```

148 \newcommand{\sequencetitleindent}{\relax}
149 \newlength{\sequencetitlesecondlineindentamount}
150 \setlength{\sequencetitlesecondlineindentamount}{0pt}
151 % \newcommand{\sequencetitlesecondlineindent}{\hspace{\sequencetitlesecondlineindentamount}}
152 \newcommand{\sequencetitlesecondlineindent}{\hspace{\relax}}
153 \newlength{\sequencesubtitleindentamount}
154 \setlength{\sequencesubtitleindentamount}{\titleindentamount}
155 \newcommand{\sequencesubtitleindent}{\hspace{\sequencesubtitleindentamount}}
156 \newlength{\sequencesubtitlesecondlineindentamount}
157 \setlength{\sequencesubtitlesecondlineindentamount}{\titleindentamount}
158 \newcommand{\sequencesubtitlesecondlineindent}{\hspace{\sequencesubtitlesecondlineindentamount}}
159 \newlength{\sequencesectiontitleindentamount}
160 \setlength{\sequencesectiontitleindentamount}{\titleindentamount}
161 \newcommand{\sequencesectiontitleindent}{\hspace{\sequencesectiontitleindentamount}}
162 \newlength{\sequencesectiontitlesecondlineindentamount}
163 \setlength{\sequencesectiontitlesecondlineindentamount}{\titleindentamount}
164 \newcommand{\sequencesectiontitlesecondlineindent}{\hspace{\sequencesectiontitlesecondlineinden}}
165 \newlength{\sequencesectionsubtitleindentamount}
166 \setlength{\sequencesectionsubtitleindentamount}{\titleindenttwoamount}
167 \newcommand{\sequencesectionsubtitleindent}{\hspace{\sequencesectionsubtitleindentamount}}
168 \newlength{\sequencesectionsubtitlesecondlineindentamount}
169 \setlength{\sequencesectionsubtitlesecondlineindentamount}{\titleindenttwoamount}
170 \newcommand{\sequencesectionsubtitlesecondlineindent}{\hspace{\sequencesectionsubtitlesecondlin}}
171 \newlength{\sequencesubsectiontitleindentamount}
172 \setlength{\sequencesubsectiontitleindentamount}{\titleindenttwoamount}
173 \newcommand{\sequencesubsectiontitleindent}{\hspace{\sequencesubsectiontitleindentamount}}
174 \newlength{\sequencesubsubsectiontitleindentamount}
175 \setlength{\sequencesubsubsectiontitleindentamount}{\titleindentthreeamount}
176 \newcommand{\sequencesubsubsectiontitleindent}{\hspace{\sequencesubsubsectiontitleindentamount}}
177 \newlength{\appendixtitleindentamount}
178 \setlength{\appendixtitleindentamount}{0pt}
179 % \newcommand{\appendixtitleindent}{\hspace{\appendixtitleindentamount}}
180 \newcommand{\appendixtitleindent}{\relax}
181 \newlength{\subappendixtitleindentamount}
182 \setlength{\subappendixtitleindentamount}{0pt}
183 % \newcommand{\subappendixtitleindent}{\hspace{\subappendixtitleindentamount}}
184 \newcommand{\subappendixtitleindent}{\relax}
185 \newlength{\forewordtitleindentamount}
186 \setlength{\forewordtitleindentamount}{0pt}
187 % \newcommand{\forewordtitleindent}{\hspace{\forewordtitleindentamount}}
188 \newcommand{\forewordtitleindent}{\relax}
189 \newlength{\notestitleindentamount}
190 \setlength{\notestitleindentamount}{0pt}
191 % \newcommand{\notestitleindent}{\hspace{\notestitleindentamount}}
192 \newcommand{\notestitleindent}{\relax}
193

```

A hierarchy of indentations for the table of contents:

```

194 \newdimen\volumetitleshiftamount \volumetitleshiftamount=1pc
195 \newcommand{\volumetitleshift}{\hbox{\hspace{\volumetitleshiftamount}}}

```

```

196 \newdimen\voladditionalamount \voladditionalamount=2pc
197 \newdimen\contentsindentoneamount \contentsindentoneamount=24pt
198 \newcommand{\contentsindentone}{\hspace{\contentsindentoneamount}}
199 \newdimen\contentsindenttwoamount \contentsindenttwoamount=42pt
200 \newcommand{\contentsindenttwo}{\hspace{\contentsindenttwoamount}}
201 \newdimen\contentsindentthreeamount \contentsindentthreeamount=60pt
202 \newcommand{\contentsindentthree}{\hspace{\contentsindentthreeamount}}
203 \newdimen\contentsindentfouramount \contentsindentfouramount=72pt
204 \newcommand{\contentsindentfour}{\hspace{\contentsindentfouramount}}
205 \newdimen\contentsindentfiveamount \contentsindentfiveamount=80pt
206 \newcommand{\contentsindentfive}{\hspace{\contentsindentfiveamount}}

```

A hierarchy of indentations for sequence section titles and subsection titles in the table of contents.

```

207 \newlength{\contentsvolumetitleindentamount}
208 \setlength{\contentsvolumetitleindentamount}{0pt}
209 %\newcommand{\contentsvolumetitleindent}{\hspace{\contentsvolumetitleindentamount}}
210 \newcommand{\contentsvolumetitleindent}{\relax}
211 \newlength{\contentsvolumetitlesecondlineindentamount}
212 \setlength{\contentsvolumetitlesecondlineindentamount}{0pt}
213 %\newcommand{\contentsvolumetitlesecondlineindent}{\hspace{\contentsvolumetitlesecondlineindent}}
214 \newcommand{\contentsvolumetitlesecondlineindent}{\relax}
215 \newlength{\contentsvolumesubtitleindentamount}
216 \setlength{\contentsvolumesubtitleindentamount}{\titleindentamount}
217 \newcommand{\contentsvolumesubtitleindent}{\hspace{\contentsvolumesubtitleindentamount}}
218 \newlength{\contentsvolumesubtitlesecondlineindentamount}
219 \setlength{\contentsvolumesubtitlesecondlineindentamount}{\titleindentamount}
220 \newcommand{\contentsvolumesubtitlesecondlineindent}{\hspace{\contentsvolumesubtitlesecondlineindent}}
221 \newlength{\contentsvolumesectiontitleindentamount}
222 \setlength{\contentsvolumesectiontitleindentamount}{0pt}
223 \newcommand{\contentsvolumesectiontitleindent}{\hspace{\contentsvolumesectiontitleindentamount}}
224 %\newcommand{\contentsvolumesectiontitleindent}{\relax}
225 \newlength{\contentsvolumesectiontitlesecondlineindentamount}
226 \setlength{\contentsvolumesectiontitlesecondlineindentamount}{0pt}
227 \newcommand{\contentsvolumesectiontitlesecondlineindent}{\hspace{\contentsvolumesectiontitlesecondlineindent}}
228 \newlength{\contentspoemtitleindentamount}
229 \setlength{\contentspoemtitleindentamount}{\contentsindentoneamount}
230 %\setlength{\contentspoemtitleindentamount}{0pt}
231 \newcommand{\contentspoemtitleindent}{\hspace{\contentspoemtitleindentamount}}
232 %\newcommand{\contentspoemtitleindent}{\relax}
233 \newlength{\contentspoemtitlesecondlineindentamount}
234 \setlength{\contentspoemtitlesecondlineindentamount}{\contentspoemtitleindentamount}
235 \newcommand{\contentspoemtitlesecondlineindent}{\hspace{\contentspoemtitlesecondlineindentamount}}
236 %\newcommand{\contentspoemtitlesecondlineindent}{\relax}
237 \newlength{\contentspoemsubsubtitleindentamount}
238 \setlength{\contentspoemsubsubtitleindentamount}{\contentspoemsubsubtitleindentamount}
239 \newcommand{\contentspoemsubsubtitleindent}{\hspace{\contentspoemsubsubtitleindentamount}}
240 \newlength{\contentspoemsectiontitleindentamount}
241 \setlength{\contentspoemsectiontitleindentamount}{\contentsindenttwoamount}
242 \newcommand{\contentspoemsectiontitleindent}{\hspace{\contentspoemsectiontitleindentamount}}

```

```

243 \newlength{\contentspoemsectiontitlesecondlineindentamount}
244 \setlength{\contentspoemsectiontitlesecondlineindentamount}{\contentspoemsectiontitleindentamount}
245 \newcommand{\contentspoemsectiontitlesecondlineindent}{\hspace{\contentspoemsectiontitlesecondlineindentamount}}
246 \newlength{\contentspoemsubsectiontitleindentamount}
247 \setlength{\contentspoemsubsectiontitleindentamount}{\contentsindentthreamount}
248 \newcommand{\contentspoemsubsectiontitleindent}{\hspace{\contentsindentthreamount}}
249 \newlength{\contentsssequencetitleindentamount}
250 \setlength{\contentsssequencetitleindentamount}{\contentsindentoneamount} %313
251 \newcommand{\contentsssequencetitleindent}{\hspace{\contentsssequencetitleindentamount}}
252 %\newcommand{\contentsssequencetitleindent}{\relax}
253 \newlength{\contentsssequencetitlesecondlineindentamount}
254 \setlength{\contentsssequencetitlesecondlineindentamount}{\contentsindentoneamount} %313
255 \newcommand{\contentsssequencetitlesecondlineindent}{\hspace{\contentsssequencetitlesecondlineindentamount}}
256 %\newcommand{\contentsssequencetitlesecondlineindent}{\hspace{\relax}}
257 \newlength{\contentsssequencesubtitleindentamount}
258 \setlength{\contentsssequencesubtitleindentamount}{\contentsindenttwoamount} %313
259 \newcommand{\contentsssequencesubtitleindent}{\hspace{\contentsssequencesubtitleindentamount}}
260 \newlength{\contentsssequencesubtitlesecondlineindentamount}
261 \setlength{\contentsssequencesubtitlesecondlineindentamount}{\contentsindenttwoamount} %313
262 \newcommand{\contentsssequencesubtitlesecondlineindent}{\hspace{\contentsssequencesubtitlesecondlineindentamount}}
263 \newlength{\contentsssequencesectiontitleindentamount}
264 \setlength{\contentsssequencesectiontitleindentamount}{\contentsindenttwoamount} %313
265 \newcommand{\contentsssequencesectiontitleindent}{\hspace{\contentsssequencesectiontitleindentamount}}
266 \newlength{\contentsssequencesectiontitlesecondlineindentamount}
267 \setlength{\contentsssequencesectiontitlesecondlineindentamount}{\contentsindenttwoamount} %313
268 \newcommand{\contentsssequencesectiontitlesecondlineindent}{\hspace{\contentsssequencesectiontitlesecondlineindentamount}}
269 \newlength{\contentsssequencesectionsubsubtitleindentamount}
270 \setlength{\contentsssequencesectionsubsubtitleindentamount}{\contentsindentthreamount} %313
271 \newcommand{\contentsssequencesectionsubsubtitleindent}{\hspace{\contentsssequencesectionsubsubtitleindentamount}}
272 \newlength{\contentsssequencesectionsubsubtitlesecondlineindentamount}
273 \setlength{\contentsssequencesectionsubsubtitlesecondlineindentamount}{\contentsindentthreamount} %313
274 \newcommand{\contentsssequencesectionsubsubtitlesecondlineindent}{\hspace{\contentsssequencesectionsubsubtitlesecondlineindentamount}}
275 \newlength{\contentsssequencesubsubsectiontitleindentamount}
276 \setlength{\contentsssequencesubsubsectiontitleindentamount}{\contentsindentthreamount}
277 \newcommand{\contentsssequencesubsubsectiontitleindent}{\hspace{\contentsssequencesubsubsectiontitleindentamount}}
278 \newlength{\contentsssequencesubsubsectiontitlesecondlineindentamount}
279 \setlength{\contentsssequencesubsubsectiontitlesecondlineindentamount}{\contentsindentfouramount}
280 \newcommand{\contentsssequencesubsubsectiontitlesecondlineindent}{\hspace{\contentsssequencesubsubsectiontitlesecondlineindentamount}}
281
282

```

White space after poem titles, after poems, and after sequence titles.

```

283 \newcommand{\afterpoemtitleskip}{\smallskip}
284 \newcommand{\afterpoemskip}{\bigskip}
285 \newcommand{\aftersequencetitleskip}{\medskip}

```

A little extra white space between stanzas.

```

286 \newcommand{\stanzaskip}{\medskip}

```

Penalties to encourage page breaks before poem titles, before multi-line poem titles, and before sequence titles.

```

287 \newcommand{\poemtitlepenalty}{\penalty-1000}
288 \newcommand{\multilinetitlepenalty}{\penalty-3000}
289 \newcommand{\sequencetitlepenalty}{\penalty-3000}
290 \newcommand{\multilinesequencepenalty}{\penalty-3500}

```

22.3 Title Schemes

Ways of controlling the placement of titles.

```

291 \newlength{\poemtitlewidth}
292 \newif\iftitlescenteredonleftverseblock
293 \newif\iftitlesatleftmarginofcenteredblock
294 \newif\iftitlesatleftversemargin
295 \newif\ifnormaltitleindentation
296 %
297 \newcommand{\normaltitleindentationscheme}{%
298 \normaltitleindentationtrue%
299 \titlesatleftversemarginfalse%
300 \titlescenteredonleftverseblockfalse%
301 \titlesatleftmarginofcenteredblockfalse%
302 \centertitlesonfalse%
303 }
304 \newcommand{\titlesatleftversemarginscheme}{%
305 \normaltitleindentationfalse%
306 \titlesatleftversemargintrue%
307 \titlescenteredonleftverseblockfalse%
308 \titlesatleftmarginofcenteredblockfalse%
309 \centertitlesonfalse%
310 }
311 \newcommand{\titlescenteredonleftverseblockscheme}{%
312 \normaltitleindentationfalse%
313 \titlesatleftversemarginfalse%
314 \titlescenteredonleftverseblocktrue%
315 \titlesatleftmarginofcenteredblockfalse%
316 \centertitlesonfalse%
317 }
318 \newcommand{\titlesatleftmarginofcenteredblockscheme}{%
319 \normaltitleindentationfalse%
320 \titlesatleftversemarginfalse%
321 \titlescenteredonleftverseblockfalse%
322 \titlesatleftmarginofcenteredblocktrue%
323 \centertitlesonfalse%
324 }
325 \newcommand{\centertitlescheme}{%
326 \normaltitleindentationfalse%
327 \titlesatleftversemarginfalse%
328 \titlescenteredonleftverseblockfalse%
329 \titlesatleftmarginofcenteredblockfalse%
330 \centertitlesontrue%
331 \centerepigraphsontrue%

```

```

332 }
333 \newlength{\lefttitleaddition}
334 \setlength{\lefttitleaddition}{0pt}
335 \newcommand{\l@ftc@ntertitleblock}{\rightmargin      \z@}%
336 \setlength{\lefttitleaddition}{\versewidth}%
337 \addtolength{\lefttitleaddition}{-\poemtitlewidth}%
338 \addtolength{\lefttitleaddition}{-0.5\lefttitleaddition}%
339 \setlength{\lefttitlemargin}{\lefttitleaddition}%
340 }
341

```

22.4 Verse

The verse environment here is taken from L^AT_EX, slightly modified to indent run over lines more. The idea is to distinguish the automatic indentation of run over lines from the explicitly declared indentation of indented lines. You can change the amount of indentation of runover lines with `\runoverindent`.

```

342 \def\makeatletter{\catcode'\@=11}
343 \def\makeatother{\catcode'\@=12 }
344 \newcommand{\runoverindent}[1]{\global\edef\runoverindentvalue{#1}
345 }
346 \runoverindent{6em}
347 % pmclverse (runover indented more than it is in the normal verse
348 % environment)
349 % \newenvironment{pmclverse}{%
350 % \let\@=\@centercr%
351 % \list{}{\itemsep\z@ \itemindent -\runoverindentvalue\listparindent \itemindent
352 % \rightmargin 1sp\leftmargin 1sp\advance\leftmargin
353 % \runoverindentvalue}\item[]}
354 % {\endlist}
355 \newif\iflinenumberscenteredwithverse
356 \linenumberscenteredwithversetrue
357 %
358 \newlength{\marginparsepmin}
359 \setlength{\marginparsepmin}{2em}
360 %
361 \newlength{\versemarginadjust}
362 \setlength{\versemarginadjust}{0pt}
363 %
364 \newif\iftextcenteringturnedon
365 \textcenteringturnedontrue
366 %
367 \newcommand{\v@riablemarginpar}{\setlength{\marginparsep}{-\leftmargin}%
368 \addtolength{\marginparsep}{\marginparsepmin}}
369 %
370 \newcommand{\c@nterverseblock}[1]{\rightmargin      \z@%
371 \setlength{\leftmargin}{\linewidth}%
372 \addtolength{\leftmargin}{-#1}%
373 \addtolength{\leftmargin}{-0.5\leftmargin}%

```

```

374 \iflinenumberscenteredwithverse\v@riablemarginpar\fi}
375 \newif\iflastpoemcentered
376 \newenvironment{pmclverse}[1][\linewidth]{%
377 \global\lastpoemcenteredfalse
378 \let\=\@centercr%
379 \list{}{\itemsep\z@
380 \itemindent -\runoverindentvalue
381 \listparindent \itemindent
382 \ifdim #1 < \linewidth
383 \iftextcenteringturnedon
384 \c@nterverseblock{#1}%
385 \global\lastpoemcenteredtrue
386 \else
387 \rightmargin \leftmargin
388 \addtolength{\leftmargin}{-\versemarginadjust}\fi
389 \else
390 \rightmargin \leftmargin
391 \addtolength{\leftmargin}{-\versemarginadjust}
392 \fi
393 \advance\leftmargin\runoverindentvalue}
394 \item[]}
395 {\endlist}
396 % next is from 2.88
397 \newenvironment{pmclverse}[1][\linewidth]{%
398 \let\=\@centercr%
399 \list{}{\itemsep\z@
400 \itemindent -\runoverindentvalue
401 \listparindent \itemindent
402 \ifdim #1 < \linewidth
403 \iftextcenteringturnedon
404 \c@nterverseblock{#1}%
405 \else
406 \rightmargin \leftmargin
407 \addtolength{\leftmargin}{-\versemarginadjust}\fi
408 \else
409 \rightmargin \leftmargin
410 \addtolength{\leftmargin}{-\versemarginadjust}
411 \fi
412 \advance\leftmargin\runoverindentvalue}
413 \item[]}
414 %{\endlist}% from 2.72 with additions
415 \newenvironment{pmclverse}[1][\linewidth]{%
416 \let\=\@centercr%
417 \list{}{\itemsep\z@
418 \itemindent -\runoverindentvalue
419 \listparindent \itemindent
420 \ifdim #1 < \linewidth
421 \rightmargin \z@
422 \setlength{\leftmargin}{\linewidth}%
423 \addtolength{\leftmargin}{-#1}%

```

```

424 %           \addtolength{\leftmargin}{-0.5\leftmargin}%
425 %           \iflinenumberscenteredwithverse
426 %           \setlength{\marginparsep}{-\leftmargin+\marginparsepmin}
427 %           \fi
428 %       \else
429 %           \rightmargin           \leftmargin
430 %           \addtolength{\leftmargin}{-\versemarginadjust}
431 %       \fi
432 % \advance\leftmargin\runoverindentvalue}
433 % \item[]}
434 % {\endlist\setlength{\marginparsep}{0pt}} % from email
435
436 % \newenvironment{pmclverse}[1][\linewidth]{%
437 % \let\=\@centercr%
438 % \list{}\itemsep\z@
439 % \itemindent -\runoverindentvalue
440 % \listparindent \itemindent
441 %     \iftextcenteringturnedon
442 %     \ifdim #1 < \linewidth
443 %         \rightmargin           \z@
444 %         \setlength{\leftmargin}{\linewidth}%
445 %         \addtolength{\leftmargin}{-#1}%
446 %         \addtolength{\leftmargin}{-0.5\leftmargin}%
447 % \iflinenumberscenteredwithverse\setlength{\marginparsep}{-\leftmargin+\marginparsepmin}\fi
448 %     \else
449 %         \rightmargin           \leftmargin
450 %         \addtolength{\leftmargin}{-\versemarginadjust}
451 %     \fi % linewidth
452 % \else
453 %     \rightmargin           \leftmargin
454 %     \addtolength{\leftmargin}{-\versemarginadjust}
455 %
456 %     \fi% textcentering
457 % \advance\leftmargin\runoverindentvalue}
458 % \item[]}
459 % {\endlist\setlength{\marginparsep}{0pt}}% % draft
460
461 % \let\=\@centercr%
462 % \list{}\itemsep\z@
463 % \itemindent -\runoverindentvalue
464 % \listparindent \itemindent
465 %     \ifdim #1 < \linewidth
466 %         \rightmargin           \z@
467 %         \setlength{\leftmargin}{\linewidth}%
468 %         \addtolength{\leftmargin}{-#1}%
469 %         \addtolength{\leftmargin}{-0.5\leftmargin}%
470 %     \else
471 %         \rightmargin           \leftmargin
472 %         \addtolength{\leftmargin}{-\versemarginadjust}
473 %     \fi

```

```

474 % \advance\leftmargin\runoverindentvalue}
475 % \item[]}
476 % {\endlist} % first version from 2.81
477 % \newenvironment{pmclverse}[1][\linewidth]{%
478 % \let\=\@centercr%
479 % \list{}{\itemsep\z@
480 % \itemindent -\runoverindentvalue
481 % \listparindent \itemindent
482 %         \ifdim #1 < \linewidth
483 %             \rightmargin \z@
484 %             \setlength{\leftmargin}{\linewidth}%
485 %             \addtolength{\leftmargin}{-#1}%
486 %             \addtolength{\leftmargin}{-0.5\leftmargin}%
487 %         \else
488 %             \rightmargin \leftmargin
489 %         \fi
490 % \advance\leftmargin\runoverindentvalue}
491 % \item[]}
492 % {\endlist}% from 2.72
493 \newif\ifinquotedverse
494 \newenvironment{quotedverse}{%
495 \inquotedversetrue
496 \let\=\@centercr%
497 \list{}{\itemsep\z@ \itemindent -\runoverindentvalue\listparindent \itemindent
498         \rightmargin Osp\leftmargin Osp\advance\leftmargin
499         \runoverindentvalue}\item[]}
500 {\endlist\inquotedversefalse}
501 % rfoverse (flushes runover to right) (Just a placeholder now.)
502 % \newif\ifrfv
503 % \rfvfalse
504 % \newcommand{\rightflushrunoververse}{\global\rfvtrue}
505 % \newcommand{\indentrunoververse}{\global\rfvfalse}
506 % \newenvironment{rfoverse}{\begin{pmclverse}}{\end{pmclverse}}
507 % % verse environment with a switch
508 % \renewenvironment{verse}{\ifrfv\begin{rfoverse}}\else\begin{pmclverse}\fi}
509 % {\ifrfv\end{rfoverse}}\else\end{pmclverse}\fi}

```

22.5 Miscellaneous internal counters

`\verselinenumber` is the line number, obviously. `\printlineindex` records how many lines have passed since the last marginal line number was output. `\lineindexrepeat` governs how often the marginal line numbers appear. `\lemmalines` and `\lemmaend` are for setting number ranges for multiline lemmas.

```

510 \newcounter{verselinenumber}
511 \newcounter{printlineindex}
512 \newcounter{verselinenumberscratch}
513 \newcounter{printlineindexscratch}
514 \newcounter{lineindexrepeat} \setcounter{lineindexrepeat}{9}
515 \newcounter{lemmalines}

```

```

516 \setcounter{lemmalines}{0}
517 \newcounter{lemmaend}
518 \setcounter{lemmaend}{0}

```

This next counter is used to make labels for each poem for the contents and notes sections.

```

519 \newcounter{poemnumber}
520 \setcounter{poemnumber}{1}

```

These next two are used to set the page numbers in the running headers of the various notes sections, which are of the form “Textual notes to pp. xx–yy.”

```

521 \newcounter{notepageholdertitle} \setcounter{notepageholdertitle}{1}
522 \newcounter{notepageholdernote} \setcounter{notepageholdernote}{1}

```

22.6 Miscellaneous token lists

Since the explanatory notes section and the emendations section should only open an entry for poems for which there actually are explanatory notes or emendations, the current are held in token lists in case they are needed. `\titlesofar` and `\titleincrement` are used to concatenate multi-line titles.

```

523 \newtoks{\fulltitleholder}
524 \newtoks{\titlesofar}
525 \newtoks{\titleincrement}

```

22.7 Miscellaneous booleans

Most of these have self-explanatory names.

```

526 \newif\ifinstanza
527 \newif\ifinpoem
528 \newif\ifpoemcontentson
529 \newif\iftextnoteson
530 \newif\ifverselinenumbers
531 \newif\ifexplanon
532 \newif\ifemendationson
533 \global\verselinenumberstrue
534 \newif\ifindexingon
535 \global\indexingontrue
536 \ifindexingon
537 \makeindex
538 \fi
539 \newif\ifincludeaccidentals
540 \global\includeaccidentalstrue
541 \newif\ifincludetypescripts
542 \global\includetypescriptstrue
543 \newif\ifredundantemendations
544 \global\redundantemendationsfalse
545 \newif\ifnoemendyet
546 \newif\ifnoexplainyet
547 \global\noemendyettrue

```

```

548 \global\noexplainyettrue
549 \newif{\ifmiddlecontentsline}
550 \middlecontentslinefalse
551 \newif{\iflastcontentsline}
552 \lastcontentslinefalse
553 \newif{\ifputpagenumberincontents}
554 \putpagenumberincontentstrue
555 \newif{\ifputpagenumberinnotes}
556 \putpagenumberinnotesttrue
557 \newif{\ifsinglelinetitle}
558 \singlelinetitletrue
559 \newif{\iftitlefirstline}
560 \titlefirstlinefalse
561 \newif{\iftitlemiddleline}
562 \titlemiddlelinefalse
563 \newif{\iftitlelastline}
564 \titlelastlinefalse
565 \newif{\ifverserightflush}
566 \verserightflushfalse
567 \newif\ifrangelemma
568 \rangelemmafalse
569 \newcommand{\makeverselinenumbers}{\global\verselinenumberstrue}
570 \let\makelinenumbers=\makeverselinenumbers% for compatibility
571 \newif\iftextnotesatend
572 \textnotesatendtrue
573 \newif\ifemendationsatend
574 \emendationsatendtrue
575 \newif\ifexplanatend
576 \explanatendtrue
577 \newif\iftextfootnotespara
578 \textfootnotesparatrue
579 \newif\ifsourcesfootnotespara
580 \sourcesfootnotesparafalse
581 \newif\ifemendationfootnotespara
582 \emendationfootnotesparatrue
583 \newif\ifexplanfootnotespara
584 \explanfootnotesparafalse

```

22.8 Defining page styles

These define several special page styles. To use them you must have the `fancyhdr` package installed. First, the default running headers: the right side (`\volumeheader`) is the title of the volume in a multivolume edition, and the left (`\lefthead`) is the title of the general collection.

```

\volumeheader
585 \newcommand{\volumeheader}[1]{\global\edef\volumeheadervalue{#1}
586 }

```

`\lefthead`

```
587 \newcommand{\lefthead}[1]{\global\edef\leftheadvalue{#1}
588 }
589 \lefthead{\relax}
590 \volumeheader{\relax}
591 \newcommand{\righthead}[1]{\volumeheader{#1}}
```

The default page style. Note the use of the mark mechanism to keep track of cases where the stanza breaks and page breaks overlap.

`\pagestylefancy`

```
592 \newlength{\headoffsetlength}
593 \setlength{\headoffsetlength}{-1sp}
594 \addtolength{\headoffsetlength}{\parindent}
595 \raggedbottom
596 \pagestyle{fancy}
597 \fancyhead{}
598 \fancyfoot{}
599 \fancyhoffset [RO,LE]{\headoffsetlength}
600 \fancyhead [RO]{{\small\textrm{\thepage}}}
601 \fancyhead [LE]{{\small\textrm{\thepage}}}
602 \fancyhead [CO]{\hfil{\small{\em \volumeheadvalue}}\hfil}
603 \fancyhead [CE]{\hfil{\small{\em \leftheadvalue}}\hfil}
604 \fancyfoot [CE]{{\small \botmark}\hfil}
605 \fancyfoot [CO]{\hfil{\small \botmark}}
606 \renewcommand{\headrulewidth}{0pt}
607 \renewcommand{\footrulewidth}{0pt}
```

`\pagestylemain`

```
608 \fancypagestyle{main}{%
609 \fancyhead{}
610 \fancyfoot{}
611 \fancyhoffset [RO,LE]{\headoffsetlength}
612 \fancyhead [RO]{{\small\textrm{\thepage}}}
613 \fancyhead [LE]{{\small\textrm{\thepage}}}
614 \fancyhead [CO]{\hfil{\small{\em \volumeheadvalue}}\hfil}
615 \fancyhead [CE]{\hfil{\small{\em \leftheadvalue}}\hfil}
616 \fancyfoot [CE]{{\small \botmark}\hfil}
617 \fancyfoot [CO]{\hfil{\small \botmark}}
618 \renewcommand{\headrulewidth}{0pt}
619 \renewcommand{\footrulewidth}{0pt}
620 }
```

Style for the first page of every volume in a Collected Poems. You don't have to call this style explicitly. It is called by the `\volumetitlepage` environment. But of course if you want to change the style of those pages, you should do it here.

`volumefirststyle`

```
621 \fancypagestyle{volumefirststyle}{%
```

```

622 \fancyhf{}
623 \fancyfoot[C]{\hfil{\small \botmark}\hfil}
624 \renewcommand{\headrulewidth}{0pt}
625 \renewcommand{\footrulewidth}{0pt}
626 }

```

Style for plain pages.

plain

```

627 \fancypagestyle{plain}{%
628 \fancyhf{}
629 \fancyhead[RO,LE]{\small\textrm{\thepage}}
630 \renewcommand{\headrulewidth}{0pt}
631 \renewcommand{\footrulewidth}{0pt}
632 }

```

Style for long poems.

\myversemarks

```

633 \newtoks{\singlelineabbrev}
634 \singlelineabbrev={1.\ }
635 \newcommand{\changesinglelineabbrev}[1]{\singlelineabbrev={#1}}
636 \newtoks{\multiplelineabbrev}
637 \newcommand{\changemultiplelineabbrev}[1]{\multiplelineabbrev={#1}}
638 \multiplelineabbrev{11.\ }
639 \newcommand{\myversemarks}{%
640 \ifthenelse{\equal{\thefirstmarks{verselinemark}}{\thebotmarks{verselinemark}}}{%
641 \unskip ~\the\singlelineabbrev~\thefirstmarks{verselinemark}}% if equal
642 {\unskip ~\the\multiplelineabbrev~\thefirstmarks{verselinemark}--\thebotmarks{verselinemark}} %

```

longpoem

```

643 \fancypagestyle{longpoem}{%
644 \fancyhead{}
645 \fancyfoot{}
646 \fancyhfoffset[RO,LE]{\headoffsetlength}
647 \fancyhead[RO]{\small\textrm{\thepage}}
648 \fancyhead[LE]{\small\textrm{\thepage}}
649 \fancyhead[CO]{\hfil{\small{\em \volumeheadervalue ~\myversemarks}}\hfil}
650 \fancyhead[CE]{\hfil{\small{\em \leftheadervalue~\myversemarks}}\hfil}
651 \fancyfoot[CE]{\small \botmark}\hfil}
652 \fancyfoot[CO]{\hfil{\small \botmark}}
653 \renewcommand{\headrulewidth}{0pt}
654 \renewcommand{\footrulewidth}{0pt}
655 }

```

Style for divider pages between volumes

volumetitlestyle

```

656 \fancypagestyle{volumetitlestyle}{%
657 \fancyhf{}

```

```

658 \renewcommand{\headrulewidth}{0pt}
659 \renewcommand{\footrulewidth}{0pt}
660 }

```

`\resetpagestyle` `\resetpagestyle` restores the fancy page style of the main sections of the book. `\putpoemcontents` changes the fancy page style, and `\resetpagestyle`, which is called by `\putpoemcontents` as it finishes, restores the original style

```

661 \newcommand{\resetpagestyle}{\pagestyle{main}
662 % \fancyhead{}
663 % \fancyfoot{}
664 % \fancyhead[RO,LE]{\small\textrm{\thepage}}
665 % \fancyhead[CO]{\hfil\small{\em \volumeheadervalue}}
666 % \fancyhead[CE]{\small{\em \leftheadervalue}\hfil}
667 % \fancyfoot[CE]{\small \botmark}\hfil}
668 % \fancyfoot[CO]{\hfil\small \botmark}}
669 \renewcommand{\headrulewidth}{0pt}
670 % \renewcommand{\footrulewidth}{0pt}
671 }

```

`\clearempydoublepage` This macro is useful for making sure that the verso of a title page is blank.

```

672 \newcommand{\clearempydoublepage}{\newpage{\pagestyle{empty}\cleardoublepage}}
673 %

```

`\mymarks` Here the marks mechanism keeps track of pages from which notes come. Marks are used different in the notes sections and in the body of the volume. In the body, they are used to keep track of cases where a stanza break falls on a page break. In the notes sections, they set the running headers.

```

674 \newtoks{\singlepageabbrev}
675 \singlepageabbrev={p.}
676 \newcommand{\changesinglepageabbrev}[1]{\singlepageabbrev={#1}}
677 \newtoks{\multiplepageabbrev}
678 \newcommand{\changemultiplepageabbrev}[1]{\multiplepageabbrev={#1}}
679 \multiplepageabbrev{pp.}
680 \newcommand{\mymarks}{%
681   \ifthenelse{equal{\firstmark}{\botmark}}%
682     {\unskip ~\the\singlepageabbrev~\firstmark}% if equal
683     {\unskip ~\the\multiplepageabbrev~\firstmark--\botmark}}%if not equal
684 \newcommand{\poemdotfill}{\dotfill}

```

22.9 Environments: poem, and stanza

Here are definitions of the poem and stanza environments, and of the `\verseline` and `\stanzalinestraddle` macros.

`stanza` Page breaks are slightly encouraged in stanza breaks. Notice that entering a stanza sets the mark to `\relax` and leaving it sets the mark to `*` (the default value of `\stanzaatbottom`). If you want to use some other symbol for this purpose, use `\stanzaatbottom` or `\nostanzaatbottom` (if you also want to mark cases where there is *no* stanza break at the bottom of the page) to change it.

```

685 \newenvironment{stanza}{\penalty-100\instanzatrue\mark{\nostanzaatbottomvalue\ }}
686 {\nobreak\mark{\stanzaatbottomvalue\ }\nobreak\ifspeciallinelock%
687 \relax\else%
688 \nolinebreak\incrementverselinenumber%
689 \fi%
690 \speciallinelockfalse%
691 \nobreak
692 \instanzafalse
693
694 \stanzaskip
695 }
696
697 \newenvironment{marginenvironment}{-}{-}
698 \newcommand{\stanzalinestraddle}
699 {\begin{stanza}\addtocounter{verselinenumber}{-1}%
700 \addtocounter{printlineindex}{-1}%
701 }

```

The next two environments are for contents entries and titles. The idea is to handle overrun titles the way overrun lines are handled in verse. Contents entries indent the overrun slightly. Titles do not indent the overrun relative to the first line, but preserve the indentation of that line.

```

702 \newlength{\contentsentryoverrun}
703 \setlength{\contentsentryoverrun}{\contentsindentoneamount}
704 \newenvironment{contentsentryenvironment}{%
705 \language=255%no hyphenation in contents
706 \let\=\@centercr%
707 \list{}{\topsep\z@%
708 \partopsep\z@%
709 \itemsep\z@ \itemindent -\contentsentryoverrun\listparindent \itemindent
710 \rightmargin 1sp\leftmargin 1sp\advance\leftmargin
711 \contentsentryoverrun}\item[]{\endlist}
712 \newlength{\titleentryoverrun}
713 \setlength{\titleentryoverrun}{\z@}
714 \newenvironment{titleentryenvironment}{%
715 \language=255%no hyphenation in poem titles
716 \let\=\@centercr%
717 \list{}{\topsep\z@%
718 \partopsep\z@%
719 \itemsep\z@ \itemindent -\titleentryoverrun%
720 \listparindent \itemindent %
721 \iftitlesatleftmarginofcenteredblock%
722 \left@ligntitleblock%
723 \rightmargin \z@\leftmargin \lefttitlemargin%
724 \else%
725 \iftitlescenteredonleftverseblock
726 \l@ftc@ntertitleblock
727 \rightmargin \z@\leftmargin \lefttitlemargin
728 \else
729 \rightmargin \z@\leftmargin \z@%

```

```

730 \fi\fi%
731 \advance\leftmargin \titleentryoverrun}\item[]}{\endlist}
732 % older version:
733 %\newenvironment{titleentryenvironment}{%
734 %\language=255%no hyphenation in poem titles
735 %\let\=\@centercr%
736 %\list{}{\topsep\z@%
737 %\partopsep\z@%
738 %\itemsep\z@ \itemindent -\titleentryoverrun%
739 %\listparindent \itemindent %
740 %\ifleftaligntitles
741 %\left@ligntitleblock
742 %\rightmargin 1sp\leftmargin \lefttitlemargin%
743 %\else
744 %\rightmargin 1sp\leftmargin 1sp%
745 %\fi
746 %\advance\leftmargin \titleentryoverrun}\item[]}{\endlist}

```

The poem environment. The little trick about setting the language number is designed to suppress automatic hyphenation in the poem environment. The booleans tell the `\emendation` and `\explanatory` macros that there have not yet been emendations or explanatory notes for this poem. The little trick with `\mark` sets the value of `\mark` to the current value of `\stanzaatbottom` (by default `*`) if the current location is in a poem but not in a stanza (which is to say, in a stanza break). The `\pagestyle` for poetry sets the value of `\mark` in the footer, which is `*` if the page break happens at a stanza break, and `\relax` if the page break happens anywhere else.

poem

```

747 \newlength{\versewidth}
748 \setlength{\versewidth}{\linewidth}% default length for \versewidth
749 \newenvironment{poem}[1][\linewidth]
750 {\raggedright%
751     \language=255%no hyphenation in verse
752     \noemendyettrue%
753     \noexplainyettrue%
754     \setcounter{verselinenum}{0}\setcounter{printlineindex}{0}%
755     \nobreak\begin{pmclverse}[#1]%
756     \inpoemtrue\nobreak\mark{\relax}%
757     }\end{pmclverse}%
758     \inpoemfalse\mark{\relax}%
759     \goodbreak\afterpoemskip%\bigskip
760 }

```

rightflushverse Sets verse with the runover portions of long lines flushed to the right. Each line must begin with `\rightversebegin`. This code was suggested to me by Mark Wooding on `comp.text.tex`, who describes the code as “very unpleasant.”

```

761 \newenvironment{rightflushverse}{\let\oldleftskip=\leftskip%
762 \leftskip=1 \leftskip\advance\leftskip by Opt plus 1fill}%
763 {\let\leftskip=\oldleftskip}

```

22.10 Environments: main title page, divider pages

Environments for the main title page, and for the divider pages for individual volumes in a Collected Poems.

```
volumetitlepage
  maintitlepage 764 \newenvironment{volumetitlepage}
booksectionpage 765 {\par\clearpage{\pagestyle{volumetitlestyle}\cleardoublepage}
766 \thispagestyle{volumetitlestyle}
767   {\newpage\thispagestyle{volumetitlestyle}
768 \cleardoublepage\thispagestyle{volumefirststyle}}
769 \newenvironment{maintitlepage}
770 {\par\cleardoublepage\thispagestyle{volumetitlestyle}
771 }{\newpage\thispagestyle{volumetitlestyle}\cleardoublepage}
772 \newenvironment{booksectionpage}
773 {\par\newpage\thispagestyle{volumetitlestyle}}{\newpage}
```

22.11 Marginal line numbers, verse lines, line cross references, etc.

The default is that the line numbers are on the left side, and that the `\marginparsep` is 18pt. If you use `\pmclleftsidepar` the placement of the number is controlled by `\marginparsep` and `\marginparwidth`. You should experiment with different values until you find a set that suits you. A rule of thumb for me is that the `\marginparsep` if the numbers is on the right should be the negative of the value if it is on the left. First, some lengths and ifs:

```
774 \setlength{\marginparsep}{18pt}
775 \setlength{\marginparwidth}{18pt}
776 \newif\ifnumbersswitch \numbersswitchfalse
777 \newif\ifnumbersright \numbersrightfalse
```

Next, code for `\pmclsidepar`, taken from the memoir class, by Peter Wilson. Modified by Dan Luecking.

```
\pmclsidepar
778 \newcommand{\pmclsidepar}{\@dblarg{\@pmclsidepar}}
779 %\long\def\@pmclsidepar[#1]#2{\@bsphack\leavevmode\vadjust{%
780 \long\def\@pmclsidepar[#1]#2{\@bsphack\strut\vadjust{% added
781 \checkoddpage
782 \ifpmclsideparswitch
783   \ifpmclreversesidepar
784     \ifoddpage
785       \oddpagetrue
786     \else
787       \oddpagetrue
788     \fi
789   \fi
790 \else
791   \oddpagetrue
```

```

792 \ifpmclreversesidepar
793 \oddpagfalse
794 \fi
795 \fi
796 \rlap{\kern-\parindent
797 \if@twocolumn
798 \if@firstcolumn % put at left
799 \kern -\marginparsep \kern -\marginparwidth % at left
800 \else % put at right
801 \kern \columnwidth \kern \marginparsep % at right
802 \fi
803 \else
804 \ifoddpage % put at right
805 \kern \textwidth \kern \marginparsep % at right
806 \else % put at left
807 \kern -\marginparsep \kern -\marginparwidth % at left
808 \fi
809 \fi
810 % \vbox to Opt{%
811 % \kern \pmclsideparvshift% % vertical shift to align top text lines
812 % \begin{minipage}{\marginparwidth}%
813 \setbox0=\vtop to Opt{% added
814 \begin{minipage}[t]{\marginparwidth}% added
815 \ifoddpage #2\else #1\fi%
816 \end{minipage}%
817 % \vss}}\@esphack}
818 \vss}% added
819 \vtop to Opt{\kern\pmclsideparvshift % default should be Opt
820 \kern-\dp\strutbox \kern-\ht0 \box0 \vss}}\@esphack}% added
821
822

```

`\thepmenc@page` The value of the page counter.

```

823 \gdef\thepmenc@page{\the\c@page}
824

```

`\pmemlabel` A version of `\label` that uses `\pmemprotected@write`.

```

825 \providecommand{\pmemlabel}[1]{\@bsphack
826 \pmemprotected@write\auxout{}%
827 {\string\newpmemlabel{#1}{\thepmenc@page}}%
828 \@esphack}

```

`\pmemprotected@write` `\pmemprotected@write` is a modified version of the kernel's `\protected@write`.

```

829 \long\def\pmemprotected@write#1#2#3{%
830 \begingroup
831 \let\thepmenc@page\relax
832 #2%
833 \let\protect\@unexpandable@protect
834 \edef\reserved@a{\write#1{#3}}%

```

```

835 \reserved@a
836 \endgroup
837 \if@nobreak\ifvmode\nobreak\fi\fi}
838

```

`\newpmemlabel` We have to be able to cope with a particular label not (yet) being in the the aux
`\pmemlabelref` file when we come to check the page number.

```

839 \providecommand{\newpmemlabel}[2]{\global\@namedef{m@#1}{#2}}
840 \providecommand{\pmemlabelref}[1]{%
841 \expandafter\ifx\csname m@#1\endcsname\relax
842 0%
843 \else
844 \csname m@#1\endcsname
845 \fi}
846

```

`\@memcnta` We need a scratch count register.

```
847 \newcount\@memcnta
```

`\checkoddpag` This is the user level command to check for odd/even page. It does a robust check
for `\strictpagecheck` otherwise the simple minded check. It sets `\ifoddpag` to
TRUE if the page is odd, otherwise it sets it to FALSE.

This is now fixed so that it should work for non-arabic page numbering. It
uses a new label/pageref variant based on the page counter value, not its printed
representation. This also gets rid of worrying about hyperref!! The problem was
discovered by Bastiaan Niels Veelo

```

848 \DeclareRobustCommand{\checkoddpag}{%
849 \oddpagfalse%
850 \ifstrictpagecheck%
851 \stepcounter{cp@ctr}\pmemlabel{\cplabel\thecp@ctr}%
852 \@memcnta=\pmemlabelref{\cplabel\thecp@ctr}\relax
853 \ifodd\@memcnta\oddpagtrue\fi
854 \else
855 \ifodd\c@page\oddpagtrue\fi
856 \fi}
857

```

`\ifpmclreversesidepar` Analogues of `\marginpar` controls.

```

\ifpmclsideparswitch 858 \newif\ifpmclreversesidepar
859 % \pmclreversesideparfalse
860 \pmclreversesidepartrue
861 \newif\ifpmclsideparswitch
862 \pmclsideparswitchfalse
863 \if@twoside \pmclsideparswitchtrue \fi
864

```

`\ifoddpag` The boolean `\ifoddpag` is TRUE if the checked page is odd. The boolean
`\ifstrictpagecheck` `\ifstrictpagecheck` is for turning on (TRUE) and off (FALSE) the strictest
`\c@cp@ctr`
`\cplabel`

method of page checking. The counter `cp@cntr` is used to make unique labels, which start with `\cplabel`.

```
865 \newif\ifoddpge
866 \newif\ifstrictpagecheck
867 \strictpagecheckfalse
868 \newcounter{cp@cntr}
869 \newcommand{\cplabel}{^_}
```

Two-column and one-column printing is again realized via a switch which is defined in the kernel. The default is single column printing.

```
\pmclsideparvshift Vertical shift for sidepar to align with text line
870 \newlength{\pmclsideparvshift}
871 % \setlength{\pmclsideparvshift}{-2.08ex}% seems to work for all font sizes
872 %\setlength{\pmclsideparvshift}{-2.58ex}
873 \setlength{\pmclsideparvshift}{0ex}
```

My code resumes here

```
\verselinenumberstoleft
\verselinenumberstoright 874 \newcommand{\verselinenumberstoleft}{%
875 % \setlength{\marginparsep}{18pt}%
876 % \setlength{\marginparwidth}{10pt}%
877 \numbersswitchfalse\numbersrightfalse}
878 \newcommand{\verselinenumberstoright}{%
879 % \setlength{\marginparsep}{18pt}%
880 % \setlength{\marginparwidth}{10pt}%
881 \numbersswitchfalse\numbersrighttrue}

\verselinenumbersswitch
\verselinenumbersgutter 882 \newcommand{\verselinenumbersswitch}{%
\verselinenumberouter 883 \strictpagechecktrue%
884 % \setlength{\marginparsep}{18pt}%
885 % \setlength{\marginparwidth}{10pt}%
886 \numbersswitchtrue\numbersrightfalse\pmclsideparswitchtrue}
887 \newif\ifnumbersgutter \numbersgutterfalse%
888 \newcommand{\verselinenumbersgutter}{\verselinenumbersswitch%
889 \pmclreversesideparfalse%
890 \numbersguttertrue%
891 }
892 \newcommand{\verselinenumberouter}{\verselinenumbersswitch%
893 \pmclreversesidepartrue%
894 \numbersgutterfalse}

\putverselinenumber
895 \newcommand{\putverselinenumber}{\nolinebreak\begin{marginenvironment}%
896 \nolinebreak%
897 % \ifnumbersswitch\marginpar{\hfil\texttrm{\scriptsize\theverselinenumber}}%
898 % \else%
```

```

899 % \ifnumbersright\marginpar{\hfil\textrm{\scriptsize\theverselinenum}}%
900 % \else%
901 % \marginpar{\textrm{\scriptsize\theverselinenum}\hfil}%
902 % \fi%
903 % \fi
904 \ifnumbersswitch\pmclsidepar{\hfil\textrm{\scriptsize\theverselinenum}}%
905 \else%
906 \ifnumbersright\pmclrightsidepar{\hfil\textrm{\scriptsize\theverselinenum}}%
907 \else%
908 \pmclleftsidepar
909 {\textrm{\scriptsize\theverselinenum}\hfil}%
910 \fi%
911 \fi%
912 \marn{\hfil\textrm{\theverselinenum}}
913 \marginpar{\hfil\textrm{\scriptsize\theverselinenum}}
914 \linenumberside{\textrm{\scriptsize\theverselinenum}\hfil}
915 \pmclrightsidepar{\textrm{\scriptsize\theverselinenum}}
916 \nolinebreak%
917 \end{marginenvironment}%
918 \nolinebreak%
919 }

```

\verseline

```

920 \newif\ifspeciallinelock
921 \speciallinelockfalse
922 \newcommand{\verseline}{\ifspeciallinelock%
923 \relax\else%
924 \nolinebreak\incrementverselinenum%
925 \fi%
926 \speciallinelockfalse%
927 \nolinebreak\\%
928 }
929 % \newif\iflongpoemon
930 % \longpoemonfalse
931 \newcommand{\incrementverselinenum}{%
932 \nolinebreak\addtocounter{verselinenum}{1}%
933 %\iflongpoemon\marksthe{verselinemark}{\theverselinenum}\fi%
934 %\makeatletter
935 \@ifundefined{marksthe}{\relax}{\marksthe{verselinemark}{\theverselinenum}}%
936 %\makeatother
937 \addtocounter{printlineindex}{1}%
938 \ifnum\theprintlineindex>\thelineindexrepeat%
939 \ifverselinenumbers\nobreak%
940 \putverselinenum\nobreak%
941 \fi\nobreak%
942 \setcounter{printlineindex}{0}%
943 \fi%
944 }
945 \newcommand{\setverselinemodulo}[1]{%
946 \setcounter{lineindexrepeat}{#1}%

```

```
947 \addtocounter{lineindexrepeat}{-1}%
948 }
```

\linebend A `\linebend` is a a normal linebreak from L^AT_EX, with no incrementing of the line number counter, but the indentation makes the line look like a run over line. If you change the value of the run over in the definition of the `\verse` environment, be sure to change it here too. `\linebend` should be used for tweaking how `poemscol` runs over long lines.

```
949 \newcommand{\linebend}{\
950 \hspace{\runoverindentvalue}%
951 }
```

`\saveverselinenumber` and `\restoreverselinenumber` are useful for setting prose interjections in the midst of poems.

```
\saveverselinenumber
\restoreverselinenumber 952 \newcommand{\saveverselinenumber}{\setcounter{verselinenumberscratch}%
953     {\value{verselinenumber}}}%
954     \setcounter{printlineindexscratch}{\value{printlineindex}}
955 \newcommand{\restoreverselinenumber}{\setcounter{verselinenumber}%
956     {\value{verselinenumberscratch}}}%
957     \setcounter{printlineindex}{\value{printlineindexscratch}}}
```

\rightversebegin By default, `poemscol` indents the runover portion of long lines by the amount `\runoverindent` (by default 6 em). It is possible to set verse so that the runover portion is flushed to the right margin. To do this, you should enclose the `\poem` environment in the `\rightflushverse` environment. And you must mark the beginning of each verse line with `\rightversebegin`

```
958 \newcommand{\rightversebegin}
959 {\leavevmode\nobreak\hskip0pt plus -1fill\ignorespaces}
```

\hour `\hour` is useful for typesetting the AM and the PM in the time.

```
960 \newcommand{\hour}[1]{\textsc{#1}}\ $!\!\\!$}
961 }
```

\brokenline **\versephantom** `\brokenline` and `\versephantom{}` are a pair, useful for setting cases where there is a line break in the midst of a single metrical line. `\tweakbrokenline` ensures that the line number will mark the first partial line if the line numbers are on the left, the last partial line if the line numbers are on the right. If you have issued `\tweakbrokenline` in your preamble, the setting of runover lines may not be consistent with the setting of broken lines, because the line number will be set on the level of the end of the line. This is not a problem if the line numbers are set on the right, but it may look odd if the numbers are set on the left. `\startverseline` will ensure that the line number marks the beginning of any line it begins. If you put `\startverseline` at the beginning of the runover lines, it will ensure that the line number marks the beginning, not the end, of the line. If you wish `\startverseline` to align the number with the beginning of runover

lines when the line number is on the left, and with the end of runover lines when the line number is on the right, issue `\tweakstartverseline` in your preamble.

```
962 \newcommand{\brokenline}{\}
963 \newcommand{\versephantom}[1]{\leavevmode\phantom{#1}}
```

`\tweakbrokenline` Causes `\brokenline` to set the line number level with the beginning of the line if the number is on the left, level with the end of the line if the number is on the right. Issue it in the preamble.

```
964 \newcommand{\tweakbrokenline}{%
965   \renewcommand{\brokenline}{\ifnumbersswitch\relax%
966     \ifnumbersgutter% shift on odd pages for gutter numbers
967     \ifodd\c@page \relax \else \speciallineclocktrue\incrementverselinenumber\fi
968     \else % shift on even pages for outer numbers
969     \ifodd\c@page \speciallineclocktrue\incrementverselinenumber \fi
970     \fi
971     \else \ifnumbersright \relax%
972       \else \speciallineclocktrue\incrementverselinenumber%
973       \fi%
974     \fi%
975 \}
976 }
```

`\brokenlineatbeginning` Issue `\brokenlineatbeginning` if you want broken line to set the line number level with the beginning of the line, regardless of whether the line number is at the right or at the left

```
977 \newcommand{\brokenlineatbeginning}{%
978   \renewcommand{\brokenline}{%
979     \speciallineclocktrue\incrementverselinenumber%
980   \}
981 }
982 }
```

`\startverseline` Put `\startverseline` at the beginning of every line where you wish to ensure that the line number is level with the beginning of the line. This is particularly useful for overrun lines when `\tweakbrokenline` or `\brokenlineatbeginning` is in effect.

```
983 \newcommand{\startverseline}{%
984 \speciallineclocktrue%
985 \leavevmode%
986 %\kern-3pt
987 \incrementverselinenumber%
988 }
```

`\tweakstartverseline` You may want `\startverseline` to align the line number with the beginning of the line if the line number is on the left, and with the end of the line if the line number is on the right. To do this, issue `\tweakstartline` in your preamble.

```
989 \newcommand{\tweakstartverseline}{%
990 \renewcommand{\startverseline}{%
```

```

991 \leavevmode%
992 \ifnumbersswitch%
993 % gutter case: shift on odd pages to top of runover line
994 \ifnumbersgutter%
995     \ifodd\c@page \relax \else \speciallineoktrue\incrementverselinenumber\fi
996 % outer case: shift on even pages to top of runover line
997 \else
998     \ifodd\c@page \speciallineoktrue\incrementverselinenumber \fi
999 \fi% end of ifnumbersgutter
1000 \else \ifnumbersright \relax% numbers don't switch. Are they to the right?
1001     \else \speciallineoktrue\incrementverselinenumber% or to the left?
1002     \fi% end of ifnumbersright
1003 \fi% end of ifnumbersswitch
1004 }% end of renewcommand
1005 }% end of tweakverseline

```

`\poemlinelabel` `\poemlinelabel` is a hacked version of `\label` for crossreferences by line.

```

1006 \def\poemlinelabel#1{\@bsphack
1007 \protected@write\@auxout{}%
1008 {\string\newlabel{#1}{\theverselinenumber}{\thepage}}}%
1009 \@esphack
1010 }

```

22.12 Setup for contents, textual notes, emendations, and explanatory notes

First, the table of contents:

`\makepoemcontents` An external file is created with the extension `.ctn`, and the filename of your driver file. The channel to that file is called `\poemcontents`. The rest of the command is the page style for the contents section. You will notice the running head Contents, and the title of the Contents section. I am assuming that the table of contents starts on page 5, but it may be different in different books. If you want to change that page number (say, to page 3) without messing with this file, issue `\literalcontents{\setcounter{page}{3}}` just after you issue `\makepoemcontents`. Alternatively, you can issue `\makepoemcontents{}` with its optional argument, putting the page number in the argument.

```

1011 \newtoks{\pmclcontentsname}
1012 \pmclcontentsname={CONTENTS}
1013 \newtoks{\pmclcontentsheader}
1014 \pmclcontentsheader={Contents}
1015 \newcommand{\changecontentsname}[1]{%
1016 \pmclcontentsname={#1}}
1017 \newcommand{\changecontentsheader}[1]{%
1018 \pmclcontentsheader={#1}}
1019 \newcommand{\makepoemcontents}[1][5]{\global\poemcontentsontrue
1020 \newwrite\poemcontents
1021 \immediate\openout\poemcontents=\jobname.ctn

```

```

1022 \literalcontents{\flushbottom\normalfont
1023 {\par\clearpage{\pagestyle{volumetitlestyle}\cleardoublepage}
1024 \pagestyle{fancy}\thispagestyle{volumetitlestyle}}
1025 \pagenumbering{roman}
1026 \setcounter{page}{#1}
1027 \fancyhead[RO,LE]{\small\textrm{\thepage}}
1028 \fancyhead[CO]{\small{\em \the\pmclcontentsheader}}
1029 \fancyhead[CE]{\small{\em \the\pmclcontentsheader}}
1030 \fancyfoot{}
1031 \backmattersink
1032 \begin{center}\normalfont \backmatterheaderfont
1033 \the\pmclcontentsname\end{center}
1034 \lefthyphenmin=2\backmatterafterheadersink\tolerance=500\language=0}
1035 \literalcontents{ \relax}}

```

Next, the textual collations:

`\maketextnotes` Like the `\makecontents` macro, `\maketextnotes` opens an external file using `\jobname`, this time with the extension `.ent`. It makes sure that line numbering is on (since it makes no sense to make notes without numbering the lines, particularly since the `\textnote{}` macro uses the line number). And it makes sure that the notes section is set with a flush bottom line, rather than with the ragged bottom line used for the verse sections. Also, it sets a label for sending the page number of the textual notes to the table of contents.

First, a few commands for use by all of the endnotes sections. `\setendnotessectiontitledefaults` sets the title of the endnotes section at the top of the first page of that species of note, and takes six arguments, which are, in order, (1) the title of the endnote section, (2) commands to be issued before setting the title (minimally, a penalty, such as `\poemtitlepenalty`), (3) the font size in which the title is to be set in the text (such as `\poemtitlefont` or `\large`), (4) any indentation of the title (`\relax` to put the title where `\poemtitle` puts it, or `\titleindent` to put it where `\sequencesectiontitle` puts it), (5) commands to be issued after the title is set (such as `\afterpoemtitleskip`) and (6) the label to be used for this section, to be used to set the page number in the table of contents.

`\setendnotessectiontitle` is a simpler version of `\setendnotessectiontitledefaults` with all the defaults filled in, leaving only two arguments, the title of the section, and the label for use by the table of contents.

`\contentsendnotesdefaults` sets the defaults for the table of contents entries for endnotes sections. It takes four arguments which are, in order, (1) the title of the endnote section, (2) the indentation of the title in the table of contents (such as `\contentsindentone`), (3), the font size in which the title should be set (such as `\contentspoemtitlefont`) and (4) the amount overrun lines in the table of contents should be indented (such as `\contentsindenttwoamount`).

`\contentsendnotesindent` sets the default indent for table of contents entries for endnotes sections, and `\contentsendnotesfont` sets the default font for the.

`\contentsendnotestitle` is a simpler command for sending information about endnote sections to the table of contents, taking only two arguments, the title and

the label used for page reference purposes.

```
1036 % Generic command for titles of endnote sections
1037 \newcommand{\setendnotessectiontitledefaults}[6]{%
1038 #2%
1039 #3 \begin{titleentryenvironment}%
1040 {\ifcentertitleson\begin{center}#1\end{center}\else #4 #1\fi}%
1041 \end{titleentryenvironment}%
1042 #5%
1043 \label{#6}
1044 }
1045 % Simpler version with only two parameters, the title and the label
1046 % for page references
1047 \newcommand{\setendnotessectiontitle}[2]{%
1048 \setendnotessectiontitledefaults{#1}{\poemtitlepenalty\backmattersink}{\backmatterheaderfont}
1049 {\notestitleindent}{\lefthyphenmin=2\backmatterafterheadersink}{#2}}
1050 % Generic command for sending info about endnotes sections to table
1051 % of contents
1052 \newcommand{\contentsendnotesdefaults}[4]{\ifpoemcontentson
1053 \immediate\write\poemcontents{\string\begin\string{contentsentryenvironment}\string}}%
1054 \literalcontents{#2{#3#1}}%
1055 \ifputpagenumberincontents
1056 \immediate\write\poemcontents{\string\contentsleaders}%
1057 \immediate\write\poemcontents{\string\pageref
1058 \string{#4\string}}%
1059 \else
1060 \literalcontents{\relax}%
1061 \fi
1062 \immediate\write\poemcontents{\string\end\string{contentsentryenvironment}\string}}%
1063 \immediate\write\poemcontents{\string\par}%
1064 \fi
1065 }
1066 % default styles for contents entries for endnotes sections
1067 \newcommand{\contentsendnotesindent}{\contentsindentone}
1068 \newcommand{\contentsendnotesfont}{\contentspoemtitlefont}
1069 % simpler command to set up contents entry with only two parameters,
1070 % the title and the label for page references
1071 \newcommand{\contentsendnotestitle}[2]{%
1072 \contentsendnotesdefaults{#1}{\contentsendnotesindent}{\contentsendnotesfont}{#2}}%
1073 }
1074 % command for paragraph breaks within notes
1075 \newlength{\noteindentation}
1076 \setlength{\noteindentation}{1em}
1077 \newcommand{\noteparbreak}{\
1078 \hspace*{\noteindentation}}
1079 % tokens to use to change the names of the sections
1080 \newtoks{\pmclnotesname}
1081 \pmclnotesname={TEXTUAL NOTES}
1082 \newcommand{\changenotesname}[1]{\pmclnotesname={#1}}
1083 \newtoks{\notesheadername}
```

```

1084 \notesheadername={Textual Notes to}
1085 \newcommand{\changenotesheader}[1]{\notesheadername={#1}}
1086 \newtoks{\textnotescontentsname}
1087 \textnotescontentsname={Textual Notes}
1088 \newcommand{\changetextnotescontentsname}[1]{\textnotescontentsname={#1}}
1089 % A boolean to change to two column notes.
1090 \newif\iftextnotestwocol
1091 \textnotestwocolfalse
1092 % Setup for textual notes
1093 \newcommand{\maketextnotes}{\global\textnotesontrue
1094   \global\verselinenumberstrue
1095   \newwrite\textnotes
1096   \immediate\openout\textnotes=\jobname.ent
1097   \literaltextnote{\flushbottom{\par\clearpage
1098     {\pagestyle{volumetitlestyle}\cleardoublepage}
1099   \thispagestyle{volumetitlestyle}}}
1100 \fancyhead{}
1101 \fancyfoot{}
1102 \fancyhead[RO,LE]{\small\textrm{\thepage}}
1103 \fancyhead[CO]{\small{\em \the\notesheadername~\mymarks}}
1104 \fancyhead[CE]{\small{\em \the\notesheadername~\mymarks}}
1105 \fancyfoot[C]{ }
1106 \mark{3}
1107 \setendnotessectiontitle{\the\pmclnotesname}{textualnotes}
1108 \tolerance=500\language=0
1109 \normalfont \backmattertextfont
1110 \iftextnotestwocol
1111 \begin{multicols}{2}
1112 \fi
1113 \setlength{\parindent}{-10pt}
1114 }
1115 }
1116

```

\makeemendations Next, the emendations section:

```

1117 % tokens for changing the names of these notes
1118 \newtoks{\emendationsname}
1119 \emendationsname={EMENDATIONS}
1120 \newcommand{\changeemendationsname}[1]{\emendationsname={#1}}
1121 \newtoks{\emendationsheadername}
1122 \emendationsheadername={Emendations to}
1123 \newcommand{\changeemendationsheader}[1]{\emendationsheadername={#1}}
1124 \newtoks{\emendationscontentsname}
1125 \emendationscontentsname={Emendations}
1126 \newcommand{\changeemendationscontentsname}[1]{%
1127 \emendationscontentsname={#1}}
1128 % two column notes
1129 \newif\ifemendationstwocol
1130 \emendationstwocolfalse
1131 % Emendations section setup

```

```

1132 \newcommand{\makeemendations}{\global\emendationsontrue
1133   \newwrite\emendations
1134   \global\verselinenumberstrue
1135   \immediate\openout\emendations=\jobname.emd
1136   \literate\emend{\flushbottom{\par\clearpage
1137     {\pagestyle{volumetitlestyle}\cleardoublepage}
1138 \thispagestyle{volumetitlestyle}}
1139 \fancyhead{}
1140 \fancyhead[RO,LE]{\small\textrm{\thepage}}
1141 \fancyhead[CO]{\small{\em \the\emendationsheadername~\mymarks}}
1142 \fancyhead[CE]{\small{\em \the\emendationsheadername~\mymarks}}
1143 \fancyfoot{}
1144 \mark{3}
1145 \setendnotessectiontitle{\the\emendationsname}{emendationnotes}
1146 \tolerance=500\language=0
1147 \normalfont \backmattertextfont
1148 \ifemendationstwocol
1149 \begin{multicols}{2}
1150 \fi
1151 \setlength{\parindent}{-10pt}
1152 }
1153 }

```

`\makeexplanatorynotes` And the explanatory notes:

```

1154 % Tokens to change names of these notes
1155 \newtoks{\explanationsname}
1156 \explanationsname={EXPLANATORY NOTES}
1157 \newcommand{\changeexplanationsname}[1]{\explanationsname={#1}}
1158 \newtoks{\explanationsheadername}
1159 \explanationsheadername={Explanatory Notes to}
1160 \newcommand{\changeexplanationsheader}[1]{\explanationsheadername={#1}}
1161 \newtoks{\explanationscontentsname}
1162 \explanationscontentsname={Explanatory Notes}
1163 \newcommand{\changeexplanationscontentsname}[1]{%
1164 \explanationscontentsname={#1}}
1165 % Two column notes
1166 \newif\ifexplanationstwocol
1167 \explanationstwocolfalse
1168 % Explanatory notes setup
1169 \newcommand{\makeexplanatorynotes}{\global\explanontrue
1170   \global\verselinenumberstrue
1171   \newwrite\explanations
1172   \immediate\openout\explanations=\jobname.enx
1173   \literate\explain{\flushbottom{\par\clearpage
1174     {\pagestyle{volumetitlestyle}\cleardoublepage}
1175 \thispagestyle{volumetitlestyle}}
1176 \fancyhead[RO,LE]{\small\textrm{\thepage}}
1177 \fancyhead[CO]{\small{\em \the\explanationsheadername~\mymarks}}
1178 \fancyhead[CE]{\small{\em \the\explanationsheadername~\mymarks}}
1179 \fancyfoot{}

```

```

1180 \mark{3}
1181 \setendnotessectiontitle{\the\explanationsname}{explanatorynotes}
1182 \tolerance=500\language=0
1183 \normalfont \backmattertextfont
1184 \ifexplanationstwocol
1185 \begin{multicols}{2}
1186 \fi
1187 \setlength{\parindent}{-10pt}
1188 }
1189 }
1190

```

Auxiliary commands for note and title sections

```

1191 %
1192 \newcommand{\@pagemarktotextnotes}[1]{%
1193 \immediate\write\textnotes{\string\setcounterfrompageref\string\notepageholdertitle\string}%
1194 \string{#1\string}\string\unskip}%
1195 \immediate\write\textnotes{\string\mark%
1196 \string{\string\thenotepageholdertitle\string}}%
1197 }
1198 \newcommand{\@poempagetotextnotes}[1]{%
1199 \immediate\write\textnotes{\string\par\string\argpageref\string{#1\string}\string\unskip}%
1200 \@pagemarktotextnotes{#1}}
1201 \newcommand{\@poemtitletotextnotes}[1]{%
1202 \ifputpagenumberinnotes%
1203 \literaltextnote{\textbf{#1}}}%
1204 \else%
1205 \literaltextnote{\par}\literaltextnote{\textbf{#1}}}%
1206 \fi}

```

22.13 Appendices, Forewords, Contents Entries

\makeappendix

```

1207 \newif\ifappendixincontents
1208 \appendixincontentstrue
1209 \newif\ifforewordincontents
1210 \forewordincontentstrue
1211 %
1212 \newcommand{\appendixdividerpage}[1]{\flushbottom{\par\clearpage
1213 {\pagestyle{volumetitlestyle}\cleardoublepage}
1214 \thispagestyle{volumetitlestyle}}
1215 \fancyhead{}
1216 \fancyfoot{}
1217 \fancyhead[RO,LE]{\small\textrm{\thepage}}
1218 \fancyhead[CO]{\small{\em #1}}
1219 \fancyhead[CE]{#1}
1220 \fancyfoot[C]{}}
1221 %
1222 \newcommand{\appendixtitle}[1]{

```

```

1223 \setendnotessectiontitledefaults{#1}{\poemtitlepenalty\backmattersink}{\backmatterheaderfont}
1224 {\appendixtitleindent}{\lefthyphenmin=2\backmatterafterheadersink}{appdx#1}
1225 \tolerance=500\language=0
1226 \normalfont \backmattertextfont
1227 \setlength{\parindent}{\noteindentation}
1228 \ifappendixincontents\contentsendnotestitle{#1}{appdx#1}\fi
1229 }
1230 %
1231 \newcommand{\makeappendix}[1]{%
1232 \appendixdividerpage{#1}
1233 \appendixtitle{#1}
1234 }
1235 %
1236 \newcommand{\contentsendnotessubtitle}[2]{
1237 \contentsendnotesdefaults{#1}{\contentsindenttwo}{\contentsendnotesfont}{#2}
1238 }
1239 %
1240 \newcommand{\subappendixtitle}[1]{%
1241 \setendnotessectiontitledefaults{#1}{\poemtitlepenalty\backmattersink}{\backmatterheaderfont}
1242 {\subappendixtitleindent}{\lefthyphenmin=2\backmatterafterheadersink}{appdx#1}
1243 \tolerance=500\language=0
1244 \normalfont \backmattertextfont
1245 \setlength{\parindent}{\noteindentation}
1246 \ifappendixincontents\contentsendnotessubtitle{#1}{appdx#1}\fi
1247 }
1248 %
1249 \newcommand{\makesubappendix}[1]{%
1250 \appendixdividerpage{#1}
1251 \subappendixtitle{#1}
1252 }
1253 \newcommand{\foreworddividerpage}[1]{\flushbottom{\par\clearpage
1254 {\pagestyle{volumetitlestyle}\cleardoublepage}
1255 \thispagestyle{volumetitlestyle}}
1256 \fancyhead{}
1257 \fancyfoot{}
1258 \fancyhead[RO,LE]{\small\textrm{\thepage}}
1259 \fancyhead[CO]{\small{\em #1}}
1260 \fancyhead[CE]{#1}
1261 \fancyfoot[C]{}}
1262 %
1263 \newcommand{\forewordtitle}[1]{
1264 \setendnotessectiontitledefaults{#1}{\poemtitlepenalty\backmattersink}{\backmatterheaderfont}
1265 {\forewordtitleindent}{\lefthyphenmin=2\backmatterafterheadersink}{foreword#1}
1266 \tolerance=500\language=0
1267 \normalfont \backmattertextfont
1268 \setlength{\parindent}{\noteindentation}
1269 \ifforewordincontents\contentsendnotestitle{#1}{foreword#1}\fi
1270 }
1271 %
1272 \newcommand{\makeforeword}[1]{%

```

```

1273 \foreworddividerpage{#1}
1274 \forewordtitle{#1}
1275 }
1276

```

`\pmclcontentsentry`

```

1277 \newcommand{\pmclcontentsentrydefaults}[4]{
1278 \ifpoemcontentson
1279 \immediate\write\poemcontents{\string\begin\string{contentsentryenvironment\string}}%
1280 \literalcontents{#2{#3#1}}%
1281 \ifputpagenumberincontents
1282 \immediate\write\poemcontents{\string\contentsleaders}%
1283 \literalcontents{#4}
1284 \else
1285 \literalcontents{\relax}%
1286 \fi
1287 \immediate\write\poemcontents{\string\end\string{contentsentryenvironment\string}}%
1288 \immediate\write\poemcontents{\string\par}%
1289 \fi
1290 }
1291 %
1292 \newcommand{\pmclcontentsentry}[3]{%
1293 \pmclcontentsentrydefaults{#1}{#2}{\contentsendnotesfont}{#3}%
1294 }

```

22.14 Book, volume, and volume section titles

`\wholebooktitle`

```

\booksection 1295 \newcommand{\wholebooktitle}[1]{\Huge\begin{center}
1296 \hbox{#1}\end{center}}
1297 }
1298 \newcommand{\booksection}[1]{\volumesection{#1}}

```

`\volumetitle`

```

1299 \newcommand{\volumetitle}[1]{%
1300 \set@p@emtitle{#1}{\volumetitlesink\par}{\volumetitlefont}
1301 {\volumetitleindent}{\nobreak\par\nobreak}{\z@}
1302 \putpagenumberincontentsfalse
1303 \putpagenumberinnotesfalse
1304 \literalcontents{\par\goodbreak\bigskip}
1305 \c@ntentsinfo{#1}{\contentsvolumetitleindent}{\contentsvolumefont}
1306 {\contentsvolumetitleindentamount}
1307 \literalcontents{\par\goodbreak\medskip}
1308 \literaltextnote{\notesvolumetitlepenalty\bigskip\goodbreak\par}
1309 \t@xtnotesinfo{\backmattervolumefont #1 \backmattertextfont\nobreak}
1310 \putpagenumberincontentstrue
1311 \putpagenumberinnotestrue}

```

`\volumetitlefirstline`

`\volumetitlelastline`

`\volumesubtitle`

`\volumesectiontitle`

```

1312 \newcommand{\volumetitlefirstline}[1]{\firstlinesettings%
1313   \set@p@emtitle{#1}{\volumetitlesink\par}
1314   {\volumetitlefont}
1315   {\volumetitleindent}{\nobreak\par\nobreak}{\z@}
1316   \putpagenumberincontentsfalse
1317   \putpagenumberinnotesfalse
1318 \literalcontents{\par\goodbreak\bigskip}
1319 \c@ntentsinfo{#1}{\contentsvolumetitleindent}{\contentsvolumefont}
1320 {\contentsvolumetitleindentamount}
1321 \literalcontents{\medskip\par\nobreak}
1322 % \literaltextnote{\notesvolumetitlepenalty\bigskip\par}
1323 \t@xtnotesinfo{\backmattervolumefont #1 \backmattertextfont\nobreak}
1324 \putpagenumberincontentstrue
1325 \putpagenumberinnotestruetrue}
1326 \newcommand{\volumetitlemiddleline}[1]{\middlelinesettings%
1327   \set@p@emtitle{#1}{\relax}
1328   {\volumetitlefont}
1329   {\volumetitlesecondlineindent}{\nobreak\par\nobreak}{\z@}
1330   \putpagenumberincontentsfalse
1331   \putpagenumberinnotesfalse
1332   \c@ntentsinfo{#1}{\contentsvolumetitleindent}{\contentsvolumefont}
1333   {\contentsvolumetitleindentamount}
1334   \literalcontents{\medskip\par\nobreak}
1335   \t@xtnotesinfo{\backmattervolumefont #1 \backmattertextfont\nobreak}
1336   \putpagenumberincontentstrue
1337   \putpagenumberinnotestruetrue}
1338 \newcommand{\volumetitlelastline}[1]{\lastlinesettings%
1339   \set@p@emtitle{#1}{\relax}
1340   {\volumetitlefont}
1341   {\volumetitlesecondlineindent}{\nobreak\par\nobreak}{\z@}
1342   \putpagenumberincontentsfalse
1343   \putpagenumberinnotesfalse
1344   \c@ntentsinfo{#1}{\contentsvolumetitleindent}{\contentsvolumefont}
1345   {\contentsvolumetitleindentamount}
1346   \literalcontents{\medskip\par\nobreak}
1347   \t@xtnotesinfo{\backmattervolumefont #1 \backmattertextfont\nobreak}
1348   \putpagenumberincontentstrue
1349   \putpagenumberinnotestruetrue}
1350 \newcommand{\volumesubtitle}[1]{\volumesubtitlefont
1351 \volumetitleshift \volumesubtitleindent #1 \par}
1352 \ifpoemcontentson
1353   \literalcontents{\contentsvolumesubtitlefont\contentsvolumesubtitleindent
1354 #1\par\medskip\nobreak}}
1355 \fi
1356 \iftextnoteson\iftextnotesatend
1357   \immediate\write\textnotes{\string\backmattervolumesubtitlefont\ #1}
1358   \immediate\write\textnotes{\string\par \string\backmattertextfont}
1359   \immediate\write\textnotes{\string\nobreak}
1360 \fi\fi
1361 }

```

```

1362 \newcommand{\volumesubtitlefirstline}[1]{\{\firstlinesettings\volumesubtitlefont
1363 \volumetitleshift \volumesubtitlesecondlineindent #1 \par}
1364 \ifpoemcontentson
1365 \literalcontents{\contentsvolumesubtitlefont\contentsvolumesubtitleindent
1366 #1\par\nobreak}}
1367 \fi
1368 \iftextnoteson\iftextnotesatend
1369 \immediate\write\textnotes{\string\backmattervolumesubtitlefont\ #1}
1370 \immediate\write\textnotes{\string\par \string\backmattertextfont}
1371 \immediate\write\textnotes{\string\nobreak}
1372 \fi\fi
1373 }
1374 \newcommand{\volumesubtitlemiddleline}[1]{\{\middlelinesettings\volumesubtitlefont
1375 %\volumetitleshift
1376 \volumesubtitlesecondlineindent #1 \par}
1377 \ifpoemcontentson
1378 \literalcontents{\contentsvolumesubtitlefont\contentsvolumesubtitleindent
1379 #1\par\nobreak}}
1380 \fi
1381 \iftextnoteson\iftextnotesatend
1382 \immediate\write\textnotes{\string\backmattervolumesubtitlefont\ #1}
1383 \immediate\write\textnotes{\string\par \string\backmattertextfont}
1384 \immediate\write\textnotes{\string\nobreak}
1385 \fi\fi
1386 }
1387 \newcommand{\volumesubtitlelastline}[1]{\{\lastlinesettings\volumesubtitlefont
1388 %\volumetitleshift
1389 \volumesubtitlesecondlineindent #1 \par}
1390 \ifpoemcontentson
1391 \literalcontents{\contentsvolumesubtitlefont\contentsvolumesubtitleindent
1392 #1\par\medskip\nobreak}}
1393 \fi
1394 \iftextnoteson\iftextnotesatend
1395 \immediate\write\textnotes{\string\backmattervolumesubtitlefont\ #1}
1396 \immediate\write\textnotes{\string\par \string\backmattertextfont}
1397 \immediate\write\textnotes{\string\nobreak}
1398 \fi\fi
1399 }
1400 \newcommand{\volumesectiontitle}[1]{\clearpage\thispagestyle{volumefirststyle}
1401 \ifcentertitleson\begin{center} {\volumesubtitlefont\textbf{#1}}
1402 \end{center}
1403 \else \volumesectiontitleindent {\volumesubtitlefont\textbf{#1}}
1404 \fi\bigskip\bigskip
1405 \ifpoemcontentson
1406 \literalcontents{\goodbreak{\ifcentertitleson\contentsvolumesubtitlefont #1\par\nobreak\else
1407 \contentsvolumesectiontitleindent #1 \par\nobreak\fi}}
1408 \fi
1409 \iftextnoteson\iftextnotesatend
1410 \immediate\write\textnotes{\string\notesvolumetitlepenalty}
1411 \immediate\write\textnotes{\string\par \string\begin{bf}}

```

```

1412     \immediate\write\textnotes{#1 \string\end{bf}}
1413     \immediate\write\textnotes{\string\par}
1414     \immediate\write\textnotes{\string\nobreak}
1415     \fi\fi
1416 }
1417 \newcommand{\volumesectiontitlefirstline}[1]{\firstlinesettings\clearpage\thispagestyle{volume}
1418 \ifcentertitleson\begin{center} {\volumesubtitlefont\textbf{#1}}
1419 \end{center}
1420 \else \volumesectiontitleindent {\volumesubtitlefont\textbf{#1}\par}
1421 \fi% \bigskip\bigskip
1422 \ifpoemcontentson
1423 \literalcontents{\goodbreak{\ifcentertitleson\contentsvolumesubtitlefont #1\par\nobreak\else
1424 \contentsvolumesectiontitleindent #1 \par\nobreak\fi}}
1425 \fi
1426 \iftextnoteson\iftextnotesatend
1427     \immediate\write\textnotes{\string\notesvolumetitlepenalty}
1428     \immediate\write\textnotes{\string\par \string\begin{bf}}
1429     \immediate\write\textnotes{#1 \string\end{bf}}
1430     \immediate\write\textnotes{\string\par}
1431     \immediate\write\textnotes{\string\nobreak}
1432     \fi\fi
1433 }
1434 \newcommand{\volumesectiontitlemiddleline}[1]{\middlelinesettings
1435 %\clearpage\thispagestyle{volume}
1436 \ifcentertitleson\begin{center} {\volumesubtitlefont\textbf{#1}}
1437 \end{center}
1438 \else \volumesectiontitleindent {\volumesubtitlefont\textbf{#1}\par}
1439 \fi% \bigskip\bigskip
1440 \ifpoemcontentson
1441 \literalcontents{\goodbreak{\ifcentertitleson\contentsvolumesubtitlefont #1\par\nobreak\else
1442 \contentsvolumesectiontitleindent #1 \par\nobreak\fi}}
1443 \fi
1444 \iftextnoteson\iftextnotesatend
1445     \immediate\write\textnotes{\string\notesvolumetitlepenalty}
1446     \immediate\write\textnotes{\string\par \string\begin{bf}}
1447     \immediate\write\textnotes{#1 \string\end{bf}}
1448     \immediate\write\textnotes{\string\par}
1449     \immediate\write\textnotes{\string\nobreak}
1450     \fi\fi
1451 }
1452 \newcommand{\volumesectiontitlelastline}[1]{\lastlinesettings
1453 %\clearpage\thispagestyle{volume}
1454 \ifcentertitleson\begin{center} {\volumesubtitlefont\textbf{#1}}
1455 \end{center}
1456 \else \volumesectiontitleindent {\volumesubtitlefont\textbf{#1}}
1457 \fi\bigskip\bigskip
1458 \ifpoemcontentson
1459 \literalcontents{\goodbreak{\ifcentertitleson\contentsvolumesubtitlefont #1\par\nobreak\else
1460 \contentsvolumesectiontitleindent #1 \par\nobreak\fi}}
1461 \fi

```

```

1462 \iftextnoteson\iftextnotesatend
1463     \immediate\write\textnotes{\string\notesvolumetitlepenalty}
1464     \immediate\write\textnotes{\string\par \string\begin{bf}}
1465     \immediate\write\textnotes{#1 \string\end{bf}}
1466     \immediate\write\textnotes{\string\par}
1467     \immediate\write\textnotes{\string\nobreak}
1468 \fi\fi
1469 }

```

22.15 Commands for setting titles of poems and sequences

First, commands for sending labels to the table of contents and to the notes sections. Since these are internal commands, not intended to be issued in the body of the text, they might have been marked out with “at” signs to prevent accidental redefinition. But since they are repeatedly written out to the external files, it seemed more economical to run the risk of redefinition than to write out `\makeatletter` and `\makeatother` with every note.

```

1470 \newcommand{\makepoemlabel}[1]{\label{#1}}
1471 \newcommand{\argpageref}[1]{\pageref{#1}}

```

22.15.1 Poem Titles

`\poemtitle` All of the other commands in this section are variations on this one, changing the penalties, the skips, the indentations, and the fonts. The command breaks into three sections. First, the title is set in the text. `\poemtitlepenalty` tests whether there is room for the title and the first couple of lines. `\poemtitlefont` globally sets the fonts for all poem titles. You can put the argument in an `\hbox{}` to make sure that the poem title is not broken across two lines, and the `\label` records the page for the contents and notes sections. `\afterpoemtitleskip` is the amount of white space after a poem title. `\fulltitleholder` and `\@compoundlabelscratch` record the title for concatenation later. All of these commands can manage titles with control sequences in them, such as for italics or international characters. In an earlier version there were special commands for such titles, using two arguments (one with the control sequence, one without it). Those commands are no longer necessary, but have been retained for backward compatibility with earlier versions.

Second, the poem is entered in the external file for the table of contents. `\contentsindentone` sets it in one level in the hierarchy of indentations, and `\contentspoemtitlefont` is the type size used for poems in the table of contents. The `\pageref{}` holds the page number of the poem.

Third, a new paragraph is opened in the textual notes for textual collations. `\@poempagetotextnotes{}` sends the page number to the textual notes. `\@poemtitletotextnotes{}` sends the title.

```

1472
1473 \newcommand{\m@kep@emlabel}{\ifsinglelinetitle%
1474     \addtocounter{poemnumber}{1}%
1475     \makepoemlabel{poem\thepoemnumber}%
1476 \else\iftitlefirstline%

```

```

1477     \addtocounter{poemnumber}{1}%
1478     \makepoemlabel{poem\thepoemnumber}%
1479     \else \relax
1480 \fi
1481 \fi
1482 }
1483
1484 \newcommand{\m@ken@teholder}[1]{%
1485 \ifsinglelinetitle
1486 \fulltitleholder={#1}%
1487 \global\edef\@compoundlabelscratch{poem\thepoemnumber}%
1488 \else\iftitlefirstline
1489     \fulltitleholder={#1}%
1490     \global\edef\@compoundlabelscratch{poem\thepoemnumber}%
1491 \else\iftitlemiddleline
1492     \titlesofar=\fulltitleholder
1493     \titleincrement={~#1}%
1494     \global\edef\titleconcat{\the\titlesofar \the\titleincrement}%
1495     \fulltitleholder=\expandafter{\titleconcat}%
1496     \global\edef\@compoundlabelscratch{poem\thepoemnumber}%
1497 \else
1498     \titlesofar=\fulltitleholder
1499     \titleincrement={~#1}%
1500     \global\edef\titleconcat{\the\titlesofar \the\titleincrement}%
1501     \fulltitleholder=\expandafter{\titleconcat}%
1502     \global\edef\@compoundlabelscratch{poem\thepoemnumber}%
1503 \fi
1504 \fi
1505 \fi
1506 }
1507 \newif\ifcentertitleson
1508 \newcommand{\centertitles}{\centertitlesontrue\centerepigraphsontrue}
1509 \makeatletter
1510 \newcommand{\set@p@emtitle}[6]{\iftitlesatleftversemargin%
1511 {\begin{pmclverse}\addtolength{\leftmargin}{-\leftmargini}{#2 #3 #4 #1 #5} \end{pmclverse}}%
1512 \else%
1513 \setlength{\titleentryoverrun}{#6}%
1514 {#2}%
1515 {#3 \begin{titleentryenvironment}%
1516 {\ifnormaltitleindentation #4 #1%
1517 \else \ifcentertitleson \begin{center} #1 \end{center} \else #1\fi\fi}}%
1518 \end{titleentryenvironment}}%
1519 {#5}%
1520 \m@kep@emlabel
1521 \m@ken@teholder{#1}%
1522 \setlength{\titleentryoverrun}{\z@}\fi}
1523 %\newcommand{\set@p@emtitle}[6]{\setlength{\titleentryoverrun}{#6}%
1524 %{#2}%
1525 %{#3 \begin{titleentryenvironment}%
1526 %{\ifcentertitleson\begin{center}#1\end{center}\else #4 #1\fi}%

```

```

1527 %\end{titleentryenvironment}}%
1528 %{\#5}%
1529 %\m@kep@emlabel
1530 %\m@ken@teholder{\#1}%
1531 %\setlength{\titleentryoverrun}{\z@}
1532 %
1533 %% special version for subtitles
1534 \newcommand{\set@p@emsubtitle}[6]{\iftitlesatleftversemargin%
1535 {\begin{pmclverse}\addtolength{\leftmargin}{-\leftmargini}{\#2 \#3 \#4 \#1 \#5} \end{pmclverse}}%
1536 \else%
1537 \setlength{\titleentryoverrun}{\#6}%
1538 {\#2}%
1539 {\#3 \begin{titleentryenvironment}}%
1540 {\ifnormaltitleindentation \#4 \#1%
1541 \else \ifcentertitleson \begin{center} \#1 \end{center} \else \#1\fi\fi}}%
1542 \end{titleentryenvironment}}%
1543 %{\#5}%
1544 %\m@kep@emlabel
1545 %\m@ken@teholder{\#1}%
1546 \setlength{\titleentryoverrun}{\z@}\fi}
1547 \newcommand{\setcontentsleaders}[1]{%
1548   \def\contentsleaders{\#1\nobreak%
1549 }}
1550 \setcontentsleaders{~/~}
1551 \newcommand{\c@ntentsinfo}[4]{\ifpoemcontentson
1552 \immediate\write\poemcontents{\string\setlength\string\contentsentryoverrun\string{\#4\string}}}%
1553 \immediate\write\poemcontents{\string\begin\string{contentsentryenvironment\string}}%
1554 \literalcontents{\#2{\#3\#1}}%
1555   \ifputpagenumberincontents
1556 \immediate\write\poemcontents{\string\contentsleaders}%
1557 \immediate\write\poemcontents{\string\pageref
1558 \string{poem\thepoemnumber\string}}}%
1559   \else
1560 \literalcontents{\relax}%
1561 \fi
1562 \immediate\write\poemcontents{\string\end\string{contentsentryenvironment\string}}%
1563 \immediate\write\poemcontents{\string\par}%
1564 \immediate\write\poemcontents{\string\setlength\string\contentsentryoverrun
1565 \string{\string\contentsindentoneamount\string}}%
1566 \fi
1567 }
1568 \newif\ifputtitleinnotes
1569 \puttitleinnotesttrue
1570 \newcommand{\t@xtnotesinfo}[1]{\iftextnoteson
1571 \iftextnotesatend
1572 \immediate\write\textnotes{\string\notespoemclubpenalty}}%
1573   \ifputpagenumberinnotes
1574   \@mpagetotextnotes{poem\thepoemnumber}%
1575   \fi
1576 \ifputtitleinnotes

```

```

1577 \poemtitletotextnotes{#1}%
1578 \fi
1579 % \else
1580 % \relax
1581 \fi\fi
1582 }
1583 \newlength{\lefttitlemargin}
1584 \newcommand{\leftaligntitlespace}{\hspace{\lefttitlemargin}}
1585 \newif\ifleftaligntitles % title flush with left margin of centered poem
1586 \leftaligntitlesfalse % default value
1587 \newcommand{\left@ligntitleblock}{\rightmargin \z@}%
1588 \setlength{\lefttitlemargin}{\linewidth}%
1589 \addtolength{\lefttitlemargin}{-\versewidth}%
1590 \addtolength{\lefttitlemargin}{-0.5\lefttitlemargin}
1591 }
1592 %
1593 \newcommand{\poemtitle}[1]{%
1594 \set@p@emtitle{#1}{\poemtitlepenalty}{\poemtitlefont}%
1595 {\poemtitleindent}{\nobreak\par\nobreak\afterpoemtiteskip\nobreak}{\z@}%
1596 \c@ntentsinfo{#1}{\contentspoemtitleindent}{\contentspoemtitlefont}%
1597 {\contentspoemtitleindentamount}%
1598 \t@xtnotesinfo{#1}%
1599 }
1600 \newcommand{\poemtitlenocontents}[1]{%
1601 \set@p@emtitle{#1}{\poemtitlepenalty}{\poemtitlefont}%
1602 {\poemtitleindent}{\nobreak\par\nobreak\afterpoemtiteskip\nobreak}{\z@}%
1603 \t@xtnotesinfo{#1}%
1604 }
1605 \newcommand{\poemtitlebaretitle}[1]{%
1606 \set@p@emsubtitle{#1}{\poemtitlepenalty}{\poemtitlefont}%
1607 {\poemtitleindent}{\nobreak\par\nobreak\afterpoemtiteskip\nobreak}{\z@}%
1608 }
1609 \newcommand{\poemtitleonlycontents}[1]{%
1610 \c@ntentsinfo{#1}{\contentspoemtitleindent}{\contentspoemtitlefont}%
1611 {\contentspoemtitleindentamount}%
1612 }
1613 \newcommand{\poemtitleonlynotes}[1]{%
1614 \m@kep@emlabel
1615 \m@ken@teholder{#1}%
1616 \t@xtnotesinfo{#1}%
1617 }
1618 \newcommand{\poemtitlenonotes}[1]{%
1619 \set@p@emtitle{#1}{\poemtitlepenalty}{\poemtitlefont}%
1620 {\poemtitleindent}{\nobreak\par\nobreak\afterpoemtiteskip\nobreak}{\z@}%
1621 \c@ntentsinfo{#1}{\contentspoemtitleindent}{\contentspoemtitlefont}%
1622 {\contentspoemtitleindentamount}%
1623 }

```

`\poemtitleitalic` Poems with italic titles or other formatting (such as `\hour{}`) take two arguments. The second argument is discarded. This command is to maintain backward com-

patibility with earlier versions.

```
1624 \newcommand{\poemtitleitalic}[2]{%
1625 \poemtitle{#1}}
```

For poem subtitles, see the entry on `\sequencesections subtitle{}`.

`\poemtitlefirstline` Next, macros for setting multiline poem titles. Notice the special larger penalty
`\poemtitlemiddleline` for page breaks in the middle of multiple line title.

```
\poemtitlelastline 1626 \newcommand{\firstlinesettings}{\singlelinetitlefalse
1627 \titlefirstlinetrue
1628 \putpagenumberincontentsfalse
1629 \putpagenumberinnotestruetrue}
1630
1631 \newcommand{\middlelinesettings}{\singlelinetitlefalse
1632 \titlemiddlelinetrue
1633 \putpagenumberincontentsfalse
1634 \putpagenumberinnotesfalse}
1635
1636 \newcommand{\lastlinesettings}{\singlelinetitlefalse
1637 \titlelastlinetrue
1638 \putpagenumberincontentstrue
1639 \putpagenumberinnotesfalse}
1640
1641 \newcommand{\restoresinglelinesettings}{\putpagenumberinnotestruetrue
1642 \putpagenumberincontentstrue
1643 \titlefirstlinefalse
1644 \titlemiddlelinefalse
1645 \titlelastlinefalse
1646 \singlelinetitletrue}
1647
1648
1649 \newcommand{\poemtitlefirstline}[1]{
1650 \firstlinesettings
1651 \set@p@emtitle{#1}{\multilinetitlepenalty}{\poemtitlefont}%
1652 {\poemtitleindent}{\nobreak\par\nobreak}{\z@}%
1653 \c@ntentsinfo{#1}{\contentspoemtitleindent}{\contentspoemtitlefont}%
1654 {\contentspoemtitleindentamount}%
1655 \t@xtnotesinfo{#1}%
1656 \restoresinglelinesettings
1657 }
```

Notice the use of token registers and `\edef` here to concatenate the first and second lines.

```
1658 \newcommand{\poemtitlemiddleline}[1]{%
1659 \middlelinesettings
1660 \set@p@emtitle{#1}{\par\nobreak}{\poemtitlefont}%
1661 {\poemtitlesecondlineindent}{\nobreak\par\nobreak}{\z@}%
1662 \c@ntentsinfo{#1}{\contentspoemtitlesecondlineindent}{\contentspoemtitlefont}%
1663 {\contentspoemtitlesecondlineindentamount}%
1664 \t@xtnotesinfo{#1}%
```

```

1665 \restoresinglelinesettings
1666 }
1667 \newcommand{\poemtitlelastline}[1]{%
1668 \lastlinesettings
1669 \set@p@emtitle{#1}{\par\nobreak}{\poemtitlefont}%
1670 {\poemtitlesecondlineindent}{\nobreak\par\afterpoemtitleskip\nobreak}{\z@}%
1671 \c@ntentsinfo{#1}{\contentspoemtitlesecondlineindent}{\contentspoemtitlefont}%
1672 {\contentspoemtitlesecondlineindentamount}%
1673 \t@xtnotesinfo{#1}%
1674 \restoresinglelinesettings
1675 }

```

Titles for sections of poems, and multi-line titles of sections of poems

```

\poemsectiontitle
\poemsectiontitlefirstline 1676 \newcommand{\poemsectiontitle}[1]{%
\poemsectiontitlemiddleline 1677 \set@p@emtitle{#1}{\poemtitlepenalty}{\subsectiontitlefont}%
\poemsectiontitlelastline 1678 {\poemsectiontitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}%
1679 {\titleindentamount}%
1680 \c@ntentsinfo{#1}{\contentspoemsectiontitleindent}{\contentspoemtitlefont}%
1681 {\contentspoemsectiontitleindentamount}%
1682 \t@xtnotesinfo{#1}%
1683 }
1684 \newcommand{\poemsectiontitlefirstline}[1]{%
1685 \firstlinesettings
1686 \set@p@emtitle{#1}{\multilinetitlepenalty}{\subsectiontitlefont}%
1687 {\poemsectiontitleindent}{\nobreak\par\nobreak}{\poemsectiontitleindentamount}%
1688 \c@ntentsinfo{#1}{\contentspoemsectiontitleindent}{\contentspoemtitlefont}%
1689 {\contentspoemsectiontitleindentamount}%
1690 \t@xtnotesinfo{#1}%
1691 \restoresinglelinesettings
1692 }
1693 \newcommand{\poemsectiontitlemiddleline}[1]{%
1694 \middlelinesettings
1695 \set@p@emtitle{#1}{\relax}{\subsectiontitlefont}%
1696 {\poemsectiontitlesecondlineindent}{\nobreak\par\nobreak}{\poemsectiontitlesecondlineindentamou
1697 \c@ntentsinfo{#1}{\contentspoemsectiontitlesecondlineindent}{\contentspoemtitlefont}%
1698 {\contentspoemsectiontitlesecondlineindentamount}%
1699 \t@xtnotesinfo{#1}%
1700 \restoresinglelinesettings
1701 }
1702 \newcommand{\poemsectiontitlelastline}[1]{%
1703 \lastlinesettings
1704 \set@p@emtitle{#1}{\par\nobreak}{\subsectiontitlefont}%
1705 {\poemsectiontitlesecondlineindent}{\nobreak\par\afterpoemtitleskip\nobreak}%
1706 {\poemsectiontitlesecondlineindentamount}%
1707 \c@ntentsinfo{#1}{\contentspoemsectiontitlesecondlineindent}{\contentspoemtitlefont}%
1708 {\contentspoemsectiontitlesecondlineindentamount}%
1709 \t@xtnotesinfo{#1}%
1710 \restoresinglelinesettings

```

1711 }

`\poemsectiontitlenocontents`

```
\poemsectionbaretitle 1712 \newcommand{\poemsectiontitlenocontents}[1]{%
  \poemsubsectiontitle 1713 \sequencesubsectiontitlenocontents{#1}}%
  \poemtitlenotitle 1714 \newcommand{\poemfirstsectiontitle}[1]{%
\poemtitlenotitleitalic 1715 \set@p@emtitle{#1}{\par\nobreak}{\subsectiontitlefont}%
  1716 {\poemsectiontitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}%
  1717 {\poemsectiontitleindentamount}%
  1718 \c@ntentsinfo{#1}{\contentspoemsectiontitleindent}{\contentspoemtitlefont}%
  1719 {\contentspoemsectiontitleindentamount}%
  1720 \t@xtnotesinfo{#1}%
  1721 }
  1722 \newcommand{\poemfirstsectiontitlebaretitle}[1]{%
  1723 \set@p@emtitle{#1}{\par\nobreak}{\subsectiontitlefont}%
  1724 {\poemsectiontitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}%
  1725 {\poemsectiontitleindentamount}}
  1726 \newcommand{\poemsectiontitlebaretitle}[1]{%
  1727 \set@p@emtitle{#1}{\poemtitlepenalty}{\subsectiontitlefont}%
  1728 {\titleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}%
  1729 {\titleindentamount}%
  1730 }
  1731 \newcommand{\poemsubsectiontitle}[1]{%
  1732 \set@p@emtitle{#1}{\poemtitlepenalty}{\subsectiontitlefont}%
  1733 {\poemsubsectiontitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}%
  1734 {\poemsubsectiontitleindentamount}%
  1735 \c@ntentsinfo{#1}{\contentspoemsubsectiontitleindent}{\contentspoemtitlefont}%
  1736 {\contentspoemsubsectiontitleindentamount}%
  1737 \t@xtnotesinfo{#1}%
  1738 }
  1739 \newcommand{\poemtitlenotitle}[1]{%
  1740 \m@kep@emlabel
  1741 \m@ken@teholder{#1}%
  1742 \c@ntentsinfo{#1}{\contentspoemtitleindent}{\contentspoemtitlefont}%
  1743 {\contentsindenttwoamount}%
  1744 \t@xtnotesinfo{#1}%
  1745 }
  1746 \newcommand{\poemtitlenotitleitalic}[2]{%
  1747 \poemtitlenotitle{#1}}
```

22.15.2 Poetic Sequences: Setting the Main Title

`\sequencetitle` Variants here for multiple line titles and titles with font commands. Also some all-purpose kludges to work around other problems.

```
1748 \newcommand{\sequencetitle}[1]{
1749 \set@p@emtitle{#1}{\sequencetitlepenalty}{\sequencetitlefont}
1750 {\sequencetitleindent}{\nobreak\par\nobreak\aftersequencetitleskip\nobreak}{\z@}
1751 \putpagenumberincontentsfalse
1752 \c@ntentsinfo{#1}{\contentssequencetitleindent}{\contentssequencetitlefont}
```

```

1753 {\contentssequencetitleindentamount}
1754 \putpagenumberincontentstrue
1755 \t@xtnotesinfo{#1}
1756 }

```

`\sequencetitlefirstline` To set the title of a poetic sequence if it requires several lines to do so.

```

\sequencetitlemiddleline 1757 \newcommand{\sequencetitlefirstline}[1]{
\sequencetitlelastline 1758 \firstlinesettings
1759 \set@p@emtitle{#1}{\multilinesequencesepenalty}{\sequencetitlefont}
1760 {\sequencetitleindent}{\nobreak\par\nobreak}{\z@}
1761 \c@ntentsinfo{#1}{\contentssequencetitleindent}{\contentssequencetitlefont}
1762 {\contentssequencetitleindentamount}
1763 \t@xtnotesinfo{#1}
1764 \restoresinglelinesettings
1765 }
1766 \newcommand{\sequencetitlemiddleline}[1]{
1767 \middlelinesettings
1768 \set@p@emtitle{#1}{\par\nobreak}{\sequencetitlefont}
1769 {\sequencetitleindent}{\nobreak\par\nobreak}{\z@}
1770 \c@ntentsinfo{#1}{\contentssequencetitlesecondlineindent}{\contentssequencetitlefont}
1771 {\contentssequencetitlesecondlineindentamount}
1772 \t@xtnotesinfo{#1}
1773 \restoresinglelinesettings
1774 }
1775 \newcommand{\sequencetitlelastline}[1]{
1776 \lastlinesettings
1777 \set@p@emtitle{#1}{\par\nobreak}{\sequencetitlefont}
1778 {\sequencetitleindent}{\nobreak\par\aftersequencetitleskip\nobreak}{\z@}
1779 \c@ntentsinfo{#1}{\contentssequencetitlesecondlineindent}{\contentssequencetitlefont}
1780 {\contentssequencetitlesecondlineindent}
1781 \t@xtnotesinfo{#1}
1782 \restoresinglelinesettings
1783 }
1784 \newcommand{\sequencesubtitle}[1]{
1785 \set@p@emsubtitle{#1}{\par\nobreak}{\sequencetitlefont}
1786 {\sequencesubtitleindent}{\nobreak\par\aftersequencetitleskip\nobreak}{\z@}
1787 \c@ntentsinfo{#1}{\contentssequencesubtitleindent}{\contentssequencetitlefont}
1788 {\contentssequencesubtitleindentamount}
1789 \t@xtnotesinfo{#1}
1790 }
1791 \newcommand{\sequencesubtitlefirstline}[1]{\firstlinesettings
1792 \set@p@emsubtitle{#1}{\par\nobreak}{\sequencetitlefont}
1793 {\sequencesubtitleindent}{\nobreak\par\aftersequencetitleskip\nobreak}{\z@}
1794 \c@ntentsinfo{#1}{\contentsindenttwo}{\contentssequencetitlefont}
1795 {\contentsindentthreeamount}
1796 \t@xtnotesinfo{#1}
1797 \restoresinglelinesettings
1798 }
1799 \newcommand{\sequencesubtitlemiddleline}[1]{\middlelinesettings
1800 \set@p@emsubtitle{#1}{\par\nobreak}{\sequencetitlefont}

```

```

1801 {\sequencesubtitlesecondlineindent}{\nobreak\par\aftersequencetitleskip\nobreak}{\z@}
1802 \c@ntentsinfo{#1}{\contentssequencesubtitlesecondlineindent}{\contentssequencetitlefont}
1803 {\contentssequencesubtitlesecondlineindentamount}
1804 %\t@xtnotesinfo{#1}
1805 \restoresinglelinesettings
1806 }
1807 \newcommand{\sequencesubtitlelastline}[1]{\lastlinesettings
1808 \set@p@emsubtitle{#1}{\par\nobreak}{\sequencetitlefont}
1809 {\sequencesubtitlesecondlineindent}{\nobreak\par\aftersequencetitleskip\nobreak}{\z@}
1810 \c@ntentsinfo{#1}{\contentssequencesubtitlesecondlineindent}{\contentssequencetitlefont}
1811 {\contentssequencesubtitlesecondlineindentamount}
1812 %\t@xtnotesinfo{#1}
1813 \restoresinglelinesettings
1814 }

```

22.15.3 Sections of poetic sequences

`\sequencesectiontitle` First, the easy case: a simple section of a poetic sequence.

```

1815 \newcommand{\sequencesectiontitle}[1]{
1816 \set@p@emtitle{#1}{\poemtitlepenalty}{\poemtitlefont}
1817 {\sequencesectiontitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}
1818 {\sequencesectiontitleindentamount}
1819 \c@ntentsinfo{#1}{\contentssequencesectiontitleindent}{\contentspoemtitlefont}
1820 {\contentssequencesectiontitleindentamount}
1821 \t@xtnotesinfo{#1}
1822 }

```

`\sequencefirstsectiontitle` The first poem in a sequence is a special case.

```

1823 \newcommand{\sequencefirstsectiontitle}[1]{
1824 \set@p@emtitle{#1}{\par\nobreak\afterpoemtitleskip}{\poemtitlefont}
1825 {\sequencesectiontitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}
1826 {\sequencesectiontitleindentamount}
1827 \c@ntentsinfo{#1}{\contentssequencesectiontitleindent}{\contentspoemtitlefont}
1828 {\contentssequencesectiontitleindentamount}
1829 \t@xtnotesinfo{#1}
1830 }

```

`\sequencesectiontitlenonotes` If you don't have any notes on a sequence section, it seems a shame to open an entry in the textual notes for that section:

```

1831 \newcommand{\sequencetitelnonotes}[1]{
1832 \set@p@emtitle{#1}{\par\nobreak}{\sequencetitlefont}
1833 {\sequencetitleindent}{\nobreak\par\aftersequencetitleskip\nobreak}{\sequencetitleindentamount}
1834 \c@ntentsinfo{#1}{\contentssequencetitleindent}{\contentssequencetitlefont}
1835 {\contentssequencetitleindentamount}
1836 %\t@xtnotesinfo{#1}
1837 }
1838 \newcommand{\sequencesectiontitlenonotes}[1]{
1839 \set@p@emtitle{#1}{\poemtitlepenalty}{\poemtitlefont}
1840 {\sequencesectiontitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}

```

```

1841 {\sequencesectiontitleindentamount}
1842 \c@ntentsinfo{#1}{\contentssequencesectiontitleindent}{\contentspoemtitlefont}
1843 {\contentssequencesectiontitleindentamount}
1844 \t@xtnotesinfo{#1}
1845 }

```

For multiple line titles of sequence sections

```

1846 \newcommand{\sequencesectiontitlefirstline}[1]{
1847 \firstlinesettings
1848 \set@p@emtitle{#1}{\multilinetitlepenalty}{\poemtitlefont}
1849 {\sequencesectiontitleindent}{\nobreak\par\nobreak}{\sequencesectiontitleindentamount}
1850 \c@ntentsinfo{#1}{\contentssequencesectiontitleindent}{\contentspoemtitlefont}
1851 {\contentssequencesectiontitleindentamount}
1852 \t@xtnotesinfo{#1}
1853 \restoresinglelinesettings
1854 }
1855 \newcommand{\sequencesectiontitlemiddleline}[1]{
1856 \middlelinesettings
1857 \set@p@emtitle{#1}{\par\nobreak}{\poemtitlefont}
1858 {\sequencesectiontitleindent}{\nobreak\par\nobreak}{\sequencesectiontitleindentamount}
1859 \c@ntentsinfo{#1}{\contentssequencesectiontitlesecondlineindent}{\contentspoemtitlefont}
1860 {\contentssequencesectiontitlesecondlineindentamount}
1861 \t@xtnotesinfo{#1}
1862 \restoresinglelinesettings
1863 }
1864 \newcommand{\sequencesectiontitlelastline}[1]{
1865 \lastlinesettings
1866 \set@p@emtitle{#1}{\par\nobreak}{\poemtitlefont}
1867 {\sequencesectiontitleindent}{\nobreak\par\afterpoemtitleskip\nobreak}{\sequencesectiontitleind
1868 \c@ntentsinfo{#1}{\contentssequencesectiontitlesecondlineindent}{\contentspoemtitlefont}
1869 {\contentssequencesectiontitlesecondlineindentamount}
1870 \t@xtnotesinfo{#1}
1871 \restoresinglelinesettings
1872 }

```

The following macros are to kludge around situations where the section title is just a number. This macro has two arguments. Originally, the first was the title of the section. The second is the title of the sequence as a whole. I've retained the second argument for backward compatibility with earlier versions, but you can set it to anything, since it's discarded now.

```

1873 \newcommand{\sequencefirstsectiontitlenocontents}[2]{
1874 \set@p@emtitle{#1}{\par\nobreak\afterpoemtitleskip}{\poemtitlefont}
1875 {\sequencesectiontitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}
1876 {\sequencesectiontitleindentamount}
1877 \c@ntentsinfo{#1}{\contentsindenttwo}{\contentspoemtitlefont}
1878 \t@xtnotesinfo{#1}
1879 }
1880 \newcommand{\sequencesectiontitlenocontents}[2]{
1881 \set@p@emtitle{#1}{\poemtitlepenalty}{\poemtitlefont}
1882 {\sequencesectiontitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}

```

```

1883 {\sequencesectiontitleindentamount}
1884 %\c@ntentsinfo{#1}{\contentsindenttwo}{\contentspoemtitlefont}
1885 \t@xtnotesinfo{#1}
1886 }

```

If the first section of a sequence is a multiple line title, the following macros can handle the special problems that situation poses.

```

1887 \newcommand{\sequencefirstsectiontitlefirstline}[1]{
1888 \firstlinesettings
1889 \set@p@emtitle{#1}{\par\nobreak\afterpoemtitleskip}{\poemtitlefont}
1890 {\sequencesectiontitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}
1891 {\sequencesectiontitleindentamount}
1892 \c@ntentsinfo{#1}{\contentssequencesectiontitleindent}{\contentspoemtitlefont}
1893 {\contentssequencesectiontitleindentamount}
1894 \t@xtnotesinfo{#1}
1895 \restoresinglelinesettings
1896 }
1897 \newcommand{\sequencefirstsectiontitlemiddleline}[1]{
1898 \sequencesectiontitlemiddleline{#1}}
1899
1900 \newcommand{\sequencefirstsectiontitlelastline}[1]
1901 {\sequencesectiontitlelastline{#1}}
1902
1903 \newcommand{\sequencefirstsectiontitlenonotes}[1]{
1904 \set@p@emtitle{#1}{\par\nobreak\afterpoemtitleskip}{\poemtitlefont}
1905 {\sequencesectiontitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}
1906 {\sequencesectiontitleindentamount}
1907 \c@ntentsinfo{#1}{\contentssequencesectiontitleindent}{\contentspoemtitlefont}
1908 {\contentssequencesectiontitleindentamount}
1909 %\t@xtnotesinfo{#1}
1910 }

```

`\sequencesectionsubsubtitle`

```

\poemsubsubtitle 1911 % \newcommand{\sequencesectionsubsubtitle}[1]{{\subsectionfont \hbox{\titleindent #1}}
1912 % \nobreak\par\nobreak\afterpoemtitleskip\nobreak
1913 % }
1914 \newcommand{\sequencesectionsubsubtitle}[1]{\set@p@emsubsubtitle{#1}{\par\nobreak\afterpoemtitleskip}
1915 {\subsectionfont}{\sequencesectionsubsubtitleindent}{\nobreak\par\nobreak\afterpoemtitleskip}
1916 }
1917 \newcommand{\sequencesectionsubsubtitlefirstline}[1]{\firstlinesettings
1918 \set@p@emsubsubtitle{#1}{\par\nobreak\afterpoemtitleskip}
1919 {\subsectionfont}{\sequencesectionsubsubtitleindent}{\nobreak\par\nobreak\afterpoemtitleskip}
1920 \restoresinglelinesettings
1921 }
1922 \newcommand{\sequencesectionsubtitlemiddleline}[1]{\middlelinesettings
1923 \set@p@emsubsubtitle{#1}{\par\nobreak\afterpoemtitleskip}
1924 {\subsectionfont}{\sequencesectionsubsubtitleindent}{\nobreak\par\nobreak\afterpoemtitleskip}
1925 \restoresinglelinesettings
1926 }
1927 \newcommand{\sequencesectionsubtitllelastline}[1]{\lastlinesettings

```

```

1928 \set@p@emsubtitle{#1}{\par\nobreak\afterpoemtitleskip}
1929 {\subsectiontitlefont}{\sequencesectionsubtitleindent}{\nobreak\par\nobreak\afterpoemtitleskip}
1930 \restoresinglelinesettings
1931 }
1932 \newcommand{\poemsubtitle}[1]{\set@p@emsubtitle{#1}{\par\nobreak\afterpoemtitleskip}
1933 {\subsectiontitlefont}{\poemsubtitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}{\t
1934 }

```

Another (former) kludge for special situations:

```

1935 \newcommand{\sequencesectiontitleitalicnonotes}[2]
1936 {\sequencesectiontitlenonotes{#1}
1937 }

```

Italic titles used to require two arguments. These commands are retained only for backward compatibility.

`\sequencesectiontitleitalic`

```

1938 \newcommand{\sequencesectiontitleitalic}[2]{
1939 \sequencesectiontitle{#1}}
1940 \newcommand{\sequencesectiontitlefirstlineitalic}[2]
1941 {\sequencesectiontitlefirstline{#1}}
1942 \newcommand{\sequencesectiontitlebaretitle}[1]{
1943 \set@p@emtitle{#1}{\poemtitlepenalty}{\poemtitlefont}
1944 {\titleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}{\titleindentamount}
1945 }

```

22.15.4 Subsections of sequences

`\sequencesubsectiontitle` Continuing several levels down: macros for setting subsections and subsubsections of sequences.

```

1946 \newcommand{\sequencesubsectiontitle}[1]{
1947 \set@p@emtitle{#1}{\poemtitlepenalty}{\subsectiontitlefont}
1948 {\sequencesubsectiontitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}
1949 {\sequencesubsectiontitleindentamount}
1950 \c@ntentsinfo{#1}{\contentssequencesubsectiontitleindent}{\contentspoemtitlefont}
1951 {\contentssequencesubsectiontitleindentamount}
1952 \t@xtnotesinfo{#1}
1953 }
1954 \newcommand{\sequencesubsectiontitlenocontents}[1]{
1955 \set@p@emtitle{#1}{\poemtitlepenalty}{\subsectiontitlefont}
1956 {\sequencesubsectiontitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}
1957 {\sequencesubsectiontitleindentamount}
1958 %\c@ntentsinfo{#1}{\contentsindentthree}{\contentspoemtitlefont}{\contentsindentfouramount}
1959 \t@xtnotesinfo{#1}
1960 }
1961 \newcommand{\sequencefirstsubsectiontitle}[1]
1962 {\set@p@emtitle{#1}{\par\nobreak}{\subsectiontitlefont}
1963 {\sequencesubsectiontitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}
1964 {\sequencesubsectiontitleindentamount}
1965 \c@ntentsinfo{#1}{\contentssequencesubsectiontitleindent}{\contentspoemtitlefont}

```

```

1966 {\contentssequencesubsectiontitleindentamount}
1967 \t@xtnotesinfo{#1}
1968 }
1969 \newcommand{\sequencefirstsubsectiontitlenocontents}[1]
1970 {\set@p@emtitle{#1}{\par\nobreak}{\subsectiontitlefont}
1971 {\sequencesubsectiontitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}
1972 {\sequencesubsectiontitleindentamount}
1973 %\c@ntentsinfo{#1}{\contentsindentthree}{\contentspoemtitlefont}
1974 %{\contentsindentfouramount}
1975 \t@xtnotesinfo{#1}
1976 }
1977 \newcommand{\sequencesubsectiontitlefirstline}[1]{
1978 \firstlinesettings
1979 \set@p@emtitle{#1}{\multilinetitlepenalty}{\subsectiontitlefont}
1980 {\sequencesubsectiontitleindent}{\nobreak\par\nobreak}{\sequencesubsectiontitleindentamount}
1981 \c@ntentsinfo{#1}{\contentssequencesubsectiontitleindent}{\contentspoemtitlefont}
1982 {\contentssequencesubsectiontitleindentamount}
1983 \t@xtnotesinfo{#1}
1984 \restoresinglelinesettings
1985 }
1986 \newcommand{\sequencesubsectiontitlemiddleline}[1]{
1987 \middlelinesettings
1988 \set@p@emtitle{#1}{\nobreak}{\subsectiontitlefont}
1989 {\sequencesubsectiontitlesecondlineindent}{\nobreak\par\nobreak}{\sequencesubsectiontitlesecond
1990 \c@ntentsinfo{#1}{\contentssequencesubsectiontitlesecondlineindent}{\contentspoemtitlefont}
1991 {\contentssequencesubsectiontitlesecondlineindentamount}
1992 \t@xtnotesinfo{#1}
1993 \restoresinglelinesettings
1994 }
1995 \newcommand{\sequencesubsectiontitlelastline}[1]{
1996 \lastlinesettings
1997 \set@p@emtitle{#1}{\nobreak}{\subsectiontitlefont}
1998 {\sequencesubsectiontitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}
1999 {\sequencesubsectiontitleindentamount}
2000 \c@ntentsinfo{#1}{\contentssequencesubsectiontitlesecondlineindent}{\contentspoemtitlefont}
2001 {\contentssequencesubsectiontitlesecondlineindentamount}
2002 \t@xtnotesinfo{#1}
2003 \restoresinglelinesettings
2004 }
2005 \newcommand{\sequencesubsubsectiontitle}[1]{
2006 \set@p@emtitle{#1}{\poemtitlepenalty}{\subsectiontitlefont}
2007 {\sequencesubsubsectiontitleindent}
2008 {\nobreak\par\nobreak\afterpoemtitleskip\nobreak}
2009 {\sequencesubsubsectiontitleindentamount}
2010 %\c@ntentsinfo{#1}{\contentssequencesubsubsectiontitleindent}{\contentspoemtitlefont}
2011 %{\contentssequencesubsubsectiontitleindentmount} % 313
2012 \t@xtnotesinfo{#1}
2013 }
2014 \newcommand{\sequencesubsubsectiontitlenocontents}[1]{
2015 \set@p@emtitle{#1}{\poemtitlepenalty}{\subsectiontitlefont}

```

```

2016 {\sequencesubsubsectionitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}
2017 {\sequencesubsubsectionitleindentamount}
2018 %\c@ntentsinfo{#1}{\contentsindentfour}{\contentspoemtitlefont}
2019 %{\contentsindentfiveamount}
2020 \t@xtnotesinfo{#1}
2021 }
2022 \newcommand{\sequencefirstsubsubsectionitlenocontents}[1]{
2023 \set@p@emtitle{#1}{\nobreak\par\nobreak}{\subsectiontitlefont}
2024 {\sequencesubsubsectionitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}
2025 {\sequencesubsubsectionitleindentamount}
2026 %\c@ntentsinfo{#1}{\contentsindentfour}{\contentspoemtitlefont}{\contentsindentfiveamount}
2027 \t@xtnotesinfo{#1}
2028 }
2029
2030
2031 \newcommand{\sequencefirstsubsectionitlefirstline}[1]{
2032 \firstlinesettings
2033 \set@p@emtitle{#1}{\par\nobreak}{\subsectiontitlefont}
2034 {\sequencesubsubsectionitleindent}{\nobreak\par\nobreak}{\sequencesubsubsectionitleindentamount}
2035 \c@ntentsinfo{#1}{\contentssequencesubsubsectionitleindent}{\contentspoemtitlefont}
2036 {\contentssequencesubsubsectionitleindent}
2037 \t@xtnotesinfo{#1}
2038 \restoresinglelinesettings
2039 }
2040 \newcommand{\sequencefirstsubsectionitlemiddleline}[1]{
2041 \sequencesubsubsectionitlemiddleline{#1}}
2042 \newcommand{\sequencefirstsubsectionitlelastline}[1]{
2043 \sequencesubsubsectionitlelastline{#1}}

```

Interjections in sequences, as in Robert Penn Warren's *Or Else*.

```

2044 \newcommand{\interjectiontitlefirstline}[1]{
2045 \sequencefirstsubsectionitlefirstline{#1}}
2046 \newcommand{\interjectiontitlelastline}[1]{
2047 \sequencefirstsubsectionitlelastline{#1}
2048 }
2049 \newcommand{\interjectiontitlemiddleline}[1]{
2050 \sequencefirstsubsectionmiddleline{#1}
2051 }
2052 % \subsubsection{Titles and Notes with marginal marks}

```

`\setmargpoemtitle` Titles with a marginal reference to the notes giving the page in the notes where a comment on the poem appears, as in Altenberg's Heredia edition. `\setmargpoemtitle` takes as its second argument anything you want to add to the line while the title is being processed. `\JHpoemtitle` is just `\setmargpoemtitle` with the second argument passed to `\JHlabel`, which actually makes the marginal mark.

```

2053 \newlength{\JHtextwidth}
2054 \setlength{\JHtextwidth}{\textwidth}
2055 \newlength{\JHmarginparsep}

```

```

2056 \setlength{\JHmarginparsep}{Opt}
2057 \newlength{\JHmarginparvshift}
2058 \setlength{\JHmarginparvshift}{Opt}
2059 \newlength{\JHmarginparwidth}
2060 \setlength{\JHmarginparwidth}{\marginparwidth}
2061 \newlength{\JHmarginparsepmin}
2062 \setlength{\JHmarginparsepmin}{\marginparsepmin}
2063 \newlength{\JHtitlemarginparsep}%
2064 \setlength{\JHtitlemarginparsep}{\JHmarginparsep}%
2065 \newif{\ifJHmarkstoleft}
2066 \JHmarkstolefttrue
2067 \newif{\ifJHmarkstoright}
2068 \JHmarkstorightfalse
2069 \newif{\ifJHmarkstoouter}
2070 \JHmarkstoouterfalse
2071 \newif{\ifJHmarkstogutter}
2072 \JHmarkstogutterfalse
2073 \newif{\ifJHmarginparswitch}
2074 \JHmarginparswitchfalse
2075 \newif{\ifJHreversemarginpar}
2076 \JHreversemarginparfalse
2077 \newcommand{\JHmarksleft}{%
2078 \JHmarkstolefttrue%
2079 \JHmarkstorightfalse%
2080 \JHmarkstoouterfalse%
2081 \JHmarkstogutterfalse%
2082 \JHmarginparswitchfalse%
2083 \JHreversemarginparfalse%
2084 \reversemarginpar
2085 }
2086 \newcommand{\JHmarksright}{%
2087 \JHmarkstoleftfalse%
2088 \JHmarkstorighttrue%
2089 \JHmarkstoouterfalse%
2090 \JHmarkstogutterfalse%
2091 \JHmarginparswitchfalse%
2092 \JHreversemarginparfalse%
2093 \normalmarginpar
2094 }
2095 % JHmarksright is the default
2096 \JHmarksright
2097 \newcommand{\JHmarksouter}{%
2098 \JHmarkstoleftfalse%
2099 \JHmarkstorightfalse%
2100 \JHmarkstooutertrue%
2101 \JHmarkstogutterfalse%
2102 \JHmarginparswitchtrue%
2103 \JHreversemarginparfalse%
2104 \@mparswitchtrue
2105 }

```

```

2106 \newcommand{\JHmarksgutter}{%
2107 \JHmarkstoleftfalse%
2108 \JHmarkstorightfalse%
2109 \JHmarkstoouterfalse%
2110 \JHmarkstoguttertrue%
2111 \JHmarginparswitchtrue%
2112 \JHreversemarginpartrue%
2113 \@mparswitchtrue
2114 \reversemarginpar
2115 }
2116 % jhrightmarginpar command for notes % right side
2117 \newcommand{\JHrightmarginpar}[1]{%
2118 \pmclbsphack\strut\vadjust{%
2119 \rlap{\kern-\parindent%
2120 \kern\JHtextwidth\kern\JHmarginparsep% at right
2121 \setbox0=\vtop to Opt{% added
2122 \begin{minipage}[t]{\JHmarginparwidth}% added
2123 #1%
2124 \end{minipage}%
2125 \vss}%
2126 \vtop to Opt{\kern\JHmarginparvshift% default should be Opt
2127 \kern-\dp\strutbox \kern-\ht0 \box0 \vss}}\pmclesphack}%
2128 % jhleftmarginpar command for notes % left side
2129 \newcommand{\JHleftmarginpar}[1]{%
2130 \pmclbsphack\strut\vadjust{% changed
2131 \rlap{\kern-\parindent%
2132 \kern -\JHmarginparsep \kern -\JHmarginparwidth% at left
2133 \setbox0=\vtop to Opt{
2134 \begin{minipage}[t]{\JHmarginparwidth}% added
2135 #1%
2136 \end{minipage}%
2137 \vss}% changed
2138 \vtop to Opt{\kern\JHmarginparvshift % default should be Opt
2139 \kern-\dp\strutbox \kern-\ht0 \box0 \vss}}\pmclesphack}% changed
2140 %
2141 %\newcommand{\JHoutermarginpar}{%
2142 %\marginpar{\scriptsize {\the\margrefmarker~p.\~\pageref{margref\themargrefnumber}}}}
2143 %\checkoddpage%
2144 %\ifoddpage%
2145 %\JHrightmarginpar{\scriptsize {\the\margrefmarker~p.\~\pageref{margref\themargrefnumber}}}}%
2146 %\else% below is for even pages
2147 %\JHleftmarginpar{\scriptsize {\the\margrefmarker~p.\~\pageref{margref\themargrefnumber}}}}%
2148 %\fi%
2149 %}
2150 \newcommand{\JHoutermarginpar}{%
2151 %\marginpar{\scriptsize {\the\margrefmarker~p.\~\pageref{margref\themargrefnumber}}}}
2152 \strictpagechecktrue%
2153 \checkoddpage%
2154 \ifoddpage%
2155 \JHswitchmarginpar{\scriptsize {\the\margrefmarker~p.\~\pageref{margref\themargrefnumber}}}}%

```

```

2156 \else% below is for even pages
2157 \JHswitchmarginpar{\scriptsize {\the\margrefmarker~p.\pageref{margref\themargrefnumber}}}%
2158 \fi%
2159 }
2160 %
2161 %\newcommand{\JHguttermarginpar}{%
2162 %\marginpar{\scriptsize {\the\margrefmarker~p.\pageref{margref\themargrefnumber}}}%
2163 %\checkoddpage%
2164 %\ifoddpage%
2165 % \JHleftmarginpar{\scriptsize {\the\margrefmarker~p.\pageref{margref\themargrefnumber}}}%
2166 %\else% below is for even pages
2167 % \JHrightmarginpar{\scriptsize {\the\margrefmarker~p.\pageref{margref\themargrefnumber}}}%
2168 %\fi%
2169 %}
2170 %
2171 \newcommand{\JHguttermarginpar}{%
2172 \strictpagechecktrue
2173 \checkoddpage%
2174 \ifoddpage%
2175 \JHswitchmarginpar{\scriptsize {\the\margrefmarker~p.\pageref{margref\themargrefnumber}}}%
2176 \else% below is for even pages
2177 \JHswitchmarginpar{\scriptsize {\the\margrefmarker~p.\pageref{margref\themargrefnumber}}}%
2178 \fi%
2179 }
2180 %
2181 % jhswitchmarginpar command for notes in gutter and outer
2182 %
2183 \newcommand{\JHswitchmarginpar}{\@dblarg{\@JHswitchmarginpar}}
2184 %\long\def\@pmclsidepar[#1]#2{\@bsphack\leavevmode\vadjust{%
2185 \long\def\@JHswitchmarginpar[#1]#2{\@bsphack\strut\vadjust{% added
2186 \checkoddpage
2187 \ifJHmarginparswitch
2188 \ifJHreversemarginpar
2189 \ifoddpage
2190 \oddpagfalse
2191 \else
2192 \oddpagtrue
2193 \fi
2194 \fi
2195 \else
2196 \oddpagtrue
2197 \ifJHreversemarginpar
2198 \oddpagfalse
2199 \fi
2200 \fi
2201 \rlap{\kern-\parindent
2202 \if@twocolumn
2203 \if@firstcolumn % put at left
2204 \kern -\JHmarginparsep \kern -\JHmarginparwidth % at left
2205 \else % put at right

```

```

2206     \kern \columnwidth \kern \JHmarginparsep % at right
2207     \fi
2208     \else
2209     \ifoddpage           % put at right
2210     \kern \textwidth \kern \JHmarginparsep           % at right
2211     \else               % put at left
2212     \kern -\JHmarginparsep \kern -\JHmarginparwidth % at left
2213     \fi
2214     \fi
2215 %     \vbox to Opt{%
2216 %     \kern \JHmarginparvshift%           % vertical shift to align top text lines
2217 %     \begin{minipage}{\JHmarginparwidth}%
2218 %     \setbox0=\vtop to Opt{% added
2219 %     \begin{minipage}[t]{\JHmarginparwidth}% added
2220 %     \ifoddpage #2\else #1\fi%
2221 %     \end{minipage}%
2222 %     \vss}}\@esphack}
2223 \vss}% added
2224 \vtop to Opt{\kern\JHmarginparvshift % default should be Opt
2225 \kern-\dp\strutbox \kern-\ht0 \box0 \vss}}\@esphack}% added
2226 %
2227 % commands for placing the marginal marks for titles
2228 % right side
2229 \newcommand{\JHrighttitlemarginpar}[1]{%
2230 \pmclbsphack\strut\vadjust{%
2231 \rlap{\kern-\parindent%
2232 \kern\textwidth\kern\JHtitlemarginparsep% at right
2233 \ifcentertitleson%
2234 \kern-.5\JHtextwidth\kern\marginparsepmin%
2235 \fi%
2236 \setbox0=\vtop to Opt{% added
2237 \begin{minipage}[t]{\JHmarginparwidth}% added
2238 #1%
2239 \end{minipage}%
2240 \vss}%
2241 \vtop to Opt{\kern\JHmarginparvshift% default should be Opt
2242 \kern-\dp\strutbox \kern-\ht0 \box0 \vss}}\@pmclesphack}%
2243 %
2244 % commands for placing the marginal marks for titles
2245 % left side
2246 \newcommand{\JHlefttitlemarginpar}[1]{%
2247 \pmclbsphack\strut\vadjust{% changed
2248 \rlap{\kern-\parindent%
2249 \kern -\JHtitlemarginparsep \kern -\JHmarginparwidth% at left
2250 \ifcentertitleson%
2251 \kern-.5\JHtextwidth\kern\marginparsepmin%
2252 \fi%
2253 \setbox0=\vtop to Opt{%
2254 \begin{minipage}[t]{\JHmarginparwidth}% added
2255 #1%

```

```

2256 \end{minipage}%
2257 \vss}% changed
2258 \vtop to Opt{\kern\JHmarginparvshift % default should be Opt
2259 \kern-\dp\strutbox \kern-\ht0 \box0 \vss}}\pmclesphack}% changed
2260 %
2261 % command for JHtitlemarks in title in outer margin or in gutter
2262 \newcommand{\JHswitchtitlemarginpar}{\@dblarg{\@JHswitchtitlemarginpar}}
2263 %\long\def\@pmclsidepar[#1]#2{\@bsphack\leavevmode\vadjust{%
2264 \long\def\@JHswitchtitlemarginpar[#1]#2{\@bsphack\strut\vadjust{% added
2265 \checkoddpage%
2266 \ifJHmarginparswitch%
2267 \ifJHreversemarginpar%
2268 \ifoddpage%
2269 \oddpagetrue%
2270 \else%
2271 \oddpagetrue%
2272 \fi%
2273 \fi%
2274 \else%
2275 \oddpagetrue%
2276 \ifJHreversemarginpar%
2277 \oddpagetrue%
2278 \fi%
2279 \fi%
2280 \rlap{\kern-\parindent%
2281 \if@twocolumn%
2282 \if@firstcolumn % put at left
2283 \kern -\JHtitlemarginparsep \kern -\marginparwidth % at left
2284 \kern-.5\JHtextwidth\kern\marginparsepmin%
2285 \else % put at right
2286 \kern \columnwidth \kern \JHtitlemarginparsep % at right
2287 \fi%
2288 \else%
2289 \ifoddpage % put at right
2290 \kern \textwidth \kern \JHtitlemarginparsep % at right
2291 \ifcentertitleson%
2292 \kern-.5\JHtextwidth\kern\marginparsepmin%
2293 \fi%
2294 \else % put at left
2295 \kern -\JHtitlemarginparsep \kern -\marginparwidth % at left
2296 \ifcentertitleson%
2297 \kern-.5\JHtextwidth\kern\marginparsepmin%
2298 \fi%
2299 \fi%
2300 \fi%
2301 % \vbox to Opt{%
2302 % \kern \pmclsideparvshift% % vertical shift to align top text lines
2303 % \begin{minipage}{\marginparwidth}%
2304 \setbox0=\vtop to Opt{% added
2305 \begin{minipage}[t]{\marginparwidth}% added

```

```

2306     \ifoddpage #2\else #1\fi%
2307     \end{minipage}%
2308 %   \vss}}\@esphack}
2309 \vss}% added
2310 \vtop to Opt{\kern\JHmarginparvshift % default should be Opt
2311 \kern-\dp\strutbox \kern-\ht0 \box0 \vss}}\@esphack}% added
2312 %
2313 \newcommand{\set@margp@emtitle}[7]{\setlength{\titleentryoverrun}{#6}%
2314 {#2}%
2315 {#3 \begin{titleentryenvironment}%
2316 {\ifcentertitleson\begin{center}#4 #1 #7\end{center}\else #4 #1
2317 #7\fi}\end{titleentryenvironment}}%
2318 {#5}%
2319 \m@kep@emlabel%
2320 \m@ken@teholder{#1}%
2321 \setlength{\titleentryoverrun}{\z@}}
2322 %% subtitle version
2323 \newcommand{\set@margp@emsubtitle}[7]{\setlength{\titleentryoverrun}{#6}%
2324 {#2}%
2325 {#3 \begin{titleentryenvironment}%
2326 {\ifcentertitleson\begin{center}#4 #1 #7\end{center}\else #4 #1
2327 #7\fi}\end{titleentryenvironment}}%
2328 {#5}%
2329 \m@kep@emlabel%
2330 \m@ken@teholder{#1}%
2331 \setlength{\titleentryoverrun}{\z@}}
2332 % user version
2333 \newcommand{\setmargpoemtitle}[2]{%
2334 \set@margp@emtitle{#1}{\poemtitlepenalty}{\poemtitlefont}%
2335 {\sequencetitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}{\z@}{#2}%
2336 \c@contentsinfo{#1}{\contentsindentone}{\contentspoemtitlefont}%
2337 {\contentsindenttwoamount}}%
2338 \t@xtnotesinfo{#1}%
2339 \sources{\label{#2}}%
2340 }
2341 %\newcommand{\set@margp@emtitle}[7]{\setlength{\titleentryoverrun}{#6}%
2342 {#2}%
2343 {#3 \begin{titleentryenvironment}%
2344 {#4 #1 #7}\end{titleentryenvironment}}%
2345 {#5}%
2346 \m@kep@emlabel%
2347 \m@ken@teholder{#1}%
2348 %\setlength{\titleentryoverrun}{\z@}}

```

`\JHpoemtitle` Macros to set marginal line references.

```

2349 % \newcommand{\JHpoemtitle}[2]{%
2350 % \setmargpoemtitle{#1}{\JHlabel{#2}}%
2351 % }
2352 \mparswitchfalse % so the title marker won't switch sides on alternate pages
2353 \newcommand{\JHpoemtitle}[2]{%

```

```

2354 \set@margp@emtitle{#1}{\poemtitlepenalty}{\poemtitlefont}%
2355 {\sequencetitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}{\z@}%
2356 {\JHlabel{#2}}%
2357 \c@ntentsinfo{#1}{\contentssequencetitleindent}{\contentspoemtitlefont}%
2358 {\contentssequencetitleindentamount}%
2359 \t@xtnotesinfo{#1}%
2360 \sources{\label{#2}}%
2361 }
2362 \newcommand{\JHprosesectiontitle}[2]{%
2363 \set@margp@emtitle{#1}{\poemtitlepenalty}{\poemtitlefont}%
2364 {\sequencetitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}{\z@}%
2365 {\JHlabel{#2}}%
2366 \c@ntentsinfo{#1}{\contentssequencetitleindent}{\contentspoemtitlefont}%
2367 {\contentssequencetitleindentamount}%
2368 \t@xtnotesinfo{#1}%
2369 \sources{\label{#2}}%
2370 }
2371 %\newcommand{\JHlabel}[1]{%
2372 %\marginpar{{\scriptsize{\the\titlemargrefmarker~p.~\pageref{#1}}}}
2373 \newcommand{\JHlabel}[1]{%
2374 \ifJHmarkstoright\JHrighttitlemarginpar
2375 {{\scriptsize{\the\margrefmarker~p.~\pageref{#1}}}}
2376 \fi
2377 \ifJHmarkstoleft
2378 \JHlefttitlemarginpar{{\scriptsize{\the\margrefmarker~p.~\pageref{#1}}}}
2379 \fi
2380 \ifJHmarkstoouter
2381 \JHswitchtitlemarginpar{{\scriptsize{\the\margrefmarker~p.~\pageref{#1}}}}
2382 \fi
2383 \ifJHmarkstogutter
2384 \JHswitchtitlemarginpar{{\scriptsize{\the\margrefmarker~p.~\pageref{#1}}}}
2385 \fi
2386 }
2387

```

`\JHsequencetitle` Macros to set marginal page references for sequences, sequence sections, poem sections, poem subtitles, dedications, and epigraphs.

```

2388 \newcommand{\JHsequencetitle}[2]{%
2389 \set@margp@emtitle{#1}{\sequencetitlepenalty}{\sequencetitlefont}%
2390 {\sequencetitleindent}{\nobreak\par\nobreak\aftersequencetitleskip\nobreak}{\z@}%
2391 {\JHlabel{#2}}%
2392 \putpagenumberincontentsfalse%
2393 \c@ntentsinfo{#1}{\contentsindentone}{\contentssequencetitlefont}%
2394 {\contentsindenttwoamount}%
2395 \putpagenumberincontentstrue%
2396 \t@xtnotesinfo{#1}%
2397 \sources{\label{#2}}%
2398 }
2399 \newcommand{\JHsequencesectiontitle}[2]{%
2400 \set@margp@emtitle{#1}{\poemtitlepenalty}{\poemtitlefont}%

```

```

2401 {\sequencesectiontitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}%
2402 {\sequencesectiontitleindentamount}{\JHlabel{#2}}%
2403 \c@contentsinfo{#1}{\contentssequencesectiontitleindent}{\contentspoemtitlefont}%
2404 {\contentsindentthreamount}%
2405 \t@xtnotesinfo{#1}%
2406 \sources{\label{#2}}%
2407 }
2408 \newcommand{\JHsequencefirstsectiontitle}[2]{%
2409 \set@margin@emtitle{#1}{\par\nobreak\afterpoemtitleskip}{\poemtitlefont}%
2410 {\sequencesectiontitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}%
2411 {\titleindentamount}{\JHlabel{#2}}%
2412 \c@contentsinfo{#1}{\contentssequencesectiontitleindent}{\contentspoemtitlefont}%
2413 {\contentssequencesectiontitleindentamount}%
2414 \t@xtnotesinfo{#1}%
2415 \sources{\label{#2}}%
2416 }
2417 \newcommand{\JHpoemsectiontitle}[2]{%
2418 \set@margin@emtitle{#1}{\poemtitlepenalty}{\subsectiontitlefont}%
2419 {\poemsectiontitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}%
2420 {\poemsectiontitleindentamount}{\JHlabel{#2}}%
2421 \c@contentsinfo{#1}{\contentspoemsectiontitleindent}{\contentspoemtitlefont}%
2422 {\contentspoemsectiontitleindentamount}%
2423 \t@xtnotesinfo{#1}%
2424 \sources{\label{#2}}%
2425 }
2426 \newcommand{\JHpoemfirstsectiontitle}[2]{%
2427 \set@margin@emtitle{#1}{\par\nobreak}{\subsectiontitlefont}%
2428 {\poemsectiontitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}%
2429 {\poemsectiontitleindentamount}{\JHlabel{#2}}%
2430 \c@contentsinfo{#1}{\contentsi\poemsectiontitleindent}{\contentspoemtitlefont}%
2431 {\contents\poemsectiontitleindentamount}%
2432 \t@xtnotesinfo{#1}%
2433 \sources{\label{#2}}%
2434 }
2435 \newcommand{\JHsequencesectionssubtitle}[2]{%
2436 \set@margin@emsubtitle{#1}{\par\nobreak}{\subsectiontitlefont}%
2437 {\titleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}%
2438 {\titleindentamount}{\JHlabel{#2}}%
2439 \sources{\label{#2}}%
2440 }
2441 \newcommand{\JHpoemsubtitle}[2]{\JHsequencesectionssubtitle{#1}{#2}}
2442 }
2443 \newcommand{\JHdedication}[2]{\nopagebreak\afterpoemtitleskip\testforcenterepigraph%
2444 \begin{epigraphquote}%
2445 \emph{#1}\JHlabel{#2}\end{epigraphquote}%
2446 \sources{\label{#2}}\afterpoemtitleskip\nopagebreak}
2447 \newcommand{\JHepigraph}[2]{\nopagebreak\afterpoemtitleskip\testforcenterepigraph%
2448 \begin{epigraphquote}%
2449 \emph{#1}\JHlabel{#2}\end{epigraphquote}%
2450 \sources{\label{#2}}\afterpoemtitleskip\nopagebreak}

```

`\backmattersectiontitle` Macros to set the titles of back matter sections such as textual notes.

```
2451 \newcommand{\backmattersectiontitle}[1]{%
2452 \set@p@emtitle{#1}{\poemtitlepenalty}{\volumetitlefont}%
2453 {\relax}{\backmattersink}{\z@}%
2454 \c@contentsinfo{#1}{contentsindentone}{\contentspoemtitlefont}%
2455 {\contentsindenttwoamount}%
2456 \t@xtnotesinfo{#1}
2457 }
```

`\margreftextnote` Macros to set marginal page references showing where in the apparatus a comment upon the marked line is to be found. `\margrefspecial{}` is for occasions when you might need to set the label by hand. For instance, suppose you have several textnotes on a line, and the note you wish to draw attention to is on a different page from the other notes. `\margreftextnote` under those circumstances will point only to the first note. Use `\margrefspecial` to point to the other note, giving `\margrefspecial` a unique argument, and opening that note with a command using the same argument.

```
2458 \newcounter{margrefnumber}
2459 \setcounter{margrefnumber}{1}
2460 \newtoks{\margrefmarker}
2461 \margrefmarker={\dag}
2462 \newcommand{\setmargrefmarker}[1]{\margrefmarker={#1}}
2463 \providecommand{\settitlemargrefmarker}[1]{\titlemargrefmarker={#1}}
2464 \newtoks{\titlemargrefmarker}
2465 \titlemargrefmarker={\dag}
2466 \newcommand{\makemargreflabel}{\string\label\string{margref\themargrefnumber\string}}
2467 \newif{\ifmargrefstomargin}
2468 \margrefstomargintrue
2469 \newcommand{\setmargref}{\nolinebreak\begin{marginenvironment}%
2470 \nolinebreak%
2471 \ifJHmarkstoright%
2472 \JHrightmarginpar{\scriptsize {\the\margrefmarker}~p.~\pageref{margref\themargrefnumber}}}%
2473 \fi%
2474 \ifJHmarkstoleft%
2475 \JHleftmarginpar{\scriptsize {\the\margrefmarker}~p.~\pageref{margref\themargrefnumber}}}%
2476 \fi%
2477 \ifJHmarkstoouter%
2478 \JHoutermarginpar%
2479 \fi%
2480 \ifJHmarkstogutter%
2481 \JHguttermarginpar%
2482 \fi%
2483 \end{marginenvironment}%
2484 \nolinebreak%
2485 }
2486
2487 %\newcommand{\setmargref}
2488 %{\marginpar{\ifmargrefstomargin\hspace*{.5\leftmargin}\fi}
2489 %\scriptsize {\the\margrefmarker}~p.~\pageref{margref\themargrefnumber}}}
```

```

2490 %}
2491 % \newcommand{\setmargref}
2492 % {\marginpar{\scriptsize {\the\margrefmarker~p.~\pageref{margref\themargrefnumber}}}
2493 % }
2494 \newcommand{\margreftextnote}{%
2495 \iftextnoteson\addtocounter{margrefnumber}{1}%
2496 \immediate\write\textnotes{\makemargreflabel}%
2497 \setmargref\else\relax\fi%
2498 }
2499 \newcommand{\margrefexplanatory}{%
2500 \ifexplanon\addtocounter{margrefnumber}{1}%
2501 \immediate\write\explanations{\makemargreflabel}%
2502 \setmargref\else\relax\fi%
2503 }
2504 \newcommand{\margrefemendation}{%
2505 \ifemendationson\addtocounter{margrefnumber}{1}%
2506 \immediate\write\emendations{\makemargreflabel}%
2507 \setmargref\else\relax\fi%
2508 }
2509 \newcommand{\margrefspecial}[1]{%
2510 \marginpar{\scriptsize {\the\margrefmarker~p.~\pageref{#1}}}
2511 }

```

To change other title making commands to produce titles which add something while processing the title, you should: 1. add one to the number of arguments it uses 2. replace the use of `\set@p@emtitle` with `\set@margp@emtitle` 3. add `{#2}` or `\JHlabel{#2}` or whatever as the last (seventh) argument to `\set@margp@emtitle`. So, to change `\sequencetitle{}` to `\JHsequencetitle{}` start with:

```

\newcommand{\sequencetitle}[1]{
\set@p@emtitle{#1}{\sequencetitlepenalty}{\sequencetitlefont}
{\sequencetitleindent}{\nobreak\par\nobreak\aftersequencetitleskip\nobreak}{\z@}
\putpagenumberincontentsfalse
\c@ntentsinfo{#1}{\contentsindentone}{\contentssequencetitlefont}
{\contentsindenttwoamount}
\putpagenumberincontentstrue
\t@xtnotesinfo{#1}
}

```

and change it to

```

\catcode'\@=11
\newcommand{\JHsequencetitle}[2]{
\set@margp@emtitle{#1}{\sequencetitlepenalty}{\sequencetitlefont}
{\relax}{\nobreak\par\nobreak\aftersequencetitleskip\nobreak}{\z@}
{\JHlabel{#2}}\putpagenumberincontentsfalse
\c@ntentsinfo{#1}{\contentsindentone}{\contentssequencetitlefont}
{\contentsindenttwoamount}

```

```

\putpagenumberincontentstrue
\t@xtnotesinfo{#1}
}
\catcode'\@=12

```

22.16 Titles with footnotes

\footnotepoemtitle

```

2512 \newif\iftitlefootnotesatpoemend%
2513 \titlefootnotesatpoemendfalse%
2514 \newif\iftitlefootnotesplain%
2515 \titlefootnotesplaintrue%
2516 \newif\iftitlefootnoteslayered%
2517 \titlefootnoteslayeredfalse%
2518 %
2519 \newcommand{\maketitlefootnoteslayered}{%
2520 \DeclareNewFootnote[plain]{H}%
2521 \titlefootnoteslayeredtrue%
2522 \titlefootnotesplainfalse%
2523 \titlefootnotesatpoemendfalse%
2524 }
2525 %
2526 \newcommand{\maketitlefootnotesatpoemend}{
2527 \titlefootnoteslayeredfalse%
2528 \titlefootnotesplainfalse%
2529 \titlefootnotesatpoemendtrue%
2530 }
2531 %
2532 \newcommand{\maketitlefootnotesplain}{
2533 \titlefootnoteslayeredfalse%
2534 \titlefootnotesplaintrue%
2535 \titlefootnotesatpoemendfalse%
2536 }
2537 %
2538 \newcommand{\placetitlefootnote}[1]{\iftitlefootnoteslayered%
2539 \footnoteH{#1}%
2540 \fi%
2541 \iftitlefootnotesatpoemend%
2542 \footnotemark%
2543 \immediate\write\poemendnotes{\string\makeatletter}%
2544 \immediate\write\poemendnotes{\string\footnotemark\string[\the\c@footnote \string]}%
2545 \immediate\write\poemendnotes{\string\makeatother}%
2546 \literalpoemendnote{#1}%
2547 \fi%
2548 \iftitlefootnotesplain%
2549 \footnote{#1}%
2550 \fi%
2551 }

```

```

2552 %
2553 \newcommand{\footnotepoemtitle}[2]{%
2554 \set@p@emtitle{#1\placetitlefootnote{#2}}{\poemtitlepenalty}{\poemtitlefont}%
2555 {\poemtitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}{\z@}%
2556 \c@ntentsinfo{#1}{\contentspoemtitleindent}{\contentspoemtitlefont}%
2557 {\contentspoemtitleindentamount}%
2558 \t@xtnotesinfo{#1}%
2559 }
2560 %

```

\footnotepoemtitlefirstline

```

2561 \newcommand{\footnotepoemtitlefirstline}[2]{%
2562 \firstlinesettings%
2563 \set@p@emtitle{#1\placetitlefootnote{#2}}{\multilinetitlepenalty}{\poemtitlefont}%
2564 {\poemtitleindent}{\nobreak\par\nobreak}{\z@}%
2565 \c@ntentsinfo{#1}{\contentspoemtitleindent}{\contentspoemtitlefont}%
2566 {\contentspoemtitleindentamount}%
2567 \t@xtnotesinfo{#1}%
2568 \restoresinglelinesettings%
2569 }
2570 %
2571 \newcommand{\footnotepoemtitlemiddleline}[2]{%
2572 \middlelinesettings%
2573 \set@p@emtitle{#1\placetitlefootnote{#2}}{\par\nobreak}{\poemtitlefont}%
2574 {\poemtitlesecondlineindent}{\nobreak\par\nobreak}{\z@}%
2575 \c@ntentsinfo{#1}{\contentspoemtitlesecondlineindent}{\contentspoemtitlefont}%
2576 {\contentspoemtitlesecondlineindentamount}%
2577 \t@xtnotesinfo{#1}%
2578 \restoresinglelinesettings%
2579 }
2580 %
2581 \newcommand{\footnotepoemtitlelastline}[2]{%
2582 \lastlinesettings%
2583 \set@p@emtitle{#1\placetitlefootnote{#2}}{\par\nobreak}{\poemtitlefont}%
2584 {\poemtitlesecondlineindent}{\nobreak\par\afterpoemtitleskip\nobreak}{\z@}%
2585 \c@ntentsinfo{#1}{\contentspoemtitlesecondlineindent}{\contentspoemtitlefont}%
2586 {\contentspoemtitlesecondlineindentamount}%
2587 \t@xtnotesinfo{#1}%
2588 \restoresinglelinesettings%
2589 }

```

\footnotesplitpoemtitle

```

2590 \newcommand{\footnotesplitpoemtitle}[3]{%
2591 \set@p@emtitle{#1\placetitlefootnote{#2} #3}{\poemtitlepenalty}{\poemtitlefont}%
2592 {\poemtitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}{\z@}%
2593 \c@ntentsinfo{#1 #3}{\contentspoemtitleindent}{\contentspoemtitlefont}%
2594 {\contentspoemtitleindentamount}%
2595 \t@xtnotesinfo{#1 #3}%
2596 }

```

22.17 Epigraphs, headnotes, attributions, dedications

Notice that epigraphs to volumes are handled differently from epigraphs to poems. Notice also the “short” commands, which are placed on the page according to the same booleans that control how titles are placed.

```
\epigraph
\headnote 2597 \newif\ifcenterepigraphson
\attribution 2598 \centerepigraphsonfalse
\poemdedication 2599 \newlength{\centerepigraphindentation}
\volumededication 2600 \setlength{\centerepigraphindentation}{6em}
\volumeepigraph 2601 \newlength{\normalepigraphindentation}
\volumeattribution 2602 \setlength{\normalepigraphindentation}{1.5em}
2603 \newcommand{\centerepigraphquote}{%
2604 \setlength{\epigraphquoteleftmargin}{\centerepigraphindentation}
2605 \setlength{\epigraphquoterightmargin}{\centerepigraphindentation}
2606 }
2607 \newcommand{\normalepigraphquote}{%
2608 \setlength{\epigraphquoteleftmargin}{\normalepigraphindentation}
2609 \setlength{\epigraphquoterightmargin}{\normalepigraphindentation}
2610 }
2611 \newcommand{\testforcenterepigraph}{\ifcenterepigraphson%
2612 \centerepigraphquote
2613 \else
2614 \normalepigraphquote
2615 \fi}
2616 \newcommand{\epigraph}[1]{\nopagebreak\afterpoemtitleskip\testforcenterepigraph%
2617 \begin{epigraphquote}%
2618 \emph{#1}\end{epigraphquote}\afterpoemtitleskip\nopagebreak}
2619 \newcommand{\headnote}[1]{\epigraph{#1}}
2620 \newcommand{\attribution}[1]{\nopagebreak\afterpoemtitleskip\testforcenterepigraph%
2621 \begin{epigraphquote}%
2622 {\small\emph{#1}}\end{epigraphquote}\afterpoemtitleskip\nopagebreak}
2623 \newcommand{\poemdedication}[1]{\nopagebreak\afterpoemtitleskip\testforcenterepigraph%
2624 \begin{epigraphquote}%
2625 \emph{#1}\end{epigraphquote}\afterpoemtitleskip\nopagebreak}
2626 \providecommand{\dedication}[1]{\poemdedication{#1}}
2627 \newcommand{\volumededication}[1]{\par\bigskip\begin{volumetitlepagequote}
2628 \emph{#1}\end{volumetitlepagequote}}
2629 \newcommand{\volumeepigraph}[1]{\par\bigskip\begin{volumetitlepagequote}
2630 \emph{#1}\end{volumetitlepagequote}}
2631 \newcommand{\volumeattribution}[1]{\par\smallskip\begin{volumetitlepagequote}
2632 {\small \emph{#1}}\end{volumetitlepagequote}}
2633 \newenvironment{epigraphenvironment}{\nopagebreak\afterpoemtitleskip\testforcenterepigraph%
2634 \begin{epigraphquote}\em}{\end{epigraphquote}\afterpoemtitleskip\nopagebreak}
2635 \newcommand{\set@short@pigraph}[1]{\iftitlesatleftversemargin%
2636 {\begin{pmclverse}\addtolength{leftmargin}{-\leftmargini}{\nobreak \emph{#1} \afterpoemtitleskip}
2637 \else\iftitlesatleftversemargin
2638 {\nobreak}%
2639 \begin{titleentryenvironment}}%
```

```

2640 \ifnormaltitleindentation
2641 \hspace{\normalepigraphindentation}\emph{#1}%
2642 \else % for the \ifnormaltitleindentation
2643 \ifcenterepigraphson
2644 \begin{center} \emph{#1}\end{center}
2645 \else \emph{#1}\fi % for ifcenterepigraphson
2646 \fi %\ifnormaltitleindentation
2647 \end{titleentryenvironment}
2648 {\afterpoemtitleskip}%
2649 \fi}% for the \iftitlesatleftversemargin
2650 \newcommand{\shortpoemepigraph}[1]{\nopagebreak\afterpoemtitleskip%
2651 \set@short@pigraph{#1}
2652 }
2653 \newcommand{\shortpoemdedication}[1]{\nopagebreak\afterpoemtitleskip%
2654 \set@short@pigraph{#1}
2655 }
2656 \newcommand{\shortpoemattribution}[1]{\nopagebreak\afterpoemtitleskip%
2657 \set@short@pigraph{\small #1}}
2658 }
2659 \newcommand{\JHshortepigraph}[2]{\nopagebreak\afterpoemtitleskip%
2660 \set@short@pigraph{#1}\marginpar{\scriptsize\the\margrefmarker`p.\pageref{#2}}}}
2661 \sources{\label{#2}}
2662 }
2663 \newcommand{\JHshortdedication}[2]{\JHshortepigraph{#1}{#2}}
2664
2665
2666 \newlength{\dateindent}%
2667 \setlength{\dateindent}{\leftmargin}%
2668 \newcommand{\variabledateindent}{%
2669 \setlength{\dateindent}{\linewidth}%
2670 \addtolength{\dateindent}{-\versewidth}%
2671 \addtolength{\dateindent}{-.5\dateindent}}
2672 %\newcommand{\poemdate}[1]{\bigskip\begin{raggedleft}\hspace{\dateindent}#1\end{raggedleft}\big
2673 \newcommand{\poemdate}[1]{\iflastpoemcentered\variabledateindent%
2674 \else\setlength{\dateindent}{\leftmargin}%
2675 \fi%
2676 \bigskip\begin{raggedleft}\hspace{\dateindent}#1\end{raggedleft}\bigskip}%
2677 %
2678 \newlength{\poemattributionindent}%
2679 \setlength{\poemattributionindent}{\leftmargin}%
2680 \newcommand{\variablepoemattributionindent}{%
2681 \setlength{\poemattributionindent}{\linewidth}%
2682 \addtolength{\poemattributionindent}{-\versewidth}%
2683 \addtolength{\poemattributionindent}{-.5\poemattributionindent}}%
2684 \newcommand{\poemattribution}[1]{\iflastpoemcentered\variablepoemattributionindent%
2685 \else\setlength{\poemattributionindent}{\leftmargin}%
2686 \fi%
2687 \bigskip\begin{raggedleft}\hspace{\poemattributionindent}#1\end{raggedleft}\bigskip}%

```

22.18 Tools used for making note sections

The main tool is a dirty trick borrowed from John Lavagnino's package for endnotes, `endnotes`, which allows for writing out literal characters to an external file. The trick involves redefining the space character as the newline character and treating the text of the note as the body of a macro that `\meaning` specifies. The result is that the text is written to the external file in a long ribbon one word wide.

```
2688 \def\strip#1>{
2689 \newcommand{\literaltextnote}[1]{\iftextnotesatend
2690     \begingroup
2691     \def\next{#1}%
2692     \newlinechar='40
2693     \immediate\write\textnotes{\expandafter\strip\meaning\next}%
2694     \endgroup\fi
2695 }
2696 \newcommand{\literatemend}[1]{\ifemendationsatend
2697     \begingroup
2698     \def\next{#1}%
2699     \newlinechar='40
2700     \immediate\write\emendations{\expandafter\strip\meaning\next}%
2701     \endgroup\fi
2702 }
2703 \newcommand{\literateexplain}[1]{\ifexplanatend
2704     \begingroup
2705     \def\next{#1}%
2706     \newlinechar='40
2707     \immediate\write\explanations{\expandafter\strip\meaning\next}%
2708     \endgroup\fi
2709 }
2710 \newcommand{\literalcontents}[1]{\ifpoemcontentson
2711     \begingroup
2712     \def\next{#1}%
2713     \newlinechar='40
2714     \immediate\write\poemcontents{\expandafter\strip\meaning\next}%
2715     \endgroup\fi
2716 }
2717 \newcommand{\literaltextnoteshort}[1]{
2718 \iftextnotesatend
2719     \begingroup
2720     \def\next{#1}%
2721     \immediate\write\textnotes{\expandafter\strip\meaning\next}%
2722     \endgroup\fi}
2723 \newcommand{\literatemendshort}[1]{\ifemendationsatend
2724     \begingroup
2725     \def\next{#1}%
2726     \immediate\write\emendations{\expandafter\strip\meaning\next}%
2727     \endgroup\fi}
2728 \newcommand{\literateexplainshort}[1]{\ifexplanatend
```

```

2729     \begingroup
2730     \def\next{#1}%
2731     \immediate\write\explanations{\expandafter\strip\meaning\next}%
2732 \endgroup\fi}
2733 \newcommand{\literalcontentsshort}[1]{\ifpoemcontentson
2734     \begingroup
2735     \immediate\write\poemcontents{\expandafter\strip\meaning\next}%
2736 \endgroup\fi}
2737 \newcommand{\sameword}{$\sim$}
2738 \newcommand{\missingpunct}{${}_-\{\wedge\}$}

```

`\pmccheckifinteger` `\pmccheckifinteger{<num>}` checks if `<num>` is an integer. If it is, then `\ifinteger` is set TRUE, otherwise it is set FALSE. (Code taken from memoir class, and based on Donald Arseneau's `\Lpack{cite}` package).

```

2739 \newcommand{\pmccheckifinteger}[1]{%
2740 \protected@edef\@vsa{#1}%
2741 \ifcat _\ifnum9<1\pmcgobm{#1} _\else A\fi
2742 \integertrue%
2743 \else
2744 \integerfalse%
2745 \fi%
2746 }
2747 \newif\ifinteger
2748 % \begin{macro}{\pmcgobm}
2749 % |\pmcgobm{|\meta{num}|}| is defined as \meta{num}. It could be defined as: \
2750 % |\newcommand{\pmcgobm}[1]{\ifx-#1\expandafter\gobm\else#1\fi}| \
2751 % which would remove a leading minus sign (hyphen) from its argument
2752 % (|\gobm| = gobble minus sign).
2753 % (Code from memoir class and a posting to comp.text.tex by Donald Arseneau on 1997/07/21).
2754 % \begin{macrocode}
2755 \newcommand{\pmcgobm}[1]{#1}

```

22.19 Commands to make notes and send info to contents

`\setlemmarange` `\setlemmarange` calculates the range of line numbers for multi-line lemmas.

```

2756 % \newcommand{\setlemmarange}[1]{
2757 % \setcounter{lemmalines}{#1}
2758 % \ifthenelse{\equal{\value{lemmalines}}{0}}{\rangelemmafalse}{\rangelemmatrue}
2759 % \setcounter{lemmaend}{\theverselinenumber}
2760 % \addtocounter{lemmaend}{\thelemmalines}
2761 % }
2762 \newcommand{\setlemmarange}[1]{%
2763 \pmccheckifinteger{#1}%
2764 \ifinteger
2765 \setcounter{lemmalines}{#1}%
2766 \ifthenelse{\equal{\value{lemmalines}}{0}}{\rangelemmafalse}{\rangelemmatrue}%
2767 \setcounter{lemmaend}{\theverselinenumber}%
2768 \addtocounter{lemmaend}{\thelemmalines}%
2769 \else

```

```

2770 \setcounterfromref{lemmaend}{#1}\rangelemmatrue
2771 \fi
2772 \makeatother}

\citerange \citerange sets the range of line numbers for multi-line lemmas
2773 \newcommand{\citerange}{%
2774 \ifrangelemma
2775 \theverselinenumber --\thelemmaend
2776 \else
2777 \theverselinenumber
2778 \fi}

\resetlemmacounters \resetlemmacounters resets the counts for multiline lemmas.
2779 \newcommand{\resetlemmacounters}{\rangelemmafalse
2780 \setcounter{lemmalines}{0}%
2781 \setcounter{lemmaend}{0}%
2782 }

\checknoteheaders \checknoteheaders Checks and corrects the values in the running headers of
notes sections. The running headers are of the form “Notes to pages xx–yy.”
Every title and every note checks whether the values in the running header should
be changed. This command essentially gives a list of strings to be written on the
external file for the note section. When these strings are read back in when the
file is set, they make a little program that recalculates the values in the headers
during the processing of every note. Also typesets the line number or line number
range in notes sections.
2783 \newcommand{\checknoteheaders}{\string\setcounter\string{notepageholdernote\string}%
2784 \string{\thepage\string}\string\ifhmode\string\unskip\string\fi%
2785 \string\ifthenelse\string{\string\value\string{notepageholdernote\string}>%
2786 \string\value\string{notepageholdertitle\string}\string}%
2787 \string{\string\mark\string{\string\thenotepageholdernote\string}\string}%
2788 \string{\string\mark\string{\string\thenotepageholdertitle\string}\string}\string\unskip
2789 \string\unskip\string\relax\ \citerange :\string~\string\nolinebreak}%
2790

\textnote The basic \textnote{} command, on which everything else is based, has several
parts. First, it writes out a little program on the external endnotes file which,
when it is read back in when the endnotes are typeset, sets a variable with the
value of the page of the line the note is commenting upon and checks to see
whether that value is equal to or greater than that of previous notes on that page
of notes. Depending upon the outcome of that test, it sets the value of \mark
with the correct numbers to print the proper running header of the form “Textual
Notes to pp.xx–yy.” Second, it sends the line number of the line it is a comment
upon and the text of the note to the notes section. The optional first argument
is the number of lines covered by a multiline lemma. If there is no optional first
argument specified, the default is 0. The second argument is the text of the note,
which includes the rest of the lemma, other than the line number. It is up to you
to suitably abbreviate long lemmas.

```

```

2791 \newif\iftextnotessinglepar
2792 \newcommand{\textnote}[2][0]{%
2793 \iftextnoteson
2794   \setlemmarange{#1}%
2795 \immediate\write\textnotes{\checknoteheaders}%
2796   \literaltextnote{#2}%
2797   \iftextnotessinglepar%
2798   \literaltextnote{\par}%
2799   \fi%
2800   \fi
2801 \resetlemmacounters
2802 }

```

`\accidental` Accidentals: As it is, the command just tests to see whether accidentals are being included or not, and sets the accidental as a textnote if accidentals are being included. It would not be hard to divert accidentals to another external file in order to compile a separate list of accidentals. Accidentals, by their nature, cannot have multiline lemmas.

```

2803 \newcommand{\accidental}[1]{%
2804 \iftextnoteson%
2805 \ifincludeaccidentals%
2806   \iftextnotesatend\immediate\write\textnotes{\string\nobreak}\fi%
2807 \textnote{#1}%
2808 \iftextnotesatend\immediate\write\textnotes{\string\nobreak}\fi%
2809   \iftextnotessinglepar%
2810   \literaltextnote{\par}%
2811   \fi%
2812 \fi\fi
2813 }

```

`\tsvariant` Typescript variants. Treated like accidentals. If they are being collected, they are sent to the textual notes. Again, it would not be hard to collect them separately. Typescript variants can have multiline lemmas.

```

2814 \newcommand{\tsvariant}[2][0]{%
2815 \iftextnoteson
2816 \ifincludetypescripts%
2817 \iftextnotesatend\immediate\write\textnotes{\string\nobreak}\fi%
2818 \textnote[1]{#2}%
2819 \iftextnotesatend\immediate\write\textnotes{\string\nobreak}\fi%
2820 \fi\fi
2821 }
2822 \newcommand{\tsaccidental}[1]{\iftextnoteson\ifincludetypescripts\accidental{#1}\fi\fi}

```

`\tsentry` Typescript entries. Allows one to selectively include or exclude typescript entries from lists of variants. If an entry begins with a comma (as it commonly will, since it will typically be a member of a list of entries, you need not put `\unskip` before the comma, since `poemscol` will do it for you. Thanks to Donald Arseneau for suggesting how to do this.

```

2823 \newcommand{\tsentry}[1]{\iftextnoteson\ifincludetypescripts{\@ifnextchar,{\unskip}{%
2824 Ê\@ifnextchar;{\unskip}{}}%
2825 }#1}\fi\fi\unskip}

```

`\sources` `\sources{}` is essentially a `\textnote{}` with no line number and no page checking. Useful for typesetting the sources of the text (hence the name) and for sending literal characters to the endnotes file for other purposes.

```

2826 \newcommand{\sources}[1]{%
2827 \iftextnoteson
2828   \begingroup
2829     \newlinechar='40
2830     \def\next{#1}%
2831     \immediate\write\textnotes{\expandafter\strip\meaning\next}%
2832   \endgroup
2833   \iftextnotessinglepar%
2834   \literaltextnote{\par}%
2835   \fi%
2836 \fi
2837 }

```

22.20 Emendations and explanatory notes

The difference between these kinds of notes and ordinary `\textnotes{}` is that they must first test to see whether there have been any emendations or explanatory notes for the poem in question. If there have not been prior notes, then a new paragraph must be opened and the page number and title of the poem set in the note section.

`\titletoothernotes` `\titletoothernotes` sends the page and title information to the Emendations or Explanatory Notes sections. It is called only for the first emendation or explanatory note for a poem. It is designed so that if the user wishes to define another category of notes in which might not apply to all of the poems to be set — not all poems, for instance, have emendations — this command can be used for those notes as well.

```

2838 \newcommand{\titletoothernotes}{\string\par
2839 \ifputpagenumberinnotes%
2840 \string\argpageref\string{\@compoundlabelscratch\string}%
2841 \string\setcounterfrompageref\string{notepageholdertitle\string}%
2842 \string{\@compoundlabelscratch\string}%
2843 \fi%
2844 \string\textbf\string{\ the\fulltitleholder\string}}%

```

`\emendation`

```

2845 \newif\ifemendationssinglepar
2846 \newcommand{\emendation}[2][0]{
2847 \ifemendationson
2848   \setlemmarange{#1}%
2849   \ifredundantemendations

```

```

2850     \iftextnoteson
2851 \ifrangelemma
2852     \textnote[#1]{#2}%
2853 \else
2854     \textnote{#2}%
2855 \fi % ifrangelemma}
2856     \iftextnotessinglepar%
2857     \literaltextnote{\par}%
2858     \fi% iftextnotesinglepar
2859     \fi %iftextnoteson
2860 \fi % ifredundantemendations
2861 \ifnoemendyet % firstemendation
2862     \firstemendation
2863     \fi %noemendyet
2864     \global\noemendyetfalse
2865 \immediate\write\emendations{\checknoteheaders}%
2866     \literatemend{#2}%
2867     \ifemendationssinglepar%
2868     \literatemend{\par}%
2869     \fi% ifemendationssinglepar
2870 \fi % ifemendationson
2871 \resetlemmacounters
2872 }

```

This next is an internal command, called by `\emendation`. There's no need to use it explicitly.

```

2873 \newcommand{\firstemendation}{\ifemendationsatend
2874 \immediate\write\emendations{\titletoothernotes}\fi
2875 }

```

`\explanatory` Again, `\firstexplanatory` is internal, called by `\explanatory`.

```

2876 \newif\ifexplanationssinglepar
2877 \newcommand{\explanatory}[2][0]{%
2878 \ifexplanon
2879     \setlemmarange{#1}%
2880     \ifnoexplainyet % first explanation
2881     \firstexplanatory
2882     \fi %noexplainyet
2883     \global\noexplainyetfalse
2884 \immediate\write\explanations{\checknoteheaders}%
2885     \literateexplain{#2}%
2886     \ifexplanationssinglepar%
2887     \literateexplain{\par}%
2888     \fi%
2889     \fi % ifexplanon
2890 \resetlemmacounters
2891 }
2892
2893 \newcommand{\firstexplanatory}{\ifexplanatend
2894 \immediate\write\explanations{\titletoothernotes}\fi

```

2895 }
2896

22.21 Making new notes sections

`\definewnotetype` This monster macro has nine sections, and does all of the things required to set up a new end notes section. If you decide to mark a new kind of note in your text with, say `\mynote`, but decide at the last moment against including those notes in your edition, simply don't issue `\putmynotes` at the point it might have appeared, and neither the notes section nor the contents entry for it will be included.

```
2897 \makeatletter
2898 \long\def\appendtomacro#1#2{%
2899 \begingroup
2900   \toks@\expandafter{#1#2}%
2901   \xdef#1{\the\toks@}%
2902 \endgroup}
2903 \makeatother
2904 \newcommand{\definewnotetype}[5]{%
2905 % 1. make an if for this kind of note and set it to true by default;
2906 % make an if for the first instance of the command per poem and set it
2907 % to false; make an if for setting the notes in single note
2908 % paragraphs and set it to false; make an if for setting
2909 % these notes in two column mode and set it to false
2910 %
2911 % Thanks to Igor Pechtchanski and Ulrich Schwarz.
2912 \expandafter\newif\csname if#1son\endcsname
2913 \global\csname #1sontrue\endcsname
2914 \expandafter\newif\csname ifno#1yet\endcsname
2915 \csname no#1yettrue\endcsname
2916 \expandafter\newif\csname if#1ssinglepar\endcsname
2917 \csname #1singleparfalse\endcsname
2918 \expandafter\newif\csname if#1stwocol\endcsname
2919 \csname #1stwocolfalse\endcsname
2920 % 2. open a new output stream
2921 \expandafter\newwrite\csname #1s\endcsname
2922 % 3. open a file to associate with the stream
2923 \immediate\expandafter\openout\csname #1s\endcsname=\expandafter\jobname .#2
2924 % 4. set up a literalwrite command
2925 \expandafter\newcommand\csname literal#1\endcsname[1]{
2926 \begingroup
2927 \def\next{##1}%
2928 \newlinechar='40
2929 \immediate\write\expandafter\csname #1s\endcsname{\expandafter\strip\meaning\next}%
2930 \endgroup}
2931 % 5. send heading information to output file
2932 % first, use literaltext to send commands without parameters
2933 \csname literal#1\endcsname{\flushbottom{\par\clearpage
2934 {\pagestyle{volumetitlestyle}\cleardoublepage}
2935 \thispagestyle{volumetitlestyle}}
```

```

2936 \fancyhead{}
2937 \fancyfoot{}
2938 \fancyhead[RO,LE]{\small\textrm{\thepage}}
2939 % then immediate write to send the parameter for the marks in the
2940 % headers
2941 \immediate\write\csname #1s\endcsname{\string\fancyhead[CO]\string{\string\small
2942 \string{\string\em\ #3\string~\string\mymarks\string}\string}\string}}
2943 \immediate\write\csname #1s\endcsname{\string\fancyhead[CE]\string{\string\small
2944 \string{\string\em\ #3\string~\string\mymarks\string}\string}\string}}
2945 % then literal to finish the headers
2946 \csname literal#1\endcsname{\fancyfoot[C]{}}
2947 \mark{3}
2948 \backmattersink}
2949 % then immediate write to send the title of the section to print at
2950 % the top of the page
2951 \immediate\write\csname #1s\endcsname{
2952 \string\setendnotessectiontitle\string{\#4\string}\string{\#1notes\string}}
2953 % literal write to turn hyphenation on, set the font for the note
2954 % section, and turn on two column mode (if the boolean is set)
2955 \csname literal#1\endcsname{\lefthyphenmin=2\backmatterafterheadersink
2956 \tolerance=500\language=0
2957 \normalfont \backmattertextfont}
2958 \immediate\write\csname #1s\endcsname{\string\if#1stwocol}
2959 \csname
2960 literal#1\endcsname{\begin{multicols}{2}\fi\setlength{\parindent}{-10pt}}%
2961 % \csname literal#1\endcsname{\setlength{\parindent}{2}}% problem here
2962 % 6. set up a command to write the page and title of the poem for the first
2963 % instance of this kind of note in a poem
2964 \expandafter\newcommand\csname first#1\endcsname{%
2965 \immediate\write\expandafter\csname #1s\endcsname{\titletoothernotes}%
2966 \immediate\write\csname #1s\endcsname{\string\if#1ssinglepar}%
2967 \immediate\write\csname #1s\endcsname{\string\par}%
2968 \immediate\write\csname #1s\endcsname{\string\fi}%
2969 }
2970 % 7. set up a command to write a note, complete with line numbers
2971 \expandafter\newcommand\csname #1\endcsname[2][0]{%
2972 \setlemmarange{##1}%
2973 \csname ifno#1yet\endcsname%
2974 \csname first#1\endcsname%
2975 \fi%
2976 \global\csname no#1yetfalse\endcsname%
2977 \immediate\write\expandafter\csname
2978 #1s\endcsname{\string\nobreak\string\nobreak\checknoteheaders}%
2979 \csname literal#1\endcsname{##2}%
2980 \csname if#1ssinglepar\endcsname%
2981 \csname literal#1\endcsname{\par}%
2982 \fi%
2983 \resetlemmacounters%
2984 }
2985 % prose version

```

```

2986 \expandafter\newcommand\csname prose#1\endcsname [3] [0] {%
2987 \unskip\proselinelabel{##2}%
2988 \setproselemmarange{##2}{##1}%
2989 \csname ifno#1yet\endcsname%
2990 \csname first#1\endcsname%
2991 \fi%
2992 \global\csname no#1yetfalse\endcsname%
2993 \immediate\write\expandafter\csname #1s\endcsname{\checkprosenoteheaders}%
2994 \csname literal#1\endcsname{##3}%
2995 \csname if#1ssinglepar\endcsname%
2996 \csname literal#1\endcsname{\par}%
2997 \unskip%
2998 \fi%
2999 \resetlemmacounters\unskip%
3000 }
3001 % pm version
3002 \expandafter\newcommand\csname pm#1\endcsname [2] [0] {%
3003     \setpmllemmarange{##1}%
3004     \csname ifno#1yet\endcsname%
3005     \csname first#1\endcsname%
3006     \fi%
3007 \global\csname no#1yetfalse\endcsname%
3008 \immediate\write\expandafter\csname #1s\endcsname{\pmchecknoteheaders\string~}%
3009 \immediate\write\expandafter\csname #1s\endcsname{\pmciterange}%
3010 \csname literal#1\endcsname{##2}%
3011 \csname if#1ssinglepar\endcsname%
3012 \csname literal#1\endcsname{\par}%
3013 \fi%
3014 \pmresetlemmacounters\unskip%
3015 }
3016 % 8. modify the end of the poem environment to reset the first
3017 % command per poem boolean (so that the page and title will be set in
3018 % the notes section when the first note is called for a poem)
3019 % thanks to Heiko Oberdiek
3020 \makeatletter
3021 \appendtomacro{\endpoem}{\global\expandafter\csname no#1yettrue\endcsname}
3022 \makeatother
3023 \makeatletter
3024 \appendtomacro{\endprosesection}{\global\expandafter\csname no#1yettrue\endcsname}
3025 \makeatother
3026 \makeatletter
3027 \appendtomacro{\endpmsection}{\global\expandafter\csname no#1yettrue\endcsname}
3028 \makeatother
3029
3030 % 9. command for closing the output file
3031 % command for reading in and printing the output file
3032 \expandafter\newcommand\csname put#1s\endcsname{
3033 \newpage\hyphenationforsmall
3034 \csname if#1stwocol\endcsname%
3035 \csname literal#1\endcsname{\end{multicols}}%

```

```

3036 \fi %\iftwocol
3037 \immediate\expandafter\closeout\csname #1s\endcsname
3038 \expandafter\input \jobname.#2
3039 \ifpoemcontentson
3040 \contentsendnotestitle{#5}{#1notes}
3041 \fi
3042 }
3043 % 10. command for making a marginal mark at a line, giving the page
3044 % number in the apparatus where a note is to be found
3045 \expandafter\newcommand\csname margref#1\endcsname{%
3046 \addtocounter{margrefnumber}{1}
3047 \immediate\write\expandafter\csname #1s\endcsname{\makemargreflabel}%
3048 \setmargref
3049 }
3050 }

```

22.22 Prose sections

poemscol calls on lineno to do all the heavy lifting for making line numbers in prose sections and for making endnotes of various kinds for prose sections. First, set up a counter for the line number and for the modulo line number for prose sections, and set it to equal that used in verse sections. Then set the font for marginal line numbers to the size used in marginal line numbers in verse sections.

```

3051 \newcounter{proselinenum}
3052 \setcounter{proselinenum}{1}
3053 \newcounter{prosemodulo}
3054 \setcounter{prosemodulo}{\value{lineindexrepeat}}
3055 \addtocounter{prosemodulo}{1}
3056 \newcommand{\setprosemodulo}[1]{\modulolinenumbers[#1]}

```

Then commands for setting titles of prose sections. These are just versions of `\poemtitle`. Fancier versions will follow if there is need.

```

3057 \newcommand{\prosesectiontitle}[1]{\poemtitle{#1}}
3058 \newcommand{\prosesectiontitlenotitle}[1]{\poemtitlenotitle{#1}}

```

Next, environments for prose sections. The environment resets (or doesn't, in the second case) the marginal line number. The default modulo line number is that prevailing in verse sections, but you can change it at will.

```

3059 \setcounter{prosemodulo}{\value{lineindexrepeat}}%
3060 \addtocounter{prosemodulo}{1}%
3061 \ifx\modulolinenumbers\undefined%
3062 \relax\else
3063 \modulolinenumbers[\value{prosemodulo}]% if lineno is called
3064 \fi
3065 \newif\ifinprosesection
3066 \newenvironment{prosesection}
3067 {\inprosesectiontrue\resetlinenum\begin{linenumbers}}%
3068 \renewcommand{\linenumfont}{\scriptsize}%
3069 \ifnumbersright\rightlinenumbers*\setlength{\linenumbersep}{-\marginparsep}%

```

```

3070 %\else\ifnumbersswitch\switchlinenumbers\setlength{\linenumbersep}{\marginparsep}%
3071 \else\ifnumbersswitch\rightlinenumbers*\setlength{\linenumbersep}{-\marginparsep}%
3072 \else\leftlinenumbers*\setlength{\linenumbersep}{\marginparsep}%
3073 \addtolength{\linenumbersep}{5pt}% seems about right
3074 \fi\fi
3075 \noemendyettrue%
3076 \noexplainyettrue%
3077 }
3078 {\end{linenumbers}\inprosesectionfalse}
3079 \newenvironment{prosesectionnoreset}
3080 {\begin{linenumbers}%
3081 \renewcommand{\linenumberfont}{\scriptsize}
3082 \ifnumbersright\rightlinenumbers*\setlength{\linenumbersep}{-\marginparsep}%
3083 %\else\ifnumbersswitch\switchlinenumbers\setlength{\linenumbersep}{\marginparsep}%
3084 \else\ifnumbersswitch\rightlinenumbers*\setlength{\linenumbersep}{-\marginparsep}%
3085 \else\leftlinenumbers*\setlength{\linenumbersep}{\marginparsep}%
3086 \addtolength{\linenumbersep}{5pt}% seems about right
3087 \fi\fi
3088 % \noemendyettrue%
3089 % \noexplainyettrue%
3090 }\end{linenumbers}}

```

Set up commands for notes sections.

`\setproselemmastart` Finds the line number at the beginning of a lemma. Thanks to Robin Fairbairns and Heiko Oberdiek for `\ifrefundefined`. Fairbairns version

```

3091 % \newcommand*\ifrefundefined[1] {%
3092 % È È\expandafter\ifx\csname r@#1\endcsname\relax
3093 % }
3094 % Oberdiek version
3095 \makeatletter
3096 \newcommand*\ifrefundefined}[1]{%
3097 \expandafter\ifx\csname r@#1\endcsname\relax
3098 \expandafter\@firstoftwo
3099 \else
3100 \expandafter\@secondoftwo
3101 \fi
3102 }
3103 \newcommand*\@extract@ref}[2]{%
3104 \expandafter\expandafter\expandafter#1\csname
3105 r@#2\endcsname\}\}\@nil
3106 }
3107
3108 \newcommand*\@extractref}{%
3109 \@extract@ref\@car
3110 }
3111
3112 \newcommand*\@extractpageref}{%
3113 \@extract@ref\@secondcar
3114 }

```

```

3115
3116 \long\def\@secondcar#1#2#3\@nil{#2}
3117
3118 \newcommand*\setcounterfromref}[2]{%
3119   \ifrefundefined{#2}{%
3120     \protect\G@refundefinedtrue
3121     \@latex@warning{Reference ‘#2’ on page \thepage \space
3122       undefined}%
3123     \setcounter{#1}{0}%
3124   }{%
3125     \setcounter{#1}{\@extractref{#2}}%
3126   }%
3127 }
3128 \newcommand*\setcounterfrompageref}[2]{%
3129   \ifrefundefined{#2}{%
3130     \protect\G@refundefinedtrue
3131     \@latex@warning{Reference ‘#2’ on page \thepage \space
3132       undefined}%
3133     \setcounter{#1}{0}%
3134   }{%
3135     \setcounter{#1}{\@extractpageref{#2}}%
3136   }%
3137 }
3138 %
3139 \makeatother
3140 \newcommand\setproselemmastart}[1]{%
3141 \unskip
3142 \setcounterfromref{proselinenum}{#1}}

```

`\setproselemmarange` Finds the end of a multi-line lemma.

```

3143 % \newcommand\setproselemmarange}[2]{%
3144 % \setproselemmastart{#1}%
3145 % \setcounter{lemmalines}{#2}%
3146 % \ifthenelse{\equal{\value{lemmalines}}{0}}{\rangelemmafalse}{\rangelemmatrue}%
3147 % \setcounter{lemmaend}{\theproselinenum}%
3148 % \addtocounter{lemmaend}{\thelemmalines}\unskip%
3149 % }
3150 \newcommand\setproselemmarange}[2]{%
3151 \setproselemmastart{#1}%
3152 \pmccheckifinteger{#2}%
3153 \ifinteger
3154 \setcounter{lemmalines}{#2}%
3155 \ifthenelse{\equal{\value{lemmalines}}{0}}{\rangelemmafalse}{\rangelemmatrue}%
3156 \setcounter{lemmaend}{\theproselinenum}%
3157 \addtocounter{lemmaend}{\thelemmalines}\unskip%
3158 \else
3159 % \ref{#2}
3160 \setcounterfromref{lemmaend}{#2}\rangelemmatrue
3161 \fi\unskip
3162 }

```

`\proseciterange` Sets the range note for in a multi-line lemma.

```
3163 \newcommand{\proseciterange}{%
3164 \ifrangelemma%
3165 \theproselinenumber --\thelemmaend%
3166 \else%
3167 \theproselinenumber%
3168 \fi}
```

`\checkprosenoteheaders` Updates running header for note sections. Typesets line number in notes.

```
3169 \newcommand{\checkprosenoteheaders}{\string\setcounter\string{notepageholdernote\string}%
3170 \string{\thepage\string}\string\ifhmode\string\unskip\string\fi
3171 \string\ifthenelse\string{\string\value\string{notepageholdernote\string}>
3172 \string\value\string{notepageholdertitle\string}\string}%
3173 \string{\string\mark\string{\string\thenotepageholdernote\string}\string}%
3174 \string{\string\mark\string{\string\thenotepageholdertitle\string}\string}\string\unskip
3175 \string\unskip\string\relax\ \proseciterange : \string~\string\nolinebreak}%
```

`\prosetextnote`

```
3176 \newcommand{\proselinelabel}[1]{\ifhmode\unskip\fi\linelabel{#1}}
3177 \newcommand{\prosetextnote}[3][0]{%
3178 \iftextnoteson%
3179 \unskip\proselinelabel{#2}%
3180 \setproselemmarange{#2}{#1}%
3181 \immediate\write\textnotes{\checkprosenoteheaders}%
3182 \literaltextnote{#3}%
3183 \iftextnotessinglepar%
3184 \literaltextnote{\par}%
3185 \fi%
3186 \resetlemmacounters%
3187 \fi\unskip%
3188 }
```

`\proseemendation` Notice that it calls `\firstemendation` as usual.

```
3189 \newcommand{\proseemendation}[3][0]{%
3190 \ifemendationson%
3191 \unskip\proselinelabel{#2}%
3192 \setproselemmarange{#2}{#1}%
3193 \ifredundantemendations
3194 \iftextnoteson
3195 \ifrangelemma
3196 \prosetextnote[#1]{#2}{#3}%
3197 \else
3198 \prosetextnote{#2}{#3}%
3199 \fi % ifrangelemma}
3200 \fi % iftextnoteson
3201 \iftextnotessinglepar%
3202 \literaltextnote{\par}%
3203 \fi% iftextnotessinglepar
3204 \fi % ifredundantemendations
```

```

3205 \ifnoemendyet % firstemendation
3206 \firstemendation
3207 \fi%noemendyet
3208 \global\noemendyetfalse
3209 \immediate\write\emendations{\checkprosenoteheaders}%
3210 \literatemend{#3}%
3211 \ifemendationssinglepar%
3212 \literatemend{\par}%
3213 \fi% ifemendationssinglep
3214 \resetlemmacounters%
3215 \fi\unskip%
3216 }

```

\proseexplanatory

```

3217 \newcommand{\proseexplanatory}[3][0]{%
3218 \ifexplanon%
3219 \unskip\proselinelabel{#2}%
3220 \setproselemmarange{#2}{#1}%
3221 \ifnoexplainyet% firstexplanation
3222 \firstexplanatory%
3223 \fi%noexplainyet
3224 \global\noexplainyetfalse%
3225 \immediate\write\explanations{\checkprosenoteheaders}%
3226 \literateexplain{#3}%
3227 \ifexplanationssinglepar%
3228 \literateexplain{\par}%
3229 \fi% ifexplanationssinglepar
3230 \resetlemmacounters%
3231 \fi\unskip%
3232 }

```

\proseaccidental

```

3233 \newcommand{\proseaccidental}[2]{
3234 \iftextnoteson
3235 \ifincludeaccidentals
3236 \immediate\write\textnotes{\string\nobreak}%
3237 \prosetextnote{#1}{#2}%
3238 \immediate\write\textnotes{\string\nobreak}%
3239 \iftextnotessinglepar%
3240 \literaltextnote{\par}%
3241 \fi%
3242 \fi\fi
3243 }
3244 \newcommand{\prosetsvariant}[3][0]{\iftextnoteson
3245 \ifincludetypescripts
3246 \immediate\write
3247 \textnotes{\string\nobreak}%
3248 \prosetextnote[#1]{#2}{#3}%
3249 \immediate\write\textnotes{\string\nobreak}%
3250 \iftextnotessinglepar%

```

```

3251 \literaltextnote{\par}%
3252 \fi%
3253 \fi\fi
3254 }
3255 \newcommand{\prosetsaccidental}[2]{\iftextnoteson
3256 \ifincludetypescripts\proseaccidental{#1}{#2}\fi\fi}

```

22.23 Annotation by Sentence and Paragraph Number

Marking sentences. First, some \ifs, token lists, and counters.

```

3257 \newif{\ifprosebysentence}
3258 \newif{\ifrunningsentencenumbers}\runningsentencenumberstrue
3259 \newif{\ifmarginsentencenumbers}\marginsentencenumberstrue
3260 \newif{\ifsuppressfirstpara}\suppressfirstparafalse
3261 \newif{\ifsuppressfirstsentence}\suppressfirstsentencefalse
3262
3263 \newtoks{\pmnoteheader}
3264
3265 \newcounter{pmsentencenumber}\setcounter{pmsentencenumber}{0}
3266 \newcounter{pmmodulo}\setcounter{pmmodulo}{3}
3267 \newcounter{pmindexcount}\setcounter{pmindexcount}{0}

```

A starter. Mostly a placeholder. For changes to a whole section.

```

3268 \newcommand{\setprosebysentence}{\prosebysentencetrue%
3269 }
3270 \newenvironment{pmsection}{
3271 \noemendyettrue%
3272 \noexplainyettrue%
3273 }{}

```

Formatting for sentence numbers in the running text and in the margin.

```

3274 \newcommand{\runningsentencenumberformat}[1]{\nobreak%
3275 \ifsuppressfirstsentence%
3276 \ifthenelse{\thepmsentencenumber=1}{\relax}{%
3277 \unskip\textsuperscript{\scriptsize{#1}}}%
3278 \unskip\nobreak%
3279 \else%
3280 \textsuperscript{\scriptsize{#1}}%\fi
3281 \unskip\nobreak}
3282 \newcommand{\marginsentencenumberformat}[1]{\scriptsize{#1}}
3283 \newcommand{\setpmmodulo}[1]{\setcounter{pmmodulo}{#1}}%
3284 \addtocounter{pmmodulo}{-1}%
3285 }
3286 \newcommand{\pmnumberstoleft}{%\catcode'\@=11%
3287 \numbersswitchfalse\numbersrightfalse%
3288 \setlength{\marginparsep}{18pt}%
3289 }
3290 \newcommand{\pmnumberstoright}{%\catcode'\@=11%
3291 \numbersswitchfalse\numbersrighttrue%
3292 \setlength{\marginparsep}{-18pt}

```

```

3293 % \setlength{\marginparsep}{18pt}
3294 }
3295 \newcommand{\pmnumbersswitch}{\strictpagechecktrue\numbersswitchtrue\numbersrightfalse%
3296 \setlength{\marginparsep}{18pt}%
3297 }
3298 \newcommand{\pmnumbersgutter}{%\catcode'\@=11%
3299 \pmnumbersswitch%
3300 \pmclreversesideparfalse\numbersguttertrue%
3301 \setlength{\marginparsep}{18pt}%
3302 }
3303 \newcommand{\pmnumbersouter}{%\catcode'\@=11%
3304 \pmnumbersswitch%
3305 \pmclreversesidepartrue\numbersgutterfalse%
3306 \setlength{\marginparsep}{18pt}%
3307 }

```

Macros for actually writing the numbers in the margin.

```

3308 \newcommand{\putpmsentencenumber}{%
3309 \ifsuppressfirstsentence%
3310 \ifthenelse{\thepmsentencenumber=1}{\relax}{\putpmmarginnumber{\thepmsentencenumber}%
3311 {\marginnumberformat}}%
3312 \else%
3313 \putpmmarginnumber{\thepmsentencenumber}%
3314 {\marginnumberformat}}%
3315 \fi}
3316 \newcommand{\putpmmarginnumber}[2]{%
3317 \nolinebreak\begin{marginenvironment}%
3318 \nolinebreak%
3319 \ifnumbersswitch%\marginpar{\hfil #2{#1}}
3320 \pmclsidepar{\hfil #2{#1}}%
3321 \else%
3322 \ifnumbersright%\marginpar{\hfil #2{#1}}
3323 \pmclrightsidepar{\hfil #2{#1}}%
3324 \else% \marginpar{#2{#1}\hfil}
3325 \pmclleftsidepar
3326 {#2{#1}\hfil}%
3327 \fi%
3328 \fi%
3329 \nolinebreak%
3330 \end{marginenvironment}\nolinebreak%
3331 }

```

`\pmsentence` Put this before every sentence. (This is the opposite of the convention in verse sections, where `\verseline` is at the end of each line.

```

3332 \newcommand{\pmsentence}{%
3333 % increment sentence number at beginning of sentence
3334 \addtocounter{pmsentencenumber}{1}%
3335 \ifrunningsentencenumber% add running number
3336 \runningsentencenumberformat{\thepmsentencenumber}%
3337 \fi%

```

```

3338 \ifmarginsentencenumber% add marginal number
3339 \addtocounter{pindexcount}{1}%
3340 \leavevmode%
3341 \ifthenelse{\value{pindexcount}>\value{pmodulo}}%
3342 {\putpmsentencenumber\nobreak%
3343 \setcounter{pindexcount}{0}%
3344 }{\relax}%
3345 \fi%
3346 % create header for notes if any are to occur
3347 \ifmparas%
3348 \global\edef\noteheaderconcat{\themparagraph:\thepmsentencenumber}%
3349 \pmnoteheader=\expandafter{\noteheaderconcat}%
3350 \else%
3351 \global\edef\noteheaderconcat{\thepmsentencenumber}%
3352 \global\edef\noteheaderconcat{\thepmsentencenumber}
3353 \pmnoteheader=\expandafter{\noteheaderconcat}%
3354 \fi%
3355 }

```

`\pmsentencetwo` Kludge for the second sentence in a line.

```

3356 \newcommand{\pmsentencetwo}{%
3357 % increment sentence number at beginning of sentence
3358 \addtocounter{pmsentencenumber}{1}%
3359 \ifrunningsentencenumber% add running number
3360 \runningsentencenumberformat{\thepmsentencenumber}%
3361 \fi%
3362 \ifmarginsentencenumber% add marginal number
3363 \addtocounter{pindexcount}{1}%
3364 \leavevmode%
3365 \ifthenelse{\value{pindexcount}>\value{pmodulo}}%
3366 { \putpmsentencenumbertwo\nobreak%
3367 \setcounter{pindexcount}{0}%
3368 }{\relax}%
3369 % \ifnum\thepindexcount>\thepmodulo%
3370 % \putpmsentencenumbertwo\nobreak%
3371 % \setcounter{pindexcount}{0}%
3372 % \fi%
3373 \fi%
3374 % create header for notes if any are to occur
3375 \ifmparas%
3376 \global\edef\noteheaderconcat{\themparagraph:\thepmsentencenumber}%
3377 \pmnoteheader=\expandafter{\noteheaderconcat}%
3378 \else%
3379 \global\edef\noteheaderconcat{\thepmsentencenumber}%
3380 \pmnoteheader=\expandafter{\noteheaderconcat}%
3381 \fi%
3382 }
3383
3384 \newcommand{\putpmsentencenumbertwo}{%
3385 \putpmmarginnumber{\rlap{\phantom{1}},~\thepmsentencenumber}}%

```

```

3386 {\marginsentencenumberformat}}

\pmsentencethree Kludge for the third sentence in a line.
3387 \newcommand{\pmsentencethree}{%
3388 % increment sentence number at beginning of sentence
3389 \addtocounter{pmsentencenumber}{1}%
3390 \ifrunningsentencenumber% add running number
3391 \runningsentencenumberformat{\thepmsentencenumber}%
3392 \fi%
3393 \ifmarginsentencenumber% add marginal number
3394 \addtocounter{pindexcount}{1}%
3395 \leavevmode%
3396 \ifthenelse{\value{pindexcount}>\value{pmodulo}}%
3397 { \putpmsentencenumberthree\nobreak%
3398 \setcounter{pindexcount}{0}%
3399 }\relax}%
3400 % \ifnum\thepindexcount>\thepmodulo%
3401 % \putpmsentencenumberthree\nobreak%
3402 % \setcounter{pindexcount}{0}%
3403 % \fi%
3404 \fi%
3405 % create header for notes if any are to occur
3406 \ifpmparas%
3407 \global\edef\noteheaderconcat{\thepmparagraph:\thepmsentencenumber}%
3408 \pnoteheader=\expandafter{\noteheaderconcat}%
3409 \else%
3410 \global\edef\noteheaderconcat{\thepmsentencenumber}%
3411 \pnoteheader=\expandafter{\noteheaderconcat}%
3412 \fi%
3413 }
3414
3415 \newcommand{\putpmsentencenumberthree}{%
3416 \putpmmarginnumber{\rlap{\phantom{1,~2}},~\thepmsentencenumber}}%
3417 {\marginsentencenumberformat}}

\pmsentencefour
3418 \newcommand{\pmsentencefour}{%
3419 % increment sentence number at beginning of sentence
3420 \addtocounter{pmsentencenumber}{1}%
3421 \ifrunningsentencenumber% add running number
3422 \runningsentencenumberformat{\thepmsentencenumber}%
3423 \fi%
3424 \ifmarginsentencenumber% add marginal number
3425 \addtocounter{pindexcount}{1}%
3426 \leavevmode%
3427 \ifthenelse{\value{pindexcount}>\value{pmodulo}}%
3428 { \putpmsentencenumberfour\nobreak%
3429 \setcounter{pindexcount}{0}%
3430 }\relax}%
3431 \fi%

```

```

3432 % create header for notes if any are to occur
3433 \ifmparas%
3434 \global\edef\noteheaderconcat{\themparagraph:\thempmsentence}%
3435 \pmnoteheader=\expandafter\noteheaderconcat}%
3436 \else%
3437 \global\edef\noteheaderconcat{\thempmsentence}%
3438 \pmnoteheader=\expandafter\noteheaderconcat}%
3439 \fi%
3440 }
3441
3442 \newcommand\putpmsentencefour{%
3443 \putpmmarginnumber{\rlap{\phantom{1,~2,~3},~\thempmsentence}}%
3444 {\marginsentenceformat}}
3445

```

Macros for numbering paragraphs

```

3446 \newcounter{pmparagraph}
3447 \setcounter{pmparagraph}{0}
3448 \newif{\ifmparas}\mparasfalse
3449 \newif{\ifmparainmar}\mparainmartrue
3450 \newif{\ifmpararunning}\mpararunningfalse
3451 \newif{\ifpmsentencebypara}% reset sentence counter every paragraph
3452 \pmsentencebypartrue

```

Formatting marginal and running paragraph numbers, printing them.

```

3453 \newcommand\pmparmarformat[1]{\textbf{\small #1}}
3454 \newcommand\pmpararunningformat[1]{%
3455 \ifsuppressfirstpara%
3456 \ifthenelse{\themparagraph=1}{\relax}{\textbf{\small #1}~}%
3457 \else%
3458 \textbf{\small #1}~}%
3459 \fi}
3460 \newcommand\putpmmarparanumber{%
3461 \ifsuppressfirstpara%
3462 \ifthenelse{\themparagraph=1}{\relax}{\putpmmarginnumber{\llap{\themparagraph~}}%
3463 {\pmparmarformat}}}%
3464 \else%
3465 \putpmmarginnumber{\llap{\themparagraph~}}{\pmparmarformat}%
3466 \fi}
3467

```

`\mpara` Mark the beginning of each paragraph with `\mpara`

```

3468 \newcommand\mpara{\leavevmode%
3469 \mparastrue\addtocounter{pmparagraph}{1}%
3470 \ifmparainmar% put in marginal paragraph number
3471 \putpmmarparanumber
3472 \fi
3473 \ifmpararunning% put in running number
3474 \pmpararunningformat{\themparagraph}%
3475 \fi

```

```

3476 \ifpmsentencebypara% reset sentence counter
3477   \setcounter{pmsentencenumber}{0}%
3478   \setcounter{pmindecount}{0}%
3479 \fi}

```

`\sentencelabel` Makes a label either by sentence number or by paragraph and sentence number, for use by `\ref` and by the various notes commands.

```

3480 \makeatletter
3481 \def\sentencelabel#1{\@bsphack%
3482 \ifmparas%
3483 \protected@write\@auxout{}%
3484  {\string\newlabel{#1}{\thempmparagraph : \thepmsentencenumber}{\thepage}}}%
3485 \else%
3486 \protected@write\@auxout{}%
3487  {\string\newlabel{#1}{\thepmsentencenumber}{\thepage}}}%
3488 \fi%
3489 \@esphack%
3490 }
3491 \makeatother

```

Macros to set up endnote commands for paragraph and sentence annotation.

```

3492 \newtoks{\pmrangeend} % for notes that refer to ranges
3493 % setting the range for the lemma:
3494 \newcommand{\setpmlanmarange}[1]{%
3495 \pmccheckifinteger{#1}%
3496 \ifinteger%
3497 \setcounter{lemmalines}{#1}%
3498 \ifthenelse{\equal{\value{lemmalines}}{0}}{\rangelemmafalse}{\rangelemmatrue}%
3499 \setcounter{lemmaend}{\thepmsentencenumber}%
3500 \addtocounter{lemmaend}{\thelemmalines}%
3501 \pmrangeend={\thelemmaend}%
3502 \else%
3503 \pmrangeend={\ref{#1}}\rangelemmatrue%
3504 \fi%
3505 }
3506 % Setting the string to include ranges in notes:
3507 \newcommand{\pmciterange}{%
3508 \ifrangelemma{\the\pmnoteheader --\the\pmrangeend:}%
3509 \else%
3510 \the\pmnoteheader:%
3511 \fi}
3512 % For running headers
3513 \newcommand{\pmchecknoteheaders}{\string\setcounter\string{notepageholdernote\string}%
3514 \string{\thepage\string}\string\ifhmode\string\unskip\string\fi
3515 \string\ifthenelse\string{\string\value\string{notepageholdernote\string}>
3516 \string\value\string{notepageholdertitle\string}\string}%
3517 \string{\string\mark\string{\string\thenotepageholdernote\string}\string}%
3518 \string{\string\mark\string{\string\thenotepageholdertitle\string}\string}\string\unskip}
3519 % to reset lemma counters at end of note
3520 \newcommand{\pmresetlemmacounters}{\rangelemmafalse%

```

```

3521 \setcounter{lemmalines}{0}%
3522 \setcounter{lemmaend}{0}%
3523 \pmrangeend={\relax}%
3524 }

```

\pmtextnote

```

3525 \newcommand{\pmtextnote}[2][0]{%
3526 \iftextnoteson%
3527 \setpmmemmarange{#1}%
3528 \immediate\write\textnotes{\pmchecknoteheaders\string~}%
3529 \immediate\write\textnotes{\pmciterange}%
3530 \literaltextnote{#2}%
3531 \iftextnotessinglepar%
3532 \literaltextnote{\par}%
3533 \fi%
3534 \fi%
3535 \pmresetlemmacounters%
3536 \unskip}

```

\pmexplanatory

```

3537 \newcommand{\pmexplanatory}[2][0]{%
3538 \ifexplanon%
3539 \setpmmemmarange{#1}%
3540 \ifnoexplainyet % first explanation
3541 \firstexplanatory%
3542 \fi %noexplainyet
3543 \global\noexplainyetfalse%
3544 \immediate\write\explanations{\pmchecknoteheaders\string~}%
3545 \immediate\write\explanations{\pmciterange}%
3546 \literalexplain{#2}%
3547 \ifexplanationssinglepar%
3548 \literalexplain{\par}%
3549 \fi %ifexplanationssinglepar
3550 \fi % ifexplanon
3551 \pmresetlemmacounters%
3552 \unskip%
3553 }

```

\pmemendation

```

3554 \newcommand{\pmemendation}[2][0]{%
3555 \ifemendationson%
3556 \setpmmemmarange{#1}%
3557 \ifredundantemendations%
3558 \iftextnoteson%
3559 \ifrangelemma%
3560 \pmtextnote[#1]{#2}%
3561 \else%
3562 \pmtextnote{#2}%
3563 \fi % ifrangelemma}

```

```

3564     \fi %iftextnoteson
3565 \fi % ifredundantemendations
3566 \ifnoemendyet % firstemendation
3567 \firstemendation%
3568 \fi %noemendyet
3569 \global\noemendyetfalse%
3570 \immediate\write\emendations{\pmchecknoteheaders\string~}%
3571 \immediate\write\emendations{\pmciterange}%
3572 \literate\emend{#2}%
3573 \ifemendationssinglepar%
3574 \literate\emend{\par}%
3575 \fi% ifemendationssinglepar
3576 \fi % ifemendationson
3577 \pmresetlemmacounters%
3578 }

```

`\pmaccidental`

```

3579 \newcommand{\pmaccidental}[1]{%
3580 \iftextnoteson%
3581 \ifincludeaccidentals%
3582 \immediate\write\textnotes{\string\nobreak}%
3583 \pmtextnote{#1}%
3584 \immediate\write\textnotes{\string\nobreak}%
3585 \iftextnotessinglepar%
3586 \literaltextnote{\par}%
3587 \fi%
3588 \fi\fi%
3589 }

```

`\pmtsvariant`

```

3590 \newcommand{\pmtsvariant}[2][0]{\iftextnoteson%
3591 \ifincludetypescripts%
3592 \immediate\write\textnotes{\string\nobreak}%
3593 \pmtextnote[#1]{#2}%
3594 \immediate\write\textnotes{\string\nobreak}%
3595 \iftextnotessinglepar%
3596 \literaltextnote{\par}%
3597 \fi%
3598 \fi\fi%
3599 }
3600 \newcommand{\pmtsaccidental}[1]{\iftextnoteson\ifincludetypescripts\pmaccidental{#1}\fi\fi}

```

22.24 Using Footnotes

`\texnotesatfoot` has to redefine `\sources` and a few others as well.

`\texnotesatfoot`

```

3601 \newcommand{\texnotesatfoot}{% first redefine textnotes
3602 \global\texnotesontrue%

```

```

3603 \global\textnotesatendfalse%
3604 \ifsourcesfootnotespara%
3605 \DeclareNewFootnote[para]{A}%
3606 \else%
3607 \DeclareNewFootnote[plain]{A}%
3608 \fi%
3609 \iftextfootnotespara%
3610 \DeclareNewFootnote[para]{B}%
3611 \else%
3612 \DeclareNewFootnote[plain]{B}%
3613 \fi%
3614 \renewcommand{\textnote}[2][0]{\setlemmarange{##1}%
3615 \FootnotetextB{\relax}{\citerange:~##2}%
3616 \resetlemmacounters}%
3617 % then redefine sources
3618 \renewcommand{\sources}[1]{\FootnotetextA{\relax}{##1}}%
3619 % then prose textnote
3620 \renewcommand{\prosetextnote}[3][0]{%
3621 \unskip\proselinelabel{##2}%
3622 \setproselemmarange{##2}{##1}%
3623 \FootnotetextB{\relax}{\proseciterange:~##3}\resetlemmacounters}%
3624 % then pmtextnote
3625 \renewcommand{\pmtextnote}[2][0]{\setpmllemmarange{##1}%
3626 \FootnotetextB{\relax}{\pmciterange~##2}\pmresetlemmacounters}
3627 }

```

\emendationsatfoot

```

3628 \newcommand{\emendationsatfoot}{%
3629 \global\emendationsontrue%
3630 \global\emendationsatendfalse%
3631 \ifemendationfootnotespara%
3632 \DeclareNewFootnote[para]{C}%
3633 \else%
3634 \DeclareNewFootnote[plain]{C}%
3635 \fi%
3636 \renewcommand{\emendation}[2][0]{\setlemmarange{##1}%
3637 \FootnotetextC{\relax}{\citerange:~##2}%
3638 \resetlemmacounters}%
3639 \renewcommand{\proseemendation}[3][0]{\unskip\proselinelabel{##2}%
3640 \setproselemmarange{##2}{##1}%
3641 \FootnotetextC{\relax}{\proseciterange:~##3}\resetlemmacounters}%
3642 \renewcommand{\pmemendation}[2][0]{\setpmllemmarange{##1}%
3643 \FootnotetextC{\relax}{\pmciterange~##2}\pmresetlemmacounters}
3644 }

```

\explanationsatfoot

```

3645 \newcommand{\explanationsatfoot}{%
3646 \global\explanontrue%
3647 \global\explanatendfalse%
3648 \ifexplanfootnotespara%

```

```

3649 \DeclareNewFootnote [para] {D}%
3650 \else%
3651 \DeclareNewFootnote [plain] {D}%
3652 \fi%
3653 \renewcommand{\explanatory} [2] [0] {\setlemmarange{##1}%
3654 \FootnotetextD{\relax}{\citerange:~##2}%
3655 \resetlemmacounters}%
3656 \renewcommand{\proseexplanatory} [3] [0] {\unskip\proselinelabel{##2}%
3657 \setproselemmarange{##2}{##1}%
3658 \FootnotetextD{\relax}{\proseciterange:~##3}}
3659 \renewcommand{\pmexplanatory} [2] [0] {\setpmlemmarange{##1}%
3660 \FootnotetextD{\relax}{\pmciterange~##2}\pmresetlemmacounters}%
3661 }

```

`\bibleverse`

```

3662 \newcommand{\bibleverse}{\pmsentence}
3663 \newcommand{\biblechapter}{\pmpara}

```

22.25 Notes at the foot of individual poems

`\poemendnote`

```

3664 \newif\ifpoemendnoteson
3665 \poemendnotesontrue
3666 \newif\ifpoemendnotessinglepar
3667 \poemendnotessinglepartrue
3668 \newcommand{\makepoemendnotes}{
3669   \global\verselinenumberstrue
3670   \newwrite\poemendnotes
3671   \immediate\openout\poemendnotes=\jobname.pnd
3672   \literalpoemendnote{\bigskip}
3673 }
3674 \newcommand{\poemendnote} [2] [0] {%
3675 \ifpoemendnoteson
3676   \setlemmarange{##1}%
3677   \immediate\write\poemendnotes{\checknoteheaders}
3678   \literalpoemendnote{##2}%
3679   \ifpoemendnotessinglepar%
3680   \literalpoemendnote{\par}%
3681   \fi%
3682   \fi
3683 \resetlemmacounters
3684 }
3685 \newcommand{\literalpoemendnote} [1] {%
3686   \begingroup
3687     \def\next{##1}%
3688     \newlinechar='40
3689     \immediate\write\poemendnotes{\expandafter\strip\meaning\next}%
3690   \endgroup
3691 }

```

```

3692 \newcommand{\putpoemendnotes}{
3693 \ifpoemendnoteson
3694   \immediate\closeout\poemendnotes
3695   \input \jobname.pnd
3696 \else
3697 \relax
3698 \fi}
3699 % \begin{macro}{\poemendemendationnote}
3700 % \begin{macrocode}
3701 \newif\ifpoemendemendationnoteson
3702 \poemendemendationnotesontrue
3703 \newif\ifpoemendemendationnotessinglepar
3704 \poemendemendationnotessinglepartrue
3705 \newcommand{\makepoemendemendationnotes}{
3706   \global\verselinenumberstrue
3707   \newwrite\poemendemendationnotes
3708   \immediate\openout\poemendemendationnotes=\jobname.pmd
3709   \literalpoemendemendationnote{\bigskip}
3710 }
3711 \newcommand{\poemendemendationnote}[2][0]{%
3712 \ifpoemendemendationnoteson
3713   \setlemmarange{#1}%
3714   \immediate\write\poemendemendationnotes{\checknoteheaders}
3715   \literalpoemendemendationnote{#2}%
3716   \ifpoemendemendationnotessinglepar%
3717     \literalpoemendemendationnote{\par}%
3718   \fi%
3719   \fi
3720 \resetlemmacounters
3721 }
3722 \newcommand{\literalpoemendemendationnote}[1]{%
3723   \begingroup
3724     \def\next{#1}%
3725     \newlinechar='40
3726     \immediate\write\poemendemendationnotes{\expandafter\strip\meaning\next}%
3727   \endgroup
3728 }
3729 \newcommand{\putpoemendemendationnotes}{
3730 \ifpoemendemendationnoteson
3731   \immediate\closeout\poemendemendationnotes
3732   \input \jobname.pmd
3733 \else
3734 \relax
3735 \fi}

```

\poemendexplanatorynote

```

3736 \newif\ifpoemendexplanatorynoteson
3737 \poemendexplanatorynotesontrue
3738 \newif\ifpoemendexplanatorynotessinglepar
3739 \poemendexplanatorynotessinglepartrue

```

```

3740 \newcommand{\makepoemendexplanatorynotes}{
3741   \global\verselinenumberstrue
3742   \newwrite\poemendexplanatorynotes
3743   \immediate\openout\poemendexplanatorynotes=\jobname.pxd
3744   \literalpoemendexplanatorynote{\bigskip}
3745 }
3746 \newcommand{\poemendexplanatorynote}[2][0]{%
3747 \ifpoemendexplanatorynoteson
3748   \setlemmarange{#1}%
3749   \immediate\write\poemendexplanatorynotes{\checknoteheaders}
3750   \literalpoemendexplanatorynote{#2}%
3751   \ifpoemendexplanatorynotessinglepar%
3752   \literalpoemendexplanatorynote{\par}%
3753   \fi%
3754   \fi
3755 \resetlemmacounters
3756 }
3757 \newcommand{\literalpoemendexplanatorynote}[1]{%
3758   \begingroup
3759     \def\next{#1}%
3760     \newlinechar='40
3761     \immediate\write\poemendexplanatorynotes{\expandafter\strip\meaning\next}%
3762   \endgroup
3763 }
3764 \newcommand{\putpoemendexplanatorynotes}{
3765 \ifpoemendexplanatorynoteson
3766   \immediate\closeout\poemendexplanatorynotes
3767   \input \jobname.pxd
3768 \else
3769 \relax
3770 \fi}

```

\poemendtextnote

```

3771 \newif\ifpoemendtextnoteson
3772 \poemendtextnotesontrue
3773 \newif\ifpoemendtextnotessinglepar
3774 \poemendtextnotessinglepartrue
3775 \newcommand{\makepoemendtextnotes}{
3776   \global\verselinenumberstrue
3777   \newwrite\poemendtextnotes
3778   \immediate\openout\poemendtextnotes=\jobname.pmd
3779   \literalpoemendtextnote{\bigskip}
3780 }
3781 \newcommand{\poemendtextnote}[2][0]{%
3782 \ifpoemendtextnoteson
3783   \setlemmarange{#1}%
3784   \immediate\write\poemendtextnotes{\checknoteheaders}
3785   \literalpoemendtextnote{#2}%
3786   \ifpoemendtextnotessinglepar%
3787   \literalpoemendtextnote{\par}%

```

```

3788   \fi%
3789   \fi
3790 \resetlemmacounters
3791 }
3792 \newcommand{\literalpoemendtextnote}[1]{%
3793   \begingroup
3794     \def\next{#1}%
3795     \newlinechar='40
3796     \immediate\write\poemendtextnotes{\expandafter\strip\meaning\next}%
3797   \endgroup
3798 }
3799 \newcommand{\putpoemendtextnotes}{
3800 \ifpoemendtextnoteson
3801   \immediate\closeout\poemendtextnotes
3802   \input \jobname.pmd
3803 \else
3804 \relax
3805 \fi}

```

22.26 Embarrassing kludges

Because the dirty trick mentioned above writes out textnotes as a ribbon one word wide, quoted poetry in the notes sections will leave a blank line at the end, which will be interpreted as a paragraph break when the file is read back in by L^AT_EX. These kludges correct that problem.

```

3806 \newcommand{\quotedversecorrectiontextnote}[1][Opt]
3807 {\iftextnoteson%
3808 \immediate\write\textnotes{\string\noindent\string\kern-#1}%
3809 \fi}
3810 \newcommand{\quotedversecorrectionemendation}[1][Opt]
3811 {\ifemendationson%
3812 \immediate\write\emendations{\string\noindent\string\kern-#1}%
3813 \fi}
3814 \newcommand{\quotedversecorrectionexplanatory}[1][Opt]
3815 {\ifexplanon%
3816 \immediate\write\explanations{\string\noindent\string\kern-#1}%
3817 \fi}

```

22.27 Marking stanza breaks on page turns

Use the macro below to change the symbol used to mark cases in which there is or is not a stanza break at a page turn.

```

3818 \newcommand{\stanzaatbottom}[1]{\global\edef\stanzaatbottomvalue{#1}}
3819 \stanzaatbottom{*}
3820 \newcommand{\nostanzaatbottom}[1]{\global\edef\nostanzaatbottomvalue{#1}}
3821 \nostanzaatbottom{\relax}

```

22.28 Parallel Texts

First, three utility macros from the memoir class:

`\cleartorecto` A repeat of `\cleardoublepage`; clears to a recto (odd-numbered) page.

```
3822 \def\cleartorecto{\clearpage\if@twoside \ifodd\c@page\else
3823 \hbox{}\thispagestyle{empty}}%
3824 \newpage\if@twocolumn\hbox{}\newpage\fi\fi\fi}
```

`\cleartoverso` Clears to a verso (even-numbered) page.

```
3825 \def\cleartoverso{\clearpage\if@twoside
3826 \ifodd\c@page\hbox{}\thispagestyle{empty}}%
3827 \newpage\if@twocolumn\hbox{}\newpage\fi\fi\fi}
```

`\ifenv` Macro for testing whether one is in a particular environment.

```
3828 \makeatletter
3829 \def\ifenv#1{%
3830     \def\reserved@a{#1}%
3831     \ifx\reserved@a\@currentenv
3832         \expandafter\@firstoftwo
3833     \else
3834         \expandafter\@secondoftwo
3835     \fi
3836 }
3837 \makeatother
```

Macros for forcing the marginal line numbers to the left side or the right side. These marginal line numbers, unlike those made with `\marginpar`, do not float. This code is modeled after code from the memoir class, by Peter Wilson.

`\pmcleftsidepar` As in the memoir class, these sidepars do not float.

```
3838 \newdimen\pmclsavsk
3839 \newcount\pmclsavsf
3840 \def\pmclbsphack{%
3841     \relax
3842     \ifhmode
3843         \pmclsavsk\lastskip
3844         \pmclsavsf\spacefactor
3845     \fi}
3846 \def\pmclesphack{%
3847     \relax
3848     \ifhmode
3849         \spacefactor\pmclsavsf
3850         \ifdim\pmclsavsk>0pt
3851             \ignorespaces
3852         \fi
3853     \fi}
3854 % \newcommand{\pmcleftsidepar}[1]{%
3855 % \pmclbsphack\leavevmode\vadjust{%
3856 %     \rlap{\kern-\parindent%
```

```

3857 % \kern -\marginparsep \kern -\marginparwidth % at left
3858 % \vbox to Opt{%
3859 % \kern \pmclsideparvshift% % vertical shift to align top text lines
3860 % \begin{minipage}{\marginparwidth}%
3861 % #1%
3862 % \end{minipage}%
3863 % \vss}}\pmclesphack%
3864 % } % version 2.44
3865 \newcommand{\pmclleftsidepar}[1]{%
3866 \pmclbsphack\strut\vadjust{% changed
3867 \rlap{\kern-\parindent%
3868 \kern -\marginparsep \kern -\marginparwidth% at left
3869 % \vbox to Opt{%
3870 % \kern \pmclsideparvshift% % vertical shift to align top text lines
3871 % \begin{minipage}{\marginparwidth}%
3872 \setbox0=\vtop to Opt{% added
3873 \begin{minipage}[t]{\marginparwidth}% added
3874 #1%
3875 \end{minipage}%
3876 % \vss}}\pmclesphack%
3877 \vss}% changed
3878 \vtop to Opt{\kern\pmclsideparvshift % default should be Opt
3879 \kern-\dp\strutbox \kern-\ht0 \box0 \vss}}\pmclesphack}% changed
3880
3881 \newcommand{\pmclrightsidepar}[1]{%
3882 % \pmclbsphack\leavevmode\vadjust{%
3883 \pmclbsphack\strut\vadjust{%
3884 \rlap{\kern-\parindent%
3885 % \kern \textwidth \kern -\marginparsep % at right
3886 \kern\textwidth\kern\marginparsep% at right
3887 % \vbox to Opt{%
3888 % \kern \pmclsideparvshift% % vertical shift to align top text lines
3889 % \begin{minipage}{\marginparwidth}%
3890 \setbox0=\vtop to Opt{% added
3891 \begin{minipage}[t]{\marginparwidth}% added
3892 #1%
3893 \end{minipage}%
3894 % \vss}}\pmclesphack%
3895 \vss}% changed
3896 \vtop to Opt{\kern\pmclsideparvshift% default should be Opt
3897 \kern-\dp\strutbox \kern-\ht0 \box0 \vss}}\pmclesphack}% changed
3898

```

Booleans for parallel texts

```

3899 \newif\ifparalleltxts
3900 \paralleltextsfalse
3901 \newif\ifrecto
3902 \rectofalse
3903 \newif\ifverso
3904 \versofalse

```

Booleans are needed to describe situations in which poems and stanzas are left open at the page break. `\finishrectopage` and `\finishversopage` will close poems and stanzas (so as not to generate errors because of environments left open), although as far as the poem is concerned the stanza or poem may still be open. (I will say that the stanza or poem in such a case is “artificially closed.”) There are two of them for each case of artificial closure. The first boolean (for each stanza or poem artificially closed) must reflect whether the stanza or poem has been (artificially) closed, to reopen on the next page of the same kind (recto or verso). If a poem or stanza has been (artificially) closed, the `\mark` will not be changed (so that it will still reflect whether the reader should understand there to be a stanza break at the bottom of the page or not). The second boolean for each case of artificial closure reflects whether the `\mark` has been changed or not.

```

3905 \newif\ifrectopoempending
3906 \rectopoempendingfalse
3907 \newif\ifversopoempending
3908 \versopoempendingfalse
3909 \newif\ifrectostanzapending
3910 \rectostanzapendingfalse
3911 \newif\ifversostanzapending
3912 \versostanzapendingfalse
3913 \newif\ifrectostanzastillopen
3914 \rectostanzastillopenfalse
3915 \newif\ifversostanzastillopen
3916 \versostanzastillopenfalse
3917 \newif\ifrectopoemstillopen
3918 \rectopoemstillopenfalse
3919 \newif\ifversopoemstillopen
3920 \versopoemstillopenfalse
3921 % the same for prose sections
3922 \newif\ifrectoprosesectionpending
3923 \rectoprosesectionpendingfalse
3924 \newif\ifversoprosesectionpending
3925 \versoprosesectionpendingfalse
3926 \newif\ifrectoprosesectionstillopen
3927 \rectoprosesectionstillopenfalse
3928 \newif\ifversoprosesectionstillopen
3929 \versoprosesectionstillopenfalse
3930 % the same for quoted verse
3931 \newif\ifrectoquotedversepending
3932 \rectoquotedversependingfalse
3933 \newif\ifversoquotedversepending
3934 \versoquotedversependingfalse
3935 \newif\ifrectoquotedversestillopen
3936 \rectoquotedversestillopenfalse
3937 \newif\ifversoquotedversestillopen
3938 \versoquotedversestillopenfalse

```

A further set of booleans is required for emendations and explanatory notes. Again the idea is that if a poem is artificially closed, but has already had its first emenda-

tion or explanatory note written to the external notes files, `poemscol` will remember that the next emendation or explanatory note it sees is not the first one for that poem and thus won't set the heading information for that poem in the notes section all over again.

```
3939 \newif\ifrectoemendationspending
3940 \rectoemendationspendingfalse
3941 \newif\ifversoemendationspending
3942 \versoemendationspendingfalse
3943 \newif\ifrectoexplanationspending
3944 \rectoexplanationspendingfalse
3945 \newif\ifversoexplanationspending
3946 \versoexplanationspendingfalse
```

Counters for parallel texts: New counters are needed, not only for the recto and verso lines, but also for the scratch value which determines whether or not it is time to output a marginal line number. These are saved at the end of every page, and restored at the beginning of every page of the same kind.

```
3947 \newcounter{rectolinecounter}
3948 \setcounter{rectolinecounter}{1}
3949 \newcounter{rectoindexscratch}
3950 \setcounter{rectoindexscratch}{1}
3951 \newcounter{versolinecounter}
3952 \setcounter{versolinecounter}{1}
3953 \newcounter{versoindexscratch}
3954 \setcounter{versoindexscratch}{1}
```

`\startparalleltxts` Clears to a verso (even-numbered) page, fixes where to put line numbers, modifies poem and stanza environments, changes where marginal line numbers are set, sets the booleans.

```
3955 \newcommand{\startparalleltxts}{%
3956 \leavevmode
3957 \cleartoverso
3958 \paralleltxtstrue
3959 \renewenvironment{poem}{\raggedright
3960     \language=255%no hyphenation in verse
3961     \noemendyettrue
3962     \noexplainyettrue
3963     \setcounter{verselinenumber}{0}\setcounter{printlineindex}{0}
3964     \nobreak\begin{pmclverse}
3965     \inpoemtrue\nobreak\mark{\relax}}
3966     % must end poem if parallel text. Don't worry,
3967     % begin recto page and begin verso page will
3968     % reopen the poem and reset the line counter to the right value
3969     % if it was finish recto page or finish verso page
3970     % that closed the poem rather than your own declaration.
3971 {\ifversopoemstilopen
3972     \end{pmclverse}
3973 \inpoemfalse\mark{\relax}
3974 \else
```

```

3975     \ifrectopoemstilopen
3976 \end{pmclverse}
3977 \inpoemfalse\mark{\relax}
3978     \else
3979 \end{pmclverse}
3980     \inpoemfalse\mark{\relax}
3981     \goodbreak\afterpoemskip%\bigskip
3982 \fi\fi    }
3983 \renewenvironment{stanza}{\penalty-100\instanzatrue\mark{\nostanzaatbottomvalue\ }}
3984 % must end stanza if parallel text. Don't worry,
3985 % begin recto page and begin verso page will
3986 % reopen the stanza and reset the line counter to the right value
3987 % if it was finish recto page or finish verso page
3988 % that closed the stanza rather than your own declaration.
3989 {\ifversostanzastilopen
3990     \relax
3991     \else
3992     \ifrectostanzastilopen
3993     \relax
3994     \else
3995     \nobreak\mark{\stanzaatbottomvalue\ }\nobreak
3996 \ifspeciallinelock%
3997 \relax\else%
3998 \nolinebreak\incrementverselinenumber%
3999 \fi%
4000 \speciallinelockfalse%
4001 \nobreak
4002 \instanzafalse
4003
4004 \stanzaskip
4005 \fi\fi
4006 }
4007 \renewcommand{\putverselinenumber}{\nolinebreak\begin{marginenvironment}}%
4008 \nolinebreak
4009 % \marn{\hfil\textrm{\theverselinenumber}}
4010 % \marginpar{\hfil\textrm{\scriptsize\theverselinenumber}}
4011 \pmclleftsidepar{\textrm{\scriptsize\theverselinenumber}}%
4012 \nolinebreak
4013 \end{marginenvironment}}%
4014 \nolinebreak
4015 }
4016 }
4017 \newenvironment{parallelverse}{\startparalleltexts}
4018 {\finishparalleltexts}
4019 \newtoks{\versotitleholder}
4020 \newtoks{\rectotitleholder}
4021 \newcommand{\makeversotitleholder}[1]{%
4022 \versotitleholder=#1}%
4023 }
4024 \newcommand{\makerectotitleholder}[1]{%

```

```
4025 \rectotitleholder={#1}%
4026 }
```

\versopoemtitle

```
4027 \makeatletter
4028 \newcommand{\versopoemtitle}[1]{%
4029 \versoset@p@emtitle{#1}{\poemtitlepenalty}{\poemtitlefont}%
4030 {\poemtitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}{\z@}%
4031 \c@ntentsinfo{#1}{\contentsindentone}{\contentspoemtitlefont}%
4032 {\contentsindenttwoamount}%
4033 }
4034 \newcommand{\versoset@p@emtitle}[6]{\pmclversoresetsettitleinnotes%
4035 \setlength{\titleentryoverrun}{#6}%
4036 {#2}%
4037 {#3} \begin{titleentryenvironment}%
4038 {\ifcentertitleson\begin{center}#1\end{center}\else #4 #1\fi}%
4039 \end{titleentryenvironment}}%
4040 {#5}%
4041 \m@kep@emlabel
4042 \versom@ken@teholder{#1}%
4043 \setlength{\titleentryoverrun}{\z@}}
4044 \newcommand{\versom@ken@teholder}[1]{%
4045 \ifsinglelinetitle
4046 \versotitleholder={#1}%
4047 \global\edef\@compoundlabelscratch{poem\thepoemnumber}%
4048 \else\iftitlefirstline
4049     \versotitleholder={#1}%
4050     \global\edef\@compoundlabelscratch{poem\thepoemnumber}%
4051 \else\iftitlemiddleline
4052     \titlesofar=\versotitleholder
4053     \titleincrement={~#1}%
4054     \global\edef\titleconcat{\the\titlesofar \the\titleincrement}%
4055     \versotitleholder=\expandafter{\titleconcat}%
4056     \global\edef\@compoundlabelscratch{poem\thepoemnumber}%
4057 \else
4058     \titlesofar=\versotitleholder
4059     \titleincrement={~#1}%
4060     \global\edef\titleconcat{\the\titlesofar \the\titleincrement}%
4061     \versotitleholder=\expandafter{\titleconcat}%
4062     \global\edef\@compoundlabelscratch{poem\thepoemnumber}%
4063 \fi
4064 \fi
4065 \fi
4066 }
4067 \newcommand{\versotitletoothernotes}{\string\par
4068 \ifputpagenumberinnotes%
4069 \string\argpageref\string{\@compoundlabelscratch\string}%
4070 \string\setcounterfrompageref\string{notepageholdertitle\string}%
4071 \string{\@compoundlabelscratch\string}%
4072 \fi%
```

```

4073 \string\textbf\string{\ \the\versotitleholder\string}
4074 }%
4075 \newcommand{\versopoemtitlenocontents}[1]{%
4076 \versoset@p@emtitle{#1}{\poemtitlepenalty}{\poemtitlefont}%
4077 {\poemtitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}{\z@}%
4078 }
4079 \newcommand{\versotitleinnotescheck}{\ifparalleltexts\let\titlotoothernotes=\versotitletoother}
4080 \makeatother

```

\rectopoemtitle

```

4081 \makeatletter
4082 \newcommand{\rectopoemtitle}[1]{%
4083 \rectoset@p@emtitle{#1}{\poemtitlepenalty}{\poemtitlefont}%
4084 {\poemtitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}{\z@}%
4085 \contentsinfo{#1}{\contentsindentone}{\contentspoemtitlefont}%
4086 {\contentsindenttwoamount}%
4087 }
4088 \newcommand{\rectoset@p@emtitle}[6]{\pmclrectoresetsettitleinnotes
4089 \setlength{\titleentryoverrun}{#6}%
4090 {#2}%
4091 {#3 \begin{titleentryenvironment}}%
4092 {\ifcentertitleson\begin{center}#1\end{center}\else #4 #1\fi}%
4093 \end{titleentryenvironment}}%
4094 {#5}%
4095 \m@kep@emlabel
4096 \rectom@ken@teholder{#1}%
4097 \setlength{\titleentryoverrun}{\z@}}
4098 \newcommand{\rectom@ken@teholder}[1]{%
4099 \ifsinglelinetitle
4100 \rectotitleholder={#1}%
4101 \global\edef\@compoundlabelscratch{poem\thepoemnumber}%
4102 \else\iftitlefirstline
4103     \rectotitleholder={#1}%
4104     \global\edef\@compoundlabelscratch{poem\thepoemnumber}%
4105     \else\iftitlemiddleline
4106     \titlesofar=\rectotitleholder
4107     \titleincrement={~#1}%
4108     \global\edef\titleconcat{\the\titlesofar \the\titleincrement}%
4109     \rectotitleholder=\expandafter{\titleconcat}%
4110     \global\edef\@compoundlabelscratch{poem\thepoemnumber}%
4111 \else
4112     \titlesofar=\rectotitleholder
4113     \titleincrement={~#1}%
4114     \global\edef\titleconcat{\the\titlesofar \the\titleincrement}%
4115     \rectotitleholder=\expandafter{\titleconcat}%
4116     \global\edef\@compoundlabelscratch{poem\thepoemnumber}%
4117 \fi
4118 \fi
4119 \fi
4120 }

```

```

4121 \newcommand{\rectotitletoothernotes}{\string\par
4122 \ifputpagenumberinnotes%
4123 \string\argpageref\string{\@compoundlabelscratch\string}%
4124 \string\setcounterfrompageref\string{notepageholdertitle\string}%
4125 \string{\@compoundlabelscratch\string}%
4126 \fi%
4127 \string\textbf\string{\ \the\rectotitleholder\string}
4128 }%
4129 \newcommand{\rectopoemtitlenocontents}[1]{%
4130 \rectosetp@emtitle{#1}{\poemtitlepenalty}{\poemtitlefont}%
4131 {\poemtitleindent}{\nobreak\par\nobreak\afterpoemtitleskip\nobreak}{\z@}%
4132 %\c@ntentsinfo{#1}{\contentsindentone}{\contentspoemtitlefont}%
4133 %{\contentsindenttwoamount}%
4134 %\t@xtnotesinfo{#1}%
4135 }
4136 \newcommand{\rectotitleinnotescheck}{\ifparalleltxts\let\titletoothernotes=\rectotitletoother
4137 \makeatother

```

`\saveversoline` Macros for saving and restoring line numbers:

```

4138 \newcommand{\saveversoline}{\setcounter{versolinecounter}%
4139 {\value{verselinenumber}}%
4140 \setcounter{versoindexscratch}{\value{printlineindex}}}

```

`\restoreversoline`

```

4141 \newcommand{\restoreversoline}{\setcounter{verselinenumber}%
4142 {\value{versolinecounter}}%
4143 \setcounter{printlineindex}{\value{versoindexscratch}}}

```

`\saverectoline`

```

4144 \newcommand{\saverectoline}{\setcounter{rectolinecounter}%
4145 {\value{verselinenumber}}%
4146 \setcounter{rectoindexscratch}{\value{printlineindex}}}

```

`\restorerectoline`

```

4147 \newcommand{\restorerectoline}{\setcounter{verselinenumber}%
4148 {\value{rectolinecounter}}%
4149 \setcounter{printlineindex}{\value{rectoindexscratch}}}

```

Macros for line cross references:

You will probably want to use line cross references to show which lines on the recto page correspond to which lines on the verso page. When you do this, you will set, in the margin of a line on the recto page, the line number of the corresponding line on the verso side, in square brackets. You may mark that line number with a distinctive identifier. `\synchroflag` is a token register to hold that identifier, and `\setsynchroflag` is a command to put the identifier in the register. For instance, if you are setting the 1805 version of Wordsworth's *The Prelude* on the verso, and the 1850 version on the recto, you might wish to set the "synchroflag" to "1805" so that the line cross reference will look something like "[1805: 147]".

`\setsynchroflag`

```
4150 \newtoks{\synchroflag}
4151 \newcommand{\setsynchroflag}[1]{\synchroflag={#1}}
4152 \setsynchroflag{\relax}
```

Here are commands for defining and calling “synchrolabels”, line cross references that tie verso and recto pages:

`\synchrolabel`

```
4153 \newcommand{\synchrolabel}[1]{\poemlinelabel{#1}}
4154 \newcommand{\hfilll}{\hskip 0pt plus 1 filll}
4155 \newcommand{\synchroref}[1]{%
4156 \pmlrightrightsidepar{\textrm{\scriptsize[\the\synchroflag\ref{#1}]}}}%
4157 % \hfill\rlap{\textrm{\scriptsize[\the\synchroflag\ref{#1}]}}
4158 % \ifnum\theprintlineindex=\thelineindexrepeat
4159 % \hspace{-7pt}
4160 % \fi
4161 }
```

Finally, the `\startversopage`, `\finishversopage`, `\startrectopage` `\finishrectopage` and `\finishparalleltxts` macros:

`\startversopage`

```
4162 \newcommand{\startversopage}{
4163 \ifrectostanzastilopen
4164 \end{stanza}
4165 \rectostanzastilopenfalse
4166 \end{poem}
4167 \rectopoemstilopenfalse
4168 \fi
4169 \ifrectopoemstilopen % from previous page
4170 \end{poem}
4171 \rectopoemstilopenfalse
4172 \fi
4173 \ifversopoempending % from previous verso
4174 \begin{poem}
4175 \global\versopoempendingfalse
4176 \fi
4177 \ifversostanzapending % from previous verso
4178 \begin{stanza}
4179 \global\versostanzapendingfalse
4180 \fi
4181 \ifversoemendationspending
4182 \noemendyetfalse
4183 \global\versoemendationspendingfalse
4184 \fi
4185 \ifversoexplanationspending
4186 \noexplainyetfalse
4187 \global\versoexplanationspendingfalse
4188 \fi
```

```
4189 \rectofalse\versotrue\restoreversoline
4190 \let\titletoothernotes=\versotitletoothernotes}
```

`\finishversopage`

```
4191 \newcommand{\finishversopage}{
4192 \saveversoline\versofalse\
4193 \ifinpoem
4194 \global\versopoempendingtrue
4195 \versopoemstillopenttrue
4196 \fi
4197 \ifinstanza
4198 \global\versostanzapendingtrue
4199 \versostanzastillopenttrue
4200 \global\versopoempendingtrue
4201 \versopoemstillopenttrue
4202 \fi
4203 \ifnoemendyet
4204 \relax
4205 \else
4206 \global\versoemendationspendingtrue
4207 \noemendyetfalse
4208 \fi
4209 \ifnoexplainyet
4210 \relax
4211 \else
4212 \global\versoexplanationspendingtrue
4213 \noexplainyetfalse
4214 \fi
4215 % \clearpage % keep in comment until footnotes problems are worked out
4216 }
```

`\startrectopage`

```
4217 \newcommand{\startrectopage}{
4218 \ifversostanzastillopen
4219 \end{stanza}
4220 \versostanzastillopenfalse
4221 \end{poem}
4222 \versopoemstillopenfalse
4223 \fi
4224 \ifversopoemstillopen
4225 \end{poem}
4226 \versopoemstillopenfalse
4227 \fi
4228 \ifrectopoempending
4229 \begin{poem}
4230 \global\rectopoempendingfalse
4231 \fi
4232 \ifrectostanzapending
4233 \begin{stanza}
4234 \global\rectostanzapendingfalse
```

```

4235 \fi
4236 \ifrectoemendationspending
4237 \noemendyetfalse
4238 \global\rectoemendationspendingfalse
4239 \fi
4240 \ifrectoexplanationspending
4241 \noexplainyetfalse
4242 \global\rectoexplanationspendingfalse
4243 \fi
4244 \versofalse\rectotrue\restorerectoline
4245 \let\titletoothernotes=\rectotitletoothernotes}

```

\finishrectopage

```

4246 \newcommand{\finishrectopage}{\saverectoline\rectofalse
4247 \ifinpoem
4248 \global\rectopoempendingtrue
4249 \rectopoemstillopentrue
4250 \fi
4251 \ifinstanza
4252 \global\rectostanzapendingtrue
4253 \rectostanzastillopentrue
4254 \global\rectopoempendingtrue
4255 \rectopoemstillopentrue
4256 \fi
4257 \ifnoemendyet
4258 \relax
4259 \else
4260 \global\rectoemendationspendingtrue
4261 \noemendyetfalse
4262 \fi
4263 \ifnoexplainyet
4264 \relax
4265 \else
4266 \global\versoexplanationspendingtrue
4267 \noexplainyetfalse
4268 \fi
4269 % \clearpage % until footnote problem is solved
4270 }

```

\finishparalleltxts

```

4271 \newcommand{\finishparalleltxts}{
4272 \ifinstanza
4273 \end{stanza}
4274 \fi
4275 \ifinpoem
4276 \end{poem}
4277 \fi
4278 \ifinprosesection
4279 \end{prosesection}
4280 \fi

```

```

4281 \ifinquotedverse
4282 \end{quotedverse}
4283 \fi
4284 \rectofalse\versofalse\paralleltexfalse
4285 \makeatletter\pmclresettitleinnotes\makeatother
4286 }

```

`\makeversotextnotes` Next, the versotextnotes section:

```

4287 % tokens for changing the names of these notes
4288 \newtoks{\versotextnotesname}
4289 \versotextnotesname={TEXTUAL NOTES}
4290 \newcommand{\changeversotextnotesname}[1]{\versotextnotesname={#1}}
4291 \newtoks{\versotextnotesheadername}
4292 \versotextnotesheadername={Textual Notes to}
4293 \newcommand{\changeversotextnotesheader}[1]{\versotextnotesheadername={#1}}
4294 \newtoks{\versotextnotescontentsname}
4295 \versotextnotescontentsname={Textual Notes}
4296 \newcommand{\changeversotextnotescontentsname}[1]{%
4297 \versotextnotescontentsname={#1}}
4298 % two column notes
4299 \newif\ifversotextnotestwocol
4300 \versotextnotestwocolfalse
4301 % versotextnotes section setup
4302 \newcommand{\makeversotextnotes}{\global\textnotesontrue
4303 \newwrite\versotextnotes
4304 \global\verselinenumberstrue
4305 \immediate\openout\versotextnotes=\jobname.vtn
4306 \literalversotextnote{\flushbottom{\par\clearpage
4307 {\pagestyle{volumetitlestyle}\cleardoublepage}
4308 \thispagestyle{volumetitlestyle}}
4309 \fancyhead{}
4310 \fancyhead[RO,LE]{{\small\textrm{\thepage}}}}
4311 \fancyhead[CO]{{\small{\em \the\versotextnotesheadername~\mymarks}}}}
4312 \fancyhead[CE]{{\small{\em \the\versotextnotesheadername~\mymarks}}}}
4313 \fancyfoot{}
4314 \mark{3}
4315 \setendnotessectiontitle{\the\versotextnotesname}{versotextnotes}
4316 \tolerance=500\language=0
4317 \normalfont \backmattertextfont
4318 \ifversotextnotestwocol
4319 \begin{multicols}{2}
4320 \fi
4321 \setlength{\parindent}{-10pt}
4322 }
4323 }

```

`\versotextnote`

```

4324 \newif\ifversotextnotessinglepar
4325 \newif\ifnoversotextnoteyet
4326 \newcommand{\literalversotextnote}[1]{\begingroup

```

```

4327         \def\next{#1}%
4328         \newlinechar='40
4329         \immediate\write\versotextnotes{\expandafter\strip\meaning\next}%
4330     \endgroup
4331 }
4332 \newcommand{\firstversotextnote}{\immediate\write\versotextnotes{\versotitletoothernotes}
4333     \ifversotextnotessinglepar%
4334     \literalversotextnote{\par}%
4335     \fi% ifversotextnotessinglepa
4336 }
4337 \newcommand{\versotextnote}[2][0]{\versotitleinnotescheck
4338     \setlemmarange{#1}%
4339     \ifnoversotextnoteyet % firstversotextnote
4340     \firstversotextnote
4341     \fi %noversotextnoteyet
4342     \global\noversotextnoteyetfalse
4343 \immediate\write\versotextnotes{\checknoteheaders}%
4344     \literalversotextnote{#2}%
4345     \ifversotextnotessinglepar%
4346     \literalversotextnote{\par}%
4347     \fi% ifversotextnotessinglepar
4348 \resetlemmacounters
4349 }

```

`\makerectotextnotes` Next, the `rectotextnotes` section:

```

4350 % tokens for changing the names of these notes
4351 \newtoks{\rectotextnotesname}
4352 \rectotextnotesname={TEXTUAL NOTES}
4353 \newcommand{\changerectotextnotesname}[1]{\rectotextnotesname={#1}}
4354 \newtoks{\rectotextnotesheadername}
4355 \rectotextnotesheadername={Textual Notes to}
4356 \newcommand{\changerectotextnotesheader}[1]{\rectotextnotesheadername={#1}}
4357 \newtoks{\rectotextnotescontentsname}
4358 \rectotextnotescontentsname={Textual Notes}
4359 \newcommand{\changerectotextnotescontentsname}[1]{%
4360 \rectotextnotescontentsname={#1}}
4361 % two column notes
4362 \newif\ifrectotextnotestwocol
4363 \rectotextnotestwocolfalse
4364 % rectotextnotes section setup
4365 \newcommand{\makerectotextnotes}{\global\textnotesontrue
4366     \newwrite\rectotextnotes
4367     \global\verselinenumberstrue
4368     \immediate\openout\rectotextnotes=\jobname.rtn
4369     \literalrectotextnote{\flushbottom{\par\clearpage
4370         {\pagestyle{volumetitlestyle}\cleardoublepage}
4371     \thispagestyle{volumetitlestyle}}
4372     \fancyhead{}
4373     \fancyhead[RO,LE]{\small\textrm{\thepage}}
4374     \fancyhead[CO]{\small{\em \the\rectotextnotesheadername~\mymarks}}

```

```

4375 \fancyhead[CE]{{\small{\em \the\rectotextnotesheadername~\mymarks}}}
4376 \fancyfoot{}
4377 \mark{3}
4378 \setendnotessectiontitle{\the\rectotextnotesname}{rectotextnotes}
4379 \tolerance=500\language=0
4380 \normalfont \backmattertextfont
4381 \ifrectotextnotestwocol
4382 \begin{multicols}{2}
4383 \fi
4384 \setlength{\parindent}{-10pt}
4385 }
4386 }

```

\rectotextnote

```

4387 \newif\ifrectotextnotessinglepar
4388 \newif\ifnorectotextnoteyet
4389 \newcommand{\literalrectotextnote}[1]{\begingroup
4390     \def\next{#1}%
4391     \newlinechar='40
4392     \immediate\write\rectotextnotes{\expandafter\strip\meaning\next}%
4393     \endgroup
4394 }
4395 \newcommand{\firstrectotextnote}{\immediate\write\rectotextnotes{\rectotitletoothernotes}
4396     \ifrectotextnotessinglepar%
4397     \literalrectotextnote{\par}%
4398     \fi% ifrectotextnotessinglepar
4399 }
4400 \newcommand{\rectotextnote}[2][0]{\rectotitleinnotescheck
4401     \setlemmarrange{#1}%
4402     \ifnorectotextnoteyet % firstrectotextnote
4403     \firstrectotextnote
4404     \fi %norectotextnoteyet
4405     \global\norectotextnoteyetfalse
4406 \immediate\write\rectotextnotes{\checknoteheaders}%
4407     \literalrectotextnote{#2}%
4408     \ifrectotextnotessinglepar%
4409     \literalrectotextnote{\par}%
4410     \fi% ifrectotextnotessinglepar
4411 \resetlemmacounters
4412 }

```

\makeversoemendations Next, the versoemendations section:

```

4413 % tokens for changing the names of these notes
4414 \newtoks{\versoemendationsname}
4415 \versoemendationsname={EMENDATIONS}
4416 \newcommand{\changeversoemendationsname}[1]{\versoemendationsname={#1}}
4417 \newtoks{\versoemendationsheadername}
4418 \versoemendationsheadername={Emendations to}
4419 \newcommand{\changeversoemendationsheader}[1]{\versoemendationsheadername={#1}}
4420 \newtoks{\versoemendationscontentsname}

```

```

4421 \versoemendationscontentsname={Emendations}
4422 \newcommand{\changeversoemendationscontentsname}[1]{%
4423 \versoemendationscontentsname={#1}}
4424 % two column notes
4425 \newif\ifversoemendationstwocol
4426 \versoemendationstwocolfalse
4427 % versoemendations section setup
4428 \newcommand{\makeversoemendations}{\global\emendationsontrue
4429 \newwrite\versoemendations
4430 \global\verselinenumberstrue
4431 \immediate\openout\versoemendations=\jobname.vem
4432 \literalversoemendation{\flushbottom{\par\clearpage
4433 {\pagestyle{volumetitlestyle}\cleardoublepage}
4434 \thispagestyle{volumetitlestyle}}
4435 \fancyhead{}
4436 \fancyhead[RO,LE]{\small\textrm{\thepage}}}
4437 \fancyhead[CO]{\small{\em \the\versoemendationsheadername~\mymarks}}}
4438 \fancyhead[CE]{\small{\em \the\versoemendationsheadername~\mymarks}}}
4439 \fancyfoot{}
4440 \mark{3}
4441 \setendnotessectiontitle{\the\versoemendationsname}{versoemendations}
4442 \tolerance=500\language=0
4443 \normalfont \backmattertextfont
4444 \ifversoemendationstwocol
4445 \begin{multicols}{2}
4446 \fi
4447 \setlength{\parindent}{-10pt}
4448 }
4449 }

```

\versoemendation

```

4450 \newif\ifversoemendationssinglepar
4451 \newif\ifnoversoemendationyet
4452 \newcommand{\literalversoemendation}[1]{\begingroup
4453 \def\next{#1}%
4454 \newlinechar='40
4455 \immediate\write\versoemendations{\expandafter\strip\meaning\next}%
4456 \endgroup
4457 }
4458 \newcommand{\firstversoemendation}{\immediate\write\versoemendations{\versotitletoothernotes}
4459 \ifversoemendationssinglepar%
4460 \literalversoemendation{\par}%
4461 \fi% ifversoemendationssinglepar
4462 }
4463 \newcommand{\versoemendation}[2][0]{\versotitleinnotescheck%
4464 \setlemmarange{#1}%
4465 \ifnoversoemendationyet % firstversoemendation
4466 \firstversoemendation
4467 \fi %noversoemendationyet
4468 \global\noversoemendationyetfalse

```

```

4469 \immediate\write\versoemendations{\checknoteheaders}%
4470   \literalversoemendation{#2}%
4471   \ifversoemendationssinglepar%
4472   \literalversoemendation{\par}%
4473   \fi% ifversoemendationssinglepar
4474 \resetlemmacounters
4475 }

```

`\makerectoemendations` Next, the rectoemendations section:

```

4476 % tokens for changing the names of these notes
4477 \newtoks{\rectoemendationsname}
4478 \rectoemendationsname={EMENDATIONS}
4479 \newcommand{\changerectoemendationsname}[1]{\rectoemendationsname={#1}}
4480 \newtoks{\rectoemendationsheadername}
4481 \rectoemendationsheadername={Emendations to}
4482 \newcommand{\changerectoemendationsheader}[1]{\rectoemendationsheadername={#1}}
4483 \newtoks{\rectoemendationscontentsname}
4484 \rectoemendationscontentsname={Emendations}
4485 \newcommand{\changerectoemendationscontentsname}[1]{%
4486 \rectoemendationscontentsname={#1}}
4487 % two column notes
4488 \newif\ifrectoemendationstwocol
4489 \rectoemendationstwocolfalse
4490 % rectoemendations section setup
4491 \newcommand{\makerectoemendations}{\global\emendationsontrue
4492   \newwrite\rectoemendations
4493   \global\verselinenumberstrue
4494   \immediate\openout\rectoemendations=\jobname.rem
4495   \literalrectoemendation{\flushbottom{\par\clearpage
4496     {\pagestyle{volumetitlestyle}\cleardoublepage}
4497   \thispagestyle{volumetitlestyle}}}
4498 \fancyhead{}
4499 \fancyhead[RO,LE]{\small\textrm{\thepage}}
4500 \fancyhead[CO]{\small{\em \the\rectoemendationsheadername~\mymarks}}
4501 \fancyhead[CE]{\small{\em \the\rectoemendationsheadername~\mymarks}}
4502 \fancyfoot{}
4503 \mark{3}
4504 \setendnotessectiontitle{\the\rectoemendationsname}{rectoemendations}
4505 \tolerance=500\language=0
4506 \normalfont \backmattertextfont
4507 \ifrectoemendationstwocol
4508 \begin{multicols}{2}
4509 \fi
4510 \setlength{\parindent}{-10pt}
4511 }
4512 }

```

`\rectoemendation`

```

4513 \newif\ifrectoemendationssinglepar
4514 \newif\ifnorectoemendationyet

```

```

4515 \newcommand{\literalrectoemendation}[1]{\begingroup
4516     \def\next{#1}%
4517     \newlinechar='40
4518     \immediate\write\rectoemendations{\expandafter\strip\meaning\next}%
4519     \endgroup
4520 }
4521 \newcommand{\firstrectoemendation}{\immediate\write\rectoemendations{\rectotitletoothernotes}
4522     \ifrectoemendationssinglepar%
4523     \literalrectoemendation{\par}%
4524     \fi% ifrectoemendationssinglepar
4525 }
4526 \newcommand{\rectoemendation}[2][0]{\rectotitleinnotescheck
4527     \setlemmarange{#1}%
4528     \ifnorectoemendationyet % firstrectoemendation
4529     \firstrectoemendation
4530     \fi %norectoemendationyet
4531     \global\norectoemendationyetfalse
4532 \immediate\write\rectoemendations{\checknoteheaders}%
4533     \literalrectoemendation{#2}%
4534     \ifrectoemendationssinglepar%
4535     \literalrectoemendation{\par}%
4536     \fi% ifrectoemendationssinglepar
4537 \resetlemmacounters
4538 }

```

`\makeversoexplanatorynotes` And the verso explanatory notes:

```

4539 % Tokens to change names of these notes
4540 \newtoks{\versoexplanationsname}
4541 \versoexplanationsname={EXPLANATORY NOTES}
4542 \newcommand{\changeversoexplanationsname}[1]{\versoexplanationsname={#1}}
4543 \newtoks{\versoexplanationsheadername}
4544 \versoexplanationsheadername={Explanatory Notes to}
4545 \newcommand{\changeversoexplanationsheader}[1]{\versoexplanationsheadername={#1}}
4546 \newtoks{\versoexplanationscontentsname}
4547 \versoexplanationscontentsname={Explanatory Notes}
4548 \newcommand{\changeversoexplanationscontentsname}[1]{%
4549 \versoexplanationscontentsname={#1}}
4550 % Two column notes
4551 \newif\ifversoexplanationstwocol
4552 \versoexplanationstwocolfalse
4553 % versoexplanatory notes setup
4554 \newcommand{\makeversoexplanatorynotes}{\global\explanontrue
4555     \global\verselinenumberstrue
4556     \newwrite\versoexplanations
4557     \immediate\openout\versoexplanations=\jobname.vex
4558     \literalversoexplain{\flushbottom{\par\clearpage
4559 {\pagestyle{volumetitlestyle}\cleardoublepage}
4560 \thispagestyle{volumetitlestyle}}
4561 \fancyhead[RO,LE]{\small\textrm{\thepage}}}
4562 \fancyhead[CO]{\small\em \the\versoexplanationsheadername~\mymarks}}

```

```

4563 \fancyhead[CE]{{\small{\em \the\versoexplanationsheadername~\mymarks}}}
4564 \fancyfoot{}
4565 \mark{3}
4566 \setendnotessectiontitle{\the\versoexplanationsname}{versoexplanatorynotes}
4567 \tolerance=500\language=0
4568 \normalfont \backmattertextfont
4569 \ifversoexplanationstwocol
4570 \begin{multicols}{2}
4571 \fi
4572 \setlength{\parindent}{-10pt}
4573 }
4574 }
4575 % \begin{macro}{\versoexplanatory}
4576 % Again, |\firstversoexplanatory| is internal, called by |\versoexplanatory|.
4577 % \begin{macrocode}
4578 \newcommand{\literalversoexplain}[1]{
4579 \begin{group}
4580 \def\next{#1}%
4581 \newlinechar='40
4582 \immediate\write\versoexplanations{\expandafter\strip\meaning\next}%
4583 \end{group}
4584 }
4585 \newif\ifversoexplanationssinglepar
4586 \newcommand{\firstversoexplanatory}{\immediate\write\versoexplanations{\versotitletoothernotes}}
4587 \ifversoexplanationssinglepar%
4588 \literalversoexplain{\par}%
4589 \fi}
4590 \newif\ifnoversoexplainyet
4591 \newcommand{\versoexplanatory}[2][0]{\versotitleinnotescheck%
4592 \ifexplanon
4593 \setlemmarange{#1}%
4594 \ifnoversoexplainyet % first versoexplanation
4595 \firstversoexplanatory
4596 \fi %noversoexplainyet
4597 \global\noversoexplainyetfalse
4598 \immediate\write\versoexplanations{\checknoteheaders}%
4599 \literalversoexplain{#2}%
4600 \ifversoexplanationssinglepar%
4601 \literalversoexplain{\par}%
4602 \fi%
4603 \fi % ifexplanon
4604 \resetlemmacounters
4605 }

```

`\makerectoexplanatorynotes` And the recto explanatory notes:

```

4606 % Tokens to change names of these notes
4607 \newtoks{\rectoexplanationsname}
4608 \rectoexplanationsname={EXPLANATORY NOTES}
4609 \newcommand{\changerectoexplanationsname}[1]{\rectoexplanationsname={#1}}
4610 \newtoks{\rectoexplanationsheadername}

```

```

4611 \rectoexplanationsheadername={Explanatory Notes to}
4612 \newcommand{\changerectoexplanationsheader}[1]{\rectoexplanationsheadername={#1}}
4613 \newtoks{\rectoexplanationscontentsname}
4614 \rectoexplanationscontentsname={Explanatory Notes}
4615 \newcommand{\changerectoexplanationscontentsname}[1]{%
4616 \rectoexplanationscontentsname={#1}}
4617 % Two column notes
4618 \newif\ifrectoexplanationstwocol
4619 \rectoexplanationstwocolfalse
4620 % rectoexplanatory notes setup
4621 \newcommand{\makerectoexplanatorynotes}{\global\explanontrue
4622     \global\verselinenumberstrue
4623     \newwrite\rectoexplanations
4624     \immediate\openout\rectoexplanations=\jobname.rex
4625     \literalrectoexplain{\flushbottom{\par\clearpage
4626     {\pagestyle{volumetitlestyle}\cleardoublepage}
4627     \thispagestyle{volumetitlestyle}}
4628     \fancyhead[RO,LE]{\small\textrm{\thepage}}}
4629     \fancyhead[CO]{\small{\em \the\rectoexplanationsheadername~\mymarks}}}
4630     \fancyhead[CE]{\small{\em \the\rectoexplanationsheadername~\mymarks}}}
4631     \fancyfoot{}
4632     \mark{3}
4633     \setendnotessectiontitle{\the\rectoexplanationsname}{rectoexplanatorynotes}
4634     \tolerance=500\language=0
4635     \normalfont \backmattertextfont
4636     \ifrectoexplanationstwocol
4637     \begin{multicols}{2}
4638     \fi
4639     \setlength{\parindent}{-10pt}
4640     }
4641     }
4642     % \begin{macro}{\rectoexplanatory}
4643     % Again, |\firstrectoexplanatory| is internal, called by |\rectoexplanatory|.
4644     % \begin{macrocode}
4645     \newcommand{\literalrectoexplain}[1]{
4646         \begingroup
4647             \def\next{#1}%
4648             \newlinechar='40
4649             \immediate\write\rectoexplanations{\expandafter\strip\meaning\next}%
4650         \endgroup
4651     }
4652     \newif\ifrectoexplanationssinglepar
4653     \newcommand{\firstrectoexplanatory}{\immediate\write\rectoexplanations{\rectotitletoothernotes}
4654     \ifrectoexplanationssinglepar%
4655     \literalrectoexplain{\par}%
4656     \fi%
4657     }
4658     \newif\ifnorectoexplainyet
4659     \newcommand{\rectoexplanatory}[2][0]{\rectotitleinnotescheck%
4660     \ifexplanon

```

```

4661 \setlemmarange{#1}%
4662 \ifnoretectoexplainyet % first rectoexplanation
4663 \firstrectoexplanatory
4664 \fi %noretectoexplainyet
4665 \global\noretectoexplainyetfalse
4666 \immediate\write\rectoexplanations{\checknoteheaders}%
4667 \literalrectoexplain{#2}%
4668 \ifrectoexplanationssinglepar%
4669 \literalrectoexplain{\par}%
4670 \fi%
4671 \fi % ifexplanon
4672 \resetlemmacounters
4673 }

```

`\versoprosetextnote`

```

4674 \newcommand{\versoprosetextnote}[3][0]{%
4675 \iftextnoteson%
4676 \versotitleinnotescheck
4677 \unskip\proselinelabel{#2}%
4678 \setproselemmarange{#2}{#1}%
4679 \ifnoversotextnoteyet % firstversotextnote
4680 \firstversotextnote
4681 \fi %noversotextnoteyet
4682 \global\noversotextnoteyetfalse
4683 \immediate\write\versotextnotes{\checkprosenoteheaders}%
4684 \literalversotextnote{#3}%
4685 \ifversotextnotessinglepar%
4686 \literalversotextnote{\par}%
4687 \fi%
4688 \resetlemmacounters%
4689 \fi\unskip%
4690 }

```

`\versoproseemendation` Notice that it calls `\firstemendation` as usual.

```

4691 \newcommand{\versoproseemendation}[3][0]{%
4692 \ifemendationson%
4693 \versotitleinnotescheck
4694 \unskip\proselinelabel{#2}%
4695 \setproselemmarange{#2}{#1}%
4696 \ifredundantemendations
4697 \iftextnoteson
4698 \ifrangelemma
4699 \versoprosetextnote[#1]{#2}{#3}%
4700 \else
4701 \versoprosetextnote{#2}{#3}%
4702 \fi % ifrangelemma}
4703 \fi %iftextnoteson
4704 \ifversotextnotessinglepar%
4705 \literalversotextnote{\par}%
4706 \fi% iftextnotessinglepar

```

```

4707 \fi % ifredundantemendations
4708 \ifnoversoemendationyet % firstemendation
4709 \firstversoemendation
4710 \fi%noemendyet
4711 \global\noversoemendationyetfalse
4712 \immediate\write\versoemendations{\checkprosenoteheaders}%
4713 \literalversoemendation{#3}%
4714 \ifversoemendationssinglepar%
4715 \literalversoemendation{\par}%
4716 \fi% ifemendationssinglep
4717 \resetlemmacounters%
4718 \fi\unskip%
4719 }

```

\versoproseeexplanatory

```

4720 \newcommand{\versoproseeexplanatory}[3][0]{%
4721 \ifexplanon%
4722 \versotitleinnotescheck
4723 \unskip\proselinelabel{#2}%
4724 \setproselemmarange{#2}{#1}%
4725 \ifnoversoexplainyet% firstexplanation
4726 \firstversoexplanatory%
4727 \fi%noexplainyet
4728 \global\noversoexplainyetfalse%
4729 \immediate\write\versoexplanations{\checkprosenoteheaders}%
4730 \literalversoexplain{#3}%
4731 \ifversoexplanationssinglepar%
4732 \literalversoexplain{\par}%
4733 \fi% ifexplanationssinglepar
4734 \resetlemmacounters%
4735 \fi\unskip%
4736 }

```

\rectoprosetextnote

```

4737 \newcommand{\rectoprosetextnote}[3][0]{%
4738 \iftextnoteson%
4739 \rectotitleinnotescheck
4740 \unskip\proselinelabel{#2}%
4741 \setproselemmarange{#2}{#1}%
4742 \ifnorectotextnoteyet % firstrectotextnote
4743 \firstrectotextnote
4744 \fi %norectotextnoteyet
4745 \global\norectotextnoteyetfalse
4746 \immediate\write\rectotextnotes{\checkprosenoteheaders}%
4747 \literalrectotextnote{#3}%
4748 \ifrectotextnotessinglepar%
4749 \literalrectotextnote{\par}%
4750 \fi%
4751 \resetlemmacounters%
4752 \fi\unskip%

```

4753 }

`\rectoproseemendation` Notice that it calls `\firstemendation` as usual.

```
4754 \newcommand{\rectoproseemendation}[3][0]{%
4755 \ifemendationson%
4756 \rectotitleinnotescheck
4757 \unskip\proselinelabel{#2}%
4758 \setproselemmarange{#2}{#1}%
4759 \ifredundantemendations
4760 \iftextnoteson
4761 \ifrangelemma
4762 \rectoprosetextnote[#1]{#2}{#3}%
4763 \else
4764 \rectoprosetextnote{#2}{#3}%
4765 \fi % ifrangelemma}
4766 \fi %iftextnoteson
4767 \ifrectotextnotessinglepar%
4768 \literalrectotextnote{\par}%
4769 \fi% iftextnotessinglepar
4770 \fi % ifredundantemendations
4771 \ifnorectoemendationyet % firstemendation
4772 \firstrectoemendation
4773 \fi%noemendyet
4774 \global\norectoemendationyetfalse
4775 \immediate\write\rectoemendations{\checkprosenoteheaders}%
4776 \literalrectoemendation{#3}%
4777 \ifrectoemendationssinglepar%
4778 \literalrectoemendation{\par}%
4779 \fi% ifemendationssinglep
4780 \resetlemmacounters%
4781 \fi\unskip%
4782 }
```

`\rectoproseexplanatory`

```
4783 \newcommand{\rectoproseexplanatory}[3][0]{%
4784 \ifexplanon%
4785 \rectotitleinnotescheck
4786 \unskip\proselinelabel{#2}%
4787 \setproselemmarange{#2}{#1}%
4788 \ifnorectoexplainyet% firstexplanation
4789 \firstrectoexplanatory%
4790 \fi%noexplainyet
4791 \global\norectoexplainyetfalse%
4792 \immediate\write\rectoexplanations{\checkprosenoteheaders}%
4793 \literalrectoexplain{#3}%
4794 \ifrectoexplanationssinglepar%
4795 \literalrectoexplain{\par}%
4796 \fi% ifexplanationssinglepar
4797 \resetlemmacounters%
4798 \fi\unskip%
```

4799 }

`\pmclresetsettitleinnotes`

```
4800 \newcommand{\pmclresetsettitleinnotes}{%
4801 \noversoemendationyetrue%
4802 \noversoexplainyetrue%
4803 \noversotextnoteyetrue%
4804 \norettoemendationyetrue%
4805 \norettoexplainyetrue%
4806 \norettotextnoteyetrue%
4807 }
```

`\pmclversoresetsettitleinnotes`

```
4808 \newcommand{\pmclversoresetsettitleinnotes}{%
4809 \noversoemendationyetrue%
4810 \noversoexplainyetrue%
4811 \noversotextnoteyetrue%
4812 }
```

`\pmclrectoresetsettitleinnotes`

```
4813 \newcommand{\pmclrectoresetsettitleinnotes}{%
4814 \norettoemendationyetrue%
4815 \norettoexplainyetrue%
4816 \norettotextnoteyetrue%
4817 }
```

`\literalexplain`

```
4818 \let\literalexplanatory=\literalexplain
4819 \let\literalversoexplanatory=\literalversoexplain
4820 \let\literalrectoexplanatory=\literalrectoexplain
```

`\putversotextnotes` Does the same for textual notes.

```
4821 \newcommand{\putversotextnotes}{
4822 \iftextnoteson
4823 \ifversotextnotestwocol
4824 \literalversotextnote{\end{multicols}}
4825 \fi %\iftextnotetwocol
4826 \newpage
4827 \hyphenationforsmall
4828 \immediate\closeout\versotextnotes
4829 \input \jobname.vtn
4830 \contentsendnotestitle{\the\versotextnotescontentsname}{versotextnotes}
4831 \else
4832 \relax
4833 \fi}
```

`\putrectotextnotes` Does the same for recto textual notes.

```
4834 \newcommand{\putrectotextnotes}{
4835 \iftextnoteson
```

```

4836 \ifrectotextnotetwocol
4837 \literalrectotextnote{\end{multicols}}
4838 \fi %\iftextnotetwocol
4839   \newpage
4840   \hyphenationforsmall
4841   \immediate\closeout\rectotextnotes
4842   \input \jobname.rtn
4843 \contentsendnotestitle{\the\rectotextnotescontentsname}{rectotextnotes}
4844 \else
4845 \relax
4846 \fi}

```

`\putversoemendations` This macro closes external file for verso emendations, reads it in, and puts an entry for the emendations into the table of contents file. The macro tests to see whether there is an .aux file from a previous run before doing this, and complains in the .log file if the .aux file does not exist.

```

4847 \newcommand{\putversoemendations}{
4848 \ifemendationson
4849 \ifversoemendationstwocol
4850 \literalversoemendation{\end{multicols}}
4851 \fi %\iftextnotetwocol
4852   \newpage
4853   \hyphenationforsmall
4854   \immediate\closeout\versoemendations
4855   \input \jobname.vem
4856 \contentsendnotestitle{\the\versoemendationscontentsname}{versoemendations}
4857 \else
4858 \relax
4859 \fi}

```

`\putrectoemendations` This macro closes external file for recto emendations, reads it in, and puts an entry for the emendations into the table of contents file. The macro tests to see whether there is an .aux file from a previous run before doing this, and complains in the .log file if the .aux file does not exist.

```

4860 \newcommand{\putrectoemendations}{
4861 \ifemendationson
4862 \ifrectoemendationstwocol
4863 \literalrectoemendation{\end{multicols}}
4864 \fi %\iftextnotetwocol
4865   \newpage
4866   \hyphenationforsmall
4867   \immediate\closeout\rectoemendations
4868   \input \jobname.rem
4869 \contentsendnotestitle{\the\rectoemendationscontentsname}{rectoemendations}
4870 \else
4871 \relax
4872 \fi}

```

`\putversoexplanatorynotes` Does the same for verso explanatory notes.

```

4873 \newcommand{\putversoexplanatorynotes}{
4874 \ifexplanon
4875 \ifversoexplanationstwocol
4876 \literalversoexplain{\end{multicols}}
4877 \fi %\iftextnotetwocol
4878   \newpage
4879   \hyphenationforsmall
4880   \immediate\closeout\versoexplanations
4881   \input \jobname.vex
4882 \ifpoemcontentson
4883 \ifexplanon
4884 \contentsendnotestitle{\the\versoexplanationscontentsname}{versoexplanatorynotes}
4885 \fi
4886 \fi
4887 \else
4888 \relax
4889 \fi}

```

`\putrectoexplanatorynotes` Does the same for recto explanatory notes.

```

4890 \newcommand{\putrectoexplanatorynotes}{
4891 \ifexplanon
4892 \ifrectoexplanationstwocol
4893 \literalrectoexplain{\end{multicols}}
4894 \fi %\iftextnotetwocol
4895   \newpage
4896   \hyphenationforsmall
4897   \immediate\closeout\rectoexplanations
4898   \input \jobname.rex
4899 \ifpoemcontentson
4900 \ifexplanon
4901 \contentsendnotestitle{\the\rectoexplanationscontentsname}{rectoexplanatorynotes}
4902 \fi
4903 \fi
4904 \else
4905 \relax
4906 \fi}

```

22.29 Parallel Texts in Prose

First, some booleans.

`\ifversopassagestillopen`

```

4907 \newif\ifversopassagestillopen
4908 \versopassagestillopenfalse
4909 \newif\ifrectopassagestillopen
4910 \rectopassagestillopenfalse

```

When the last recto page ended, was the last paragraph finished? True means the next recto should continue the paragraph from the last recto

`\ifinpara`

```
4911 \newif\ifinpara
4912 \inparafalse
4913 \newif\ifrectoparapending
4914 \rectoparapendingfalse
4915 \newif\ifrectoparaopen
4916 \rectoparaopenfalse
4917 \newif\ifversoparapending
4918 \versoparapendingfalse
4919 \newif\ifversoparaopen
4920 \versoparaopenfalse
```

Counters: `prosepage` `versoprolinecounter`, etc., and commands to set them.

`\makeprosepagelabel`

```
4921 \newcounter{prosepage}
4922 \setcounter{prosepage}{1}
4923 \newcommand{\makeprosepagelabel}{\proselinelabel{prosepageno\theprosepage}}
4924 \newcounter{versoprolinecounter}
4925 \newcommand{\saveversoproline}{%
4926 \refstepcounter{prosepage}%
4927 \makeprosepagelabel
4928 \setcounterfromref{versoprolinecounter}{prosepageno\theprosepage}
4929 }
4930 \newcommand{\restoreversoproline}{\setcounter{linenumber}{\value{versoprolinecounter}}}%
4931 \newcounter{rectoprolinecounter}
4932 \newcommand{\saverectoproline}{%
4933 \refstepcounter{prosepage}%
4934 \makeprosepagelabel
4935 \setcounterfromref{rectoprolinecounter}{prosepageno\theprosepage}
4936 }
4937 \newcommand{\restorerectoproline}{\setcounter{linenumber}%
4938 {\value{rectoprolinecounter}}}%
```

The `\parastart` and `\paraend` macros, to mark the beginning and end of paragraphs

`\parastart`

```
4939 \newcommand{\parastart}{\inparatrue}
```

`\paraend`

```
4940 \newcommand{\paraend}{\inparafalse}
```

`\startparalleltextsprose` and `\finishparalleltextsprose`

`\startparalleltextsprose`

```
4941 \newcommand{\startparalleltextsprose}{%
4942 \leavevmode
4943 \cleartoverso
4944 \paralleltextstrue}
```

```

4945 \inparafalse
4946 }

\finishparalleltextsprose
4947 \newcommand{\finishparalleltextsprose}{%
4948 \paralleltextsfalse}

paralleprose
4949 \newenvironment{paralleprose}{\startparalleltextsprose} {\finishparalleltextsprose}

\startversoprosepage
4950 \newcommand{\startversoprosepage}{%
4951 \let\titletoothernotes=\versotitletoothernotes
4952 \restoreversoprosetline%
4953 \ifversoparapending{\inparatrue}\else{\inparafalse}\fi%
4954 \ifinpara{\noindent}\else{\relax}\fi%
4955 }

\finishversoprosepage

\finishversoprosepage
4956 \newcommand{\finishversoprosepage}{%
4957 \ifinpara{\versoparapendingtrue}\else{\versoparapendingfalse}\fi%
4958 \saveversoprosetline%
4959 }

\startrectoprosepage
4960 \newcommand{\startrectoprosepage}{%
4961 \let\titletoothernotes=\rectotitletoothernotes
4962 \restorerectoprosetline%
4963 \ifrectoparapending{\inparatrue}\else{\inparafalse}\fi%
4964 \ifinpara{\noindent}\else{\relax}\fi%
4965 }

\finishrectoprosepage
4966 \newcommand{\finishrectoprosepage}{%
4967 \ifinpara{\rectoparapendingtrue}\else{\rectoparapendingfalse}\fi%
4968 \saverectoprosetline
4969 }

```

22.30 Finishing up

`\finish` The `\finish` macro reads in the notes, the index (previously created from your `.aux` file by `MakeIndex`), and the contents sections and sets them. The notes sections send page information to the contents file as they are set. Then the

page information for the index is sent to the contents file. Finally the contents file is closed and read in. If you have an editor's introduction or a list of abbreviations, copy this macro, uncomment out the commented out lines, and issue it all as a `\renewcommand` for `\finish`. Be sure to have the command `\label{editorsintroduction}` on the first page of your introduction.

It usually takes three passes to get the table of contents and the index files correct.

The consequence of doing using `\finish` is that the table of contents comes last. There are ways around this that are described earlier. The notes sections are all typeset in the `\small` size.

```

4970 \newcommand{\finish}{
4971 \small\bf \hyphenchar\font=45
4972 \small\it \hyphenchar\font=45
4973 \small\rm \hyphenchar\font=45
4974
4975 \ifemendationson
4976   \newpage
4977   \immediate\closeout\emendations
4978   \input \jobname.emd
4979 \fi
4980 \iftextnoteson
4981   \newpage
4982   \immediate\closeout\textnotes
4983   \input \jobname.ent
4984   \newpage
4985 \fi
4986 \ifexplanon
4987   \immediate\closeout\explanations
4988   \input \jobname.enx
4989   \newpage
4990 \fi
4991 \ifindexingon
4992 \printindex
4993 \fi
4994 \ifpoemcontentson
4995 %   \immediate\write\poemcontents{\string\vspace{10pt}\string\par}
4996 %   \immediate\write
4997 % \poemcontents{\string\contentspoemtitlefont\ Introduction to the Notes}
4998 %   \immediate\write
4999 % \poemcontents{\string~ / \string~\ \string\pageref{editorsintroduction} \string\par}
5000 %   \immediate\write\poemcontents{\string\par \string\smallskip}
5001 %   \immediate\write\poemcontents{\string\contentspoemtitlefont\ Abbreviations}
5002 %   \immediate\write
5003 % \poemcontents{\string~ / \string~\ \string\pageref{abbreviations} \string\par}
5004 %   \immediate\write\poemcontents{\string\par \string\smallskip}
5005   \ifemendationson
5006   \immediate\write\poemcontents{\string\contentspoemtitlefont\
5007   \the\emendationscontentsname}
5008   \immediate\write

```

```

5009 \poemcontents{\string~ / \string~\ \string\pageref{emendationnotes} \string\par}
5010     \immediate\write\poemcontents{\string\par \string\smallskip}
5011     \fi
5012     \iftextnoteson
5013         \immediate\write\poemcontents{\string\contentspoemtitlefont\
5014         \the\textnotescontentsname}
5015         \immediate\write
5016 \poemcontents{\string~ / \string~\ \string\pageref{textualnotes} \string\par}
5017     \immediate\write\poemcontents{\string\par \string\smallskip}
5018     \fi
5019     \ifexplanon
5020         \immediate\write
5021 \poemcontents{\string\contentspoemtitlefont\ \the\explanationscontentsname}
5022         \immediate\write
5023 \poemcontents{\string~ / \string~\ \string\pageref{explanatorynotes}}
5024     \fi
5025     \ifindexingon
5026         \immediate\write\poemcontents{\string\par \string\smallskip}
5027         \immediate\write
5028 \poemcontents{\string\contentspoemtitlefont\ \the\poemindexcontentsname}
5029         \immediate\write
5030 \poemcontents{\string~ / \string~\ \string\pageref{indexpage}\string\par}
5031     \fi
5032     \immediate\closeout\poemcontents
5033     \input \jobname.ctn
5034 \fi
5035 \clearpage
5036 \thispagestyle{volumetitlestyle}
5037 \vspace{106pt}
5038 \begin{center}
5039 {\poemtitlefont Note}
5040 \end{center}
5041
5042 \noindent The symbol \stanzaatbottomvalue\ is used to indicate
5043 a space between sections of a poem
5044 wherever such spaces are lost in pagination.
5045 \cleardoublepage
5046 }

```

`\testforauxonfirstrun` Put this in the preamble. It suppresses `\finish`, `\puttextnotes`, `\putemendations`, and `\putexplanatory` unless there is an `.aux` file from a previous run, this avoiding some error messages.

```

5047 \newcommand{\testforauxonfirstrun}{\IfFileExists{\jobname.aux}{\relax}
5048 {\let\finish=\relax
5049 \let\puttextnotes=\relax
5050 \let\putexplanatory=\relax
5051 \let\putemendations=\relax
5052 \typeout{Run again to read in endnotes files}}}

```

`\putpoemcontents` You may wish to do the tasks done by `\finish` separately. This will give you

more flexibility. `\putpoemcontents` inserts the table of contents file from a prior run. Be sure to issue it *before* you issue `\makepoemcontents`.

```
5053 \newcommand{\putpoemcontents}{
5054 \IfFileExists{\jobname.ctn}{\input \jobname.ctn
5055 \clearpage \resetpagestyle\normalsize}
5056 {\typeout{Run again to input contents file here}}
5057 }
```

`\hyphenationforsmall` This command restores hyphenation for the backmatter sections of the book. Hyphenation is turned off in the main body of the book, because verse should not be hyphenated. This macro turns hyphenation on, but only for small roman, italic, and bold fonts. Backmatter sections are all set in `\small`. `\putemendations`, `\puttextnotes`, and `\putexplanatory` all call `\hyphenationforsmall`.

```
5058 \newcommand{\hyphenationforsmall}{\small\bf \hyphenchar\font=45
5059 \small\it \hyphenchar\font=45
5060 \small\rm \hyphenchar\font=45
5061 }
```

`\putemendations` This macro closes external file for emendations, reads it in, and puts an entry for the emendations into the table of contents file. The macro tests to see whether there is an `.aux` file from a previous run before doing this, and complains in the `.log` file if the `.aux` file does not exist.

```
5062 \newcommand{\putemendations}{
5063 \ifemendationson
5064 \ifemendationstwocol
5065 \literate\end{\end{multicols}}
5066 \fi %\iftextnotetwocol
5067 \newpage
5068 \hyphenationforsmall
5069 \immediate\closeout\emendations
5070 \input \jobname.emd
5071 \contentsendnotestitle{\the\emendationscontentsname}{emendationnotes}
5072 \else
5073 \relax
5074 \fi}
```

`\putexplanatory` Does the same for explanatory notes.

```
5075 \newcommand{\putexplanatory}{
5076 \ifexplanon
5077 \ifexplanationstwocol
5078 \literate\explain{\end{multicols}}
5079 \fi %\iftextnotetwocol
5080 \newpage
5081 \hyphenationforsmall
5082 \immediate\closeout\explanations
5083 \input \jobname.enx
5084 \ifpoemcontentson
5085 \ifexplanon
```

```

5086 \contentsendnotestitle{\the\explanationscontentsname}{explanatorynotes}
5087 \fi
5088 \fi
5089 \else
5090 \relax
5091 \fi}

```

`\puttextnotes` Does the same for textual notes.

```

5092 \newcommand{\puttextnotes}{
5093 \iftextnoteson
5094 \iftextnotestwocol
5095 \literaltextnote{\end{multicols}}
5096 \fi %\iftextnotetwocol
5097 \newpage
5098 \hyphenationforsmall
5099 \immediate\closeout\textnotes
5100 \input \jobname.ent
5101 \contentsendnotestitle{\the\textnotescontentsname}{textualnotes}
5102 \else
5103 \relax
5104 \fi}

```

`\putpoemindex` Reads in the index of titles and first lines and adds an entry for the index into the table of contents.

```

5105 \newtoks{\poemindexname}
5106 \poemindexname={Index of Titles and First Lines}
5107 \newcommand{\change-poemindexname}[1]{\poemindexname={#1}}
5108 \newtoks{\poemindexheadername}
5109 \poemindexheadername={Index of Titles and First Lines}
5110 \newcommand{\change-poemindexheader}[1]{\poemindexheadername={#1}}
5111 \newtoks{\poemindexcontentsname}
5112 \poemindexcontentsname={Index of Titles and First Lines}
5113 \newcommand{\change-poemindexcontentsname}[1]{\poemindexcontentsname={#1}}
5114 \newcommand{\putpoemindex}{\ifindexingon
5115 \printindex
5116 \fi
5117 \ifpoemcontentson\ifindexingon
5118 \immediate\write\poemcontents{\string\par \string\smallskip}
5119 \immediate\write
5120 \poemcontents{\string\contentspoemtitlefont\ \the\poemindexcontentsname}
5121 \immediate\write
5122 \poemcontents{\string~\string\contentsleaders \string~\ \string\pageref{indexpage}\string\par}
5123 \fi\fi}
5124 \newcommand{\putmultiplepoemindex}[4]{%
5125 \ifindexingon
5126 \poemindexname={#2}
5127 \poemindexheadername={#3}
5128 \poemindexcontentsname={#4}
5129 \poemindexlabelname={#4}

```

```

5130 \printindex[#1][#2]
5131 \fi
5132 \ifpoemcontentson\ifindexingon
5133     \immediate\write\poemcontents{\string\par \string\smallskip}
5134     \immediate\write
5135 \poemcontents{\string\contentspoemtitlefont\ \the\poemindexcontentsname}
5136     \immediate\write
5137 \poemcontents{\string~ \string\contentsleaders \string~\
5138 \string\pageref{\the\poemindexlabelname}\string\par}
5139 \fi\fi
5140 }
5141 \newcommand{\noteaboutstanzamarkpage}{\begin{volumetitlepage}
5142 %\thispagestyle{volumetitlestyle}
5143 \vspace{106pt}
5144 \begin{center}
5145 {\poemtitlefont Note}
5146 \end{center}
5147
5148 \noindent The symbol \stanzaatbottomvalue\ is used to indicate
5149 a space between sections of a poem
5150 wherever such spaces are lost in pagination.
5151 \end{volumetitlepage}}

```

22.31 Visual formatting

The ideal in \LaTeX is to separate content markup and formatting as completely as possible. In the text itself you simply mark the logical units (a poem, a title, a stanza, a textual note), and a header program like this interprets the meaning of those terms typographically. However, one still winds up having to do some visual formatting. Sometimes you have to enlarge or shrink a page by one line in order to avoid an intractable widow or club line, and when one does so one must be careful to do the same to the other member of the two-page spread of which that page is a part. These commands enable one to wiggle pagelength enough to handle these problems.

```

5152 \newcommand{\longpage}{\enlargethispage{\baselineskip}}
5153 \newcommand{\shortpage}{\enlargethispage{-\baselineskip}}

```

22.32 Special environments: cjquotation and theindex

An environment for special prose quotations within verse as in “Chief Joseph of the Nez Perce”

`cjquotation`

```

5154 \newenvironment{cjquotation}
5155     {\tolerance=2000%
5156     \vspace{-\bigskipamount}
5157     \restoreverselinenumber
5158     \language=255

```

```

5159             \noindent\relax
5160             \list{}{\listparindent 0em%
5161                 \itemindent 0em%
5162                 \rightmargin 2em%
5163                 \leftmargin 2em%
5164                 \topsep 0em%
5165                 \parskip 0em%
5166                 \itemindent \listparindent
5167                 \rightmargin \leftmargin
5168                 \parsep \z@ \@plus\p}%
5169             \item[]
5170         }
5171     {\endlist}

```

theindex And the environment for the index:

```

5172 \newtoks{\poemindexlabelname}
5173 \poemindexlabelname={indexpage}
5174 \newcommand{\changeindexlabelname}[1]{\poemindexlabelname={#1}}
5175 \renewenvironment{theindex}
5176     {{\par\clearpage{\pagestyle{volumetitlestyle}\cleardoublepage}
5177     \thispagestyle{volumetitlestyle}}
5178     \makeatletter
5179     \def\pmclidxitem{\par\hangindent 1em}
5180 \fancyhead[RO,LE]{{\small\textrm{\thepage}}}
5181 \fancyhead[CO]{{\small\em \the\poemindexheadername}}}
5182 \fancyhead[CE]{{\small\em \the\poemindexheadername}}}
5183 \fancyfoot{}
5184     \label{\the\poemindexlabelname}
5185     \leftthyphenmin=2\tolerance=500\language=0
5186     \normalfont \backmattertextfont
5187     \raggedright
5188     \begin{multicols}
5189 {2}\backmattersink\begin{center}{\normalfont
5190 \backmatterheaderfont \the\poemindexname}\end{center}
5191 \backmatterafterheadersink}%
5192         \let\item\pmclidxitem
5193     {\end{multicols}\clearpage}
5194 \makeatother

```

Finally, some other miscellaneous environments.

```

5195 \newlength{\epigraphquoteleftmargin}
5196 \newlength{\epigraphquoterightmargin}
5197 \setlength{\epigraphquoteleftmargin}{1.5em}
5198 \setlength{\epigraphquoterightmargin}{1.5em}
5199 \newif\ifleftalignepigraphs
5200 \leftalignepigraphsfalse
5201 \makeatletter
5202 \newenvironment{epigraphquote}{\list{}{\%
5203 \ifleftalignepigraphs\left@lighttitleblock%
5204 \rightmargin 1sp\leftmargin \lefttitlemargin%

```

```

5205 \else
5206 \rightmargin\epigraphquoterightmargin%
5207 \leftmargin\epigraphquoteleftmargin%
5208 \fi
5209             \topsep Opt%
5210             \partopsep Opt%
5211             \listparindent Opt%
5212             }%
5213         \item\relax}
5214     {\endlist}\makeatother
5215 \newenvironment{volumetitlepagequote}{\list{}{\rightmargin \voladditionalamount%
5216                                     \leftmargin \voladditionalamount%
5217                                     \topsep Opt%
5218                                     \partopsep Opt%
5219                                     \listparindent Opt
5220                                     }%
5221         \item\relax}
5222     {\endlist}

```

Change History

v1.0	General: Initial version 1	v1.7	General: Changed how labels are made for use in contents and notes sections. Control sequences in titles (such as for italics and so on) no longer require special commands, although those commands are retained for backward compatibility. 1
v1.01	General: Added commands for titles of poems without formal titles. Corrected typographical errors in manual. 1	v2.01	General: Rewrote all of the title commands in order to make them easier to maintain. Added environment for flushing runover lines in verse to the right margin. Added information on how to customize titles. 1
v1.1	General: Added commands to change mark in cases where page break fall (or does not fall) on stanza break. Added command to change the amount of indentation in runover lines in verse. Removed special geometry to make the program more generic. 1	v2.02	General: Corrected an error in setting poems without formal titles 1
v1.11	General: Corrected bugs in headers for explanatory notes and emendations. 1	v2.12	General: Notes sections can take ranges of lines. 1
v1.2	General: Accidentals and typescript variants test to see whether textual notes are being made. Corrected a bug when quoting verse in note sections. Added a command to change the page number of the table of contents. Added a command to input the table of contents file. Added commands to input the external files for emendations, explanatory notes, textual notes, and the index of titles and first lines. Added a command to test whether there is an .aux file from a previous run and to prevent typesetting of the external files for emendations, explanatory notes, textual notes if there is not. Added a command to restore the main page style after the table of contents. 1	v2.13	General: tsenry no longer needs an unskip if the entry starts with a comma. 1
		v2.2	General: The user can create new kinds of endnote. 1
		v2.21	General: Cross references can refer to line numbers 1
		v2.22	General: Removed dependence upon marn.sty. Enabled multiple levels of block-formatted footnotes 1
		v2.24	General: commands to aid typesetting parallel texts. 1
		v2.25	General: Bug fix in running headers to notes sections 1

v2.26	General: Fix no unskip in vertical mode error	1	making a mess of it. Modified commands for volume titles to use the facilities for poem titles.	1
v2.27	General: Changed name of linelabel command, to prepare for making poemscol and lineno compatible	1	v2.36	General: Versions of note commands for typescript variants and accidentals for annotated prose. Commands for marking up and annotating prose by paragraph and sentence number. Commands for cross references by sentence and paragraph number.
v2.30	General: Prose sections such as Authors' Introductions are line numbered by lineno.sty. Textnotes, emendations, and explanatory notes for prose sections may be either footnotes or endnotes, and the latter are sent to the same place as their verse equivalents. Good solution to "missing number" problem on first runs.	1	v2.37	General: In cases of broken lines or runover lines you can choose whether to set the line number with the beginning of the line or with the end of the line. Also, you can choose to have it set the number always at the beginning if the line number is at the left, and always at the end if it is at the right.
v2.301	General: Corrected small bug in table of contents commands, rewrote manual for clarity	1	v2.38	General: Checked cases where commands might introduce extra white space. Made sure that line numbers for verse, prose, and paragraph-sentence prose line up. Fixed overlapping of paragraph and line numbers for paragraph-sentence mode. Up to four sentences can appear on a line in paragraph-line mode without having their marginal line numbers overlap. Fixed a bug that added an extra colon in footnotes in paragraph-sentence format. Changed "gutter" and "outer" line numbering in verse and paragraph-sentence prose to use Peter Wilson's sidepars rather than marginpars.
v2.31	General: Ranges of line for notes sections (in verse or prose sections) need no longer involve counting of lines. Lemmas may be nested, may overlap, and may cross stanza boundaries.	1		
v2.32	General: Simpler configuration of marginal line numbers, revision of manual	1		
v2.33	General: Fixed a bug in index generation, compensated for odd interaction between fancyhdr and reversemarginpar	1		
v2.34	General: Easier modification of format of tables of contents	1		
v2.35	General: poemscol can break the lines for long titles in the table of contents on its own without making a mess of it. poemscol can break the lines for long titles on its own without		v2.39	General: Left a DeclareOption hanging in version 2.38. Fixed that.

v2.391	General: Corrections to user's guide.	1	find the depth of the line, restored line number commands to use sidepar and its variants.	1
v2.392	General: More corrections to user's guide.	1	v2.47	General: Changed name of sidepar to pcmclsidepar to avoid conflicts with the sidepar command from the memoir class, since they are no longer exactly the same. Added commands to put a marginal reference to the notes section in the margins of poem titles.
v2.394	General: More corrections to user's guide.	1	v2.48	General: Added more general form of the commands to put a marginal reference to the notes section in the margins of poem titles.
v2.4	General: Commands to make new kinds of endnotes also make notes for line numbered prose sections and for prose sections with paragraph and sentence numbering.	1	v2.49	General: Changed marginal reference command to use marginpar rather than pmclsidepar (alas, it still adds vertical white space after the title with pmclsidepar). Added marginal reference commands for sequences and sequence sections. Fixed errors in manual.
v2.41	General: Fixed a bug in line numbers of new kinds of prose note.	1	v2.50	General: Added marginal reference commands for poem sections, poem subtitles, epigraphs, and dedications. These commands no longer require an additional label command to set the label to which they refer. Added commands to make marginal references to the pages in notes sections where comments on individual lines may be found, for textual notes, explanatory notes, emendations, and user-defined notes. Added commands for changing the names of the Table of Contents, the various endnotes sections, and the running
v2.42	General: Fixed error in handling conditionals when setting prose numbered by sentence and paragraph.	1		
v2.43	General: Notes in prose numbered by sentence and paragraph number can refer only to the sentence number even when paragraphs are also being counted.	1		
v2.44	General: Fixed a bug which caused new kinds of endnotes in prose sections to add unwanted white space to the output.	1		
v2.45	General: Use of sidepar in v2.38 introduced a problem, causing line numbers sometimes to drift up a point. Changed commands for putting verse line numbers, but not paragraph and sentence numbers, to use marginpars again.	1		
v2.46	General: Changed definition of sidepar so that it uses struts to			

	headers for the contents and endnotes sections, in order to facilitate editions of works in languages other than English. 1		Two column formatting for notes sections. 1
v2.51	General: Changed prose section environment so that it does not always assume that the modulo for line numbers in prose is the same as the number in verse. Corrected a problem with alignment of line numbers in the <code>prosesectionnoreset</code> environment. Added commands to support generation of multiple indices using the <code>splitindex</code> package. Fixed a variety of small bugs, including a newly introduced one in the correction to textual notes for quoted verse. 1	v2.62	General: You can adjust the margins of epigraphs, dedications, and similar things. Made the appearance of entries in the table of contents for endnotes sections customizable. Fixed a bug which caused user-defined endnotes to put extra white space in prose passages. 1
v2.52	General: Changed dedication to <code>poemdedication</code> to avoid a conflict with a command in <code>koma-script</code> . <code>dedication</code> command is provided using <code>providecommand</code> for compatibility 1	v2.63	General: Revisions to manual. 1
v2.53	General: Changed the name of an internal token register to avoid a conflict with <code>babel</code> 1	v2.64	General: Bug fix: remove extra white space in custom endnotes for prose sections when notes are in single paragraph mode. Fix appearance of page number in endnote sections. 1
v2.531	General: Fixed a typo in example code. 1	v2.65	General: Modifications to parallel text commands, corrections to manual. 1
v2.6	General: Added an optional argument to the <code>poem</code> environment to center the text block of the poem on the longest line. Added a switch to enable titles to be centered on the page. 1	v2.66	General: Change to page styles 1
v2.61	General: Added a boolean to switch notes to one note per paragraph form. Boolean to switch off poem titles in notes.	v2.7	General: Improvements to parallel texts. 1
		v2.72	General: Improvements to parallel texts. Generic note types for parallel texts. corrections to manual. 1
		v2.8	General: Changes in default values about where line numbers are placed. <code>verselinenumberstoleft</code> and related commands no longer change <code>marginparsep</code> . Endnote sections may have normal or hanging paragraphs. Endnotes may have multiple paragraphs. 1
		v2.81	General: <code>Versemarginadjust</code> to adjust margins of the verse block. Line numbers

automatically move closer to the text when the text block is centered on the longest line.		customization of epigraphs and similar things.	1
New boolean to force line numbers to the margins when the text block is centered. New commands to control the distance of line numbers from margins of centered text block. New default values for marginparwidth and marginparsep.	1	v2.97	
v2.85	General: Boolean to turn centering of verse block on and off. Subtitles center when centertitles is issued. New boolean to adjust placement of marginal reference markers in jhtextnote and related commands.	1	General: Correction to JHepigraphs. Epigraphenvironment for headnotes with more than one stanza or paragraph. Corrections to manual.
v2.87	General: Notes to appear at the end of individual poems.	1	v2.98
v2.88	General: Revisions to manual.	1	General: Corrections to manual.
v2.89	General: Append the date to the end of the poem.	1	v2.99
v2.9	General: Date aligns with left margin of poem even when poem is centered.	1	General: Hierarchy of indented stanzas
v2.95	General: Long poems can put firstline—lastline in running header. Revisions to manual. Textual notes, emendation notes, and explanatory notes can also be placed at the end of the poem rather than at the bottom of the page or in an endnote section. Commands to set the title only in the contents and only in the notes.	1	v3
v2.96	General: Epigraphs, headnotes, dedications, and attributions move towards the center when titles are centered. Easier		General: With centered verse you can align the title, epigraphs, attributions, and so on with the left margin of the verse block.
		v3.01	General: Corrections to manual
		v3.04	General: Appendix sections. New contents entries.
		v3.08	General: Indentations of species of titles in text can be independently changed without changing the definition of the title. Appendix and Foreword section titles can be indented differently from notes section titles.
		v3.081	General: Fixed centertitles bug for subsections
		v3.09	General: New schemes for titles. Titles can be placed according the indentation schemes introduced in version 3.08, at the left text margin, at the left verse margin, centered over the longest line of a verse block at the left verse margin, at the left margin of a verse block centered on the longest line, and centered over a verse block centered over the longest line.

v3.1	General: New commands shortpoemepigraph, shortpoemdedication, shortpoemattribution, JHshortepigraph, JHshortdedication. These commands are controlled by the same booleans that control placement of titles.	1	suppress the appearance of the first paragraph number, whether in the margin or in the running text.	1
v3.12	General: Bug fix. Fix command clash with titlesec. Manual revision	1	v3.1415 General: Changed controlling how to place marginal marks in JHpoemtitle and its siblings, and in JHtextnote and its siblings. Marginal marks are now set using their own inserts, rather than using marginpar.	1
v3.13	General: Fixed subtitles in emendations and explanations, Fixed bug in sequencesectiontitlefirstline, changed sequence hierarchy of indentations, subsubsections of sequences no longer appear in contents	1	v3.14159 General: Marginal marks set by JHpoemtitle now work with the different title placement schemes.	1
v3.14	General: Bug fix: ifpagenumberinnotesfalse, Manual revision	1	v3.141592 General: Special commands for titles with footnotes (where the footnotes are authorial and part of the title). Title footnotes can be set at the bottom of the page, like traditional footnotes, at the bottom of the page like “Layered” footnotes, or at the end of the poem. Marginal marks set by JHpoemtitle can be placed independently of the marginal marks produced by margreftextnote..	1
v3.141	General: Manual revisions. Fixed spacing of sentence and paragraph numbers in sections numbered by paragraph and sentence. You can suppress the appearance of the first sentence number, whether in the margin or in the running text. You can		v3.1415926 General: Bug fix. Extra white space problem. Thanks to David Carlisle.	1

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols	
\!	960
\@	342, 343, 3286, 3290, 3298, 3303
\@JHswitchmarginpar	2183, 2185
\@JHswitchtitlemarginpar	2262, 2264
\@auxout	826, 1007, 3483, 3486
\@bsphack	779, 780, 825, 1006, 2184, 2185, 2263, 2264, 3481
\@car	3109
\@centercr	85, 350, 378, 398, 416,

437, 461, 478, 496, 706, 716, 735
\@compoundlabelscratch 1487, 1490,
1496, 1502, 2840, 2842, 4047,
4050, 4056, 4062, 4069, 4071,
4101, 4104, 4110, 4116, 4123, 4125
\@currenvir 3831
\@dblarg 778, 2183, 2262
\@esphack 817, 820, 828,
1009, 2222, 2225, 2308, 2311, 3489
\@extract@ref 3103, 3109, 3113
\@extractpageref 3112, 3135
\@extractref 3108, 3125
\@firstoftwo 3098, 3832
\@ifnextchar 2823, 2824
\@ifundefined 935
\@ixpt 23
\@latex@warning 3121, 3131
\@listI 18
\@memcnta 847, 852, 853
\@minus 14, 16, 24, 26, 28, 29
\@mparswitchfalse 2352
\@mparswitchtrue 2104, 2113
\@namedef 839
\@nil 3105, 3116
\@pagemarktotextnotes ... 1192, 1200
\@plus 14–16, 24–26, 28, 29, 5168
\@pmclsidepar ... 778–780, 2184, 2263
\@poempagetotextnotes ... 1198, 1574
\@poemtitletotextnotes .. 1201, 1577
\@secondcar 3113, 3116
\@secondoftwo 3100, 3834
\@setfontsize 13, 23
\@unexpandable@protect 833
\@vsa 2740
\\ 85, 350, 378,
398, 416, 437, 461, 478, 496,
706, 716, 735, 927, 949, 962,
975, 980, 1077, 2429, 2749, 2750

\l ... 634, 638, 685, 686, 960, 1357,
1369, 1382, 1395, 2789, 2844,
2942, 2944, 3175, 3983, 3995,
4073, 4127, 4192, 4997, 4999,
5001, 5003, 5006, 5009, 5013,
5016, 5021, 5023, 5028, 5030,
5042, 5120, 5122, 5135, 5137, 5148

A
\accidental 32, 2803, 2822

\addtolength 77, 337, 338, 368, 372,
373, 388, 391, 407, 410, 423,
424, 430, 445, 446, 450, 454,
468, 469, 472, 485, 486, 594,
1511, 1535, 1589, 1590, 2636,
2670, 2671, 2682, 2683, 3073, 3086
\adjustst@nzindent 75, 84
\afterpoemskip 284, 759, 3981
\afterpoemtitleskip 14
\aftersequencetitleskip
..... 285, 1750, 1778,
1786, 1793, 1801, 1809, 1833, 2390
\appendixdividerpage 1212, 1232, 1250
\appendixincontents 39
\appendixincontentstrue 1208
\appendixtitle 39, 1222, 1233
\appendixtitleindent .. 179, 180, 1224
\appendixtitleindentamount . 177–179
\appendtomacro . 2898, 3021, 3024, 3027
\argpageref 1199, 1471, 2840, 4069, 4123
\attribution 40, 2597

B
\backmatterafterheadersink
..... 44, 1034,
1049, 1224, 1242, 1265, 2955, 5191
\backmatterheaderfont 41,
1032, 1048, 1223, 1241, 1264, 5190
\backmatterintrofont 46
\backmattersectiontitle 2451
\backmattersink .. 43, 1031, 1048,
1223, 1241, 1264, 2453, 2948, 5189
\backmattertextfont 45, 1109,
1147, 1183, 1226, 1244, 1267,
1309, 1323, 1335, 1347, 1358,
1370, 1383, 1396, 2957, 4317,
4380, 4443, 4506, 4568, 4635, 5186
\backmattervolumefont
..... 47, 1309, 1323, 1335, 1347
\backmattervolumesubtitlefont ..
..... 48, 1357, 1369, 1382, 1395
\baselineskip 5152, 5153
\beginngroup 830,
2690, 2697, 2704, 2711, 2719,
2724, 2729, 2734, 2828, 2899,
2926, 3686, 3723, 3758, 3793,
4326, 4389, 4452, 4515, 4579, 4646
\biblechapter 3663
\bibleverse 3662
\booksection 1295

<code>\booksectionpage</code>	<u>764</u>	<code>\changeпоemindexname</code>	67, 5107
<code>\box</code>	820, 2127, 2139, 2225, 2242, 2259, 2311, 3879, 3897	<code>\changerectoemendationscontentsname</code>	4485
<code>\brokenline</code>	20, <u>962</u> , 965, 978	<code>\changerectoemendationsheader</code>	..	4482
<code>\brokenlineatbeginning</code>	21, <u>977</u>	<code>\changerectoemendationsname</code>	...	4479
C					
<code>\c@cp@cntr</code>	<u>865</u>	<code>\changerectoexplanationscontentsname</code>	4615
<code>\c@footnote</code>	2544	<code>\changerectoexplanationsheader</code>		4612
<code>\c@ntentsinfo</code>		<code>\changerectoexplanationsname</code>	..	4609
		26, 50, 1305, 1319, 1332, 1344, 1551, 1596, 1610, 1621, 1653, 1662, 1671, 1680, 1688, 1697, 1707, 1718, 1735, 1742, 1752, 1761, 1770, 1779, 1787, 1794, 1802, 1810, 1819, 1827, 1834, 1842, 1850, 1859, 1868, 1877, 1884, 1892, 1907, 1950, 1958, 1965, 1973, 1981, 1990, 2000, 2010, 2018, 2026, 2035, 2336, 2357, 2366, 2393, 2403, 2412, 2421, 2430, 2454, 2556, 2565, 2575, 2585, 2593, 4031, 4085, 4132	<code>\changerectotextnotescontentsname</code>	4359
<code>\c@nterverseblock</code>	370, 384, 404	<code>\changerectotextnotesheader</code>	<i>64</i> ,	4356
<code>\c@page</code>	823, 855, 967, 969, 995, 998, 3822, 3826	<code>\changerectotextnotesname</code>	..	<i>64</i> , 4353
<code>\centerepigraphindentation</code>		<code>\changesinglelineabbrev</code>	635
	 2599, 2600, 2604, 2605	<code>\changesinglepageabbrev</code>	66, 676
<code>\centerepigraphquote</code>	2603, 2612	<code>\changetextnotescontentsname</code>	..	1088
<code>\centerepigraphsonfalse</code>	2598	<code>\changeversoemendationscontentsname</code>	4422
<code>\centerepigraphsontrue</code>	...	331, 1508	<code>\changeversoemendationsheader</code>	..	4419
<code>\centertitles</code>	16, 40, 1508	<code>\changeversoemendationsname</code>	...	4416
<code>\centertitlesonfalse</code>		302, 309, 316, 323	<code>\changeversoexplanationscontentsname</code>	4548
<code>\centertitlesontrue</code>	330, 1508	<code>\changeversoexplanationsheader</code>		4545
<code>\centertitlesontrue</code>	12, 325	<code>\changeversoexplanationsname</code>	..	4542
<code>\changecontentsheader</code>	1017	<code>\changeversotextnotescontentsname</code>	4296
<code>\changecontentsname</code>	66, 1015	<code>\changeversotextnotesheader</code>	...	4293
<code>\changeemendationscontentsname</code>		1126	<code>\changeversotextnotesname</code>	4290
<code>\changeemendationsheader</code>	1123	<code>\checknoteheaders</code>	
<code>\changeemendationsname</code>	66, 1120		 <u>2783</u> , 2795, 2865, 2884, 2978, 3677, 3714, 3749, 3784, 4343, 4406, 4469, 4532, 4598, 4666
<code>\changeexplanationscontentsname</code>		1163	<code>\checkoddpage</code>	781, <u>848</u> , 2143, 2153, 2163, 2173, 2186, 2265
<code>\changeexplanationsheader</code>	1160	<code>\checkprosenoteheaders</code>	
<code>\changeexplanationsname</code>	...	66, 1157			.. 2993, <u>3169</u> , 3181, 3209, 3225, 4683, 4712, 4729, 4746, 4775, 4792
<code>\changemultiplelineabbrev</code>	637	<code>\citerange</code>	<u>2773</u> , 2789, 3615, 3637, 3654	
<code>\changemultiplepageabbrev</code>	...	66, 678	<code>\cjquotation</code>	<u>5154</u>
<code>\changenotesheader</code>	1085	<code>\cleardoublepage</code>	672, 765, 768, 770, 771, 1023, 1098, 1137, 1174, 1213, 1254, 2934, 4307, 4370, 4433, 4496, 4559, 4626, 5045, 5176	
<code>\changenotesname</code>	66, 1082	<code>\clearemptydoublepage</code>	<u>672</u>
<code>\changeпоemindexcontentsname</code>	..	5113	<code>\clearpage</code>	
<code>\changeпоemindexheader</code>	5110			.. 765, 1023, 1097, 1136, 1173, 1212, 1253, 1400, 1417, 1435, 1453, 2933, 3822, 3825, 4215, 4269, 4306, 4369, 4432, 4495, 4558, 4625, 5035, 5055, 5176, 5193
<code>\changeпоemindexlabelname</code>	5174			

<code>\cleartorecto</code>	3822	<code>\contentspoemsubsectiontitleindentamount</code>	246, 247, 1736
<code>\cleartoverso</code>	3825, 3957, 4943	<code>\contentspoemsubsectiontitleindent</code>	239	
<code>\clubpenalty</code>	54	<code>\contentspoemsubsectiontitleindentamount</code>	237–239
<code>\columnsep</code>	90	<code>\contentspoemtitlefont</code>		
<code>\columnwidth</code>	801, 2206, 2286	. 14, 24, 52, 1068, 1596, 1610,		
<code>\contents</code>	2431	1621, 1653, 1662, 1671, 1680,		
<code>\contentsendnotesdefaults</code>		1688, 1697, 1707, 1718, 1735,		
.....	1052, 1072, 1237	1742, 1819, 1827, 1842, 1850,		
<code>\contentsendnotesfont</code>		1859, 1868, 1877, 1884, 1892,		
.....	30, 1068, 1072, 1237, 1293	1907, 1950, 1958, 1965, 1973,		
<code>\contentsendnotesindent</code>	30, 1067, 1072	1981, 1990, 2000, 2010, 2018,		
<code>\contentsendnotessubtitle</code>	1236, 1246	2026, 2035, 2336, 2357, 2366,		
<code>\contentsendnotestitle</code>	1071, 1228,	2403, 2412, 2421, 2430, 2454,		
.....	1269, 3040, 4830, 4843, 4856,	2556, 2565, 2575, 2585, 2593,		
.....	4869, 4884, 4901, 5071, 5086, 5101	4031, 4085, 4132, 4997, 5001,		
<code>\contentsentryoverrun</code>		5006, 5013, 5021, 5028, 5120, 5135		
.....	702, 703, 709, 711, 1552, 1564	<code>\contentspoemtitleindent</code>		
<code>\contentsi</code>	2430	231, 232, 1596, 1610,	
<code>\contentsindentfive</code>	206	1621, 1653, 1742, 2556, 2565, 2593		
<code>\contentsindentfiveamount</code>		<code>\contentspoemtitleindentamount</code>		
.....	205, 206, 2019, 2026	228–231, 234, 1597,	
<code>\contentsindentfour</code>	204, 2018, 2026	1611, 1622, 1654, 2557, 2566, 2594		
<code>\contentsindentfouramount</code>		<code>\contentspoemtitlesecondlineindent</code>		
.....	203, 204, 279, 1958, 1974	235, 236, 1662, 1671, 2575, 2585	
<code>\contentsindentone</code>	198,	<code>\contentspoemtitlesecondlineindentamount</code>		
.....	1067, 2336, 2393, 4031, 4085, 4132	233–235, 1663, 1672, 2576, 2586	
<code>\contentsindentoneamount</code>	24,	<code>\contentsssequencesubtitleindent</code>		
.....	197, 198, 229, 250, 254, 703, 1565	271	
<code>\contentsindentthree</code>	202, 1958, 1973	<code>\contentsssequencesubtitleindentamount</code>		
<code>\contentsindentthreeamount</code>	269–271	
.....	201, 202,	<code>\contentsssequencesubtitlesecondlineindent</code>		
.....	247, 248, 270, 273, 276, 1795, 2404	274	
<code>\contentsindenttwo</code>		<code>\contentsssequencesubtitlesecondlineindentamount</code>		
.....	200, 1237, 1794, 1877, 1884	272–274	
<code>\contentsindenttwoamount</code>	199, 200,	<code>\contentsssequencesubtitlesecondlineindentamount</code>		
.....	241, 258, 261, 264, 267, 1743,	263–265, 1820,	
.....	2337, 2394, 2455, 4032, 4086, 4133	<code>\contentsssequencesubtitlesecondlineindentamount</code>		
<code>\contentsleaders</code>	268, 1859, 1868	
.....	1056, 1282, 1548, 1556, 5122, 5137	<code>\contentsssequencesubtitlesecondlineindentamount</code>		
<code>\contentspoemsectiontitleindent</code>	266–268, 1860, 1869	
.....	242, 1680, 1688, 1718, 2421	<code>\contentsssequencesubtitlesecondlineindentamount</code>		
<code>\contentspoemsectiontitleindentamount</code>	240–	277, 1950, 1965, 1981, 2035, 2036	
.....	242, 244, 1681, 1689, 1719, 2422	<code>\contentsssequencesubtitlesecondlineindentamount</code>		
<code>\contentspoemsectiontitlesecondlineindent</code>	245, 1697, 1707	275–277, 1951, 1966, 1982	
<code>\contentspoemsectiontitlesecondlineindentamount</code>	243–245, 1698, 1708	<code>\contentsssequencesubsectiontitleindent</code>		
<code>\contentspoemsubsectiontitleindent</code>	248, 1735		

<code>\contentssequencesubsectiontitleindentamount</code>	2011	<code>\contentsvolumesubtitlesecondlineindentamount</code>	218–220
<code>\contentssequencesubsectiontitlesecondlineindentamount</code>	1990, 2000	<code>\contentsvolumetitleindent</code>	209, 210, 1305, 1319, 1332, 1344
<code>\contentssequencesubsectiontitlesecondlineindentamount</code>	1991, 2001	<code>\contentsvolumetitleindentamount</code>	207–209, 1306, 1320, 1333, 1345
<code>\contentssequencesubsubsectiontitleindentamount</code>	280, 2010	<code>\contentsvolumetitlesecondlineindentamount</code>	213, 214
<code>\contentssequencesubsubsectiontitleindentamount</code>	278–280	<code>\contentsvolumetitlesecondlineindentamount</code>	211–213
<code>\contentssequencesubtitleindent</code>	259, 1787	<code>\cplabel</code>	851, 852, <u>865</u>
<code>\contentssequencesubtitleindentamount</code>	257–259, 1788	<code>\csname</code>	841, 844,
<code>\contentssequencesubtitlesecondlineindent</code>	262, 1802, 1810		2912–2919, 2921, 2923, 2925,
<code>\contentssequencesubtitlesecondlineindentamount</code>	260–262, 1803, 1811		2929, 2933, 2941, 2943, 2946,
<code>\contentssequencetitlefont</code>	51, 1752, 1761, 1770, 1779, 1787, 1794, 1802, 1810, 1834, 2393		2951, 2955, 2958, 2959, 2961, 2964–2968, 2971, 2973, 2974, 2976, 2977, 2979–2981, 2986, 2989, 2990, 2992–2996, 3002, 3004, 3005, 3007–3012, 3021, 3024, 3027, 3032, 3034, 3035, 3037, 3045, 3047, 3092, 3097, 3104
<code>\contentssequencetitleindent</code>	251, 252, 1752, 1761, 1834, 2357, 2366	D	
<code>\contentssequencetitleindentamount</code>	249– 251, 1753, 1762, 1835, 2358, 2367	<code>\dag</code>	2461, 2465
<code>\contentssequencetitlesecondlineindent</code>	255, 256, 1770, 1779, 1780	<code>\dateindent</code>	2666, 2667, 2669–2672, 2674, 2676
<code>\contentssequencetitlesecondlineindentamount</code>	253–255, 1771	<code>\DeclareNewFootnote</code>	37, 2520, 3605, 3607, 3610, 3612, 3632, 3634, 3649, 3651
<code>\contentsvolumefont</code>	49, 1305, 1319, 1332, 1344	<code>\DeclareRobustCommand</code>	848
<code>\contentsvolumesectiontitleindent</code>	223, 224, 1407, 1424, 1442, 1460	<code>\dedication</code>	2626
<code>\contentsvolumesectiontitleindentamount</code>	221–223	<code>\definewnotetype</code>	34, <u>2897</u>
<code>\contentsvolumesectiontitlesecondlineindent</code>	227	<code>\dotfill</code>	684
<code>\contentsvolumesectiontitlesecondlineindentamount</code>	225–227	<code>\dp</code>	820, 2127, 2139, 2225, 2242, 2259, 2311, 3879, 3897
<code>\contentsvolumesubtitlefont</code>	50, 1353, 1365, 1378, 1391, 1406, 1423, 1441, 1459	E	
<code>\contentsvolumesubtitleindent</code>	217, 1353, 1365, 1378, 1391	<code>\dedication</code>	31, <u>2845</u> , 3636
<code>\contentsvolumesubtitleindentamount</code>	215–217	<code>\dedicationfootnotesparatrue</code>	582
<code>\contentsvolumesubtitlesecondlineindent</code>	220	<code>\dedications</code>	1133, 1135, 2506, 2700, 2726, 2865, 2874,
		<code>\emendationsatendfalse</code>	3630
		<code>\emendationsatendtrue</code>	574
		<code>\emendationsatfoot</code>	<u>3628</u>
		<code>\emendationscontentsname</code>	
		<code>\emendationsheadername</code>	1124, 1125, 1127, 5007, 5071
		<code>\emendationsname</code>	1121–1123, 1141, 1142
			1118–1120, 1145

<code>\emendationsontrue</code>	stanza	17
..... 1132, 3629, 4428, 4491	<code>volumetitlepage</code>	27
<code>\emendationstwocolfalse</code>	<code>\epigraph</code>	40, <u>2597</u>
..... 1130	<code>\epigraphquotelleftmargin</code>	
<code>\end</code> 2604, 2608, 5195, 5197, 5207	
757, 816, 917, 1033, 1040, 1041,	<code>\epigraphquoterightmargin</code>	
1062, 1287, 1296, 1402, 1412, 2605, 2609, 5196, 5198, 5206	
1419, 1429, 1437, 1447, 1455,	<code>\explanatendfalse</code>	3647
1465, 1511, 1517, 1518, 1526,	<code>\explanatendtrue</code>	576
1527, 1535, 1541, 1542, 1562,	<code>\explanations</code>	1171, 1172,
2124, 2136, 2221, 2239, 2256,	2501, 2707, 2731, 2884, 2894,	3225, 3544, 3545, 3816, 4987, 5082
2307, 2316, 2317, 2326, 2327,	<code>\explanationsatfoot</code>	<u>3645</u>
2344, 2445, 2449, 2483, 2618,	<code>\explanationscontentsname</code>	
2622, 2625, 2628, 2630, 2632, 1161, 1162, 1164, 5021, 5086	
2634, 2636, 2644, 2647, 2672,	<code>\explanationsheadername</code>	
2676, 2687, 3035, 3078, 3090, 1158–1160, 1177, 1178	
3330, 3862, 3875, 3893, 3972,	<code>\explanationsname</code> ..	1155–1157, 1181
3976, 3979, 4013, 4038, 4039,	<code>\explanationstwocolfalse</code>	1167
4092, 4093, 4164, 4166, 4170,	<code>\explanatory</code>	31, <u>2876</u> , 3653
4219, 4221, 4225, 4273, 4276,	<code>\explanfootnotesparafalse</code>	584
4279, 4282, 4824, 4837, 4850,	<code>\explanontrue</code> ..	1169, 3646, 4554, 4621
4863, 4876, 4893, 5040, 5065,		
5078, 5095, 5146, 5151, 5190, 5193		
<code>\endcsname</code>		
841,		
844, 2912–2919, 2921, 2923,		
2925, 2929, 2933, 2941, 2943,		
2946, 2951, 2955, 2958, 2960,		
2961, 2964–2968, 2971, 2973,		
2974, 2976, 2978–2981, 2986,		
2989, 2990, 2992–2996, 3002,		
3004, 3005, 3007–3012, 3021,		
3024, 3027, 3032, 3034, 3035,		
3037, 3045, 3047, 3092, 3097, 3105		
<code>\endgroup</code>		
836,		
2694, 2701, 2708, 2715, 2722,		
2727, 2732, 2736, 2832, 2902,		
2930, 3690, 3727, 3762, 3797,		
4330, 4393, 4456, 4519, 4583, 4650		
<code>\endlist</code>		
89, 354,		
395, 414, 434, 459, 476, 492,		
500, 711, 731, 746, 5171, 5214, 5222		
<code>\endpmsection</code>		
3027		
<code>\endpoem</code>		
3021		
<code>\endprosesection</code>		
3024		
<code>\enlargethispage</code>		
5152, 5153		
environments:		
<code>maintitlepage</code>		27
<code>parallelverse</code>		62
<code>pmclverse</code>		15
<code>poem</code>		15
<code>rightflushverse</code>		22
	<code>stanza</code>	17
	<code>volumetitlepage</code>	27
	<code>\epigraph</code>	40, <u>2597</u>
	<code>\epigraphquotelleftmargin</code>	
 2604, 2608, 5195, 5197, 5207	
	<code>\epigraphquoterightmargin</code>	
 2605, 2609, 5196, 5198, 5206	
	<code>\explanatendfalse</code>	3647
	<code>\explanatendtrue</code>	576
	<code>\explanations</code>	1171, 1172,
	2501, 2707, 2731, 2884, 2894,	3225, 3544, 3545, 3816, 4987, 5082
	<code>\explanationsatfoot</code>	<u>3645</u>
	<code>\explanationscontentsname</code>	
 1161, 1162, 1164, 5021, 5086	
	<code>\explanationsheadername</code>	
 1158–1160, 1177, 1178	
	<code>\explanationsname</code> ..	1155–1157, 1181
	<code>\explanationstwocolfalse</code>	1167
	<code>\explanatory</code>	31, <u>2876</u> , 3653
	<code>\explanfootnotesparafalse</code>	584
	<code>\explanontrue</code> ..	1169, 3646, 4554, 4621
	F	
	<code>\fancyhfoffset</code>	599, 611, 646
	<code>\finish</code>	39, <u>4970</u> , 5048
	<code>\finishparalleltxtprose</code>	65
	<code>\finishparalleltxts</code> ..	62, 4018, <u>4271</u>
	<code>\finishparalleltxtsprose</code> ..	<u>4947</u> , 4949
	<code>\finishrectopage</code>	62, <u>4246</u>
	<code>\finishrectoprosepage</code>	65, <u>4966</u>
	<code>\finishversopage</code>	62, <u>4191</u>
	<code>\finishversoprosepage</code>	65, <u>4956</u>
	<code>\firstemendation</code> ..	2862, 2873, 3206, 3567
	<code>\firstexplanatory</code>	
 2881, 2893, 3222, 3541	
	<code>\firstlinesettings</code>	
 51, 1312, 1362, 1417,	
	1626, 1650, 1685, 1758, 1791,	
	1847, 1888, 1917, 1978, 2032, 2562	
	<code>\firstrectoemendation</code> ..	4521, 4529, 4772
	<code>\firstrectoexplanatory</code>	
 4643, 4653, 4663, 4789	
	<code>\firstrectotextnote</code> ..	4395, 4403, 4743
	<code>\firstversoemendation</code> ..	4458, 4466, 4709
	<code>\firstversoexplanatory</code>	
 4576, 4586, 4595, 4726	
	<code>\firstversotextnote</code> ..	4332, 4340, 4680

<code>\flushbottom</code>	1022, 1097, 1136, 1173, 1212, 1253, 2933, 4306, 4369, 4432, 4495, 4558, 4625	
<code>\font</code>	4971–4973, 5058–5060	
<code>\footnote</code>	2549	
<code>\footnoteH</code>	2539	
<code>\footnotemark</code>	2542, 2544	
<code>\footnotepoemtitle</code>	47, <u>2512</u>	
<code>\footnotepoemtitlefirstline</code>	47, <u>2561</u>	
<code>\footnotepoemtitlelastline</code>	2581	
<code>\footnotepoemtitlemiddleline</code>	2571	
<code>\footnotesplitpoemtitle</code>	48, <u>2590</u>	
<code>\FootnotetextA</code>	3618	
<code>\FootnotetextB</code>	3615, 3623, 3626	
<code>\FootnotetextC</code>	3637, 3641, 3643	
<code>\FootnotetextD</code>	3654, 3658, 3660	
<code>\foreworddividerpage</code>	1253, 1273	
<code>\forewordincontentstrue</code>	1210	
<code>\forewordtitle</code>	1263, 1274	
<code>\forewordtitleindent</code>	187, 188, 1265	
<code>\forewordtitleindentamount</code>	185–187	
<code>\fulltitleholder</code>	523, 1486, 1489, 1492, 1495, 1498, 1501, 2844	
G		
<code>\G@refundefinedtrue</code>	3120, 3130	
<code>\gdef</code>	823	
<code>\geometry</code>	1	
<code>\gobm</code>	2750	
<code>\goodbreak</code>	759, 1304, 1307, 1308, 1318, 1406, 1423, 1441, 1459, 3981	
H		
<code>\hangindent</code>	5179	
<code>\headnote</code>	40, <u>2597</u>	
<code>\headoffsetlength</code>	592–594, 599, 611, 646	
<code>\hfill</code>	4157	
<code>\hfilll</code>	4154	
<code>\hfuzz</code>	58	
<code>\hour</code>	<u>960</u>	
<code>\hskip</code>	959, 4154	
<code>\ht</code>	820, 2127, 2139, 2225, 2242, 2259, 2311, 3879, 3897	
<code>\hyphenationforsmall</code>	3033, 4827, 4840, 4853, 4866, 4879, 4896, <u>5058</u> , 5068, 5081, 5098	
<code>\hyphenchar</code>	4971–4973, 5058–5060	
I		
<code>\if</code>	2958, 2966	
<code>\if@firstcolumn</code>	798, 2203, 2282	
<code>\if@nobreak</code>	837	
<code>\if@twocolumn</code>	797, 2202, 2281, 3824, 3827	
<code>\if@twoside</code>	863, 3822, 3825	
<code>\ifappendixincontents</code>	1207, 1228, 1246	
<code>\ifcat</code>	2741	
<code>\ifcenterepigraphson</code>	16, 2597, 2611, 2643	
<code>\ifcentertitleson</code>	1040, 1401, 1406, 1418, 1423, 1436, 1441, 1454, 1459, 1507, 1517, 1526, 1541, 2233, 2250, 2291, 2296, 2316, 2326, 4038, 4092	
<code>\ifdim</code>	382, 402, 420, 442, 465, 482, 3850	
<code>\ifemendationfootnotespara</code>	36, 581, 3631	
<code>\ifemendationsatend</code>	573, 2696, 2723, 2873	
<code>\ifemendationson</code>	532, 2505, 2847, 3190, 3555, 3811, 4692, 4755, 4848, 4861, 4975, 5005, 5063	
<code>\ifemendationssinglepar</code>	2845, 2867, 3211, 3573	
<code>\ifemendationssingplepar</code>	29	
<code>\ifemendationstwocol</code>	30, 1129, 1148, 5064	
<code>\ifenv</code>	<u>3828</u>	
<code>\ifexplanatend</code>	575, 2703, 2728, 2893	
<code>\ifexplanationssinglepar</code>	29, 2876, 2886, 3227, 3547	
<code>\ifexplanationstwocol</code>	30, 1166, 1184, 5077	
<code>\ifexplanfootnotespara</code>	36, 583, 3648	
<code>\ifexplanon</code>	531, 2500, 2878, 3218, 3538, 3815, 4592, 4660, 4721, 4784, 4874, 4883, 4891, 4900, 4986, 5019, 5076, 5085	
<code>\IfFileExists</code>	5047, 5054	
<code>\ifforewordincontents</code>	1209, 1269	
<code>\ifhmode</code>	2784, 3170, 3176, 3514, 3842, 3848	
<code>\ifincludeaccidentals</code>	539, 2805, 3235, 3581	
<code>\ifincludetypescripts</code>	541, 2816, 2822, 2823, 3245, 3256, 3591, 3600	
<code>\ifindexingon</code>	534, 536, 4991, 5025, 5114, 5117, 5125, 5132	

<code>\ifinindentedverse</code>	81	<code>\ifparalleltxts</code> ...	3899, 4079, 4136
<code>\ifinpara</code> 4911 , 4954, 4957, 4964, 4967		<code>\ifpmclreversesidepar</code> .	783, 792, 858
<code>\ifinpoem</code>	527, 4193, 4247, 4275	<code>\ifpmclsidesparswitch</code>	782, 858
<code>\ifinprosesection</code>	3065, 4278	<code>\ifpmparainmar</code>	3449, 3470
<code>\ifinquotedverse</code>	493, 4281	<code>\ifpmpararunning</code>	3450, 3473
<code>\ifinstanza</code>	526, 4197, 4251, 4272	<code>\ifpmparas</code>	
<code>\ifinteger</code>	2747, 2764, 3153, 3496		3347, 3375, 3406, 3433, 3448, 3482
<code>\ifJHmarginparswitch</code>	2073, 2187, 2266	<code>\ifpmsentencebypara</code>	3451, 3476
<code>\ifJHmarkstogutter</code> ..	2071, 2383, 2480	<code>\ifpoemcontentson</code>	
<code>\ifJHmarkstoleft</code> ...	2065, 2377, 2474		.. 528, 1052, 1278, 1352, 1364,
<code>\ifJHmarkstoouter</code> ..	2069, 2380, 2477		1377, 1390, 1405, 1422, 1440,
<code>\ifJHmarkstoright</code> ..	2067, 2374, 2471		1458, 1551, 2710, 2733, 3039,
<code>\ifJHreversemarginpar</code>			4882, 4899, 4994, 5084, 5117, 5132
	2075, 2188, 2197, 2267, 2276	<code>\ifpoemendemendationnoteson</code>	
<code>\iflastcontentsline</code>	551	 3701, 3712, 3730
<code>\iflastpoemcentered</code> ..	375, 2673, 2684	<code>\ifpoemendemendationnotessinglepar</code>	
<code>\ifleftalignepigraphs</code> ...	5199, 5203	 3703, 3716
<code>\ifleftaligntitles</code>	740, 1585	<code>\ifpoemendexplanatorynoteson</code> ...	
<code>\iflinenumbercenteredwithverse</code> 3736, 3747, 3765
	355, 374, 425, 447	<code>\ifpoemendexplanatorynotessinglepar</code>	
<code>\iflongpoemon</code>	929, 933	 3738, 3751
<code>\ifmargincentencenumber</code>		<code>\ifpoemendnoteson</code> ..	3664, 3675, 3693
	3259, 3338, 3362, 3393, 3424	<code>\ifpoemendnotessinglepar</code>	
<code>\ifmarginrefstomargin</code>	2467, 2488	 37, 3666, 3679
<code>\ifmiddlecontentsline</code>	549	<code>\ifpoemendtextnoteson</code> 3771, 3782, 3800	
<code>\ifnoemendyet</code>		<code>\ifpoemendtextnotessinglepar</code> ...	
	545, 2861, 3205, 3566, 4203, 4257	 38, 3773, 3786
<code>\ifnoexplainyet</code>		<code>\ifprosebysentence</code>	3257
	546, 2880, 3221, 3540, 4209, 4263	<code>\ifputpagenumberincontents</code>	
<code>\ifnoectoemendationyet</code>			553, 1055, 1281, 1555
	4514, 4528, 4771	<code>\ifputpagenumberinnotes</code>	
<code>\ifnoectoexplainyet</code> 4658, 4662, 4788			555, 1202, 1573, 2839, 4068, 4122
<code>\ifnoectotextnoteyet</code> 4388, 4402, 4742		<code>\ifputtitleinnotes</code>	1568, 1576
<code>\ifnormaltitleindentation</code>		<code>\ifrangelemma</code>	567, 2774, 2851,
	295, 1516, 1540, 2640, 2642, 2646		3164, 3195, 3508, 3559, 4698, 4761
<code>\ifnoversoemendationyet</code>		<code>\ifrecto</code>	3901
	4451, 4465, 4708	<code>\ifrectoemendationsspending</code>	3939, 4236
<code>\ifnoversoexplainyet</code> 4590, 4594, 4725		<code>\ifrectoemendationssinglepar</code> ...	
<code>\ifnoversotextnoteyet</code> 4325, 4339, 4679		 4513, 4522, 4534, 4777
<code>\ifnum</code> 64, 79, 938, 2741, 3369, 3400, 4158		<code>\ifrectoemendationstwocol</code>	
<code>\ifnumbersgutter</code>	887, 966, 994	 4488, 4507, 4862
<code>\ifnumbersright</code>	777, 899,	<code>\ifrectoexplanationspending</code>	
	906, 971, 1000, 3069, 3082, 3322	 3943, 4240
<code>\ifnumbersswitch</code> 776, 897, 904, 965,		<code>\ifrectoexplanationssinglepar</code> ..	
	992, 3070, 3071, 3083, 3084, 3319	 4652, 4654, 4668, 4794
<code>\ifodd</code>	853,	<code>\ifrectoexplanationsstwocol</code>	
	855, 967, 969, 995, 998, 3822, 3826	 4618, 4636, 4892
<code>\ifoddpag</code>	784, 804, 815,	<code>\ifrectoparaopen</code>	4915
	865 , 2144, 2154, 2164, 2174,	<code>\ifrectoparapending</code>	4913, 4963
	2189, 2209, 2220, 2268, 2289, 2306	<code>\ifrectopassagestilopen</code>	4909

<code>\ifrectopoempending</code>	3905, 4228	<code>\iftitlefirstline</code>	
<code>\ifrectopoemstillopen</code>	3917, 3975, 4169	559, 1476, 1488, 4048, 4102
<code>\ifrectoprosesectionpending</code> . . .	3922	<code>\iftitlefootnotesatpoemend</code>	2512, 2541
<code>\ifrectoprosesectionstillopen</code> .	3926	<code>\iftitlefootnoteslayered</code> .	2516, 2538
<code>\ifrectoquotedversepending</code>	3931	<code>\iftitlefootnotesplain</code> . .	2514, 2548
<code>\ifrectoquotedversestillopen</code> . .	3935	<code>\iftitlelastline</code>	563
<code>\ifrectostanzapending</code> . . .	3909, 4232	<code>\iftitlemiddleline</code>	
<code>\ifrectostanzastillopen</code>	561, 1491, 4051, 4105
.	3913, 3992, 4163	<code>\iftitlesatleftmarginofcenteredblock</code>	
<code>\ifrectotextnotessinglepar</code>	293, 721
.	4387, 4396, 4408, 4748, 4767	<code>\iftitlesatleftversemargin</code>	
<code>\ifrectotextnotestwocol</code>	294, 1510, 1534, 2635, 2637, 2649
.	4362, 4381, 4836	<code>\iftitlescenteredonleftverseblock</code>	
<code>\ifredundantemendations</code>	292, 725
.	543, 2849, 3193, 3557, 4696, 4759	<code>\iftwocol</code>	3036
<code>\ifrefundefined</code>	3091, 3096, 3119, 3129	<code>\ifverselinenumbers</code>	530, 939
<code>\ifrfv</code>	502, 508, 509	<code>\ifverserightflush</code>	565
<code>\ifrunningsentencenumbers</code>		<code>\ifverso</code>	3903
.	3258, 3335, 3359, 3390, 3421	<code>\ifversoemendationspending</code>	3941, 4181
<code>\ifsinglelinetitle</code>		<code>\ifversoemendationssinglepar</code> . . .	
.	557, 1473, 1485, 4045, 4099	4450, 4459, 4471, 4714
<code>\ifsourcesfootnotespara</code> <i>36</i> , 579, 3604		<code>\ifversoemendationstwocol</code>	
<code>\ifspeciallinelock</code> 686, 920, 922, 3996		4425, 4444, 4849
<code>\ifstrictpagecheck</code>	850, 865	<code>\ifversoexplanationspending</code>	
<code>\ifsuppressfirstpara</code> 3260, 3455, 3461		3945, 4185
<code>\ifsuppressfirstsentence</code>		<code>\ifversoexplanationssinglepar</code> . .	
.	60, 3261, 3275, 3309	4585, 4587, 4600, 4731
<code>\ifsupressfirstpara</code>	60	<code>\ifversoexplanationstwocol</code>	
<code>\iftextcenteringturnedon</code>	4551, 4569, 4875
.	16, 364, 383, 403, 441	<code>\ifversoparaopen</code>	4919
<code>\iftextfootnotespara</code> . . <i>36</i> , 577, 3609		<code>\ifversoparapending</code>	4917, 4953
<code>\iftextnotesatend</code>		<code>\ifversopassagestillopen</code>	4907
.	571, 1356, 1368, 1381, 1394,	<code>\ifversopoempending</code>	3907, 4173
.	1409, 1426, 1444, 1462, 1571,	<code>\ifversopoemstillopen</code>	3919, 3971, 4224
.	2689, 2718, 2806, 2808, 2817, 2819	<code>\ifversoprosesectionpending</code> . . .	3924
<code>\iftextnoteson</code>	529, 1356,	<code>\ifversoprosesectionstillopen</code> .	3928
.	1368, 1381, 1394, 1409, 1426,	<code>\ifversoquotedversepending</code>	3933
.	1444, 1462, 1570, 2495, 2793,	<code>\ifversoquotedversestillopen</code> . .	3937
.	2804, 2815, 2822, 2823, 2827,	<code>\ifversostanzapending</code> . . .	3911, 4177
.	2850, 3178, 3194, 3234, 3244,	<code>\ifversostanzastillopen</code>	
.	3255, 3526, 3558, 3580, 3590,	3915, 3989, 4218
.	3600, 3807, 4675, 4697, 4738,	<code>\ifversotextnotessinglepar</code>	
.	4760, 4822, 4835, 4980, 5012, 5093	4324, 4333, 4345, 4685, 4704
<code>\iftextnotessinglepar</code> . . <i>29</i> , 2791,		<code>\ifversotextnotestwocol</code>	
.	2797, 2809, 2833, 2856, 3183,	4299, 4318, 4823
.	3201, 3239, 3250, 3531, 3585, 3595	<code>\ifvmode</code>	837
<code>\iftextnotestwocol</code> <i>30</i> , 1090, 1110, 5094		<code>\ifx</code> . .	841, 2750, 3061, 3092, 3097, 3831
<code>\iftextnotetwocol</code> 4825, 4838, 4851,		<code>\ignorespaces</code>	959, 3851
.	4864, 4877, 4894, 5066, 5079, 5096	<code>\includeaccidentalstrue</code>	540
		<code>\includetypescriptstrue</code>	542

<code>\incrementverselinenumber</code>	<code>\JHmarksouter</code> 2097
. 688, 924, 931, 967, 969,	<code>\JHmarksright</code> 2086, 2096
972, 979, 987, 995, 998, 1001, 3998	<code>\JHmarkstogutterfalse</code>
<code>\indentedstanzaamount</code> 71, 72, 74, 77, 89 2072, 2081, 2090, 2101
<code>\indentedverse</code> 17, 19	<code>\JHmarkstoguttertrue</code> 2110
<code>\indentrunoververse</code> 505	<code>\JHmarkstoleftfalse</code> . 2087, 2098, 2107
<code>\indexingontrue</code> 26, 535	<code>\JHmarkstolefttrue</code> 2066, 2078
<code>\inindentedversefalse</code> 89	<code>\JHmarkstoouterfalse</code>
<code>\inindentedversetrue</code> 83 2070, 2080, 2089, 2109
<code>\inparafalse</code>	<code>\JHmarkstooutertrue</code> 2100
. 4912, 4940, 4945, 4953, 4963	<code>\JHmarkstorightfalse</code>
<code>\inparatrue</code> 4939, 4953, 4963 2068, 2079, 2099, 2108
<code>\inpoemfalse</code> . . . 758, 3973, 3977, 3980	<code>\JHmarkstorighttrue</code> 2088
<code>\inpoemtrue</code> 756, 3965	<code>\JHoutermarginpar</code> . . 2141, 2150, 2478
<code>\inprosesectionfalse</code> 3078	<code>\JHpoemfirstsectiontitle</code> 2426
<code>\inprosesectiontrue</code> 3067	<code>\JHpoemsectiontitle</code> 2417
<code>\inquotedversefalse</code> 500	<code>\JHpoemsubtitle</code> 2441
<code>\inquotedversetrue</code> 495	<code>\JHpoemtitle</code> 45, 2349
<code>\instanzafalse</code> 692, 4002	<code>\JHprosesectiontitle</code> 2362
<code>\instanzatrue</code> 685, 3983	<code>\JHreversemarginparfalse</code>
<code>\integerfalse</code> 2744 2076, 2083, 2092, 2103
<code>\integertrue</code> 2742	<code>\JHreversemarginpartrue</code> 2112
<code>\interjectiontitlefirstline</code> . . . 2044	<code>\JHrightmarginpar</code>
<code>\interjectiontitlelastline</code> 2046 2117, 2145, 2167, 2472
<code>\interjectiontitlemiddleline</code> . . . 2049	<code>\JHrighttitlemarginpar</code> . . 2229, 2374
<code>\itemsep</code> 30, 86, 351, 379, 399, 417,	<code>\JHsequencefirstsectiontitle</code> . . 2408
438, 462, 479, 497, 709, 719, 738	<code>\JHsequencesectionsubtitle</code> 2435, 2441
	<code>\JHsequencesectiontitle</code> 2399
	<code>\JHsequencetitle</code> 2388
	<code>\JHshortdedication</code> 2663
	<code>\JHshortepigraph</code> 41, 2659, 2663
	<code>\JHswitchmarginpar</code>
 2155, 2157, 2175, 2177, 2183
	<code>\JHswitchtitlemarginpar</code>
 2262, 2381, 2384
	<code>\JHtextwidth</code> 2053, 2054,
	2120, 2234, 2251, 2284, 2292, 2297
	<code>\JHtitlemarginparsep</code> . 2063, 2064,
	2232, 2249, 2283, 2286, 2290, 2295
	K
	<code>\keeptitlestraight</code> 63
	L
	<code>\l@pcounter</code> . 61, 62, 64, 66, 75, 78, 79
	<code>\l@ftc@ntertitleblock</code> 335, 726
	<code>\language</code> 705, 715, 734, 751, 1034,
	1108, 1146, 1182, 1225, 1243,
	1266, 2956, 3960, 4316, 4379,
	4442, 4505, 4567, 4634, 5158, 5185
<code>\incrementverselinenumber</code>	
. 688, 924, 931, 967, 969,	
972, 979, 987, 995, 998, 1001, 3998	
<code>\indentedstanzaamount</code> 71, 72, 74, 77, 89	
<code>\indentedverse</code> 17, 19	
<code>\indentrunoververse</code> 505	
<code>\indexingontrue</code> 26, 535	
<code>\inindentedversefalse</code> 89	
<code>\inindentedversetrue</code> 83	
<code>\inparafalse</code>	
. 4912, 4940, 4945, 4953, 4963	
<code>\inparatrue</code> 4939, 4953, 4963	
<code>\inpoemfalse</code> . . . 758, 3973, 3977, 3980	
<code>\inpoemtrue</code> 756, 3965	
<code>\inprosesectionfalse</code> 3078	
<code>\inprosesectiontrue</code> 3067	
<code>\inquotedversefalse</code> 500	
<code>\inquotedversetrue</code> 495	
<code>\instanzafalse</code> 692, 4002	
<code>\instanzatrue</code> 685, 3983	
<code>\integerfalse</code> 2744	
<code>\integertrue</code> 2742	
<code>\interjectiontitlefirstline</code> . . . 2044	
<code>\interjectiontitlelastline</code> 2046	
<code>\interjectiontitlemiddleline</code> . . . 2049	
<code>\itemsep</code> 30, 86, 351, 379, 399, 417,	
438, 462, 479, 497, 709, 719, 738	
J	
<code>\JHdedication</code> 2443	
<code>\JHepigraph</code> 2447	
<code>\JHguttermarginpar</code> . . 2161, 2171, 2481	
<code>\JHlabel</code> 2350, 2356,	
2365, 2371, 2373, 2391, 2402,	
2411, 2420, 2429, 2438, 2445, 2449	
<code>\JHleftmarginpar</code> 2129, 2147, 2165, 2475	
<code>\JHlefttitlemarginpar</code> . . . 2246, 2378	
<code>\JHmarginparsep</code> . 2055, 2056, 2064,	
2120, 2132, 2204, 2206, 2210, 2212	
<code>\JHmarginparsepmin</code> 2061, 2062	
<code>\JHmarginparswitchfalse</code>	
. 2074, 2082, 2091	
<code>\JHmarginparswitchtrue</code> . . 2102, 2111	
<code>\JHmarginparvshift</code> 2057, 2058, 2126,	
2138, 2216, 2224, 2241, 2258, 2310	
<code>\JHmarginparwidth</code> 2059,	
2060, 2122, 2132, 2134, 2204,	
2212, 2217, 2219, 2237, 2249, 2254	
<code>\JHmarksgutter</code> 2106	
<code>\JHmarksleft</code> 2077	

<code>\lastcontentslinefalse</code>	552	<code>\literalpoemendemendationnote</code>	..
<code>\lastlinesettings</code>	51, 1338, 1387, 1452, 1636, 1668, 1703, 1776, 1807, 1865, 1927, 1996, 2582	<code>\literalpoemendexplanatorynote</code>	3709, 3715, 3717, 3722
<code>\lastpoemcenteredfalse</code>	377	<code>\literalpoemendnote</code>	2546, 3672, 3678, 3680, 3685
<code>\lastpoemcenteredtrue</code>	385	<code>\literalpoemendtextnote</code>	3779, 3785, 3787, 3792
<code>\lastskip</code>	3843	<code>\literalrectoemendation</code>	4495, 4515, 4523, 4533, 4535, 4776, 4778, 4863
<code>\left@lighttitleblock</code>	722, 741, 1587, 5203	<code>\literalrectoexplain</code>	4625, 4645, 4655, 4667, 4669, 4793, 4795, 4820, 4893
<code>\leftalignepigraphs</code>	13	<code>\literalrectoexplanatory</code>	4820
<code>\leftalignepigraphsfalse</code>	5200	<code>\literalrectotextnote</code>	4369, 4389, 4397, 4407, 4409, 4747, 4749, 4768, 4837
<code>\leftaligntitlesfalse</code>	1586	<code>\literaltextnote</code>	1097, 1203, 1205, 1308, 1322, 2689, 2796, 2798, 2810, 2834, 2857, 3182, 3184, 3202, 3240, 3251, 3530, 3532, 3586, 3596, 5095
<code>\leftaligntitlespace</code>	1584	<code>\literaltextnoteshort</code>	2717
<code>\lefthead</code>	28, 587	<code>\literalversoemendation</code>	4432, 4452, 4460, 4470, 4472, 4713, 4715, 4850
<code>\lefthyphenmin</code>	1034, 1049, 1224, 1242, 1265, 2955, 5185	<code>\literalversoexplain</code>	4558, 4578, 4588, 4599, 4601, 4730, 4732, 4819, 4876
<code>\leftlinenumbers</code>	3072, 3085	<code>\literalversoexplanatory</code>	4819
<code>\leftskip</code>	761–763	<code>\literalversotextnote</code>	4306, 4326, 4334, 4344, 4346, 4684, 4686, 4705, 4824
<code>\lefttitleaddition</code>	333, 334, 336–339	<code>\llap</code>	3462, 3465
<code>\lefttitlemargin</code>	339, 723, 727, 742, 1583, 1584, 1588–1590, 5204	<code>\long</code>	779, 780, 829, 2184, 2185, 2263, 2264, 2898, 3116
<code>\linebend</code>	19, 949	<code>\longpage</code>	52, 5152
<code>\linelabel</code>	3176	<code>\longpoem</code>	643
<code>\linenumberfont</code>	3068, 3081	<code>\longpoemonfalse</code>	930
<code>\linenumberscenteredwithverse</code>	16	<code>\loop</code>	63, 76
<code>\linenumberscenteredwithversetrue</code>	356	M	
<code>\linenumbersep</code>	3069–3073, 3082–3086	<code>\m@ken@teholder</code>	1484, 1521, 1530, 1545, 1615, 1741, 2320, 2330, 2347
<code>\linenumberside</code>	914	<code>\m@kep@emlabel</code>	1473, 1520, 1529, 1544, 1614, 1740, 2319, 2329, 2346, 4041, 4095
<code>\linewidth</code>	371, 376, 382, 397, 402, 415, 420, 422, 436, 442, 444, 465, 467, 477, 482, 484, 748, 749, 1588, 2669, 2681	<code>\maintitlepage</code>	764
<code>\list</code>	86, 351, 379, 399, 417, 438, 462, 479, 497, 707, 717, 736, 5160, 5202, 5215	<code>\maintitlepage (environment)</code>	27
<code>\literalcontents</code>	1022, 1035, 1054, 1060, 1280, 1283, 1285, 1304, 1307, 1318, 1321, 1334, 1346, 1353, 1365, 1378, 1391, 1406, 1423, 1441, 1459, 1554, 1560, 2710	<code>\makeappendix</code>	39, 1207
<code>\literalcontentsshort</code>	2733	<code>\makeemendations</code>	28, 1117
<code>\literatelemend</code>	1136, 2696, 2866, 2868, 3210, 3212, 3572, 3574, 5065		
<code>\literatelemendshort</code>	2723		
<code>\literatelexplain</code>	1173, 2703, 2885, 2887, 3226, 3228, 3546, 3548, 4818, 5078		
<code>\literatelexplainshort</code>	2728		
<code>\literatelexplanatory</code>	4818		

<code>\makeexplanatorynotes</code>	28, 1154	<code>\margrefmarker</code>	2142, 2145, 2147, 2151, 2155, 2157, 2162, 2165, 2167, 2175, 2177, 2375, 2378, 2381, 2384, 2460–2462, 2472, 2475, 2489, 2492, 2510, 2660
<code>\makeforeword</code>	39, 1272	<code>\margrefspecial</code>	2509
<code>\makeindex</code>	537	<code>\margrefstomargintrue</code>	2468
<code>\makelinenumbers</code>	570	<code>\margrefstextnote</code>	33, 46 , 2458
<code>\makemargreflabel</code>		<code>\mark</code> 685, 686, 756, 758, 1106, 1144, 1180, 1195, 2787, 2788, 2947, 3173, 3174, 3517, 3518, 3965, 3973, 3977, 3980, 3983, 3995, 4314, 4377, 4440, 4503, 4565, 4632	
.	2466, 2496, 2501, 2506, 3047	<code>\marksthe</code>	933, 935
<code>\makepoemcontents</code>	22, 1011	<code>\marn</code>	912, 4009
<code>\makepoemendendationnotes</code> 38, 3705		<code>\meaning</code>	2693, 2700, 2707, 2714, 2721, 2726, 2731, 2735, 2831, 2929, 3689, 3726, 3761, 3796, 4329, 4392, 4455, 4518, 4582, 4649
<code>\makepoemendexplanatorynotes</code> 38, 3740		<code>\meta</code>	2749
<code>\makepoemendnotes</code>	37, 3668	<code>\middlecontentslinefalse</code>	550
<code>\makepoemendtextnotes</code>	38, 3775	<code>\middlelinesettings</code>	51, 1326, 1374, 1434, 1631, 1659, 1694, 1767, 1799, 1856, 1922, 1987, 2572
<code>\makepoemlabel</code>	1470, 1475, 1478	<code>\missingpunct</code>	31, 2738
<code>\makeprosepagelabel</code>	4921	<code>\modulolinenumbers</code>	3056, 3061, 3063
<code>\makerectoemendations</code>	64, 4476	<code>\multilinesequencepenalty</code>	290, 1759
<code>\makerectoexplanatorynotes</code>	64, 4606	<code>\multilinetitlepenalty</code>	288, 1651, 1686, 1848, 1979, 2563
<code>\makerectotextnotes</code>	64	<code>\multiplelineabbrev</code>	636–638, 642
<code>\makerectotextnotes</code>	4350	<code>\multiplepageabbrev</code>	677–679, 683
<code>\makerectotitleholder</code>	4024	<code>\mymarks</code> 674 , 1103, 1104, 1141, 1142, 1177, 1178, 2942, 2944, 4311, 4312, 4374, 4375, 4437, 4438, 4500, 4501, 4562, 4563, 4629, 4630	
<code>\makesubappendix</code>	39, 1249	<code>\myversemarks</code>	633 , 649, 650
<code>\maketextnotes</code>	28, 1036		
<code>\maketitlefootnotesatpoemend</code>	2526		
<code>\maketitlefootnoteslayered</code>	2519		
<code>\maketitlefootnotesplain</code>	2532		
<code>\makeverselinenumbers</code>	18, 569, 570		
<code>\makeversoemendations</code>	4413		
<code>\makeversoexplanatorynotes</code>	4539		
<code>\makeversotextnotes</code>	4287		
<code>\makeversotitleholder</code>	4021		
<code>\marginpar</code> 897, 899, 901, 913, 2142, 2151, 2162, 2372, 2488, 2492, 2510, 2660, 3319, 3322, 3324, 4010			
<code>\marginparsep</code>			
.	18, 367, 368, 426, 434, 447, 459, 774, 799, 801, 805, 807, 875, 879, 884, 3069–3072, 3082– 3085, 3288, 3292, 3293, 3296, 3301, 3306, 3857, 3868, 3885, 3886		
<code>\marginparsepmin</code>			
.	18, 358, 359, 368, 426, 447, 2062, 2234, 2251, 2284, 2292, 2297		
<code>\marginparwidth</code>	775, 799, 807, 812, 814, 876, 880, 885, 2060, 2283, 2295, 2303, 2305, 3857, 3860, 3868, 3871, 3873, 3889, 3891		
<code>\marginsentencenumberformat</code>			
.	3282, 3311, 3314, 3386, 3417, 3444		
<code>\marginsentencenumberstrue</code>	3259		
<code>\margrefemendation</code>	33, 47 , 2504		
<code>\margrefexplanatory</code>	33, 47 , 2499		

N

<code>\newcount</code>	61, 847, 3839
<code>\newlabel</code>	1008, 3484, 3487
<code>\newlength</code>	59, 71, 73, 91, 95, 97, 102, 106, 111, 114, 117, 121, 125, 129, 133, 136, 139, 142, 145, 149, 153, 156, 159, 162, 165, 168, 171, 174, 177, 181, 185, 189, 207, 211, 215, 218, 221, 225, 228, 233, 237, 240, 243, 246, 249, 253, 257, 260, 263, 266, 269, 272, 275, 278, 291, 333, 358, 361, 592, 702,

712, 747, 870, 1075, 1583, 2053,
2055, 2057, 2059, 2061, 2063,
2599, 2601, 2666, 2678, 5195, 5196

`\newlinechar`
. 2692, 2699, 2706, 2713, 2829,
2928, 3688, 3725, 3760, 3795,
4328, 4391, 4454, 4517, 4581, 4648

`\newpage` 672, 767, 771, 773,
3033, 3824, 3827, 4826, 4839,
4852, 4865, 4878, 4895, 4976,
4981, 4984, 4989, 5067, 5080, 5097

`\newpmemlabel` 827, 839

`\newtoks` . . 523–525, 633, 636, 674,
677, 1011, 1013, 1080, 1083,
1086, 1118, 1121, 1124, 1155,
1158, 1161, 2460, 2464, 3263,
3492, 4019, 4020, 4150, 4288,
4291, 4294, 4351, 4354, 4357,
4414, 4417, 4420, 4477, 4480,
4483, 4540, 4543, 4546, 4607,
4610, 4613, 5105, 5108, 5111, 5172

`\next` 2691, 2693, 2698,
2700, 2705, 2707, 2712, 2714,
2720, 2721, 2725, 2726, 2730,
2731, 2735, 2830, 2831, 2927,
2929, 3687, 3689, 3724, 3726,
3759, 3761, 3794, 3796, 4327,
4329, 4390, 4392, 4453, 4455,
4516, 4518, 4580, 4582, 4647, 4649

`\noemendyetfalse` 2864,
3208, 3569, 4182, 4207, 4237, 4261

`\noemendyettrue`
. 547, 752, 3075, 3088, 3271, 3961

`\noexplainyetfalse` 2883,
3224, 3543, 4186, 4213, 4241, 4267

`\noexplainyettrue`
. 548, 753, 3076, 3089, 3272, 3962

`\noindent` 3808, 3812,
3816, 4954, 4964, 5042, 5148, 5159

`\nopagebreak`
. 2443, 2446, 2447, 2450, 2616,
2618, 2620, 2622, 2623, 2625,
2633, 2634, 2650, 2653, 2656, 2659

`\noretectoemendationyetfalse` 4531, 4774

`\noretectoemendationyettrue` 4804, 4814

`\noretctoexplainyetfalse` . 4665, 4791

`\noretctoexplainyettrue` . . 4805, 4815

`\noretctotextnoteyetfalse` . 4405, 4745

`\noretctotextnoteyettrue` . 4806, 4816

`\normalepigraphindentation`
. 2601, 2602, 2608, 2609, 2641

`\normalepigraphquote` 2607, 2614

`\normalfont` 1022,
1032, 1109, 1147, 1183, 1226,
1244, 1267, 2957, 4317, 4380,
4443, 4506, 4568, 4635, 5186, 5189

`\normalmarginpar` 2093

`\normaltitleindentationfalse`
. 305, 312, 319, 326

`\normaltitleindentationscheme` . . 297

`\normaltitleindentationtrue` . . . 298

`\nostanzaatbottom` 17, 3820, 3821

`\nostanzaatbottomvalue` 685, 3820, 3983

`\noteaboutstanzamarkpage` 5141

`\noteheaderconcat`
. 3348, 3349, 3351–3353, 3376,
3377, 3379, 3380, 3407, 3408,
3410, 3411, 3434, 3435, 3437, 3438

`\noteindentation` 29,
1075, 1076, 1078, 1227, 1245, 1268

`\noteparbreak` 30, 1077

`\notesheadername` 1083–1085, 1103, 1104

`\notespoemclubpenalty` 55, 1572

`\notessequenceclubpenalty` 56

`\notestitleindent` 191, 192, 1049

`\notestitleindentamount` . . . 189–191

`\notesvolumetitlepenalty` . . . 57,
1308, 1322, 1410, 1427, 1445, 1463

`\noversoemendationyetfalse` 4468, 4711

`\noversoemendationyettrue` 4801, 4809

`\noversoexplainyetfalse` . 4597, 4728

`\noversoexplainyettrue` . . 4802, 4810

`\noversotextnoteyetfalse` . 4342, 4682

`\noversotextnoteyettrue` . 4803, 4811

`\numbersgutterfalse` . . . 887, 894, 3305

`\numbersguttertrue` 890, 3300

`\numbersrightfalse`
. 777, 877, 886, 3287, 3295

`\numbersrighttrue` 881, 3291

`\numbersswitchfalse`
. 776, 877, 881, 3287, 3291

`\numbersswitchtrue` 886, 3295

O

`\oddpagefalse` 785,
793, 849, 2190, 2198, 2269, 2277

`\oddpagetrue` 787, 791,
853, 855, 2192, 2196, 2271, 2275

`\oldleftskip` 761, 763

P

<code>\pagenumbering</code>	23	<code>\pmclrightsidedepar</code>	906, 915, 3323, 3881, 4156
<code>\pagestyle{fancy}</code>	592	<code>\pmclsavsf</code>	3839, 3844, 3849
<code>\pagestyle{main}</code>	608	<code>\pmclsavsk</code>	3838, 3843, 3850
<code>\paraend</code>	66, 4940	<code>\pmclsidedepar</code>	778, 904, 3320
<code>\parallelprose</code>	65, 4949	<code>\pmclsidedeparswitchfalse</code>	862
<code>\paralleltextsfalse</code> ..	3900, 4284, 4948	<code>\pmclsidedeparswitchtrue</code>	863, 886
<code>\paralleltextstrue</code>	3958, 4944	<code>\pmclsidedeparvshift</code> 18, 811, 819, 870,	2302, 3859, 3870, 3878, 3888, 3896
<code>parallelverse</code> (environment)	62	<code>pmclverse</code> (environment)	15
<code>\parastart</code>	66, 4939	<code>\pmclversoresetsettitleinnotes</code> .	4034, 4808
<code>\parindent</code> 101, 594, 796, 1113, 1151,	1187, 1227, 1245, 1268, 2119,	<code>\pmmemendation</code>	61, 3554, 3642
2131, 2201, 2231, 2248, 2280,	2960, 2961, 3856, 3867, 3884,	<code>\pmmemlabel</code>	825, 851
4321, 4384, 4447, 4510, 4572, 4639		<code>\pmmemlabelref</code>	839, 852
<code>\parsep</code>	29, 30, 5168	<code>\pmmemprotected@write</code>	826, 829
<code>\parskip</code>	5165	<code>\pmmexplanatory</code>	61, 3537, 3659
<code>\partopsep</code> ..	708, 718, 737, 5210, 5218	<code>\pmmnoteheader</code>	3263, 3349, 3353, 3377, 3380,
<code>\penalty</code> ...	55–57, 287–290, 685, 3983	3408, 3411, 3435, 3438, 3508, 3510	
<code>\phantom</code>	963, 3385, 3416, 3443	<code>\pmmnumbersgutter</code>	60, 3298
<code>\placetitlefootnote</code>	2538, 2554, 2563, 2573, 2583, 2591	<code>\pmmnumbersouter</code>	60, 3303
<code>\plain</code>	627	<code>\pmmnumbersswitch</code> ...	3295, 3299, 3304
<code>\pmmaccidental</code>	61, 3579, 3600	<code>\pmmnumberstoleft</code>	60, 3286
<code>\pmmcheckifinteger</code>	2739, 2763, 3152, 3495	<code>\pmmnumberstoright</code>	60, 3290
<code>\pmmcbgobm</code>	2741, 2748–2750, 2755	<code>\pmmpara</code>	60, 3468, 3663
<code>\pmmchecknoteheaders</code>	3008, 3513, 3528, 3544, 3570	<code>\pmmparainmartrue</code>	3449
<code>\pmmciterange</code>	3009, 3507,	<code>\pmmpararunningfalse</code>	3450
3529, 3545, 3571, 3626, 3643, 3660		<code>\pmmpararunningformat</code> ..	60, 3454, 3474
<code>\pmmclsbspback</code> ...	2118, 2130, 2230,	<code>\pmmpararunningtrue</code>	60
2247, 3840, 3855, 3866, 3882, 3883		<code>\pmmparasfalse</code>	3448
<code>\pmmclcontentsentry</code>	24, 40, 1277	<code>\pmmparastrue</code>	3469
<code>\pmmclcontentsentrydefaults</code> 1277, 1293		<code>\pmmparmarformat</code> ..	60, 3453, 3463, 3465
<code>\pmmclcontentsheader</code>	1013, 1014, 1018, 1028, 1029	<code>\pmmrangeend</code> 3492, 3501, 3503, 3508, 3523	
<code>\pmmclcontentsname</code>	1011, 1012, 1016, 1033	<code>\pmmresetlemmacounters</code> 3014, 3520,	3535, 3551, 3577, 3626, 3643, 3660
<code>\pmmcllesphack</code> 2127, 2139, 2242, 2259,	3846, 3863, 3876, 3879, 3894, 3897	<code>\pmmsection</code>	59
<code>\pmmclidxitem</code>	5179, 5192	<code>\pmmsentence</code>	59, 3332, 3662
<code>\pmmclleftsidedepar</code> 908, 3325, 3838, 4011		<code>\pmmsentencebypara</code>	60
<code>\pmmclnotesname</code>	1080–1082, 1107	<code>\pmmsentencebyparatrue</code>	3452
<code>\pmmclrectoresetsettitleinnotes</code> .	4088, 4813	<code>\pmmsentencefour</code>	59, 3418
<code>\pmmclresetsettitleinnotes</code> 4285, 4800		<code>\pmmsentencethree</code>	59, 3387
<code>\pmmclreversesidedeparfalse</code>	859, 889, 3300	<code>\pmmsentencetwo</code>	59, 3356
<code>\pmmclreversesidedepartrue</code> 860, 893, 3305		<code>\pmmsparrainmartrue</code>	60
		<code>\pmmtextnote</code>	61,
		3525, 3560, 3562, 3583, 3593, 3625	
		<code>\pmmtsaccidental</code>	61, 3600
		<code>\pmmtsvariant</code>	61, 3590
		<code>\mpoem</code>	747
		<code>poem</code> (environment)	15

<code>\poemattrIBUTION</code>	2684	<code>\poemsectiontitlebaretitle</code>	1726
<code>\poemattrIBUTIONINDENT</code>	2678, 2679, 2681–2683, 2685, 2687	<code>\poemsectiontitlefirstline</code>	1676
<code>\poemCONTENTS</code>	1020, 1021, 1053, 1056, 1057, 1062, 1063, 1279, 1282, 1287, 1288, 1552, 1553, 1556, 1557, 1562–1564, 2714, 2735, 4995, 4997, 4999–5001, 5003, 5004, 5006, 5009, 5010, 5013, 5016, 5017, 5021, 5023, 5026, 5028, 5030, 5032, 5118, 5120, 5122, 5133, 5135, 5137	<code>\poemsectiontitleindent</code>	138, 1678, 1687, 1716, 1724, 2419, 2428, 2430
<code>\poemCONTENTSONTRUE</code>	1019	<code>\poemsectiontitleindentAMOUNT</code>	136–138, 144, 1687, 1717, 1725, 2420, 2431
<code>\poemDATE</code>	41, 2672, 2673	<code>\poemsectiontitlelastline</code>	1676
<code>\poemDEDICATION</code>	40, 2597	<code>\poemsectiontitleMIDDLELINE</code>	1676
<code>\poemDOTFILL</code>	684	<code>\poemsectiontitleNOCONTENTS</code>	1712
<code>\poemENDEMENDATIONNOTE</code>	38, 3699, 3711	<code>\poemsectiontitleSECONDLINEINDENT</code>	141, 1696, 1705
<code>\poemENDEMENDATIONNOTES</code>	3707, 3708, 3714, 3726, 3731	<code>\poemsectiontitleSECONDLINEINDENTAMOUNT</code>	139–141, 1696, 1706
<code>\poemENDEMENDATIONNOTESONTRUE</code>	3702	<code>\poemSUBSECTIONTITLE</code>	1712
<code>\poemENDEMENDATIONNOTESSINGLEPARTRUE</code>	3704	<code>\poemSUBSECTIONTITLEINDENT</code>	144, 1733
<code>\poemENDEXPLANATORYNOTE</code>	38, 3736	<code>\poemSUBSECTIONTITLEINDENTAMOUNT</code>	142, 143, 1734
<code>\poemENDEXPLANATORYNOTES</code>	3742, 3743, 3749, 3761, 3766	<code>\poemSUBTITLE</code>	15, 1911
<code>\poemENDEXPLANATORYNOTESONTRUE</code>	3737	<code>\poemSUBTITLEINDENT</code>	135, 1933
<code>\poemENDEXPLANATORYNOTESSINGLEPARTRUE</code>	3739	<code>\poemSUBTITLEINDENTAMOUNT</code>	133–135
<code>\poemENDNOTE</code>	37, 3664	<code>\poemTITLE</code>	10, 1472, 1625, 3057
<code>\poemENDNOTES</code>	2543–2545, 3670, 3671, 3677, 3689, 3694	<code>\poemTITLEBARETITLE</code>	49, 1605
<code>\poemENDNOTESONTRUE</code>	3665	<code>\poemTITLEFIRSTLINE</code>	42, 1626
<code>\poemENDNOTESSINGLEPARTRUE</code>	3667	<code>\poemTITLEFONT</code>	14, 38, 1594, 1601, 1606, 1619, 1651, 1660, 1669, 1816, 1824, 1839, 1848, 1857, 1866, 1874, 1881, 1889, 1904, 1943, 2334, 2354, 2363, 2400, 2409, 2554, 2563, 2573, 2583, 2591, 4029, 4076, 4083, 4130, 5039, 5145
<code>\poemENDTEXTNOTE</code>	38, 3771	<code>\poemTITLEINDENT</code>	127, 128, 1595, 1602, 1607, 1620, 1652, 2555, 2564, 2592, 4030, 4077, 4084, 4131
<code>\poemENDTEXTNOTES</code>	3777, 3778, 3784, 3796, 3801	<code>\poemTITLEINDENTAMOUNT</code>	125–127
<code>\poemENDTEXTNOTESONTRUE</code>	3772	<code>\poemTITLEITALIC</code>	48, 1624
<code>\poemENDTEXTNOTESSINGLEPARTRUE</code>	3774	<code>\poemTITLELASTLINE</code>	42, 1626
<code>\poemFIRSTSECTIONTITLE</code>	1714	<code>\poemTITLEMIDDLELINE</code>	42, 1626
<code>\poemFIRSTSECTIONTITLEBARETITLE</code>	1722	<code>\poemTITLENOCOUNTENTS</code>	49, 1600
<code>\poemINDEXCONTENTSNAME</code>	5028, 5111–5113, 5120, 5128, 5135	<code>\poemTITLENONOTES</code>	49, 1618
<code>\poemINDEXHEADERNAME</code>	5108–5110, 5127, 5181, 5182	<code>\poemTITLENOTITLE</code>	48, 49, 1712, 3058
<code>\poemINDEXLABELNAME</code>	5129, 5138, 5172–5174, 5184	<code>\poemTITLENOTITLEITALIC</code>	48, 1712
<code>\poemINDEXNAME</code>	5105–5107, 5126, 5190	<code>\poemTITLEONLYCONTENTS</code>	49, 1609
<code>\poemLINELABEL</code>	22, 1006, 4153	<code>\poemTITLEONLYNOTES</code>	49, 1613
<code>\poemSECTIONBARETITLE</code>	1712	<code>\poemTITLEPENALTY</code>	14, 287, 1048, 1223, 1241, 1264, 1594, 1601, 1606, 1619, 1677, 1727, 1732, 1816, 1839, 1881, 1943, 1947, 1955, 2006, 2015, 2334,
<code>\poemSECTIONTITLE</code>	43, 1676		

2354, 2363, 2400, 2418, 2452,
 2554, 2591, 4029, 4076, 4083, 4130
 \poemtitlesecondlineindent
 . 131, 132, 1661, 1670, 2574, 2584
 \poemtitlesecondlineindentamount
 129–131
 \poemtitlewidth 291, 337
 \printindex 4992, 5115, 5130
 \proseaccidental 58, 3233
 \prosebysentencetrue 3268
 \proseciterange
 3163, 3175, 3623, 3641, 3658
 \proseemendation 3189, 3639
 \proseexplanatory 57, 3217, 3656
 \proselinelabel
 57, 2987, 3176, 3179, 3191,
 3219, 3621, 3639, 3656, 4677,
 4694, 4723, 4740, 4757, 4786, 4923
 \prosemendation 57
 \prosesection 57
 \prosesectiontitle 57, 3057
 \prosesectiontitlenotitle 3058
 \prosetextnote 57,
 3176, 3196, 3198, 3237, 3248, 3620
 \prosetsaccidental 58, 3255
 \prosetsvariant 58, 3244
 \protect 833, 3120, 3130
 \protected@edef 2740
 \protected@write 1007, 3483, 3486
 \providecommand
 825, 839, 840, 2463, 2626
 \putemendations 23, 38, 5051, 5062
 \putexplanatory 23, 38, 5050, 5075
 \putmultiplepoemindex 23, 39, 5124
 \putpagenumberincontentsfalse . .
 1302, 1316,
 1330, 1342, 1628, 1633, 1751, 2392
 \putpagenumberincontentstrue . . .
 554, 1310, 1324,
 1336, 1348, 1638, 1642, 1754, 2395
 \putpagenumberinnotesfalse 14, 30,
 1303, 1317, 1331, 1343, 1634, 1639
 \putpagenumberinnotestrue . . 556,
 1311, 1325, 1337, 1349, 1629, 1641
 \putpmmarginnumber . . . 3310, 3313,
 3316, 3385, 3416, 3443, 3462, 3465
 \putpmmarparanumber 3460, 3471
 \putpmsentencenumber 3308, 3342
 \putpmsentencenumberfour . 3428, 3442
 \putpmsentencenumberthree
 3397, 3401, 3415
 \putpmsentencenumbertwo
 3366, 3370, 3384
 \putpoemcontents 23, 5053
 \putpoemendemendationnotes . 38, 3729
 \putpoemendexplanatorynotes 38, 3764
 \putpoemendnotes 37, 3692
 \putpoemendtextnotes 38, 3799
 \putpoemindex 23, 26, 39, 5105
 \putrectoemendations 4860
 \putrectoexplanatorynotes 4890
 \putrectotextnotes 64, 4834
 \puttextnotes 23, 38, 5049, 5092
 \puttitleinnotesfalse 30
 \puttitleinnotestrue 1569
 \putverselinenumber 895, 940, 4007
 \putversoemendations 4847
 \putversoexplanatorynotes 4873
 \putversotextnotes 4821

Q

\quotedverse 42
 \quotedversecorrectionemendation
 3810
 \quotedversecorrectionexplanatory
 3814
 \quotedversecorrectiontextnote .
 33, 3806

R

\raggedright 750, 3959, 5187
 \rangelemmafalse 568, 2758,
 2766, 2779, 3146, 3155, 3498, 3520
 \rangelemmatrue 2758, 2766,
 2770, 3146, 3155, 3160, 3498, 3503
 \rectoemendation 64, 4513
 \rectoemendations 4492,
 4494, 4518, 4521, 4532, 4775, 4867
 \rectoemendationscontentsname . .
 4483, 4484, 4486, 4869
 \rectoemendationsheadername
 4480–4482, 4500, 4501
 \rectoemendationsname 4477–4479, 4504
 \rectoemendationspendingfalse . .
 3940, 4238
 \rectoemendationspendingtrue . . 4260
 \rectoemendationstwocolfalse . . 4489
 \rectoexplanations 4623,
 4624, 4649, 4653, 4666, 4792, 4897

<code>\rectoexplanationscontentsname</code> .	<code>\rectotitleinnotescheck</code> . . .
. 4613, 4614, 4616, 4901	4400, 4526, 4659, 4739, 4756, 4785
<code>\rectoexplanationsheadername</code> . . .	<code>\rectotitletoothernotes</code> . . .
. 4610–4612, 4629, 4630	4136, 4245, 4395, 4521, 4653, 4961
<code>\rectoexplanationsname</code>	<code>\rectotrue</code>
. 4607–4609, 4633	4244
<code>\rectoexplanationspendingfalse</code> .	<code>\redundantemendationsfalse</code>
. 3944, 4242	544
<code>\rectoexplanationstwocolfalse</code> .	<code>\ref</code>
4619	3159, 3503, 4156, 4157
<code>\rectoexplanatory</code> <i>64</i> , 4642, 4643, 4659	<code>\refstepcounter</code>
<code>\rectofalse</code> 3902, 4189, 4246, 4284	4926, 4933
<code>\rectom@ken@teholder</code> 4096, 4098	<code>\renewcommand</code>
<code>\rectoparaopenfalse</code>	25
4916	<code>\repeat</code>
<code>\rectoparapendingfalse</code> . . . 4914, 4967	67, 80
<code>\rectoparapendingtrue</code>	<code>\repeatedindent</code>
4967	62, 69
<code>\rectopassagestillopenfalse</code> . . . 4910	<code>\reserved@a</code>
<code>\rectopoempendingfalse</code> . . . 3906, 4230	834, 835, 3830, 3831
<code>\rectopoempendingtrue</code> . . . 4248, 4254	<code>\resetlemmacounters</code>
<code>\rectopoemstillopenfalse</code> 2779, 2801, 2871, 2890,
. 3918, 4167, 4171	2983, 2999, 3186, 3214, 3230,
<code>\rectopoemstillopentrue</code> . 4249, 4255	3616, 3623, 3638, 3641, 3655,
<code>\rectopoemtitle</code> <i>62</i> , <u>4081</u>	3683, 3720, 3755, 3790, 4348,
<code>\rectopoemtitlenocontents</code> . . <i>62</i> , 4129	4411, 4474, 4537, 4604, 4672,
<code>\rectoproseeemendation</code> <u>4754</u>	4688, 4717, 4734, 4751, 4780, 4797
<code>\rectoproseeexplanatory</code> <u>4783</u>	<code>\resetlinenumber</code>
<code>\rectoprosesectionpendingfalse</code> 3923	3067
<code>\rectoprosesectionstillopenfalse</code>	<code>\resetpagestyle</code>
. 3927	23, <u>661</u> , 5055
<code>\rectoprosetextnote</code> . <u>4737</u> , 4762, 4764	<code>\resettitleinnotes</code>
<code>\rectoquotedversependingfalse</code> . 3932	63
<code>\rectoquotedversestillopenfalse</code> 3936	<code>\restorerectoline</code>
<code>\rectoset@p@emtitle</code> . 4083, 4088, 4130	<u>4147</u> , 4244
<code>\rectostanzapendingfalse</code> . 3910, 4234	<code>\restorerectoproseline</code> . . 4937, 4962
<code>\rectostanzapendingtrue</code> 4252	<code>\restoresinglelinesettings</code>
<code>\rectostanzastillopenfalse</code> 3914, 4165 51, 1641,
<code>\rectostanzastillopentrue</code> 4253	1656, 1665, 1674, 1691, 1700,
<code>\rectotextnote</code> <i>64</i>	1710, 1764, 1773, 1782, 1797,
<code>\rectotextnote</code> <u>4387</u>	1805, 1813, 1853, 1862, 1871,
<code>\rectotextnotes</code> 4366,	1895, 1920, 1925, 1930, 1984,
4368, 4392, 4395, 4406, 4746, 4841	1993, 2003, 2038, 2568, 2578, 2588
<code>\rectotextnotescontentsname</code>	<code>\restoreverselinenumber</code> <i>42</i> , <u>952</u> , 5157
. 4357, 4358, 4360, 4843	<code>\restoreversoline</code>
<code>\rectotextnotesheadername</code>	<u>4141</u> , 4189
. 4354–4356, 4374, 4375	<code>\restoreversoproseline</code> . . 4930, 4952
<code>\rectotextnotesname</code> . 4351–4353, 4378	<code>\reversemarginpar</code>
<code>\rectotextnotessinglepar</code> <i>64</i>	2084, 2114
<code>\rectotextnotestwocol</code> <i>64</i>	<code>\rfvfalse</code>
<code>\rectotextnotestwocolfalse</code> 4363	503, 505
<code>\rectotitleholder</code> 4020, 4025, 4100,	<code>\rfvtrue</code>
4103, 4106, 4109, 4112, 4115, 4127	504
	<code>\rightflushrunoververse</code>
	504
	<code>\rightflushverse</code>
	<u>761</u>
	<code>rightflushverse (environment)</code> 22
	<code>\righthead</code>
	28, 591
	<code>\rightlinenumber</code>
 3069, 3071, 3082, 3084
	<code>\rightmargin</code>
 87, 335, 352, 370, 387, 390,
	406, 409, 421, 429, 443, 449,
	453, 466, 471, 483, 488, 498,
	710, 723, 727, 729, 742, 744,
	1587, 5162, 5167, 5204, 5206, 5215
	<code>\rightversebegin</code>
	22, <u>958</u>

<code>\rlap</code>	796, 2119, 2131, 2201, 2231, 2248, 2280, 3385, 3416, 3443, 3856, 3867, 3884, 4157	<code>\sequencesectionsubentitledamount</code>	165–167, 1915, 1919, 1924, 1929
<code>\runningsentencenumberformat</code>	3274, 3336, 3360, 3391, 3422	<code>\sequencesectionsubentitledlastline</code>	1927
<code>\runningsentencenumberstrue</code>	3258	<code>\sequencesectionsubentitledmiddleline</code>	1922
<code>\runoverindent</code>	20, 344, 346	<code>\sequencesectionsubentitledsecondlineindent</code>	170
<code>\runoverindentvalue</code>	86, 344, 351, 353, 380, 393, 400, 412, 418, 432, 439, 457, 463, 474, 480, 490, 497, 499, 950	<code>\sequencesectionsubentitledsecondlineindentamount</code>	168–170
S		<code>\sequencesectiontitle</code>	43, 1815, 1939
<code>\sameword</code>	31, 2737	<code>\sequencesectiontitlebaretitle</code>	1942
<code>\saverectoline</code>	4144, 4246	<code>\sequencesectiontitlefirstline</code>	1846, 1941
<code>\saverectoproseline</code>	4932, 4968	<code>\sequencesectiontitlefirstlineitalic</code>	1940
<code>\saveverselinenumber</code>	42, 952	<code>\sequencesectiontitleindent</code>	161, 1817, 1825, 1840, 1849, 1858, 1867, 1875, 1882, 1890, 1905, 2401, 2410
<code>\saveversoline</code>	4138, 4192	<code>\sequencesectiontitleindentamount</code>	159–161, 1818, 1826, 1841, 1849, 1858, 1867, 1876, 1883, 1891, 1906, 2402
<code>\saveversoproseline</code>	4925, 4958	<code>\sequencesectiontitleitalic</code>	1938
<code>\sentencelabel</code>	61, 3480	<code>\sequencesectiontitleitaliconotes</code>	1935
<code>\sequencefirstsectiontitle</code>	43, 1823	<code>\sequencesectiontitlelastline</code>	1864, 1901
<code>\sequencefirstsectiontitlefirstline</code>	1887	<code>\sequencesectiontitlemiddleline</code>	1855, 1898
<code>\sequencefirstsectiontitlelastline</code>	1900	<code>\sequencesectiontitlenocontents</code>	1880
<code>\sequencefirstsectiontitlemiddleline</code>	1897	<code>\sequencesectiontitlenonotes</code>	1831, 1936
<code>\sequencefirstsectiontitlenocontents</code>	1873	<code>\sequencesectiontitlesecondlineindent</code>	164
<code>\sequencefirstsectiontitlenonotes</code>	1903	<code>\sequencesectiontitlesecondlineindentamount</code>	162–164
<code>\sequencefirstsubsectionmiddleline</code>	2050	<code>\sequencesubsectiontitle</code>	43, 1946
<code>\sequencefirstsubsectiontitle</code>	1961	<code>\sequencesubsectiontitlefirstline</code>	1977
<code>\sequencefirstsubsectiontitlefirstline</code>	2031, 2045	<code>\sequencesubsectiontitleindent</code>	173, 1948, 1956, 1963, 1971, 1980, 1998, 2034
<code>\sequencefirstsubsectiontitlelastline</code>	2042, 2047	<code>\sequencesubsectiontitleindentamount</code>	171–173, 1949, 1957, 1964, 1972, 1980, 1999, 2034
<code>\sequencefirstsubsectiontitlemiddleline</code>	2040	<code>\sequencesubsectiontitlelastline</code>	1995, 2043
<code>\sequencefirstsubsectiontitlenocontents</code>	1969		
<code>\sequencefirstsubsubsectiontitlenocontents</code>	2022		
<code>\sequencesectionsubentitled</code>	1911		
<code>\sequencesectionsubentitledfirstline</code>	1917		
<code>\sequencesectionsubentitledindent</code>	167, 1915, 1919, 1924, 1929		

<code>\sequencesubsectiontitlemiddleline</code>	1986, 2041	<code>\set@p@emsubtitle</code>	1534, 1606, 1785, 1792, 1800, 1808, 1914, 1918, 1923, 1928, 1932
<code>\sequencesubsectiontitlenocontents</code>	1713, 1954	<code>\set@p@emtitle</code>	50, 1300, 1313,
<code>\sequencesubsectiontitlesecondlineindent</code>	1989		1327, 1339, 1510, 1523, 1594,
<code>\sequencesubsectiontitlesecondlineindentamount</code>	1989		1601, 1619, 1651, 1660, 1669,
<code>\sequencesubsubsectiontitle</code>	2005		1677, 1686, 1695, 1704, 1715,
<code>\sequencesubsubsectiontitleindent</code>	176, 2007, 2016, 2024		1723, 1727, 1732, 1749, 1759,
<code>\sequencesubsubsectiontitleindentamount</code>	174–176, 2009, 2017, 2025		1768, 1777, 1816, 1824, 1832,
<code>\sequencesubsubsectiontitlenocontents</code>	2014		1839, 1848, 1857, 1866, 1874,
<code>\sequencesubtitle</code>	1784		1881, 1889, 1904, 1943, 1947,
<code>\sequencesubtitlefirstline</code>	1791		1955, 1962, 1970, 1979, 1988,
<code>\sequencesubtitleindent</code>	155, 1786, 1793		1997, 2006, 2015, 2023, 2033,
<code>\sequencesubtitleindentamount</code>	153–155		2452, 2554, 2563, 2573, 2583, 2591
<code>\sequencesubtitlelastline</code>	1807	<code>\set@short@pigraph</code>	2635, 2651, 2654, 2657, 2660
<code>\sequencesubtitlemiddleline</code>	1799	<code>\setbox</code>	813, 2121, 2133,
<code>\sequencesubtitlesecondlineindent</code>	158, 1801, 1809		2218, 2236, 2253, 2304, 3872, 3890
<code>\sequencesubtitlesecondlineindentamount</code>	156–158	<code>\setcontentsleaders</code>	24, 1547, 1550
<code>\sequencetitle</code>	43, 1748	<code>\setcounterfrompageref</code>	1193, 2841, 3128, 4070, 4124
<code>\sequencetitlefirstline</code>	1757	<code>\setcounterfromref</code>	2770, 3118, 3142, 3160, 4928, 4935
<code>\sequencetitlefont</code>	39, 1749, 1759, 1768, 1777, 1785, 1792, 1800, 1808, 1832, 2389	<code>\setendnotessectiontitle</code>	1047, 1107, 1145, 1181, 2952, 4315, 4378, 4441, 4504, 4566, 4633
<code>\sequencetitleindent</code>	147, 148, 1750, 1760, 1769, 1778, 1833, 2335, 2355, 2364, 2390	<code>\setendnotessectiontitledefaults</code>	1037, 1048, 1223, 1241, 1264
<code>\sequencetitleindentamount</code>	145–147, 1833	<code>\setlemmarange</code>	2756, 2794,
<code>\sequencetitlelastline</code>	1757		2848, 2879, 2972, 3614, 3636,
<code>\sequencetitlemiddleline</code>	1757		3653, 3676, 3713, 3748, 3783,
<code>\sequencetitlenonotes</code>	1831		4338, 4401, 4464, 4527, 4593, 4661
<code>\sequencetitlepenalty</code>	289, 1749, 2389	<code>\setlength</code>	25
<code>\sequencetitlesecondlineindent</code>	151, 152	<code>\setmargpoemtitle</code>	46, 2053, 2350
<code>\sequencetitlesecondlineindentamount</code>	149–151	<code>\setmargref</code>	2469,
<code>\set@margp@emsubtitle</code>	2323, 2436		2487, 2491, 2497, 2502, 2507, 3048
<code>\set@margp@emtitle</code>	2313, 2334, 2341, 2354, 2363, 2389, 2400, 2409, 2418, 2427	<code>\setmargrefmarker</code>	47, 2462
		<code>\setpmllemmarange</code>	3003, 3494,
			3527, 3539, 3556, 3625, 3642, 3659
		<code>\setpmodulo</code>	59, 3283
		<code>\setprosebysentence</code>	59, 3268
		<code>\setproselemmarange</code>	2988, 3143, 3180,
			3192, 3220, 3622, 3640, 3657,
		<code>\setproselemmastart</code>	3091, 3144, 3151
		<code>\setprosemodulo</code>	57, 3056
		<code>\setsynchroflag</code>	65, 4150
		<code>\settitlemargrefmarker</code>	47, 2463
		<code>\setverselinemodulo</code>	18, 945

<code>\textnotesontrue</code>	1093, 3602, 4302, 4365	<code>\thepoemnumber</code>
<code>\textnotestwocolfalse</code> 1091		. 1475, 1478, 1487, 1490, 1496,
<code>\textsuperscript</code> 3277, 3280		1502, 1558, 1574, 4047, 4050,
<code>\textwidth</code> 805,		4056, 4062, 4101, 4104, 4110, 4116
	2054, 2210, 2232, 2290, 3885, 3886	<code>\theprintlineindex</code> 938, 4158
<code>\the</code>	.. 641, 642, 682, 683, 823, 1028,	<code>\theproselinenum</code>
	1029, 1033, 1103, 1104, 1107,	 3147, 3156, 3165, 3167
	1141, 1142, 1145, 1177, 1178,	<code>\theprosepage</code> 4923, 4928, 4935
	1181, 1494, 1500, 2142, 2145,	<code>\theverselinenum</code>
	2147, 2151, 2155, 2157, 2162,	 897, 899, 901, 904, 906,
	2165, 2167, 2175, 2177, 2372,		909, 912–915, 933, 935, 1008,
	2375, 2378, 2381, 2384, 2472,		2759, 2767, 2775, 2777, 4009–4011
	2475, 2489, 2492, 2510, 2544,	<code>\thispagestyle</code>
	2660, 2844, 2901, 3508, 3510,		. 766–768, 770, 771, 773, 1024,
	4054, 4060, 4073, 4108, 4114,		1099, 1138, 1175, 1214, 1255,
	4127, 4156, 4157, 4311, 4312,		1400, 1417, 1435, 1453, 2935,
	4315, 4374, 4375, 4378, 4437,		3823, 3826, 4308, 4371, 4434,
	4438, 4441, 4500, 4501, 4504,		4497, 4560, 4627, 5036, 5142, 5177
	4562, 4563, 4566, 4629, 4630,	<code>\tightgeometry</code> $\frac{1}{2}$
	4633, 4830, 4843, 4856, 4869,	<code>\tightleading</code> 10
	4884, 4901, 5007, 5014, 5021,	<code>\titleconcat</code> 1494,
	5028, 5071, 5086, 5101, 5120,		1495, 1500, 1501, 4054, 4055,
	5135, 5138, 5181, 5182, 5184, 5190		4060, 4061, 4108, 4109, 4114, 4115
<code>\thebotmarks</code> 640, 642	<code>\titleentryoverrun</code>
<code>\thecp@cntr</code> 851, 852		. 712, 713, 719, 731, 738, 746,
<code>\thefirstmarks</code> 640–642		1513, 1522, 1523, 1531, 1537,
<code>\theindex</code> 5172		1546, 2313, 2321, 2323, 2331,
<code>\thelemmaend</code> 2775, 3165, 3501		2341, 2348, 4035, 4043, 4089, 4097
<code>\thelemmalines</code>	<code>\titlefirstlinefalse</code> 560, 1643
 2760, 2768, 3148, 3157, 3500	<code>\titlefirstlinetrue</code> 1627
<code>\thelineindexrepeat</code> 938, 4158	<code>\titlefootnotesatpoemendfalse</code>	..
<code>\themargrefnumber</code> 2513, 2523, 2535
	. 2142, 2145, 2147, 2151, 2155,	<code>\titlefootnotesatpoemendtrue</code>	.. 2529
	2157, 2162, 2165, 2167, 2175,	<code>\titlefootnoteslayeredfalse</code>
	2177, 2466, 2472, 2475, 2489, 2492	 2517, 2527, 2533
<code>\thenotepageholdernote</code>	<code>\titlefootnoteslayeredtrue</code> 2521
 2787, 3173, 3517	<code>\titlefootnotesplainfalse</code>	2522, 2528
<code>\thenotepageholdertitle</code>	<code>\titlefootnotesplaintrue</code>	. 2515, 2534
 1196, 2788, 3174, 3518	<code>\titleincrement</code> 525, 1493,
<code>\thepmenc@page</code> 823 , 827, 831		1494, 1499, 1500, 4053, 4054,
<code>\thepmindexcount</code> 3369, 3400		4059, 4060, 4107, 4108, 4113, 4114
<code>\thepmmodulo</code> 3369, 3400	<code>\titleindent</code>
<code>\thepmparagraph</code>	. 3348, 3376, 3407,		.. <i>l</i> , 100, 1728, 1911, 1944, 2437
	3434, 3456, 3462, 3465, 3474, 3484	<code>\titleindentamount</code>	.. 91–93, 100,
<code>\thepmsentencenumber</code> 3276,		110, 112, 115, 134, 137, 140,
	3310, 3313, 3336, 3348, 3351,		154, 157, 160, 163, 216, 219,
	3352, 3360, 3376, 3379, 3385,		1679, 1729, 1933, 1944, 2411, 2438
	3391, 3407, 3410, 3416, 3422,	<code>\titleindentthreamount</code>	. 97–99, 175
	3434, 3437, 3443, 3484, 3487, 3499	<code>\titleindenttwoamount</code>
		 94–96, 143, 166, 169, 172

<code>\titlelastlinefalse</code>	564, 1645	<code>\variablepoemtributionindent</code> .	
<code>\titlelastlinetrue</code>	1637		2680, 2684
<code>\titlemargrefmarker</code> .	2372, 2463–2465	<code>\variablestanzaamount</code> 73, 74, 77, 88, 89	
<code>\titlemiddlelinefalse</code>	562, 1644	<code>\vbox</code> .	810, 2215, 2301, 3858, 3869, 3887
<code>\titlemiddlelinetrue</code>	1632	<code>\verseindent</code>	19, 68, 70
<code>\titlesatleftmarginofcenteredblockfalse</code>	301, 308, 315, 329	<code>\verseindentamount</code> 59, 60, 65, 69, 70, 72	
<code>\titlesatleftmarginofcenteredblockscheme</code>	13, 318	<code>\verseline</code>	18, <u>920</u>
<code>\titlesatleftmarginofcenteredblocktrue</code>	322	<code>\verselinenumbersgutter</code>	18, <u>882</u>
<code>\titlesatleftversemarginfalse</code> . .	299, 313, 320, 327	<code>\verselinenumbersouter</code>	18, <u>882</u>
<code>\titlesatleftversemargintrue</code>	306	<code>\verselinenumbersswitch</code>	<u>882</u>
<code>\titlescenteredonleftverseblockfalse</code>	300, 307, 321, 328	<code>\verselinenumbersstoleft</code>	18, <u>874</u>
<code>\titlescenteredonleftverseblockscheme</code>	12, 311	<code>\verselinenumbersstoright</code>	18, <u>874</u>
<code>\titlescenteredonleftverseblocktrue</code>	314	<code>\verselinenumberstrue</code>	533, 569, 1094, 1134, 1170, 3669, 3706, 3741, 3776, 4304, 4367, 4430, 4493, 4555, 4622
<code>\titlesofar</code>	524, 1492, 1494, 1498, 1500, 4052, 4054, 4058, 4060, 4106, 4108, 4112, 4114	<code>\versemarginadjust</code> 16, 361, 362, 388, 391, 407, 410, 430, 450, 454, 472	
<code>\titletoothernotes</code>	2838, 2874, 2894, 2965, 4079, 4136, 4190, 4245, 4951, 4961	<code>\versephantom</code>	20, <u>962</u>
<code>\toks@</code>	2900, 2901	<code>\verserightflushfalse</code>	566
<code>\tolerance</code>	1034, 1108, 1146, 1182, 1225, 1243, 1266, 2956, 4316, 4379, 4442, 4505, 4567, 4634, 5155, 5185	<code>\versewidth</code>	15, 336, 747, 748, 1589, 2670, 2682
<code>\topsep</code>	28, 707, 717, 736, 5164, 5209, 5217	<code>\versoemendation</code>	64, <u>4450</u>
<code>\tsaccidental</code>	<u>2814</u>	<code>\versoemendations</code>	4429, 4431, 4455, 4458, 4469, 4712, 4854
<code>\tsentry</code>	32, <u>2823</u>	<code>\versoemendationscontentsname</code> . .	4420, 4421, 4423, 4856
<code>\tsvariant</code>	32, <u>2814</u>	<code>\versoemendationsheadername</code>	4417–4419, 4437, 4438
<code>\tweakbrokenline</code>	21, <u>964</u>	<code>\versoemendationsname</code> 4414–4416, 4441	
<code>\tweakstartverseline</code>	21, <u>989</u>	<code>\versoemendationspendingfalse</code> . .	3942, 4183
<code>\typeout</code>	5052, 5056	<code>\versoemendationspendingtrue</code> . .	4206
		<code>\versoemendationstwocolfalse</code> . .	4426
		<code>\versoexplanations</code>	4556, 4557, 4582, 4586, 4598, 4729, 4880
		<code>\versoexplanationscontentsname</code> .	4546, 4547, 4549, 4884
		<code>\versoexplanationsheadername</code>	4543–4545, 4562, 4563
		<code>\versoexplanationsname</code>	4540–4542, 4566
		<code>\versoexplanationspendingfalse</code> .	3946, 4187
		<code>\versoexplanationspendingtrue</code> . .	4212, 4266
		<code>\versoexplanationstwocolfalse</code> .	4552
		<code>\versoexplanatory</code> 64, 4575, 4576, 4591	
		<code>\versofalse</code>	3904, 4192, 4244, 4284
		<code>\versom@ken@teholder</code>	4042, 4044
U			
<code>\undefined</code>	3061		
V			
<code>\v@riablemarginpar</code>	367, 374		
<code>\vadjust</code>	779, 780, 2118, 2130, 2184, 2185, 2230, 2247, 2263, 2264, 3855, 3866, 3882, 3883		
<code>\variabledateindent</code>	2668, 2673		

<code>\versoparaopenfalse</code>	4920	<code>\volumesectiontitle</code>	28, 1312
<code>\versoparapendingfalse</code> ..	4918, 4957	<code>\volumesectiontitlefirstline</code> ..	1417
<code>\versoparapendingtrue</code>	4957	<code>\volumesectiontitleindent</code>	
<code>\versopassagestilopenfalse</code> ...	4908	. 119, 120, 1403, 1420, 1438, 1456	
<code>\versopoempendingfalse</code> ..	3908, 4175	<code>\volumesectiontitleindentamount</code> .	
<code>\versopoempendingtrue</code> ...	4194, 4200 117–119	
<code>\versopoemstilopenfalse</code>		<code>\volumesectiontitlelastline</code> ...	1452
..... 3920, 4222, 4226		<code>\volumesectiontitlemiddleline</code> .	1434
<code>\versopoemstilopentrue</code> .	4195, 4201	<code>\volumesectiontitlesecondlineindent</code>	
<code>\versopoemtitle</code>	62, 4027 123, 124	
<code>\versopoemtitlenocontents</code> ..	62, 4075	<code>\volumesectiontitlesecondlineindentamount</code>	
<code>\versoproseemendation</code>	4691 121–123	
<code>\versoproseexplanatory</code>	4720	<code>\volumesubtitle</code>	28, 1312
<code>\versoprosesectionpendingfalse</code>	3925	<code>\volumesubtitlefirstline</code>	1362
<code>\versoprosesectionstilopenfalse</code>		<code>\volumesubtitlefont</code>	37, 1350,
..... 3929		1362, 1374, 1387, 1401, 1403,	
<code>\versoprosetextnote</code> .	4674, 4699, 4701	1418, 1420, 1436, 1438, 1454, 1456	
<code>\versoquotedversependingfalse</code> .	3934	<code>\volumesubtitleindent</code>	113, 1351
<code>\versoquotedversestilopenfalse</code>	3938	<code>\volumesubtitleindentamount</code>	111–113
<code>\versoset@p@emtitle</code> .	4029, 4034, 4076	<code>\volumesubtitlelastline</code>	1387
<code>\versostanzapendingfalse</code> .	3912, 4179	<code>\volumesubtitlemiddleline</code>	1374
<code>\versostanzapendingtrue</code>	4198	<code>\volumesubtitlesecondlineindent</code> .	
<code>\versostanzastilopenfalse</code>	3916, 4220 116, 1363, 1376, 1389	
<code>\versostanzastilopentrue</code>	4199	<code>\volumesubtitlesecondlineindentamount</code>	
<code>\versotextnote</code>	64 114–116	
<code>\versotextnotes</code>	4324	<code>\volumetitle</code>	28, 1299
<code>\versotextnotes</code>	4303,	<code>\volumetitlefirstline</code>	28, 1312
4305, 4329, 4332, 4343, 4683, 4828		<code>\volumetitlefont</code>	
<code>\versotextnotescontentsname</code> 36, 1300, 1314, 1328, 1340, 2452	
..... 4294, 4295, 4297, 4830		<code>\volumetitleindent</code> 104, 105, 1301, 1315	
<code>\versotextnotesheadername</code>		<code>\volumetitleindentamount</code> ...	102–104
..... 4291–4293, 4311, 4312		<code>\volumetitlelastline</code>	28, 1312
<code>\versotextnotesname</code> .	4288–4290, 4315	<code>\volumetitlemiddleline</code>	28, 1326
<code>\versotextnotestwocolfalse</code>	4300	<code>\volumetitlepage</code>	764
<code>\versotitleholder</code> 4019, 4022, 4046,		<code>\volumetitlepage (environment)</code> ...	27
4049, 4052, 4055, 4058, 4061, 4073		<code>\volumetitlesecondlineindent</code> ...	
<code>\versotitleinnotescheck</code> ...	4079, 108, 109, 1329, 1341	
4337, 4463, 4591, 4676, 4693, 4722		<code>\volumetitlesecondlineindentamount</code>	
<code>\versotitletoothernotes</code> ...	4067, 106–108	
4079, 4190, 4332, 4458, 4586, 4951		<code>\volumetitleshift</code>	
<code>\versotrue</code>	4189 195, 1351, 1363, 1375, 1388	
<code>\voladditionalamount</code> .	196, 5215, 5216	<code>\volumetitleshiftamount</code> ...	194, 195
<code>\volumeattribution</code>	28, 2597	<code>\volumetitlesink</code>	42, 1300, 1313
<code>\volumededication</code>	2597	<code>\volumetitlestyle</code>	656
<code>\volumeepigraph</code>	28, 40, 2597	<code>\volumetitle{}</code>	1299
<code>\volumefirststyle</code>	621	<code>\vss</code>	817, 818, 820,
<code>\volumeheader</code>	28, 585 , 590, 591	2125, 2127, 2137, 2139, 2222,	
<code>\volumeheadervalue</code>		2223, 2225, 2240, 2242, 2257,	
..... 585, 602, 614, 649, 665		2259, 2308, 2309, 2311, 3863,	
<code>\volumesection</code>	1298	3876, 3877, 3879, 3894, 3895, 3897	

<code>\vtop</code>	813, 819, 2121, 2126, 2133, 2138, 2218, 2224, 2236, 2241, 2253, 2258, 2304, 2310, 3872, 3878, 3890, 3896	<code>\wholebooktitle</code>	28, <u>1295</u>
		<code>\widowpenalty</code>	53
	W		X
<code>\wedge</code>	2738	<code>\xdef</code>	2901